INCH-POUND

MIL-C-46666B(AR)
AMENDMENT 2
11 March 1991
SUPERSEDING
AMENDMENT 1
24 JULY 1984

MILITARY SPECIFICATION

CARTRIDGE, GRENADE, 7.62MM, NATO, RIFLE, M64

This Amendment forms a part of Military Specification MIL-C-46666B(MU), dated 10 August 1973, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

Delete "AMCR 715-505 Volume 3" wherever it appears in the specification and substitute "SCATP-7.62mm".

PAGE 2

* 2.1 In Paragraph 2.1 and under Drawings, delete the following drawing and its title:

"F10521851"

and substitute the following:

"9362607 - Packing and Marking for Box, Wirebound for Cartridge, 7.62mm"

PAGE 3

3.3: Delete "ambient temperature" and substitute "65°F to 75°F (room temperature)".

PAGE 7

4.3.3.2 Table III:

Change defect numbers from "2, 3 and 4" to "3, 4 and 5" respectively. Then insert new defect number 2 as follows:

"2. Hangfire 3/ 0 -"

AMSC N/A

FSC1305

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:37Z
Check the source to verify that this is the current version before use.

Add footnote 3 to Table III as follows:

"3/ For definition of a hangfire, see SCATP-7.62 paragraph 10.6.2."

4.4.1: Delete "ambient temperature" and substitute "room temperature (65°F to 75°F)."

4.4.1.1: Delete "ambient temperature" and substitute "room temperature (65°F to 75°F)."

4.4.1.2: Delete the phrase "temperature at which the ammunition is conditioned shall be plus 125 to plus 130 degrees F" and substitute "test sample shall be stored for 4 to 5 hours at 125°F to 130°F and fired at that temperature."

4.4.1.3, Add new paragraph as follows:

"4.4.1.3 Room temperature tests. The test sample shall be conditioned for not less than 2 hours at 65°F to 75°F (room temperature) and fired at that temperature."

* 5. Delete "paragraph 5" in its entirety and substitute the following:

"5. PREPARATION FOR DELIVERY

5.1 Preservation and packing.

5.1.1 Packing, Level A. The cartridges shall be packed in accordance with drawings 9362607.

5.1.2 Marking. Markings shall be in accordance with Dwgs 9362607.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

5.2 Shipping. When cartridges from more than one lot are shipped at one time, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of the lots in transit."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections or deletions) from the previous amendment were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1305-AD62)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.