MIL-C-46679A (AR)
12 February 1982
SUPERSEDING
MIL-C-46679 (Ord)
24 July 1962

MILITARY SPECIFICATION

CHARGE, PROPELLING, DUMMY, M4

This specification is approved for use by US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of propelling charge for 8 inch cannon, designated as the M4 dummy propelling charge.

2. APPLICABLE DOCUMENTS

2.1 Government documents

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

FSC: 1320

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:39Z
Check the source to verify that this is the current version before use.

2.1.2 Other government documents, drawings and publications. The following other Government documents form a part of this specification to the extent specified herein.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

7548187 - Packing and Marking of Metal Containers for Propelling Charges

8863354 - Charge, Propelling, 8 inch, Dummy: M4, for 8 inch Cannon

8880527 - Container, Metal, Propelling Charge: M113A2

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

(Copies of specifications, standards, handbooks, drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Propelling charge. The charge shall comply with all requirements specified on Drawing (dwg.) 8863354 and with all requirements specified in applicable specifications.

3.3 Workmanship. All components shall be free of dirt, grease and other foreign material. There shall be no discoloration or deterioration of cloth and no evidence of rips, tears, or other cloth defects. All work shall be performed in a thorough workmanlike manner.

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:39Z
Check the source to verify that this is the current version before use.

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. Quality Conformance Inspection

4.3 Quality conformance inspection

4.3.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.3.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:39Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46679A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.3.2.1	Filler, Base Increment 5		8863382
			NEXT HIGHER ASSEMBLY 8863355

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Total length		0.65%	3.2	Gage
202	Maximum diameter		0.65%	3.2	Gage
203	Lead insecure		0.65%	3.2	Manual
204	Improper handle recess		0.65%	3.2	Gage
205	Weight		0.65%	3.2	Balance
206	Coating improper or missing		0.65%	3.2	Visual
207	Chamfer missing		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:39Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46679A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.2	Filler, Increment, Body				8863383
					NEXT HIGHER ASSEMBLY
					8863356
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Total length		0.65%	3.2	Gage
202	Maximum diameter		0.65%	3.2	Gage
203	Lead insecure		0.65%	3.2	Manual
204	Weight		0.65%	3.2	Balance
205	Coating improper or missing		0.65%	3.2	Visual
206	Chamfer missing		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.3	Base Increment 5 Loading Assembly				8863355
					NEXT HIGHER ASSEMBLY
					8863354
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Handle not secured with screws		0.65%	3.2	Visual
202	Stitching missing or improper		0.65%	3.2	Visual
203	Marking misleading or unidentifiable		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:39Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46679A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8863356
4.3.2.4	Increment Loading Assembly				NEXT HIGHER ASSEMBLY 8863354
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Stitching missing or improper		0.65%	3.2	Visual
202	Marking misleading or unidentifiable		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:39Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46679A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.5	Charge, Propelling, 8 Inch Dummy: M4, for 8 Inch Cannon				8863354
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Total length		0.65%	3.2	Gage
202	Outside diameter		0.65%	3.2	Gage
203	Any component missing or improperly assembled		0.65%	3.2	Visual
204	Marking misleading or unidentifiable		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:39Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46679A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.6	Container, Prior to Sealing				(8880527 & 7548187)
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Any packing component missing		0.65%	3.2	Visual
202	Cover cannot be removed by hand		0.65%	3.2	Manual
203	Charge cannot be removed by hand		0.65%	3.2	Manual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:39Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46679A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.7	Sealed Container				(8880527 & 7548187)
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Cover incompletely engaged		0.65%	3.2	Manual
202	Marking misleading or unidentifiable		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:39Z
Check the source to verify that this is the current version before use.

4.3.3 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.3.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and paragraph 6.3 of this specification.

5. PACKAGING

5.1 Packing and marking. The propellant charges shall be packed in a M113A2 container conforming to dwg 8880527 and the container shall be marked and sealed in accordance with drawing 7548187.

6. NOTES

6.1 Intended use. The propelling charges covered by this specification are intended for use as training devices in 8 inch cannons.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of designs for approval. See 6.2.3 of MIL-48078. Submit equipment designs, as required, to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801.

6.4 Visual examination qualification. When a compliance with the applicable requirement is in doubt as a result of visual examination, the characteristic may be measured or gaged to determine acceptability.

Custodian:
Army - AR

Preparing Activity:
Army - AR
Project Number: 1320-A641

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:39Z
Check the source to verify that this is the current version before use.