MILITARY SPECIFICATION

DEMOLITION KIT, PROJECTED CHARGE, M173, AND PRACTICE, M174 LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-D-46688A dated 30 April 1965.

Para. 4.3.2.1 Add Major defect 107. Connection J8-P8 taped properly Visual Code No. 09002.

Add para. 4.3.3.2.2 Pull test, Connector assembly J8-P8, (dwg. number 8846709) - Major defect - Code No. 09003.-This test will be performed 100 percent. Any connector assembly which fails to comply with the applicable requirement shall be classed defective and removed from the lot. Test shall be performed as specified in 4.4.3 using equipment in accordance with 4.3.4.

* Add para. 4.3.3.2.4 Pull test of ferrule crimp, panel cover end (dwg. number 8846709) Major defect. This Test shall be performed 100%. Any ferrule which moves in relation to the lanyard shall be classified defective and removed from the lot. Test shall be performed as specified in 4.4.5 using equipment in accordance with 4.3.4.

* Add para. 4.3.3.2.5 Pull test of ferrule crimp, trip launcher assembly end (dwg. number 8846709) Major defect. This test shall be performed 100 percent. Any ferrule which moves in relation to the lanyard shall be classified defective and removed from the lot. Test shall be performed as specified in 4.4.5 using equipment in accordance with 4.3.4.

Add para. 4.4.3 Pull test, Connector assembly.- The aft end of the connector cable shall be clamped to the bulkhead eyebolt. The forward end of the connector cable shall be attached by a suitable clamp to a measuring device in accordance with 4.3.4. The clamps shall not be in contact with the tape covered portion of the cable. A linear static load shall be applied to the taped connector assembly to determine compliance with the applicable drawing requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:41Z
Check the source to verify that this is the current version before use.

Add para. 4.4.4 Resistance of fuze connector assembly.- A continuity check of the fuze connector assembly with the shorting plug in place shall be made by measuring the resistance across the terminals of the fuze connector to determine that the resistance value is in compliance with the drawing requirement, using equipment in accordance with 4.3.4.

* Add para. 4.4.5 Pull test of ferrule crimp. Each end shall be tested and evaluated as an individual defect. There shall be no slippage between the lanyard and the ferrule when the minimum prescribed force is applied between the loop in the lanyard and the main lanyard body using equipment in accordance with paragraph 4.3.4.

The margins of this amendment are marked wih an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

Project Number: 1375-A132

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:41Z
Check the source to verify that this is the current version before use.