MIL-F-46657D (PA)
15 August 1974
SUPERSEDING
MIL-F-46657C (MU)
16 August 1968

MILITARY SPECIFICATION

FIRING DEVICE, DEMOLITION PULL TYPE, M1 LOADING, ASSEMBLING AND PACKING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of firing device designated as Firing Device, Demolition, Pull Type, M1.

2. APPLICABLE DOCUMENTS

*2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition, General Specification For
MIL-P-12951 - Primer, Percussion, M39A1, Loading Assembling and Packing
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

*STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 202640-22T06:36Z
Check the source to verify that this is the current version before use.

MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-1168- Lot Numbering of Ammunition
MIL-STD-1235- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

*DRAWINGS

U.S. ARMY PICATINNY ARSENAL

PRODUCT AND PACKAGE DRAWINGS

2128158 - Pack, Shipping and Storage (For Firing Device, Pull Type, M1, With Trip Wire)
3139666 - Package, Shipping and Storage (Firing Device, Pull Type, M1 With Spools Trip Wire)
7548176 - Wire, Spool Assembly
8797446 - Carton, Packing, Ammunition For Firing Device, Pull Type, M1 with Trip Wire
8797447 - Box, Packing, Ammunition For Firing Device Pull Type, M1 With Trip Wire
8797612 - Firing Device, Demolition, Pull Type, M1 Assembly

INSPECTION EQUIPMENT DRAWINGS

8802728 - Layout

(Copies of specifications, standards drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

*(For meaning of asterisk (*) see 6.6)

*2.2 Other publications. - The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS

Code of Federal Regulations Title 49 - Transportation, Parts 100 - 199.

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:36Z
Check the source to verify that this is the current version before use.

(The Code of Federal Regulations is available from the Washington, D.C. 20402. Orders shall specify 49 CFR-100-199 latest revision).

3. REQUIREMENTS

3.1 Material. - Materials shall be in accordance with applicable drawings and specifications.

3.2 Assembly. - The assembly shall comply with all requirements specified on Drawing (dwg.) 8797612 and with all requirements specified in applicable specifications.

*3.3 Embrittlement of springs. - Springs shall not break or fracture when pulled to the point of minimum permanent distortion.

*3.4 Non-functioning. - The firing device shall not function when a load of three pounds, minimum, is applied to the release pin ring in a direction parallel to the axis of the release pin.

*3.5 Functioning. - The firing device shall function the primer when a load of six pounds, maximum, is applied to the release pin ring in a direction parallel to the axis of the release pin.

*3.6 Workmanship. - All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

3.7 First article inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

*4.1 Responsibility for inspection. - The responsibility for inspection shall comply with MIL-A-48078 (PA).

4.1.1 Submission of product. - At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted.

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agents authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 Classification of inspections. - See MIL-A-48078

*4.3 First article inspection. - Prior to the start of regular production the contractor shall submit a first article sample to a Government approved facility (see 6.2b) as designated by the contracting officer for evaluation in accordance with the provisions of 4.3.2. The first article sample will consist of 100 assemblies and 25 complete sets of parts and sub-assemblies (i.e. 25 each of every component and sub-assembly, including at least five (5) items from each cavity used to produce die cast parts and be so identified as to permit tracing each item to the cavity in which it was molded) which have been produced by the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials including packaging and packing shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample including a certificate of conformance for materials. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.3.1 Submission. - The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2 and 4.3.3. The first article sample shall consist of the following items in sample quantities as indicated.

	Part Description	Drawings	Quantity
a.	Firing Device, Demo Pull Type M1 Assembly	8797612	100
b.	All other components		25
c.	Head	8797614	5 (Consecutively produced from each cavity of each mold)
	Tube, Housing	8797613	
	Base Coupling	8837263	

4.3.2 Inspections to be performed. - The First Article parts submitted in accordance with paragraph 4.3.1 will be submitted by the Government to any or all the requirements of the applicable drawings and to the inspections and tests of this specification.

4.3.2.1 Embrittlement of springs. - A sample of ten (10) loading springs or compression springs, as applicable, shall be tested as specified in 4.5.1.

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:36Z
Check the source to verify that this is the current version before use.

4.3.2.2 Pull test of cotter pins. - A sample of twenty-five (25) cotter pins shall be tested as specified in 4.5.2.

4.3.2.3 Non-functioning test. - A sample of fifty (50) firing devices shall be tested as specified in 4.5.3.

4.3.2.4 Functioning test. - A sample of fifty (50) firing devices shall be tested as specified in 4.5.4.

4.3.2.5 Load test of springs at assembled height. - A sample of ten (10) loading springs, and compression springs, as applicable shall be tested as specified in 4.5.5.

4.3.3 Rejection. (see MIL-A-48078 (PA)).

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. - See MIL-A-48078 (PA). Lot numbering as required shall be in accordance with MIL-STD-1168. Each lot of firing devices shall contain percussion primers from not more than 1 lot interfix number from one manufacturer.

4.4.2 Examination. - See MIL-A-48078 (PA). The examinations listed in the following tables and subparagraphs shall be performed on inspection lots of the components or assemblies designated in the Classification of Defects and Test tables or paragraphs. Sampling plans for major or minor defects shall be in accordance with MIL-STD-105, Inspection Level II, unless otherwise specified. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 7548177
4.4.2.1	Wire, Trip				NEXT HIGHER ASSEMBLY 7548176
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Diameter of wire, minimum (min.)		0.40%	3.2	Gage
132.	Length of wire		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:
7

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 7548176
4.4.2.2	Assembly, Wire Spool				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:	None defined				
Minor: 201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8797617
4.4.2.3	Spring, Loading				NEXT HIGHER ASSEMBLY 8797612
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Solid Height, Maximum (max.)		0.40%	3.2	Gage
132.	Inside diameter, min.		0.40%	3.2	Gage
133.	Protective finish incomplete or inadequate		0.40%	3.2	Visual
134.	Ends not squared		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Spring, Compression				8797618
					NEXT HIGHER ASSEMBLY 8797612
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Solid height, max.		0.40%	3.2	Gage
132.	Inside diameter, min.		0.40%	3.2	Gage
133.	Outside diameter, max.		0.40%	3.2	Gage
134.	Protective finish incomplete or inadequate		0.40%	3.2	Visual
135.	Ends not closed		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8797619
4.4.2.5	Ring, Pin, Release				NEXT HIGHER ASSEMBLY 8797612
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Protective finish incomplete or inadequate		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:
11

Source: http://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Head				8797614
					NEXT HIGHER ASSEMBLY 8797612
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Diameter of large hole		0.40%	3.2	Gage
132.	Diameter of cotter pin hole		0.40%	3.2	Gage
133.	Location of cotter pin hole		0.40%	3.2	Gage
134.	Finish of large hole improper		0.40%	3.2	Visual
135.	Protective finish incomplete or inadequate		0.40%	3.2	Visual
136.	Color improper		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH #	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8797615
4.4.2.7	Pin, Release				NEXT HIGHER ASSEMBLY 8797612
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Small diameter below flange		0.40%	3.2	Gage
132.	Large diameter above flange		0.40%	3.2	Gage
133.	Diameter of through holes		0.40%	3.2	Gage
134.	Length from flange to cotter pin holes		0.40%	3.2	Gage
135.	Length of small diameter below flange, min.		0.40%	3.2	Gage
136.	True position of small diameter with large diameter above flange		0.40%	3.2	Gage
137.	Finish of small diameter below flange		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:
13

SARPA-QA FORM 2567 FEB 74

Downloaded: 2026-10-22T06:36Z Source: https://assist.dla.mil -- Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8797613
4.4.2.8	Tube, Housing				NEXT HIGHER ASSEMBLY 8797612
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Diameter of head seating counterbore, max.		0.40%	3.2	Gage
132.	Diameter of release pin cavity, min.		0.40%	3.2	Gage
133.	Diameter of firing pin cavity		0.40%	3.2	Gage
134.	Diameter of cotter pin hole		0.40%	3.2	Gage
135.	Diameter of release pin hole, min.		0.40%	3.2	Gage
136.	Pitch diameter of thread, max.		0.40%	3.2	Gage
137.	Minor diameter of thread, max.		0.40%	3.2	Gage
Minor:					
201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8797616
*4.4.2.9	Pin, Firing				NEXT HIGHER ASSEMBLY 8797612
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Diameter of hole (prior to slotting)		0.40%	3.2	Gage
132.	True position of hole with shoulder (prior to slotting)		0.40%	3.2	Gage
133.	Diameter of shoulder at tip, max.		0.40%	3.2	Gage
134.	True position of tip with shoulder		0.40%	3.2	Gage
135.	Profile of tip		0.40%	3.2	8802728
136.	Diameter of release pin end (prior to slotting)		0.40%	3.2	Gage
137.	Diameter of hole and diameter of release pin end (after slotting)		0.40%	3.2	Gage
138.	True position of release pin end with shoulder (prior to slotting)		0.40%	3.2	Gage
139.	Finish of release pin end improper		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8837263
#4.4.2.10	Base, Coupling				NEXT HIGHER ASSEMBLY 8797612
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:					
101.	Pitch diameter of large thread		0.40%	3.2	Gage
102.	Major Diameter of large thread		0.40%	3.2	Gage
Major B:					
131.	Pitch diameter of small thread		0.40%	3.2	Gage
132.	Major diameter of small thread		0.40%	3.2	Gage
133.	Inside diameter of primer cavity, max.		0.40%	3.2	Gage
134.	Diameter of flash hole, min.		0.40%	3.2	Gage
135.	Depth of primer cavity		0.40%	3.2	Gage
136.	Length of shipping cup end		0.40%	3.2	Gage
137.	Flash hole obstructed		0.40%	3.2	Visual
Minor:					
201.	Total length		0.65%	3.2	Gage
202.	Length to flange from end		0.65%	3.2	Gage
203.	Diameter of shipping cup end		0.65%	3.2	Gage
204.	Outside diameter below larger thread		0.65%	3.2	Gage
205.	Improper finish		0.65%	3.2	Gage
206.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8837262
*4.4.2.11	Base Coupling Assembly				NEXT HIGHER ASSEMBLY 8797612
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:					
101.	Primer missing or loose		0.40%	3.2	Visual/Manual
102.	Primer cocked (incorrectly seated)		0.40%	3.2	Visual
103.	Compound or other foreign matter on primer		0.40%	3.2	Visual
104.	Primer cracked, punctured or with deep scratch		0.40%	3.2	Visual
105.	Excessive compound		0.40%	3.2	Visual
106.	Crack, split or deep cut		0.40%	3.2	Visual
107.	Thread(s) damaged		0.40%	3.2	Visual
Major B:	None defined				
Minor:					
201.	Shipping cup missing or damaged		0.65%	3.2	Visual
202.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

17

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Assembly				8797612
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	Cotter Pin(s) missing		100%	3.2	Visual
2.	Cotter pin below firing pin not spread		100%	3.2	Visual
Major A:					
101.	Head loose		0.40%	3.2	Manual
102.	Head not crimped 360 degrees		0.40%	3.2	Visual
103.	Component missing or loose		0.40%	3.2	Visual/Manual
Major B:	None defined				
Minor:					
201.	Cord missing		0.65%	3.2	Visual
202.	Cord improperly tied		0.65%	3.2	Visual
203.	Marking incomplete, incorrect or illegible		0.65%	3.2	Visual
204.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Box, Fiberboard				8797446
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Box damaged		0.40%	3.2	Visual
132.	Sealing incomplete or inadequate		0.40%	3.2	Visual
Minor:					
201.	Contents loose		0.65%	3.2	Manual
202.	Marking incomplete, incorrect or illegible		0.65%	3.2	Visual
203.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.14	Sealed packed barrier bag (prior to packing in box)				8797446
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Waterproofness of barrier bag destroyed by rupture, puncture, or separation of heat seal		0.40%	3.2	Visual
132.	Evidence of crushed carton (see Note 1)		0.40%	3.2	Visual
Minor:					
201.	Heat seal of barrier bag located so that one or more subsequent seals cannot be applied		0.65%	3.2	Visual
202.	Marking of bag misleading or unidentifiable		0.65%	3.6	Visual

NOTES:

NOTE 1. - Package should be opened for inspection if there is evidence of crushing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8797447
4.4.2.15	Box, Packing				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Box damaged to the extent that contents are exposed or liable to become exposed		0.40%	3.2	Visual
132.	Top improperly assembled		0.40%	3.2	Visual
133.	Contents loose		0.40%	3.2	Manual
134.	Metallic seal missing		0.40%	3.2	Visual
Minor:					
201.	Marking incomplete, incorrect or illegible		0.65%	3.2	Visual
202.	Swivel missing		0.65%	3.2	Visual
203.	Closure incomplete or inadequate		0.65%	3.2	Visual
204.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:
21

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 20260-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 3139666
4.4.2.16	Packing, Shipping and Storage (Firing Device Pull Type, M1 with Spools Trip Wire) (Prior to closing)				NEXT HIGHER ASSEMBLY 2128158
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Any packing component missing, or improperly assembled		0.40%	3.2	Visual
Minor:					
201.	Number of dessicant units incorrect		0.65%	3.2	Visual
202.	Dessicant bags not properly secured		0.65%	3.2	Visual
203.	Indicator card missing		0.65%	3.2	Visual
204.	Number of inner packages incorrect		0.65%	3.2	Visual
205.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.17	Packaging, Shipping and Storage (Firing Device Pull Type, M1 with Spools Trip Wire)	1 OF 1	3139666
			NEXT HIGHER ASSEMBLY 2128158

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	C.F.R. markings missing or unidentifiable		100%	3.2	Visual
Major A:	None Defined				
Major B:					
131.	Edges of tray interfere with seal of box lid		0.40%	3.2	Visual/Manual
Minor:					
201.	Descriptive marking missing, misleading, or unidentifiable		0.65%	3.2	Visual
202.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

23

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.18	Pack, Shipping and Storage (For Firing Device Pull Type, M1, with Trip Wire) (Prior to closing)				2128158
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Package missing or positioned improperly		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.19	Pack, Shipping and Storage (for Firing Device Pull Type, M1, with Trip Wire)				2128158
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	C.F.R. marking missing or not legible		100%	3.2	Visual
Major A:	None defined				
Major B:					
131.	Wire binding not properly secured		0.40%	3.2	Visual
132.	Car seal missing		0.40%	3.2	Visual
Minor:					
201.	Descriptive marking missing, misleading or unidentifiable		0.65%	3.2	Visual
202.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

25

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Embrittlement of springs. (see 3.3, dwg. 8797617 and dwg. 8797618) - Major A defects. - A sample of ten (10) loading springs or compression springs, as applicable, shall be selected from each heat treatment batch. A heat treatment batch shall be restricted to those springs that are heat treated for removal of hydrogen embrittlement at the same time in accordance with identical requirements specified on the applicable drawings. The sample shall be tested as specified in 4.5.1 and the heat treatment batch shall be rejected if one or more springs fail to comply with the specified requirement.

4.4.3.2 Pull test of cotter pins. (see dwg. 8797612) - Major A defect. - The sampling plan for this requirement shall be in accordance with MIL-STD-105 using Code Letter H and an AQL of 1.00 percent. The test shall be performed as specified in 4.5.2, using test equipment specified in 4.4.4.

4.4.3.3 Non-functioning (See 3.4) - Major A defect. - The sampling plan for this requirement shall be in accordance with MIL-STD-105 using Code Letter H and an AQL of 1.00 percent. The test shall be performed as specified in 4.5.3, using test equipment specified in 4.4.4.

4.4.3.4 Functioning (see 3.5) - Major A defect. - The sampling plan for this requirement shall be in accordance with MIL-STD-105 using Code Letter H and an AQL of 1.00 percent. The test shall be performed as specified in 4.5.4, using test equipment specified in 4.4.4.

4.4.3.5 Check test for possible deterioration of primers - Major A defect. - If the total elapsed time between the original acceptance of any primer lot and the assembly of that lot into the firing devices exceeds two years, or if the primers have been subjected to adverse conditions, however brief, at any time since previous test, the primer lot shall be subjected to and must satisfactorily pass the check test specified in MIL-P-12951 immediately before the primer lot is assembled into the firing device assembly. This test shall be performed by the contractor on primers selected by the Government inspector at the facility assembling the primer lot into the firing device assembly and shall be conducted at Government expense without cost to the contractor (see 6.5), who loaded the primers or the contractor assembling the primers into the firing device assembly. Furthermore, this test shall not constitute a basis of rejection against either contractor except where deterioration has occurred as a direct result of

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

4.4.3.6 Load test of springs at assembled height (see dwg. 8797617 and dwg. 8797618) - Major A defects. - A sample of ten (10) loading springs or compression springs, as applicable, shall be selected from each heat treatment batch. If any spring fails to comply with the applicable drawing requirement, the batch of springs represented by the sample shall be rejected. The test shall be performed as specified in 4.5.5 using equipment in accordance with 4.4.4.

4.4.3.7 Heat sealed seam test (see dwg. 8797446) Major Defect B. - Ten (10) fiberboard boxes in sealed barrier bags shall be selected from each lot for this test. If two or more packages show evidence of heat sealed seam separation, the lot shall be rejected.

4.4.4 Inspection Equipment. - The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078.

4.4.5 Dimensional control of cast parts. - (The requirements of this paragraph apply to those dimensions which are considered "as cast", and which do not undergo subsequent operations.) In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least five (5) parts (as cast) from each cavity shall be dimensionally inspected to qualify a new or reworked cavity for use in production and as a control of the cavity during production. The cast parts shall carry individual cavity identification when more than one cavity is used in production. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in paragraphs 4.4.5.1 through 4.4.5.3 after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. Individual cavity identification must be provided. If any defective parts are found during qualification of the cavity, the cavity producing the defective part shall not be used in production. If any defective parts are found when inspection is performed for control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

for corrective action, or for inspection for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All cavities or molds removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test specified above. The contractor may request a change of inspection frequency providing he presents objective evidence to substantiate the request to the Contracting Officer.

The following subparagraphs identify those items and the minimum inspections subject to the requirements of this paragraph. (Defect classifications of Major and Minor have been assigned to all defects listed herein).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER 8797614
4.4.5.1	Head				NEXT HIGHER ASSEMBLY 8797612
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Diameter of large hole	5 parts/cavity		4.4.5	Gage
132.	Diameter of cotter pin hole	5 parts/cavity		4.4.5	Gage
133.	Location of cotter pin hole	5 parts/cavity		4.4.5	Gage
134.	Evidence of poor workmanship	5 parts/cavity		4.4.5 & 3.6	Visual
Minor:	None defined				

NOTES:
29

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8797613
4.4.5.2	Tube, Housing				NEXT HIGHER ASSEMBLY 8797612
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:	None defined				
Major B:					
131.	Diameter of head seating counterbore, max.	5 parts/cavity		4.4.5	Gage
132.	Diameter of release pin cavity, min.	5 parts/cavity		4.4.5	Gage
133.	Diameter of firing pin cavity	5 parts/cavity		4.4.5	Gage
134.	Diameter of cotter pin hole	5 parts/cavity		4.4.5	Gage
135.	Diameter of release pin hole, min.	5 parts/cavity		4.4.5	Gage
136.	Pitch diameter of thread, max.	5 parts/cavity		4.4.5	Gage
137.	Minor diameter of thread, max.	5 parts/cavity		4.4.5	Gage
138.	Evidence of poor workmanship	5 parts/cavity		4.4.5 & 3.6	Visual
Minor:	None defined				

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil - Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF		DRAWING NUMBER
*4.4.5.3	Base, Coupling				8837263
					NEXT HIGHER ASSEMBLY 8797612
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:					
101.	Pitch diameter of large thread	5 parts/cavity		4.4.5	Gage
102.	Major Diameter of large thread	5 parts/cavity		4.4.5	Gage
Major B:					
131.	Pitch diameter of small thread	5 parts/cavity		4.4.5	Gage
132.	Major diameter of small thread	5 parts/cavity		4.4.5	Gage
133.	Inside diameter of primer cavity, max.	5 parts/cavity		4.4.5	Gage
134.	Diameter of flash hole, min.	5 parts/cavity		4.4.5	Gage
135.	Depth of primer cavity	5 parts/cavity		4.4.5	Gage
136.	Length of shipping cup end	5 parts/cavity		4.4.5	Gage
137.	Flash hole obstructed	5 parts/cavity		4.4.5	Visual
Minor:					
201.	Total length	5 parts/cavity		3.2	Gage
202.	Length to flange from end	5 parts/cavity		3.2	Gage
203.	Diameter of shipping cup end	5 parts/cavity		3.2	Gage
204.	Outside diameter below larger thread	5 parts/cavity		3.2	Gage
205.	Improper Finish	5 parts/cavity		3.2	Gage
206.	Evidence of poor workmanship	5 parts/cavity		4.4.5 & 3.6	Visual

NOTES:
31

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

4.5 Test Methods and Procedures

4.5.1 Embrittlement of springs. - Springs to be tested for embrittlement shall be extended to the point of minimum permanent distortion. Any spring which breaks or fractures when tested shall be classed defective.

4.5.2 Pull test of cotter pins. - The assembly shall be mounted in the applicable test fixture specified in 4.4.4. A steady increasing force shall be applied, without impact, to the cotter pin in a direction parallel to the length of the pin and shall be applied at the eye. The assembly shall be classed defective if the force required to withdraw the cotter pin from the assembly is not in accordance with the limits specified on the applicable drawing.

4.5.3 Non-functioning. - The assembly shall be mounted in the applicable test fixture specified in 4.4.4. The cotter pins shall be removed from the assembly and the specified non-functioning load shall be applied to the release pin in a direction parallel to the axis of the pin. Observation shall be made for actuation of the firing pin. The assembly shall be classed defective if the firing pin is released.

4.5.4 Functioning. - The assembly shall be mounted in the applicable test fixture specified in 4.4.4. The cotter pins shall be removed from the assembly and the specified functioning load shall be applied, without impact, to the release pin in a direction parallel to the axis of the release pin. Observation shall be made for actuation of the firing pin. The assembly shall be classed defective if the firing pin fails to release or if the primer fails to function.

4.5.5 Load test of springs at assembled height. - The springs shall be maintained at the specified height for 24 hours minimum. The springs shall then be tested for compliance with the load requirement.

4.5.6 Heat sealed seam test. - This test shall be performed as specified in MIL-P-116.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging

5.1.1 Level A

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

5.1.1.1 Packaging. - Packaging, shall be in accordance with dwg. 8797446.

*5.1.1.2 Level A. - For Marine Corps use, preservation and packaging shall be in accordance with dwg. 3139666.

5.2 Packing

5.2.1 Level A. - Packing shall be in accordance with dwg. 8797447.

*5.2.2 Level A. - For Marine Corps use, packing shall be in accordance with dwg. 2128158.

5.3 Marking . - Marking shall be in accordance with dwgs. 8797446 and 8797447 or dwgs. 3139666 and 2128158.

6. NOTES

*6.1 Intended Use. - This firing device is intended for use with improvised anti-personnel mines, for booby trapping anti-tank mines, and for setting boobytraps.

6.2 Ordering data . - Procurement documents shall specify the following

a. Title, number and date of this specification.
b. Provisions for submission of first article samples.
c. Provisions of MIL-A-48078.
d. For Marine Corps packing, packaging and marking see 5.1.2 and 5.2.2.

*6.3 Submission of designs for approval. - (see 6.2.3 of MIL-A-48078 (PA). Designs shall be submitted for approval to Commander: Picatinny Arsenal, ATTN: SARPA-QA-T-T Dover, New Jersey 07801.

6.4 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M, Dover, New Jersey 07801.

6.5 Check Test. - The Contracting Officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check test for possible deterioration.

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:36Z
Check the source to verify that this is the current version before use.

Asterisks -

6.6 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-105

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 JAN 72 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED.

Source: https://assist.dla.mil - Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.