MIL-F-46657D(PA)
AMENDMENT 1
6 MAY 1976

MILITARY SPECIFICATION

FIRING DEVICE, DEMOLITION, PULL TYPE, M1
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-F-46657D(PA) dated 15 August 1974 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 To Specifications add the following:

"Federal

TT-E-516 - Enamel, Lusterless, Quick-Drying Styrenated Alkyd Type"

To Specifications - Military add the following:

"MIL-F-11195 - Lacquer, Lusterless, Hot Spray"

PAGE 8

4.4.2.2 Delete: "Major B - None defined" and substitute as follows:

"Major B

131	Wire not tight	0.40%	3.2	Visual
132	Wire above flush	0.40%	3.2	Visual - Straight edge
133	End of wire not inserted into plastic spool I.D.	0.40%	3.2	Visual"

PAGE 27

4.4.3.8 - Add as follows:

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:36Z
Check the source to verify that this is the current version before use.

"4.4.3.8 Salt spray test of trip wire - Major A Defect Sampling plan for this test shall be in accordance with applicable protective finish apecified on drawings. Test shall be performed as specified in 4.5.7."

PAGE 31A

4.4.5.4 - Add new Classification of Defects as follows:

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46657D(PA)
AMENDMENT 1

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.5.4	Spool		9312585
			NEXT HIGHER ASSEMBLY
			7548176

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Height of spool	(a)	0.40%	3.2	Gage
132	Thickness of hub		0.40%	3.2	Gage
133	Diameter of body of spool		0.40%	3.2	Gage
134	Diameter of large hole		0.40%	3.2	Gage
Minor					
201	Location of small hole		0.65%	3.2	Gage
202	Diameter of small hole		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

(a) 5 parts per cavity

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:36Z
Check the source to verify that this is the current version before use.

PAGE 32

4.5.7 - Add as follows:

"4.5.7 Salt Spray Test - This test shall be performed in accordance with TT-E-516 or MIL-F-11195 whichever is applicable. The duration of the test shall be six (6) hours."

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-171

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:36Z
Check the source to verify that this is the current version before use.