MIL-P-46686C (MU)
20 August 1968
Superseding
MIL-P-46686B (MU)
30 June 1964

MILITARY SPECIFICATION

PRIMER, PERCUSSION, M92E1 PARTS FOR

1. SCOPE

1.1 This Specification covers the parts for one type of percussion primer designated as Primer, Percussion, M92E1.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons; General Specification for.
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedure and Tables for Inspection by Attributes.
MIL-STD-109 - Quality Assurance Terms and Definitions.
MIL-STD-1167 - Ammunition Data Card.
MIL-STD-1168 - Lot Numbering of Ammunition.
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components.
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS

ARMY

8863397 - Cap

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:40Z
Check the source to verify that this is the current version before use.

8863399 - Wad
8863400 - Tube
9231622 - Sleeve
9231699 - Head, Primer
9231700 - Body Assembly

PUBLICATIONS

ARMY

ET-8872317- Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on Drawings 8863399, 8863400, 8863397, 9231622, 9231699, and 9231700, as applicable, and with all requirements specified in applicable specifications.

3.3 Workmanship.-All parts shall be fabricated and finished in a thorough, workmanlike manner.

3.3.1 Metal components.-They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, cracks, chips, dirt, grease, corrosion and other foreign matter. The cleaning method used shall not be injurious to any parts nor shall the parts be contaminated by the cleaning agent.

3.3.2 Plastic components.-They shall be free from cracks, excessive flash, air bubbles, holes, blisters and foreign material.

3.3.3 First Article Inspection.- This specification makes provisions for first article inspection. Requirements for submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:40Z
Check the source to verify that this is the current version before use.

contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.

b. Number of units of product inspected.

c. Results obtained, by defect code, for all inspections performed.

d. Drawing, specification number and date, together with an identification and date of changes.

e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.

f. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission.- The contractor shall submit a first article sample designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of 10 each individual components, (see Note below) which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:40Z
Check the source to verify that this is the current version before use.

and equipment which will be used in fulfilling the contract. All parts and materials including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including statements of findings for materials, processes, and tests. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample or portion there of as directed by the contracting officer shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

Note: On molded parts when more than 1 (one) single cavity mold or multiple cavity molds are used in the fabrication of any component, 5 (five) sample components from each mold cavity shall be submitted in lieu of the above requirements of 10 (ten) samples of each component. Molded components shall be identified as to mold and cavity numbers.

4.2.2. Inspections to be performed.-Assemblies and components will be subjected by the Government to any or all of the examinations or tests specified in this specification and any or all requirements of the applicable drawings.

4.2.3 Rejection.-If any assembly or component fails to comply with any or all of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of assembly component in the sample to comply with any or all of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article sample or portion thereof. Until a first article sample is accepted, the contractor is, in no way, authorized by the Government to initiate regular production unless otherwise directed by the contracting officer.

4.3 Inspection provisions

4.3.1 Lot formation.-The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:40Z
Check the source to verify that this is the current version before use.

from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer, in one unchanged process using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. Changes to the process, specifications, or drawings, not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105. Unless otherwise approved by the contracting officer, the inspection lot size of end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lots of components or subassemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the contractor and the Government inspector. Lot numbering, as required, shall be in accordance with MIL-STD-1168.

4.3.2 Examination.-Inspection for Critical defects (and Major defects, when so specified), shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect, except where 100 percent inspection is specified. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.

4.3.2.1 Tube (see dwg. 8863400)

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:	None defined		
Major:	None defined		
Minor:	AQL 1.5 percent		
201.	Outside diameter.....	Gage	01001

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:40Z
Check the source to verify that this is the current version before use.

202.	Inside diameter	Gage	01002
203.	Length	Gage	01004
204.	Evidence of poor workmanship (see 3.3)	Visual	01003

4.3.2.2 Primer Head (see dwg. 9231699)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.0 percent		
101.	Flange thickness	Gage	06001
102.	Flange diameter, max.	Gage	06002
103.	Depth of primer element cavity counterbore, min.	Gage	06003
104.	Diameter of primer element cavity counterbore, min.	Gage	06004
105.	Diameter of primer element cavity	Gage	06005
106.	Pitch diameter of thread	Gage	06006
107.	Major diameter of thread	Gage	06007
108.	Diameter below the shoulder, max.	Gage	06008
109.	Radius of crimping groove, min.	Gage	06009
Minor:	AQL 4.0 percent		
201.	Depth of primer element cavity counterbore, max.	Gage	06010
202.	Depth of primer element cavity	Gage	06011
203.	Length of full threads, min.	Gage	06012
204.	Thread chamfer missing	Gage	06013
205.	Radius of crimping groove, max.	Gage	06014
206.	Location of crimping groove	Gage	06015
207.	Crimping groove having sharp edge	Visual-Manual	06016
208.	Fillet radius at base of flange, max.	Gage	06017
209.	Diameter of flash hole	Gage	06018
210.	Outside diameter of small end, min.	Gage	06019
211.	Chamfer missing at flash hole	Visual	06020
212.	Diameter of wrench hole	Gage	06021
213.	Location of wrench hole	Gage	06022
214.	Overall length	Gage	06023
215.	Evidence of poor workmanship (see 3.3)	Visual	06024

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:40Z
Check the source to verify that this is the current version before use.

4.3.2.3 Sleeve (see dwg. 9231622)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Wall thickness	Gage	07001
Minor:	AQL 1.5 percent		
201.	Outside diameter	Gage	07002
202.	Length	Gage	07003
203.	Evidence of poor workmanship (see 3.3)	Visual	07004

4.3.2.4 Body Assembly (see dwg. 9231700)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Sleeve not inserted all the way onto the tube	Visual	08001
102.	Cut or rupture of tube	Visual	08002
103.	Inner surface of tube at the reduced portion wrinkled or distorted	Visual	08003
Minor:	None defined		

4.3.2.5 Cap (see dwg. 8863397)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined		
Minor:	AQL 2.5 percent		
201.	Large diameter	Gage	04001
202.	Diameter of large end of taper	Gage	04002
203.	Thickness	Gage	04003
204.	Thickness of flange	Gage	04004

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:40Z
Check the source to verify that this is the current version before use.

205.	Angle of taper (max.)	Gage	04005
206.	Evidence of poor workmanship (see 3.3)	Visual	04006

4.3.2.6 Wad (see dwg. 8863399)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major: None defined			
Minor:	AQL 1.0 percent		
201.	Thickness, min.	Gage	05001
202.	Evidence of poor workmanship (see 3.3)	Visual	05002

4.4 Inspection Equipment.-Equipment Tabulation Number ET-8872317 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3.

4.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed in the ET shall be in accordance with Specification MIL-I-45607.

4.4.3 Government use of contractor's inspection equipment.-The contractor shall make available to the Government all inspection equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

5. PREPARATION FOR DELIVERY

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:40Z
Check the source to verify that this is the current version before use.

5.1 Packing and marking

5.1.1 Level C.-Packing and marking shall be in accordance with Standard MIL-STD-1169.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists (EL).-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:40Z
Check the source to verify that this is the current version before use.

for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND12. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:40Z
Check the source to verify that this is the current version before use.

for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 Submission of first article sample.-Instructions, as to the location for the evaluation of first article sample shall be obtained from the Contracting Officer. Upon receipt of such request, the Contracting Officer shall advise Picatinny Arsenal and instructions will be issued accordingly. All inquiries should be forwarded to: Commanding Officer, Picatinny Arsenal, ATTN: SMUAP-NI.

Custodian:
Army-MU

Preparing activity:
Army-MU

Projecct Number: 1390-A-653

☆ U. S. GOVERNMENT PRINTING OFFICE: 1968-341-511/A-1550

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:40Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE PLATE NO. 15419

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:40Z
Check the source to verify that this is the current version before use.