MILITARY SPECIFICATION

THRUSTER, PROPELLANT ACTUATED, XM24 PARTS FOR AND LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-T-46682A (MU) dated 26 February 1965.

Paragraph 3.7: Delete and substitute: "The thruster, while at a temperature of —25°F., shall function when a potential of 12 volts direct current maximum is applied between the leads. It shall have sufficient explosive force to shift the cover of a launching skid, M3, so that it will clear the center compartment sufficiently, so as not to impede or obstruct the flight of a faked linear charge or release the launching tube, loaded with an inert M95 rocket."

Paragraph 4.4.6: Delete entire paragraph and substitute: "The thruster shall be conditioned in a temperature chamber at —25°F plus or minus 5°F for a minimum of 24 hours. The thruster shall then be removed from the chamber and within 5 minutes of removal shall be assembled and tested as follows: The cover of the launching skid shall be fully engaged in the skid and the thruster assembly mounted on the guides. Observation shall be made for engagement of the plunger of the thruster assembly with the skid. The skid shall be anchored by two lines diverging from the forward eyebolt. The leads of the thruster shall be assembled to the power source and the unit functioned. Failure of the cover to trip the latch freeing the launcher tube or to clear the center compartment sufficiently to insure that it will not impede or obstruct the flight of the linear charge shall class the unit defective.

Custodian:

Army—MU

Preparing activity:

Army—MU

Project No. 1375-A957

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:40Z
Check the source to verify that this is the current version before use.