MIL-C-45956(WC)
AMENDMENT 2
11 June 1976
SUPERSEDING
AMENDMENT 1
18 December 1975

MILITARY SPECIFICATION

CONTROLLER, WEAPONS GUN SPEED

AND LAUNCHER BRAKE, LH

This amendment forms a part of Military Specification MIL-C-45956(WC), dated 23 July 1974.

Page 2

Paragraph 2.1 - Under "STANDARDS" add the following standard:

"MIL-STD-781 - Reliability tests: Exponential Distribution."

Page 7

Paragraph 3.4, line 6 - Delete "265 rounds" and substitute "283 rounds".

Paragraph 3.6 - Delete "When subjected to the EMI, the weapons controller shall not exhibit any detrimental damage or deterioration which would prevent acceptable performance."

Page 8

Paragraph 4.4:

Line 6 - After "contract" add "(see 6.2)".
Line 7 - Delete "(see 3.5)" and substitute "(see 3.5 and 4.6.3)".
Line 8 - Delete "(see 3.6)" and substitute "(see 3.6 and 4.6.4)".

Page 11

Paragraph 4.6.2 - At beginning of first sentence, add "When specified (see 6.2),".

FSC 1090

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:27Z
Check the source to verify that this is the current version before use.