INCH-POUND
MIL-C-45964B(AR)
20 October 1988

SUPERSEDING
MIL-C-45964A(AR)
7 November 1984

MILITARY SPECIFICATION

CANNON, 155MM HOWITZER: M185

This specification is approved for use by the Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification supports the acquisition of the Cannon, 155MM Howitzer: M185 consisting of a tube, breech mechanism, bore evacuator, and muzzle brake. This specification includes the minimum essential Engineering and Packaging Requirements and the necessary Quality Assurance Provisions to determine that these requirements have been met.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the soliciatation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-C-13931 - Cannon, General Specification for

MIL-P-14232 - Parts, Equipment and Tools for Army Material, Packaging of

MIL-I-45607 - Inspection Equipment, Acquisition, Maintenance and Disposition of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Armament Research, Development and Engineering Center, US Army Armament, Munitions and Chemical Command, ATTN: SMCAR-CCB-SAS, Watervliet, N.Y. 12189-4050 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1025

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:29Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-129 - Marking for Shipment and Storage

MIL-STD-1189 - Standard Symbology for Marking Unit Packs, Outer Containers, and Selected Documents

MIL-STD-1190 - Minimum Guidelines for Level C Preservation, Packing and Marking

MIL-STD-1235 - Single and Multi-1evel Continuous Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-2073-1 - DoD Material Procedures for Development and Appication of Packaging Requirements

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)'

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the-solicitation.

DRAWINGS (see 6.7) .

U.S. Army Armament Research, Development and Engineering Center (ARDEC)

F 11578365 - General Drawing, Cannon, 155MM Howitzer: N185

P11578365 - Packaging Data Sheet, Cannon, 155MM Howitzer: M185

PUBLICATIONS

Master LQAP 11578365 - Master Index of Quality Assurance Provisions for Cannon. 155MM Howitzer: M185

QAP-APPENDIX WVA - General Quality Assurance Provisions

(Copies of drawings, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity. or as directed by the Procuring Contracting Officer.)

2.2 Non-Government publications. The following document (s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:29Z
Check the source to verify that this is the current version before use.

American Society foresting and Materials (ASTM)

ASTM D 3951 - Commercial Packaging, Practice for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania I9103-1137J

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicavle laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General requirements. Cannon and component parts shall be in accordance with the applicable drawings (General Drawing F11578365), the requirements of this specification, the applicable-paragraphs of the General Cannon Specification_ MIL-C-13931 as incorporated in this document, and all referenced documents. Any conflicts are to be resolved by means of the order of precedence (see 2.3).

3.2 First article. The contractor shall submit a first article unless it is specifically waived in the contract (see 4.3 and 6.2). No first article requirements shall be waived without review and approval by the Procuring Contracting Officer (see 6.4 and 6.5).

3.3 Functioning. All parts shall function smoothly without interference, erratic movement or malfunction

3.3.1 Breech mechanism. Camming of the operating crank during counter-recoil or rotating the operating handle rearward and to the right shall force the breechblock operating rack downward and to the right. This action shall cause the breechblock to rotate counterclockwise to disengage the sectored threads. At this time sufficient force shall be exerted, through action of the operating crank, to overcome the carrier-latching plungers thereby releasing the plungers from the . catches attached to the breech ring and in turn allowing the carrier and breechblock assembly to swing to the open position. The breech mechanism shall be retained in the open position by means external to the cannon, i.e., engagement of the operating crank rollers in the operating cam of the mount.

3.3.2 Breech closing. With the adjustor set on the minimum preload position and the cannon at t e normal loading elevation, closing of the breech shall be accomplished by lifting the operating-cam of the mount clear of the operating crank rollers. Release of the crank shall allow the torsion springs to drive the crank clockwise and forcibly return the breechblock and carrier to the closed position. Action of the rack springs against the breechblock operating rack shall rotate the breechblock clockwise to engage the sectored threads. If the breech fails to close fully, manual closing shall be accomplished by engaging the clutch in the notch of the operating crank assembly and rotating the operating handle to

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:29Z
Check the source to verify that this is the current version before use.

the left and forward. The operating handle shall latch in the closed position. Counter-clockwise rotation of the adjustor shall increase the pre-load on the torsion springs.

3.3.3 Obturator surface. The obturator surfaces shall conform to the requirements prescribed in MIL-C-13931.

3.3.4 Block assembly. The block assembly, with the specified percussion-type firing mechanism mounted in position, shall slide in the slot in the housing assembly into the extract position when the breechblock is moved to the open position. As the extract position is reached, the extractor shall forcibly eject the primer out of the spindle chamber. When the breechblock, is moved to close the breech, the block assembly shall be automatically caromed from the extract to the load position while the extractor is caromed forward against the rear of the spindle. The block assembly shall be capable of moving to the clsed position only when the breechblock is closed and locked. In this position the block assembly shall also be capable of being moved manually into the load and extract positions.

3.4 Primer headspace. Primer headspace, the distance between the front face of the block assembly and the rear face of the obturator spindle, shall be not less than 0.054 inch nor more than 0.062 inch. "

3.5 Firing pin protrusion and retraction. The firing pin protrusion measured from the front face of the black shall be not less thean 0.114 inch and not more than 0.118 inch in the fired Position. Firing Pin retraction behind the front face of the block shall be not less than 0.008 inch.

3.6 Performance.

3.6.1 High pressure resistance. The cannon and tubes shall be capble of withstanding a chamber pressure of 43,500 ± 1500 psi.

3.6.2 Material soundness. After completion of acceptance testing, all parts shall be free of cracks and fractures and shall comply with soundness requirements " when specified on the applicable drawings and QAPs.

3.6.3 Bore enlargement. Bore diameters across lands, after firing no more than 15 rounds, shall not exceed the before firing diameters by more than 0.002

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where-such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:29Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection. Unless otherwise specified in the contract, (see 6.2.1}, First Article cannon and speified parts thereof shall be inspected by the contractor and submitted to the Government for approval. Inspection shall be in accordance with applicable Quality Assurance Provisions (QAPs) and QAP-APPENDIX-WVA. QAPs are listed in Master LQAP 11578365. First Article sammple sizes shall be as specified in applicable item QAPs, or the contract, as applicable. First article cannon and parts thereof shall be representative of the production processes to be used during quantity production.

4.3.1 First Article - Initial Production Test (FA-IPT). When specified in the contract, (see 6.2). First article cannon shaall be subjected to FA-IPT by the Government or any agency specified by the Government and may be conducted at a Government facility to assure compliance with the requirements of this specification and any additional requirements listed in the contract. FA-IPT procedures and the sample size of first article cannon shall be as specified in the contract. Firt article cannon and parts thereof shallb e representative of the production processes to be used during quantity production.

4.4 Quality conformance inspection. Quality conformance inspection is listed in Table 1.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:29Z
Check the source to verify that this is the current version before use.

TABLE I. TABLE Quality conformance inspection.

Categories/Characteristics	Requirement Paragraph	Inspection/Test Method Paragraph
Examinations		
Primer headspace	3.4	4.4.4.1
Firing pin protrusion and retraction	3.5	4.4.4.2
Material soundness	3.6.2	4.4.4.3
Packaging	5.	4.4.4.4
Functional inspections		
Cannon	3.3	4.4.5.1
Breech mechanism	3.3.1	4.4.5.2
Breech closing	3.3.2	4.4.5.2
Block assembly	3.3.4	4.4.5.3
Tests		
Proof acceptance	3.6	4.4.6.1
Proof firing		4.5.1
Proof pressure simulation		4.5.2

4.4.1 Inspection provisions. Cannon and parts thereof shall be inspected for conformance to the requirements of this specification, MIL-C-13931, QAPs listed in Master LQAP 11578365, and QAP-APPENDIX-WVA.

4.4.2 Inspection approval stamp. The application of the inspection approval stamp shall be as specified in MIL-C-13931

4.4.3 Inspection equipment. Inspection equipment used in the inspection of parts, subassemblies, and assemblies is prescribed in applicable item QAPs.

4.4.3.1 Acquisition, maintenance, and disposition. Unless otherwise specified (see 6.2.3), responsibility for acquisition, maintenance, and disposition of inspection equipment prescribed in applicable item QAPs, and for all other inspection equipment required to perform inspection prescribed by applicable specifications, or the contract, shall be in accordance with MIL-I-45607.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:29Z
Check the source to verify that this is the current version before use.

4.4.3.2 Accuracy of standard measuring equipment. When commercial and modified-commercial inspection equipment is used, it shall be capable of repetitive measurements to an accuracy of 10 percent of the total tolerance of the characteristic being inspected.

4.4.4 Examinations.

4.4.4.1 Primer headspace. Primer headspace shall be gaged on each cannon with the applicable gage prescribed in the applicable item QAP, or with an approved equivalent gage. Cannon failing to meet the requirements of 3.4 shall be subject to rejection.

4.4.4.2 Firing pin protrusion and retraction, Firing pin protrusion and retraction shall be gaged on each cannon with the applicable gages prescribed in the applicable item QAP, or with approved equivalent gages. Cannon failing to meet the requirements of 3.5 shall be subject to rejection.

4.4.4.3 Material soundness. All external and internal surfaces of each tube, breech ring, breechblock, carrier housing, evacuator, and muzzle brake shall be examined by magnetic particle inspection in accordance with the procedures and acceptance criteria of the applicable General Data Drawings.

4.4.4.4 Packaging inspection. Packaging inspection for the level designated in the contract shall be performed in accordance with the applicable packaging data sheets and MIL-P-14232. Packages failing to comply with the packaging requirements shall be subject to rejection.

4.4.5 Functional inspections.

4.4.5.1 Cannon. Functioning tests shall be conducted in accordance with MIL-C-139 and as specified herein. A minimum of two complete cyclyes of operation shall be performed on each cannon.

4.4.5.2 Breech mechanism. Each breech mechanism shall be operated manually to determine smoothness of operation. Action of the operating handle shall be observed to insure that the handle will latch in the closed position after each complete cycle of operation. Any evidence of interference, erratic movement, or malfunction of any parts shall be cause for rejection.

4.4.5.3 Block assembly. Each block assembly shall be operated manually to determine whether requirements are met. Any deviation from the requirements of 3.3.4 shall be cause for rejection.

4.4.6 Tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:29Z
Check the source to verify that this is the current version before use.

4.4.6.1 Proof acceptance. Cannon shall be proof accepted through proof firing. breech mechanism proof pressure simulation tests, or both. Cannon and replacement tubes to be proof fired shall be-fired using the test method of 4.5.1. Failure to comply with the requirements of 3.6 shall be cause for rejection. -Breech mechanisms to be simulation proof tested shall be proof tested using the test method of 4.5.2. Failure to comply with the requirements of 3.6.1 and 3.6.2, shall be cause for rejection. Proof firing performed on a sampling basis shall be conducted as follows:

a. Based on CSP-1 of MIL-STD-1235 and an AQL of 1.0, the Procuring Contracting Officer shall" designate the appropriate initial quantity (i) and sample frequency (f), in the contract (see 6.2).

b. The first "i" quantity of cannon or tubes produced in a particular buy shall be proof fired. When the "i" quantity has been satisfied, sampling shall be put into effect using the "f" sampling frequency. If a cannon is rejected, sampling shall be discontinued and the "i" quantity reinstated. All cannon not proof fired shall have the breech mechanisms simulation proof tested in the Product Assurance Weapon Test Facility at Watervliet Arsenal or other Government approved test facility:

c. Successive production buys shall not require "i" quantities. However, if the time lag between two successive buys exceeds one year, or if a new cannon or tube contractor is utilized, a new "i" quantity shall be proof fired.

d. Proof fired cannon and replacement tubes, and simulation proof tested . breech mechanisms shall be furnished with applicable data on DA Form 2408-4 (Weapon Record Data), as specified by the Procuring Contracting. Officer:

e. When specified in the contract (see 6.2), the weapon simulation test facility shall be qualified as follows: a sample of breech mechanisms of cannon to be sent to the proving ground for proof firing shall be subjected initially to simulation proof testing at the weapon simulation test facility.

4.5 Test methods.

4.5.1 Proof firing. Proof firing shall be conducted at a Government approved test site. The procedure shall be as follows:

a. Each cannon or replacement tube shall be proof fired within the-proof pressure range specified in 3.6.1. If the lower limit is not attained additional rounds shall be fired until the minimum value is attained. The number of additional rounds shall not exceed five.

b. A facility mount may be used if necessary.

c. Chamber pressure shall be measured and recorded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:29Z
Check the source to verify that this is the current version before use.

d. After proof firing:

(1) The bore of each tube shall be examined for bore enlargement using an approved gage (3.6.3).

(2) Each tube shall be borescoped and magnetic particle inspected (see 4.4.4.3).

(3) The evacuator and muzzle brake of each tube assembly shall be magnetic particle inspected (see 4.4.4.3).

(4) Each breech mechanism and block assembly shall be examined for looseness or interference of fit and other defects of workmanship and function (see 4.4.5).

(5) Each breech mechanism shall be disassembled and examined for soundness of material. All components shall be examined to assure freedom from cracks and fractures. Each breech ring and breechblock and carrier shall be magnetic particle inspected (see 4.4.4.3).

(6) Each breech mechanism shall be cleaned and reassembled. Each breech mechanism and block assembly shall then be functioned in accordance with 4.4.5.

e. Cannon found to be defective at the proving ground shall be reported to the Product Assurance Directorate, Watervliet Arsenal, Watervliet, NY 12189~4050 and Benet Laboratories, Watervliet Arsenal, Watervliet, NY 12189-4050 within one working day. The test agency shall forward a Test Incident Report (TIR), incident to the deficiency, within three working days.

4.5.2 Proof pressure simulation. All cannon not proof fired at a proving ground shall have the breech mechanism proof tested in accordance with the following procedure:

a. Each breech mechanism shall be tested by means of suitable hydraulic pressure testing equipment at a pressure within the proof pressure range specified in 3.6.1.

b. Cycle time to achieve test pressure and release shall not exceed three minutes. Test pressure shall be immediately released upon its attainment with dwell time at test pressure not to exceed three seconds.

(1) When difficulty is encountered in attaining test pressure, the number of attempts in which 10 percent or less of the test pressure is attained, shall not be counted. The number of attempts in which over 10 percent of the test pressure is attained, shall not exceed five.

(2) If the cause of difficulty is not identified and corrected within five pressure cycles, the breech mechanism shall be subjected to proof firing as part of a cannon (see 4.5.1). A notification Of this condition shall be submitted with-the breech mechanism to the proving ground.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T04:29Z
Check the source to verify that this is the currentversion before use.

c. The peak pressure shall be recorded for each test and attached to inspection records identifiable with the specific breech mechanism undergoing test.

d. After the pressure test, each breech mechanism shall be examined for looseness or interference of fit and other defects of workmanship and function (see 4.4.502).

e. Each breech mechanism shall be disassembled and examined for soundness of material. All components shall be visually examined to assure freedom from cracks and fractures. Each breech ring, breechblock, and carrier shall be magnetic particle inspected (see 4.4.4.3).

f. Each breech mechanism shall be cleaned and reassembled. The breech mechanism and the block assembly shall then be functioned in accordance with 4.4.5.2 and 4.4.5.3.

5. PACKAGING

5.1 Cannon - Levels A, B and C. Cleaning, drying, preservation, unit packaging and packing of cannon shall be in accordance with the requirements of Packagaing Data Sheet (PDS) P11578365 and MIL-P-14232 for the level of protection specified in the contract (see 6.2).

5.2 Repair parts - Level A, B and C. Cleanig , drying, preservation, unit packaging and packing of repair parts, shall be in accordance with the applicable repair Part PDS and MIL-P-14232 or the applicable repair part SPI - and MIL-STD-2073-1′ for the level of protection specified in the-contract (see 6.2). When Level C requirements are not shown on the PDS/SPI, level C packaging shall be in accordance with MIL-STD-1190.

5.2.1 Level X - Industrial packaging. Cleaning; drying, preservation, unit packaging and packing of repair parts shall be in accordance with ASTMD 3951 when industrial packaging is specified in the contract (see 6.2).

5.2.1.1 Quantity in unit package (QUP). When Level C packaging in accordance with MIL-STD - 1190 or industrial packaging of repair parts is specified in the contract, the QUP shall be the same as specified in the contract (see 6.2).

5.3 Marking of packages.

5.3.1 Levels A, B and C. Marking of the unit package, Intermediate packages, and exterior shipping containers shall be in accordance with MIL-STD-129. When-specified (see 6.2), bar code marking shall be in accordance with MIL-STD-129 and MIL-STD-1189.

5.3.2 Level X - industrial. Marking of the unit package, intermediate packages, and exterior shipping containers shall be in accordance with ASTM D 3951. When specified (see 6.2), bar code marking shall be in accordance with MIL-STD-129 and MIL-STD-1189.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:29Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains Information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The cannon specified herein is intended for use with the Howitzer, Medium. Self-Propelled, 155MM: M109A1, M109A2, and M109A3 systems.

6,2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of the specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1).

c. Requirements for and the number of cannon, components thereof, or both to be submitted for first article by the contractor (see 3.2).

d. The examinations and tests to be performed by the contractor and the examinations and tests to be performed by the Government.

e. All inspection and test data that is required.

f. At whose expense a retest may be performed.

g. Any additional or extended examinations and tests beyond the scope of this specification.

h. Serial numbers for the cannon and repair tube assemblies.

i. Inspection equipment, responsibility for acquisition, manintenance, and disposition thereof, if other than as speciified (see 4.4.3).

j. Availability of inspection equipment from the Government.

k. Extent of contractor’s responsibility for Government furnished and for contractor-required final inspection equipment.

l. Applicable acceptance test procedures.

m. When a proof firing sampling plan is authorized, the proof firing sampling plan parameters: initial consecutive quantity (i), and sampling frequency (f) (see 4,4.6.1).

n. Under what conditions simulated firing may be performed, the test equipment available, and the procedures to be followed.

o. The levels of preservation, packaging, and packing required for cannon assemblies (see 5.1) and repair parts (see 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:29Z
Check the source to verify that this is the current version before use.

p. When applicable, bar code marking requirements (see 5.3).

q. When warranted, the application of MIL-Q-9858 or MIL-I-45208, as appropriate.

r. Unless otherwise specified, the application of MIL-I-45607 and MIL-STD-45662.

6.3 Consideration of Data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DID's) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DID's are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared 'to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Reference Paragraph	DID Number	DID Title	Suggested Tailoring
4.3	DI-T-4902	First Article Inspection Report	

The above DID's were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DID's are-cited on-the DD Form 1423.

6.4. First article. When first article inspection is required, the Procuring Contracting Officer should-provide specific guidance to offerors whether the " item(s) should be a preproduction sample, a first article sample, a first production item, a sample selected from the first lot of production items, a standard production item from the contractor's current inventory, and the number " of items to be tested as specified in 4.3. The Procuring Contracting Officer should also include specific instructions in-acquisition documents regarding - arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations - for bids should provide that the Government reserves the right to-waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government and that bidders offering such products, who wish to rely on-such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.5 Waivers and deviations. The Procuring Contracting Officer shall coordinate all requests for waiver or deviation to this specification with Benet Laboratories and the Product Assurance Directorate at Watervliet Arsenal.

6.6 Subject term (key word) listing.

Cannon, 155MM: M185
Howitzer, 155MM: M185

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:29Z
Check the source to verify that this is the current version before use.

6.7 Drawings. Drawungs listed in Section 2 or this specification under the heading "U.S. Army Armament Research, Development and Engineering Center" (ARDEC) may also-include drawings prepared by, and indentified as Watervliet Arsenal, Ordnance Corps, Weapons Command, or U.S. Army Armament Research and Development, Command, U.S. Army Armament, Munitions and Chemical Command, etc. Technical data originally prepared by these activities are now under the cognizance of ARDEC.

6.8 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1025-A165)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-45964B (AR)	CANNON, 155MM HOWITZER: M185

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:29Z
Check the source to verify that this is the current version before use.