INCH-POUND
MIL-C-45978A(AR)
12 February 1992
SUPERSEDING
MIL-C-45978(AR)
3 SEPTEMBER 1986

MILITARY SPECIFICATION
CANNON, 105mM HOWITZER: m205

This specification is approved for use by the Department of the ArMy and is available for use by all Departments and Agencies of the DEPartment of Defense.

1. SCOPE

1.1 Scope. This specification supports the acquisition of the Cannon, 105MM HOWITZER: M205 consisting of the tube and the breech mechanism assembly. This specification includes the minimum essential Engineering and Packaging Requirements and the necessary Quality Assurance Provisions to determine that these requirements have been met.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 specifiication standards and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Armament Research, Development and Engineering Center, US Army Armament, Munitions and Chemical command, ATTN: SMCAR-CCB-SC, Watervliet, NY 12189-4050 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

APISC N/A

Fsc 1015

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-C-13931 - Cannon, General Specification for

MIL-P-14232 - Parts, Equipment and Tools for Army Materiel, Packaging of

MIL-I-45607 - Inspection Equipment, Acquisition, Maintenance and Disposition of

MIL-H-63192 - Howitzer, Light, Towed, 105MM: M204

STANDARDS

MILITARY

MIL-STD-129 - Marking for Shipment and Storage

MIL-STD-1190 - Minimum Guidelines for Level C Preservation, Packing and Marking

MIL-STD-1235 - Single and Multi-Level Continuous Sampling Procedures and Table for Inspection by Attributes

MIL-STD-2073 -1 - DOD Materiel Procedures for Development & Application of Packaging Requirements

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (see 6.8)

U.S. Army Armament Research development Engineering

Master LQAP 11579150 - Master List of Quality Assurance Provisions for Cannon, 105MM Howitzer: M205

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

I 11579150 Cannon, 105MM Howitzer: M205

P11579150 - Packaging Data Sheet, Cannon 105MM Howitzer: M205

QAP-APPENDIX - General Quality Assurance Provisions -WA

(Copies of drawings, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the Procuring Contracting Officer.)

2.2 NON-GOVERNMENT publiations. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2) .

American Society for Testing and Materials (ASTM)

ASTM D 3951 - Commercial Packaging, Practice for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103-1137.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3* REQUIREMENTS

3.1 General requirements. Cannon and component parts shall be in accordance with the applicable drawings (11579150), this specification, MIL-C-13931, and all referenced documents. Any conflicts are to be resolved by means of the order of precedence (see 2.3).

3.2 First article. The contractor shall submit a first article unless it is specifically waived in the contract (see 4.4 and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

6.2). No first article requirements shall be waived without review and approval by the Procuring Contracting Officer (see 6.2).

3.2.1 First Artitle - Initial Production Testlna (FA-IPTI Requirement~ The requirements for First Article - Initial Production Testing are collected and included in Appendix A. *When* specified, these FA-IPT requirements are mandatory for compliance (see 6.2) .

3.3 Functional characteristic~ The cannon shall perform the firing, pressure sustaining, and projectile launching functions of the Howitzer, Light, Towed 105MM:M204. The breech mechanism, firing mechanism, and other moving parts shall function smoothly without interference, erratic movement or malfunction.

3.3.1 Breech mechanism. When the operating lever is unlatched and rotated clockwise (rearward) , it shall rotate the crank clockwise. The rotation of the operating lever shall cock the firing mechanism and cause the horizontally sliding breechblock to move to the right, and open the breech. The extractor shall eject the empty cartridge case from the breech chamber. When the operating lever is rotated counterclockwise, the breechblock shall move to the left, and close the breech.

3.3.2 Firing mechanism group. During the first thirty-five degrees clockwise rotation of the operating lever, the crank shall rotate the retractor cam counterclockwise. The rotation of the retractor cam shall cause the retractor to force the firing pin rearward past the sear and the firing pin spring shall compress. Rearward movement of the firing plunger shall pivot the trigger and the sear, which shall rotate and release the firing pin. The rotation of the sear and release of the firing pin shall cause the firing pin spring to expand and drive the firing pin forward to strike and fire the cartridge primer.

3.3.2.1 Firing plunger reset position The firing plunger reset position is an indication of the distance that the firing plunger is caromed forward as the breech mechanism is opened. This position shall be measured as the minimum recessed distance from the front face of the breech ring to the front end of the firing plunger. This distance shall be not less than 0.055 inch nor more than 0.110 inch.

3.3.2.2 firing plunger fire position The firing plunger fire position is an indication of the location of the firing plunger just as the firing pin is released by the sear (breech mechanism closed) . This position shall be measured as the recessed distance from the front face of the breech ring to the front end of the firing plunger. This distance shall be not less than

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T04:33Z
Check the source to verify that this is the current version before use.

0.330 inch nor more than 0.480 inch.

3.3.2.3 firing plunger fin 1 position The firing plunger final position is an indication of its maximum possible rearward travel (breech mechanism closed). This position shall be measured as the recessed distance from the front face of the breech ring to the front end of the firing plunger. This distance shall be not less #an 0.540 inch *nor* more *than* 0.580 inch.

3.3.2.4 Firing pin protrustion. firiwpinprotn=ion measured from the front face of the breechblock shall be not less than 0.130 inch nor more than 0.145 inch in the fired position.

3.3,2.5 *Firing pin over* travel. Firing pin over—travel is an indication of the maximum amount of firing pin travel beyond the sear as the breech mechanism is opened. Over-travel shall be not less than 0.145 inch nor more than 0.278 inch.

3.3.3 Headspace Headspace, the distance between the front face of the closed and locked breechblock and the rear face of the tube, shall be not less than 0.190 inch nor more than 0.200 inch.

3.4 Reliabilitv. Availability. Maintainability and Durability (RAM-D) The RAM-D requirements of the M204 Howitzer system are stated in MIL-H-63192(AR). Since the availability.requirements *are* specified for the M204 Howitzer system only, this attribute cannot be apportioned to the cannon. The requirements for Reliability, Maintainability, and Durability are collected and included in Appendix B. When specified, these requirements are mandatory for compliance.

3.5 Performance.

3.5.1 High Pressure resistance. The cannon and spare tubes shall be capable of withstanding a chamber proof pressure of 55,000 ~ 2,000 psi within its operating temperature range (see 30.3 *of* Appendix A) when tested as specified in 4.7.6.

3.5.2. Material soundness All parts shall comply with soundness requirements specified on the applicable drawings.

3.5.3 Bore enlargement. The bore diameters, measured across the rifled lands after proof firing no more than eight rounds shall not exceed the before firing diameters by more than the amounts shown in TABLE I.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T04:33Z
Check the source to verify that this is the current version before use.

TABLE 1. Bore enlargement.

Distance forward of the Commencement of rifling	0.10 inch	1 inch	1 cal.	2 cals to muzzle
mount (inches)	0.008	0.008	0.006	0.003

NOTE : Interpolate to determine the amount between given distances.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).

b. First Article - Initial Production Test (FA-IPT) (see 4.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

c. RAM-D Inspection (see 4.6)

d. Quality conformance inspection (see 4.7).

4.3 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in the applicable test document, applicable paragraph(s) in the specification, or in the applicable drawing.

4.4 First article inspection Unless otherwise specified in the contract (see 6.2 and 6.4) , first article cannon and specified parts thereof shall be submitted for inspection in accordance with QAP-APPENDIX-WVA and applicable item QAPs. First article cannon and parts thereof,shall be representative of the production processes to be used during quantity production. Quality Assurance Provisions (QAPs) are listed in Master LQAP 11579150. First article quantities are specified in the applicable item QAPs.

4.5 First Article Initial Production Test (FA-IPT). The requirements, tests, and test methods for FA-IPT are contained in Appendix A.

4.6 Reliabilitv, Maintainabilitv, and Durability The requirements, tests, and test methods for reliability, maintainability, and durability are contained in Appendix B.

4.7 Quality conformance inspection Quality conformance inspection shall be as specified in Table II.

TABLE 11. Quality conformance inspection.

Inspection	Requirement Paragraph	Test Paragraph	Test method Paragraph
1. Firing Plunger			
a. reset position	3.3.2.1	4.7.4.1	4.7.7.1.1
b. fire position	3.3.2.2	4.7.4.2	4.7.7.1.2
c. final position	3.3.2.3	4.7.4.3	4.7.7.1.3
2. Firing pin			
a. protrusion	3.3.2.4	4.7*4.4	4.7.7.1.4
b. over-travel	3.3.2.5	4.7.4.5	4.7.7.1.5
3. Headspace	3.3.3	4.7.4.6	4.7.7.1.6
4. High Pressure resistance	3.5.1	4.7.6	4.7.7.3.1 4.7.7.3.2

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T04:33Z
Check the source to verify that this is the current version before use.

5.	Material soundness	3.5.2	4.7.4.7	4.7.7.1.7
6.	Bore Enlargement	3.5.3	4.7.6	4.7.7.3.ld
7.	Packaging	5.	4.7.4.8	
8.	Breech mechanism and firing . mechanism group	3.3, 3.3.1, 3.3.2	4.7.5.1	4.7.7.2.1

4.7.1 Inspecti on provisions. Cannon and parts thereof shall be inspected for conformance to-the requirements of this specification. to MIL-C-13931, QAPs listed in Master LQAP li579150, QAP APPENDIX-WVA and any additional requirements listed in the contract (see 6.2).

4.7.2 Inspection apProval stamp. The application of the inspection approval stamp shall be as specified in MIL-C-13931.

4.7.3 Inspection equipment.

4.7.3.1 ACfquisition, maintenance and disposition. Unless otherwise specified (see 6.2) responsibility for acquisition, maintenance, "and disposition of inspection equipment prescribed in applicable item QAP's, shall be in accordance with MIL-I-45607 .

4.7.3.2 accuracy of commercial inspection equipment. When commercial and modified commercial inspection equipment is used, it shall be capable of repetitive measurements to *an accuracy* of 10 percent of the total tolerance of the characteristic being inspected.

4.7.3.2.1 Accuracy of prOof pressure measurim devices. The devices for measuring proof firing pressures shall have the following accuracy:

Device	Maximum error of measurement (%)
copper crusher gages	± 3 of reading
pressure transducers	± 2 of reading

4.7.4 Quality conformance examinations.

4.7.4.1 Firing plunger reset position. The firing plunger reset position shall be measured using the examination method of 4.7.7.1.1. Cannon failing to comply with the requirements of

Source: https://assist.dla.mil -- Downloaded: 2026t0-22T04:33Z
Check the source to verify that this is the currentversion before use.

3.3 .2.1 shall be cause for rejection.

4.7.4.2 Firing plunger fire position The firing plunger fire position shall be measured using the examination method of 4.7.7.1.2. Cannon failing to comply with the requirements of 3.3.2.2 shall be cause for rejection.

4.7.4*3 firing plunger final position. The firing plunger final position shall be measured using the examination method of 4.7.7.1.3. Cannon failing to comply with the requirements of 3.3.2.3 shall be cause for rejection.

4.7.4.4 Firing pin protrusion The firing pin protrusion shall be *measured using the* examination method & 4.7.7.1.4. Cannon failing to comply with the requirements of 3.3.2.4 shall be cause for rejection.

4.7.4.5 Firing Din Ov r-travel. The firing pin over-travel shall be measured usin~ the examination method of 4.7.7.1.5. Cannon failing to comply with the requirements of 3.3.2.5 shall be cause for rejection.

4 . 7 . 4 . 6 Headspace shall be measured using the examination method of 4.7.7.1.6. Cannon failing to comply with the requirements of 3.3.3 shall be cause for rejection.

4.7.4.7 Material soundness.

4.7.4.7.1 BorescoPe and Magnetic Particle All surfaces of each cannon tube, breech ring, and breechblock shall be magnetic particle inspected using the methods of 4.7.7.1.7.1 and 4.7.7.1.7.2. Failure to comply with requirements of 3.5.2 shall be cause for rejection.

4.7.4.8 packaging *in*Spection. Unless otherwise specified, inspection to determine compliance with packaging requirements of Section 5 and the applicable packaging data sheet for the level designated *in* the contract shall be as specified in MIL-P-14232.

4.7*5 Quality conformance functional inspections.

4.7.5.1 Breech mechanism and firing mechanism arOUnD. The breech mechanism and the firing mechanism shall be inspected using the method of 4.7.7.2.1. Cannon failing to comply with the requirements of 3.3, 3.3.1, and 3.3.2 shall *be* rejected.

4.7.6 Proof acceptance. Cannon shall be proof accepted through proof firing, simulation tests, or both. Cannon and spare tubes to be proof fired shall be tested using the method of 4.7.7.3.1. Failure to comply with the requirements of 3.5.1, 3.5.2, and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

3.5.3 shall be cause for rejection. Cannon breech mechanisms to be simulation tested shall be tested using the method of 4.7.7.3.2. Failure to comply with the requirements of 3.5.1 and 3.5.2 shall be cause for rejection. Proof firing shall be done on a sampling basis and shall be conducted as follows:

a. Using sampling plan CSP-1 of MIL-STD-1235, the Product Assurance Directorate at Watervliet Arsenal will designate the appropriate initial quantity (i) and sample frequency (f) in the contract (see 6.2).

b. The first "i" quantity of cannon or spare tubes produced in the particular buy shall be proof fired. When the 'i" quantity has been satisfied, sampling shall be put into effect using the "f" sampling frequency. All cannons not proof fired shall have the breech mechanisms simulation proof tested in the Product Assurance weapon test facility at Watervliet Arsenal.

c. Successive production buys shall not require "i" quantities. However, if the time lag between two successive buys exceeds one year, or if a new cannon or tube contractor is utilized, a new "i" quantity shall be proof fired.

do Proof fired cannon and spare tubes, and simulation tested breech mechanisms shall be furnished with applicable data on DA Form 2408-4 (Weapon Record Data) as specified by Watervliet Arsenal Product Assurance Directorate.

4.7.7 Methods of Inspection.

4.7.7.1 Examination methods.

4.7.7.1.1 Firing plunger reset Position. The firing plunger reset position shall be gaged on each cannon with the applicable gage referenced in the applicable item QAP or with Government approved equivalent gage.

4.7.7.1.2 Firing plunger f i r e position. Firing plunger fire position shall be gaged on each cannon with the applicable gage referenced in the applicable item QAP or with Government approved equivalent gage.

4.7.7.1.3 Firing plunger final p ition Firing plunger final position shall be gaged on each cannon with the applicable gage referenced in the applicable item QAP or with Government approved equivalent gage.

4.7.7.1.4 Firing pin protrusion. Firing pin protrusion shall be gaged on each cannon with the applicable gage referenced in the applicable item QAP or with Government approved equivalent gage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

4.7.7.1.5 Firing Pin over-travel. Firing pin over-travel shall be gaged on each cannon with the applicable gage referenced in the applicable item QAP or with Government approved equivalent gage.

4.7.7.1.6 HEADSPACE Headspace shall be gaged on each cannon with the applicable gage referenced in the applicable item QAP or with Government approved equivalent gage.

4.7.7.1.7 material soundness.

4.7.7.1.7.1 BbORESCQPE EXAMINATION ~ The inner surface of each tube shall be examined with a blacK-light borescope to assure aconformance with applicable drawings and specifications.

4.7.7.1.7.2 Magnetic particle Examination. The outer surface of each tube, all surfaces of each breechblock and each breech ring, shall be magnetic particle examined in accordance with applicable item QAPs.

4.7.7.2 Functional inspection methods.

4.7.7.2.1 Breech mechanism and firing mechanism group functional inspection The inspection shall be done either manually or through the use of a functional tester. A minimum of five complete cycles of breech operation shall be performed on each breech mechanism and firing mechanism group. An empty case cartridge, M14B3E1, shall be inserted into the chamber for each of the five cycles. When the breech is opened, the extractor shall eject the empty cartridge case from the breech chamber. For each of the-cycles, the firing plunger shall be activated upon closing the breech to assure that the firing pin operates as required.

4.7.7.3 Test Methods.

4.7.7.3.1 Proof firing test. Proof firing shall be conducted at a Government specified test site. The procedure shall be as follows:

a. Each cannon or spare tube submitted shall be proof fired once at 55,000 + 2,000 psi.

b. A facilities mount may be used if necessary.

c. Chamber pressure shall be measured (see 4.7.3.2.1) and recorded.

d. Bore enlargement shall be checked with a star gage, air gage, electronic gage, or other Government approved gage.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:33Z
Check the source to verify that this is the currentversion before use.

e. Cannon shall be borescoped (see 4.7.7.1.7.1) and magnetic particle inspected (see 4.7.7.1.7.2).

f. Cannon found to be defective at the proving ground, as a result of a critical failure, shall be reported to the Product Assurance Directorate, Watervliet Arsenal, Watervliet, NY 12189 and Benet Laboratories, Watervliet Arsenal, Watervliet, NY 12189 within one working day. The test agency shall forward an Equipment Performance Report (EPR), incident to the deficiency within three working days.

4.7.7.3.2 Breech mechanism simulation proof test. All cannon not proof fired at a proving ground shall have the breech mechanism tested in accordance with the following procedure:

a. Each breech mechanism shall be tested by means of a suitable hydrostatic pressure testing equipment for one application of an internal overpressure (proof pressure) of 55,000 + 2,000 psi. Proof pressure shall be immediately released upon attainment. Cycle time to achieve proof pressure and release shall not exceed one minute.

(1) When difficulty is encountered in attaining the test pressure the number of attempts in which 10 percent or less of the test pressure is attained shall not be counted. However, the number of attempts in which over 10 percent of the test pressure is attained shall not exceed five.

(2) If the cause of difficulty is not identified and corrected within five pressure cycles, the breech mechanism, as part of the cannon, shall be proof fired in accordance with 4.7.7.3.1.

(3) The peak pressure shall be recorded for each test pressure cycle and attached to the inspection records for the particular breech mechanism undergoing test.

b. After pressure testing, each mechanism shall be examined for looseness or interference of fit or function.

c. The breech mechanism shall be disassembled and examined for material soundness by magnetic particle inspection, conducted in accordance with specifications, procedures, and acceptance criteria as specified on applicable drawings.

5. PACKAGING

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

5.1 Cannon - Levels A, B and C. Cleaning, drying, preservation, unit packaging and packing of cannon shall be in accordance with the requirements of Packaging Data Sheet (PDS) P11579150 and MIL-P-14232 for the level of protection specified in the contract (see 6.2 and 6.5).

5.2 Repair parts - Level A, B and C. Cleaning, drying, preservation, unit packaging and packing of repair parts, shall be in accordance with the applicable repair part PDS and MIL-P-14232 or the applicable repair part Special Packaging Instruction (SPI) and MIL-STD-2073-1 for the level of protection specified in the contract (see 6.2 and 6.5). When Level C requirements are not shown on the PDS/SPI, Level C packaging shall be in accordance with MIL-STD-1190.

5.2.1 Level x - Industrial packaging Cleaning, drying, preservation, unit packaging and packing of repair parts shall be in accordance with ASTM D 3951 when industrial packaging is specified in the contract (see 6.2).

5.2.1.1 quantity in unit package (QUP) . When Level C packaging in accordance with MIL-sTD-1190 or industrial packaging of repair parts is specified in the contract, the QUP shall be the same as specified in the contract (see 6.2).

5.3 Marking of paackages.

5.3.1 Levels A, B and c Marking (including bar code marking) of the unit package, intermediate packages, and exterior shipping containers shall be in accordance with MIL-STD-129.

5.3.2 Level x - industrial. Marking of the unit package, intermediate packages, and exterior shipping containers shall be in accordance with ASTM D 3951 (see 6.2). Barcode marking shall be in accordance with MIL-STD-129.

6. NOTES

(Thus section contains information of a general or explanation nature that may be helpful, but is not mandatory.)

6 . Intended use. The cannon specified herein is intended for use with the 105MM M204 Howitzer system.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of the specification.

b. Issue of DODISS to be cited in the solicitation, and if

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:33Z
Check the source to verify that this is the current version before use.

required, the specific issue of individual documents referenced (see 2.1.1) .

c. Requirements for and the number of cannon, components thereof, *or* both to be submitted for first article, first article initial production test (FA-IPT) or RAM-D tests by the contractor (see 3.2, 3.2.1 or 3.4).

d. The examinations and tests to be performed by the contractor and the examinations and tests to be performed by the Government.

e. All inspection and test data that is required.

f. At whose expense a retest may be performed.

g" Any additional or extended examinations and tests beyond the scope of this specification.

h. Serial numbers for the cannon and repair tube assemblies.

i. Inspection equipment, responsibility for acquisition, maintenance, and disposition thereof, if other than as specified (see 4.7.3.1).

j. Availability of inspection equipment from the Government.

k. Extent of contractor's responsibility for Government furnished and for contractor required final inspection equipment.

1. Applicable acceptance test procedures.

m. When a proof firing sampling plan is authorized, the proof firing sampling plan parameters: initial consecutive quantity (i), sampling frequency (f) and an AQL of 1.0 (see 4.7.6a).

n. Under what conditions simulated firing may be performed, the test equipment available, and the procedures to be followed.

o. The levels of preservation, packaging, and packing required for cannon assemblies (see 5.1) and repair parts (see 5.2).

p. Marking and bar code marking requirements (see 5.3).

q. When warranted, the application of MIL-Q-9858 or MIL-I-45208, as appropriate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

r. Unless otherwise specified, the application of MIL-I-45607 and MIL-STD-45662.

s. Monthly reports of the results of final examination and performance testing shall be as specified for delivery on DD Form 1423 in the contract.

6.3 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DID's) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DID's are tailored to reflect the requirements of the specific aquisition To ensure correct contractual application of the data requirements a contract Data Requirements List (DD Form 1423) must be PrePared to obtain the . data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Reference paragraph~	DID Number	DID Title.	suggested Tailoring
3.2	DI-T-4902	First Article Inspection Report	

The above DID's were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DID's are cited on the DD Form 1423.

6.4 First article. men first article inspection is required, the Procuring Contracting Officer should provide specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a first production item, a sample selected from the first lot of production items, a standard production item from the contractor's current inventory, and the number of items to be tested as specified in 4.4. The Procuring Contracting Officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government-reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit

Source: https://assist.dla.mil -- Downloaded: 20261O-22T04:33Z
Check the source to verify that this is the current version before use.

alternate bids unless specifically requested to do so in the solicitation.

6.5 Conditions for use of level B preservation. When level B preservation is specified (see 5.1 and 5.2), this level of protection should be reserved for the acquisition *of* cannon, parts thereof, and repair parts for supply worldwide under known favorable handling,... transportation , and storage conditions.

6.6 Waivers and deviations. The Procuring Contracting Officer shall coordinate all requests for waiver or deviation to this specification with Benet Laboratories and the Product Assurance Directorate at Watervliet Arsenal.

6.7 Subject term (key word) lising.

Cannon, 105MM Howitzer: M205
Howitzer, Light, Towed:105MM, M204

6*8 Drawings. Drawings listed in Section 2 of this specification under the heading "U.S. Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as Watervliet Arsenal, ordnance Corps, Weapons Command, or U.S. Army Armament Research and Development Command, U.S. Army Armament, Munitions and Chemical Command, etc. Technical data originally prepared by these activities are *now* under the cognizance of *ARDEC.*

6.9 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:

Army-AR

Preparing activity:

Army-AR

(Project 1015 -A333)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

APPENDIX A

FIRST ARTICLE-INITIAL PRODUCTION TESTING REQUIREMENTS FOR CANNON: 105MM M205

10. SCOPE

10.1 sCOPE- This AppendiX details all. requirements and inspection methods necessary for First Article - Initial Production Testing (FA-IPT). This Appendix is a mandatory part of the specification. The information contained herein is intended for compliance.

20. APPLICABLE DOCUMENTS. This section is not applicable to this Appendix.

30. REQUIREMENTS

30.1 FA-IPT testing FA-IPT tests shall be conducted on cannon or critical assemblies or parts thereof when:

a. a new contractor is utilized,

b. a time lapse of one year has occurred since the item was last produced by the contractor,

c. significant changes have been made in a manufacturing process or material,

d. a design change is made.

If the cannon or critical assemblies or parts thereof fail FA-IPT testing, then failure analysis shall be invoked (see 40.4).

30.2 Proof Firing Test. The requirements for the proof firing are contained in 3.5.1, 3.5.2, and 3.5.3.

30.3 CLimatic= The cannon shall function satisfactorily within the temperature range of +125°F to -50°F. Satisfactory function shall be defined as the breech closing on loading a round, firing of the round and ejection of the empty cartridge case with the breech remaining open after ejection. In addition, the breech must perform the firing and ejection functions without damage to the breech components.

30.4 RAM-D. The requirements for RAM-D are contained in Appendix B of MIL-C-45978. When specified, these RAM-D requirements shall be met during FA-IPT.

40. INSPECTION METHODS

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T04:33Z
Check the source to verify that this is the current version before use.

APPENDIX A

40.1 First Article Initial Production Test (FA-IpT) When specified in the contract (see 6.2), first article cannon shall be subjected to first article initial production testing (FA-IPT) by a Government activity to assure compliance with the requirements of this specification and the contract.

40.1.1 Sample. Two first article cannon shall be randomly selected from the first month's production. First article cannon and parts thereof shall be representative of the production processes to be used during quantity production. When specified, two additional cannon shall be included for RAM-D testing (see Appendix B, 40.1.1).

40.1.2 Inspection Provisions. First article cannon shall be subjected to normal inspection per applicable item QAP's, quality conformance inspection (see 4.7) including proof acceptance (see 4.7.6) , and any additional requirements listed in the contract.

40.1.2.1 Physical Configuration Audit. One cannon selected from the first article sample shall undergo a physical configuration audit in addition to the normal inspection cited in 40.1.2.

40.1.2.2 Proof Acceptance Through Proof Firing. First article cannon shall have successfully passed proof acceptance (see 4.7.6) prior to commencement of First Article Initial Production Testing.

40.1.3 Tests. Unless otherwise specified herein or in the contract, first article cannon tests listed in this specification shall be performed in a fully operational Howitzer, Light, Towed, 105mm:M204, and shall not normally be integrated with other tests. Integration with Operational Testing by the user is allowable provided all components of the system conform to technical requirements.

40.2 Tests.

40.2.1 Proof Firing Test. The test method for the proof firing are contained in 4.7.7.3.1.

40.2.2 climatic Test. A climatic test shall be conducted on two cannon using the test method of 40.3.1. If the requirements of 30.3 are not complied with, acceptance shall be deferred and 40.4 shall apply.

40.2.3 RAM-D Tests. The tests to verify the RAM-X) requirements are contained in Appendix B.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T04:33Z
Check the source to verify that this is the current version before use.

APPENDIX A

4003 Test methods.

40.3.1 Climatic test A climatic test shall be conducted on two cannon with both the cannon and ammunition conditioned to the temperature specified in TABLE III. Ammunition used in this test shall be inert loaded Cartridge M760, Zone 8. BoresCope [see 4.7.7.1.7.1] and magnetic particle (see 4.7.7.1.7.2) examinations shall be conducted on cannon after firing in accordance with TABLE 111. Facilities components may be used if necessary.

TABLE 111. Climatic test schedule.

Rounds	Temperature of Cannon and Ammunition
5	+125F
5	25F
5	. 5oF

40.4 Failure analysis. The contractor shall assist" the Government in the failure analysis procedure by performing a dimensional, physical and visual examination of the FA-IPT components which are suspected to have caused the failure. Results shall be submitted to the Government for a failure cause determination. If it is determined that failure occurred because of deviation from specified dimensions, physical properties, or both, the contractor shall accomplish, as applicable, the following actions:

a. Evaluate and correct the applicable production processes and procedures to prevent recurrence of the same defects in future production.

b. Examine completely assembled cannon and partially assembled cannon and components to ensure that material containing the same defect is purged from the inventory and not presented to the Government for acceptance.

c. Submit the results of the failure analysis and the corrective actions taken to the Government for evaluation and approval of retest or continuation of test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

APPENDIX B

RELIABILITY, MAINTAINABILITY, DURABILITY REQUIREMENTS AND RELIABILITY SCORING CRITERIA FOR CANNON: 105MM M205

10. SCOPE

10.1 Score. This Appendix details all requirements and inspection methods necessary for Reliability, Maintainability and Durability. This Appendix also provides Reliability assessors guidelines for the consistent classification of failure for assessing the Reliability requirements of the Cannon: 105MM M205. This Appendix is a mandatory part of the specification. The information contained herein is intended for compliance.

20. APPLICABLE DOCUMENTS

STANDARDS

MILITARY

MIL-STD-721 - Definitions of terms for Reliability and Maintainability

MIL-STD-882 - System Safety Program Requirements

PUBLICATIONS

"XM204 Howitzer Scoring Criteria Plan" dated May 1973.

30. REQUIREMENTS

30.1 reliabilitv. The cannon as a component of a fully operational M204 Howitzer system, shall have a minimum acceptable value (MAV) of 1200 equivalent full charge (EFC) mean rounds between failure (MRBF) with a confidence level of 80%. Components most impacting cannon MRBF will be identified and designated as reliability sensitive in the contract or purchase order (see 6.2). To insure cannon reliability, special attention needs to be focused on these critical components. Emphasis should be placed on stringent component quality control and supplemental component tests in production.

30.2 Maintainability. The cannon parts and components shall have the following maintainabilities:

a. Tube: Cleaning and lubricating the tube after firing, in accordance with applicable maintenance procedures, to prevent corrosion shall be the only maintenance required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

b. Breech: Service of the breech shall be carried out by the crew and shall be limited to minor maintenance and cleanup. Disassembly, cleaning and reassembly of the breechblock, firing mechanism, and associated operating linkage shall be carried out by the crew within 1.5 man-hours. Repair shall be carried out at unit (company or battalion) level.

30.3 Durability The durability of the M204 Howitzer system as it pertains to & cannon shall be:

30.3.1 Fatigue The following are the required minimum durabilities for the tube and breech mechanism:

a. Tube - 7,500 EFC rounds.

b. Breech mechanism - 22,500 EFC rounds.

30.3.2 life The required minimum tube wear has not been apportioned to the tube. Data from future firings shall be analyzed to establish the tube wear requirement.

40. INSPECTION METHODS

40.1 RAM-D Test. RAM-D testing shall be performed at the completion of the FA-IPT test specified in Appendix A when:

a. There is a new producer or a change in producers.

b. Significant changes in the manufacturing processes have occurred.

c. Significant changes in the Technical Data Packages (TDP) have occurred.

d. Sufficient incidents have occurred with fielded systems to indicate that a RAM-D problem exists.

e. When specified in the contract.

NOTE: When RAM-D testing is required under paragraphs b, c, d, or e, the full RAM-D testing or a portion of the RAM-D testing may be specified by the engineering or product assurance activities. The scope of the testing shall be at the discretion of the engineering and product assurance activities at a level appropriate to the changes or incidents involved. When the change or the incident relates only to a specific component, then component level testing may be substituted for RAM-D testing at

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

the discretion of the engineering and product assurance activities. Simulation testing may be utilized if applicable.

40.1.1 RAM-D Sample The RAM-D test shall be performed on four cannon using the methods specified in 40.1.2. When RAM-D testing is to be performed, the sample shall consist of the two cannon that completed FA-IPT testing and two additional cannon.

40.1.2 RAM-D Tests At the completion of FA-IPT testing (see Appendix A), the RAM-D test shall be performed.

40.1.2.1 Reliability Test. The combined test (tube-wear and reliability) shall consist of firing 5 sequences, each sequence consisting of firing 96 rounds from each of 4 cannon. The type of round fired shall be as specified in Table IV.

40.1.2.2 Cannon reliability demonstration. To demonstrate that the reliability requirement has been satisfied, the tests specified in Table IV shall be performed without a reliability failure. Failure scoring criteria for assessing reliability requirements shall be in accordance with 50.2. If a failure occurs during testing, the failure analysis procedures outlined in 40.2 shall apply.

TABLE IV. RAM-D Test. *, **

SEQ.	CANNON REQ / D	ROUNDS PER CANNON	M760 ZONE 8 (TOTAL)	M760 ZOnE 8 (CUM. 1
1	4	96	384	384
2	4	96	384	768
3	4	96	384	1.152
4	4	96	384	1.536
5	4	96	384	1.920

GENERAL NOTES :

a. To demonstrate that the tube wear requirement has been achieved, the tests specified in Table IV shall be completed within the tube wear requirement. Failure to do so shall require the application of the procedures outlined in 40.2.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T04:33Z
Check the source to verify that this is the current version before use.

b. Rate of fire shall not exceed 3-5 rounds per minute.

* Borescope and measure tube ID at the beginning of each sequence.

** Magnetic particle inspect, borescope, and measure tube at at the end of each sequence.

40.1.2.3 cannon durability test method. The durability test shall be conducted on two cannon, essentially by hydraulic pressure cycling at the applicable service chamber pressure(s) of the cannon tube (54,0CM3 + 1,500 psi) and breech mechanism (breech ring and breechblock) (54,000 + 1,500 psi). Rounds fired in other tests of Appendices A and B may be counted as cycles for the durability tests.

I

40.1.2.3.1 Tube durability test method. The two tubes shall be conditioned by initial firing of 250 rounds from each tube. Durability shall be demonstrated by hydraulically pressurizing the two tubes at Watervliet Arsenal or other Government approved facility. Each tube shall be cycled to destruction at pressures conforming to the pressure travel curve for service ammunition. The fatigue life shall be consistent with the requirement of 30.3.l.a based on a log normal failure distribution. If the requirement is not satisfied, 40.2 applies.

40.1.2.3.2 Breech mechanism durability test method. Durability shall be demonstrated by hydrodynamic impact testing two breech mechanisms (breech ring and breechblock) at Watervliet Arsenal or other Government approved facility. Each breech mechanism shall be cycled to destruction at 43,7oo + 1,500 psi. The fatigue life shall be consistent with the requirement of 30.3.l.b based on a log normal failure distribution. If the requirement is not satisfied, 40.2 of Appendix B applies.

40.2 Failure analysis The contractor shall assist the Government in the failure analysis procedure by performing a dimensional, physical and visual examination of the FA-IPT components which are suspected to have caused the failure. Results shall be submitted to the Government for a failure cause determination. If it is determined that failure occurred because of deviation from specified dimensions, physical properties, or both, the contractor shall accomplish, as applicable, the following actions:

a. Evaluate and correct the applicable production processes and procedures to prevent recurrence of the same defects in future production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

b. Examine completely assembled cannon, partially assembled cannon and components to ensure that material containing the same defect is purged from the inventory and not presented to the Government for acceptance.

c. Submit the results of the failure analysis and the corrective actions taken to the Government for evaluation and approval of retest or continuation of test.

50. RELIABILITY SCORING CRITERIA

50.1 basis. This scoring criteria is based on the reliability scoring procedure approved by the Department of the Army. It was extracted from the "XM204 Howitzer Scoring Criteria Plan" dated May 1973. The Failure Scoring Procedure (see 50.2) provides for the use of the Failure definition (see 60.1.3) which is amplified (see 50.1.1). Failure modes (see 50.1.2], Degraded modes of Operation (see 50.1.3) and Failure exclusions (see 50.1.1.1) pertaining to the cannon provide additional failure scoring guidelines as specified in the "XM204 Howitzer Scoring Criteria Plan" dated May 1973.

50.1.1 Failure definition amplification.

50.1.1.1 The following are not considered as reliability failures:

a. Scheduled replacement of parts before failure.

b. An incipient malfunction corrected during scheduled preventive maintenance on the part in question provided a higher level of maintenance is not necessary.

c. A malfunction resulting from not following the prescribed operational or maintenance procedures or schedule dictated by the equipment manuals.

d. A malfunction resulting from test item abuse, unrealistic operating conditions or accident.

e. Actual or incipient malfunctions detected or corrected during initial technical inspections and incipient malfunction detected during final technical inspection.

50.1.1.2 The following are considered as reliability failures:

a. A failure detected and/or corrected during the correction of another failure provided the failures are totally unrelated.

b. Corrected incipient malfunctions not covered by 50.1.1.1 examples b and e.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

c. Failure detected and/or corrected during final technical inspection.

d. Failures resulting from lack of Clarity of instruction or other fault in the maintenance test package.

50.1.2 Failure modes The following are two typical failure modes for use in assesment of mission reliability failures. These failure modes are subject to performance degradation (see 50.1.3).

1. Breechblock cannot be closed or opened.

2. Gun will not fire.

50.1.3 Degraded modes of operation. A certain amount of performance degradation must take place before a reliability failure can be assumed. Of course, if the system ceases to function, performance becomes unacceptable (i.e., non-existent) ; however, if performance is only degraded, then some threshold must be established to define where reliability failures begin. Allowable degradation thresholds have been established for the various performance parameters. Performance beyond these thresholds constitutes a reliability failure. As long as performance remains above the threshold or is returned above the threshold within a five minute maintenance period, no reliability failure is charged. The allowable degradation thresholds are:

1. Rate of Fire - maximum	15 RPM (Rounds Per Minute)
2. Rate of Fire - sustained	3-5 RPM (Rounds Per Minute)

50.2 Failure scoring Procedure. The following scheme provides the instructions for the use of the Failure Definition (see 60.1.3) for assessing reliability requirements of the Cannon, 105MM Howitzer; M205 (see 50.1). These instructions assume that an incident or malfunction has occurred during test, and a record has been prepared against this action to the extent where it is necessary to determine the chargeability of the action. Incidents where the identification of a reliability failure is in doubt will be deferred to a user/developer/tester Scoring Conference. The step-by-step instructions for using the Failure Definition are as follows:

Step 1. Record the incident information (i.e. rounds on test item and system, description of incident, nature of maintenance action required, maintenance time in hours, maintenance manhours, etc.) when a malfunction of the cannon occurs or is

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

detected. Proceed to the next step answering the question posed and taking action according to the answer given.

Step 2. Is this a scheduled replacement of parts before failure? If yes, do not charge a failure; if no, proceed to step 3.

Step 3. Is this a malfunction resulting from not following the prescribed operational or maintenance procedures or schedule dictated by the equipment manuals? If yes, do not charge a failure; if no, proceed to Step 4.

Step 4. Is this a malfunction resulting from test item abuse, unrealistic operating conditions or accident? If yes, do not charge a failure: if no, proceed to Step 5.

Step 5. Is this an actual or incipient malfunction detected or corrected during initial technical inspection or an incipient malfunction detected during final technical inspection? If yes, do not charge a failure; if no, proceed to Step 6.

Step 6. Is this an incipient malfunction corrected during scheduled preventive maintenance on the part in question, provided a higher level of maintenance is not necessary? If yes, do not charge a failure; if no, proceed to Step 7.

Step 7. Is this incident related to or caused by another reliability failure? If yes, do not charge a failure; if no, proceed to Step 8.

Step 8. The following statements are addressed collectively. (A) The malfunction did not and would not cause a critical or catastrophic hazard to personnel or equipment as defined by MIL-STD-882 . (B) The system performance is above acceptable levels (see 50.1.3). (C) The malfunction did not and would not preclude the ability to commence or the cessation of any mode of operation (e.g., load and fire at any range, charge, elevation, or direction) (see 50.1.2). If all three of the above statements are true, do not charge a reliability failure; if any are not true, proceed to Step 9.

Step 9. Is the operator/crew authorized and able to remedy the malfunction by adjustment, repair, or replacement action within five minutes, using the controls, Basic issue Items (BII), Items Troop Installed or Authorized (ITIA) and parts authorized to the crew? If the answer is yes, do not charge a reliability failure; if no, proceed to Step 10.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

Step 10. If the previous 9 **steps** provide inconclusive evidence as **to the chargeability or non-chargeability of a reliability failure, the incident should be checked against the criteria of 50.1. If categorization of the incident remains in doubt, defer classification to a user/developer/tester Scoring Conference.**

60. RAM-D DEFINITIONS.

60.1 Reliability, Availability , Maintainability, and Durability (RAM-D) term and definitions **Reliability, maintainability and durability terms and definitions used in this** specification are in accordance with **MIL-STD-721** and **60.1.1**.

60.1.1 Durability. Durability is the probability that an item will successfully survive its projected life, overhaul point, or rebuild point (whichever is the more appropriate durability measure for the item) without a durability failure.

60.1.2 Durability failure. A durability failure is considered to be a malfunction that precludes further operation of the item and is great enough in terms of cost, safety, or time to restore, that the item must be replaced or rebuilt.

60.1.3 **Failure. For the purpose of assessing reliability, a failure is a malfunction that** the **operator or crew cannot *or is not* authorized to remedy by adjustment, repair, or replacement action within five** minutes, using the controls, **Basic Issue Items (BII), Items Troop Installed or Authorized (ITIA) and parts authorized to the crew, which causes or would cause:**

a. inability to commence or the cessation of any mode of operation.

b. a critical or catastrophic hazard to personnel or equipment as defined by **MIL-STD-882.** For **related** malfunctions only the primary malfunction **will be counted against reliability (see 50.1.1).**

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarifcation of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(c) or to amend contractual requirements.

1. DOCUMENT	2. DOCUMENT DATE (yymmdd)
MIL-C-45978A (AR)	2 FEBRUARY 1992

3. DOCUMENT TITLE

CANNON. 105MM HOWITZER: M205

4 NATURE OF CHANGE *identity paragraph number amd include proposed rewrite, if posible. Attach extra Sheets if needad.)*

5 REASON FOR RECOMMENDATION

6 SUBMITTER

NAME (Last, First, *Middle Initiial))* . ORGANZATION

ADDRESS (includes zip Code)

d. TELPHONE (Includes Area Code)
(1) *Commercial*
(2) AUTOVON (if applicable)

7. DATE SUBMITTED(YYMMDD)

8 PREPARING ACTIVITY

a. NAME US ARMY ARDEC Standarization Office

b. TELEPHONE (include Area Code)
(1) Commmercial (201)724-6662 (2)AUTOVON 880-6662

c. ADDRESS (Include Zip Code)
ATTN: SMCAR-BAC-S
PICATINNY ARSENAL, NJ 07806-5000

IF YOU DO NOT RECEIVE A REPLY WITHtN 45 DAYS, CONTACT:
Defense Quality and Standardozation Office
5203 Leesburg Pike, 1403, Falls Church, VA 22041-3466
Telephone *(703) 756-2340 AUTOVON 289-2340*

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.