MIL-F-45966
AMENDMENT 1
17 December 1976

MILITARY SPECIFICATION

FEEDER, AUTOMATIC GUN:

M89 AND M89E1

This amendment forms a part of Military Specification MIL-F-45966, dated 25 October 1974.

PAGE 5

Para 3.3.2 - Delete in its entirety and substitute the following:

"3.3.2 Endurance. The feeder shall withstand the feeding of 25,000 rounds of Government standard 20MM, M51A1B1 dummy cartridges or M55A2 cartridges with at least 250 clutching and declutching operations with no more than one stoppage or malfunction attributable to the feeder when operated at a steady state rate of 1,350 to 1,650 rounds per minute. Testing shall be as specified in 4.5.3.3."

PAGE 11

Para 4.6.2.2 - Delete sentence 6 and 7 and substitute the following:

"Scheduled preventative maintenance permitted during the test shall consist of lubrication of the feeder at each 2500 round interval using lubricant conforming to MIL-L-46150. In the event that the one permitted stoppage or malfunction occurs, the feeder may be repaired or adjusted as required. The nature of the stoppage or malfunction and the round at which it occurred shall be recorded. When this has been accomplished, the endurance test shall be continued."

Custodian:
Army - WC
Navy - OS

Preparing Activity:
Army - WC

Project Number:
1005-0573

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:30Z
Check the source to verify that this is the current version before use.