MIL-F-45966

25 October 1974
SUPERSEDING
(See Section 6)

MILITARY SPECIFICATION

FEEDER, AUTOMATIC GUN: M89 and M89E1

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of gun-driven feed mechanism for ammunition belted with M14 series links for use on the 20mm, M197 and M197E1 automatic gun. The feeder pulls in the link-belted ammunition, strips the ammunition from the links, ejects the empty links, and feeds the delinked ammunition into the gun. The feeder includes an electrically operated declutching feature for engaging or disengaging the drive.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-W-13855	-	Weapons, Small Arms and Aircraft Armament Subsystems, General Specification For.
MIL-P-14232	-	Parts, Equipment and Tools For Army Material, Packaging and Packing of.
MIL-I-45607	-	Inspection Equipment, Acquisition, Maintenance, and Disposition of.
MIL-L-46150	-	Lubricant, Weapons, Semi-Fluid (High Load-Carrying Capacity.

FSC 1005

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:30Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-109 - Quality Assurance Terms and Definitions.

DRAWINGS

U.S. Army Weapons Command

F11838573 - Feeder, Automatic Gun: M89.

F12007300 - Feeder, Automatic Gun: M89E1

PUBLICATIONS

U.S. Army Weapons Command

IEL11838573 - Index of Inspection Equipment List.

P11838573 - Packaging Data Sheet for Feeder, Assembly, Declutching: M89.

P12007300 - Packaging Data Sheet for Feeder, Assembly, Declutching, M89E1.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 First article. Requirements for submission of first article shall be as specified in the contract (see 6.2). Unless otherwise specified in the contract (see 6.2), the first article shall include the pilot pack (see 5.1).

3.2 Materials, construction and design. The feeders shall conform to the materials, construction and design requirements specified herein, on Drawing F11838573 (M89) or F12007300 (M89E1) and MIL-W-13855.

3.2.1 Clutch lock assembly. The clutch lock assembly shall slide freely on the shaft mounted sleeve bearing. The clutch lock assembly shall engage the driven gear and aft housing in the non-feed mode and shall smoothly engage the drive gear and driven gear in the feed mode.

3.2.2 Rotating vane. The rotating vane shall slide freely on the drive gear mounted sleeve bearing. The rotating vane shall rotate freely with the drive gear in the non-feed mode and shall slide relative to the drive gear, under actuation of the clutch wedge, so as to smoothly engage the clutch lock assembly in the drive gear in the feed mode.

Source: https://assist.dla.mil -- Downloaded: 202640-22T04:30Z
Check the source to verify that this is the current version before use.

3.2.3 Drive gear. The drive gear shall rotate freely on the aft housing and shall smoothly mesh with the feeder sprocket cluster gear. The drive gear shall drive the rotating vane during the non-feed mode and shall allow the rotating vane to shift axially so as to cause engagement of the clutch lock assembly during the firing mode. Three backlash pins mounted in the drive gear shall actuate smoothly for their full length of travel and shall return to the extended position due to spring action.

3.2.4 Clutch wedge. The clutch wedge shall slide freely on the guide pin mounted in the feeder aft housing assembly. When actuated by the wedge drive arm, the clutch wedge shall engage the rotating vane so as to cause it to move axially to initiate the feed mode.

3.2.5 Wedge drive arm. The wedge drive arm shall pivot freely on its mounting bolt. When actuated by the solenoid, the wedge drive arm shall shift the clutch wedge to the firing mode position.

3.2.6 Stripper sprocket assembly. The stripper sprocket assembly shall rotate freely and shall engage and advance linked (M14 type) 20mm ammunition through the link stripping guides and smoothly transfer the rounds to the accelerator sprocket assembly.

3.2.7 Accelerator sprocket assembly. The accelerator sprocket assembly shall rotate freely and smoothly transfer rounds from the stripper sprocket assembly to the feeder sprocket assembly.

3.2.8 Feeder sprocket assembly. The feeder sprocket assembly shall rotate freely and shall smoothly transfer rounds from the accelerator sprocket assembly to exit area of the feeder into position for hand-off of rounds to the gun.

3.2.9 T-bar guide assembly. The link guide (T-rail) shall engage the guide slot on the links and smoothly guide the link chain to the link exit area of the feeder. The repositioning guide shall support the forward part of the round during the stripping function and shall be capable of properly repositioning a round that has been improperly placed in the link in a nose forward condition.

3.2.10 Link stripper. The link stripper shall separate the rounds from the links and guide the body end of the rounds to the accelerator sprocket.

Source: https://assist.dla.mil -- Downloaded: 202640-22T04:30Z
Check the source to verify that this is the currentversion before use.

3.2.11 Feeder aft housing assembly. The feeder aft housing assembly shall provide for correct positioning and free rotation of the aft ends of the three sprocket shafts. It shall provide for mounting of the ammunition feed chute and the gun.

3.2.12 Feeder forward housing assembly. The feeder forward assembly shall provide for correct positioning and for rotation of the forward ends of the three sprocket shafts. An inner nose guide and an outer nose guide shall be so mounted as to freely guide the neck of rounds from the stripper sprocket assembly, through the accelerator sprocket assembly and feeder sprocket assembly into position for hand-off of rounds to the gun. It shall provide for mounting of the ammunition feed chute and the gun.

3.2.13 Timing pin. The timing pin shall engage the timing hole in the drive gear to correctly position the feeder gears for mounting the feeder on a properly timed gun. The timing pin shall move through its full range of travel without binding and shall be returned and held in the retracted position by action of the spring.

3.2.14 Solenoid assembly. The solenoid assembly shall be securely fastened to the feeder in accordance with the applicable drawing.

3.2.14.1 Solenoid operation. The solenoid shall actuate the wedge drive arm to engage the feeder when 20 to 30 volts direct current is properly applied to the connector. When de-energized, it shall return the wedge drive arm to its normal position under spring action of the solenoid.

3.2.14.2 Electrical circuit. The elctrical circuit wiring of the solenoid to the connector shall be in accordance with the applicable drawing.

3.2.14.3 Solenoid electrical characteristics. The solenoid electrical characteristic shall be as follows:

a. Solenoid insulation shall have a minimum resistance of 500 megohms at 1,500 volts dc.
b. With an applied 20 volt dc, the solenoid shall be capable of 5 pounds pull force of 0.25 inch stroke at 165°F.
c. Solenoid coil resistance shall be 3 ohms ± 0.15 ohm at 76°F.

3.2.15 Timing. The relationship of the sprockets to the gears shall be within the limits specified on the applicable drawings and shall provide for smooth transfer of rounds from the ammunition belt to the gun hand-off position. Timing marks shall be provided on the gears to permit the correct positioning of the gears relative to one another during assembly.

Source: https://assist.dla.mil -- Downloaded: 202640-22T04:30Z
Check the source to verify that this is the current version before use.

3.2.16 Feeder torque.

3.2.16.1 Non-stripping torque. With the clutch engaged but without ammunition, the torque required to rotate the feeder shaft and gears shall not be more than 2 inch-pounds.

3.2.16.2 Stripping torque. With an ammunition belt of linked Government standard 20mm, M51A1 dummy cartridges engaged in the feeder sprocket, the torque required to strip the links and cycle the rounds shall not be more than 250 inch-pounds at feeding rate of 1350 to 1650 rounds per minute.

3.3 Performance characteristics.

3.3.1 Functioning. The feeder shall operate without stoppage or breakage of parts attributable to the feeder using Government standard 20mm, M51A1B1 dummy cartridges or M55A2 cartridges. The feeder shall completely strip all rounds from the links, shall feed the stripped rounds into the gun, shall eject the empty links completely from the feeder, and perform its clutching and declutching function when operated at a steady state feeding rate of 1,350 to 1,650 rounds per minute. Testing shall be as specified in 4.5.3.2.

3.3.2 Endurance. The feeder shall withstand the feeding of 25,000 rounds of Government standard 20mm, M51A1B1 dummy cartridges, or M55A2 cartridges with at least 250 clutching and declutching operations without functioning failures attributable to the feeder when operated at a steady state rate of 1,350 to 1,650 rounds per minute. Testing shall be as specified in 4.5.3.3.

3.4 Interchangeability. Unless otherwise specified on the drawing, all parts shall be interchangeable. Testing shall be as specified in 4.5.3.4.

3.5 Marking. The feeder shall be clearly marked in accordance with MIL-W-13855. The identification plate shall be fastened securely to the feeder as specified on the drawing. Each feeder shall be identified by a serial number assigned by the procuring activity (see 6.2).

3.6 Workmanship. Workmanship shall be in accordance with MIL-W-13855.

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 202640-22T04:30Z
Check the source to verify that this is the currentversion before use.

4.1 Responsiblility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality assurance terms and definitions. Quality assurance terms and definitions used herein are in accordance with MIL-STD-109.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. The first article (initial production unit(s) shall be submitted for inspection in accordance with the contract (see 6.2). The first article shall be representative of the production processes to be used during quantity production. The first article shall be subjected to the quality conformance inspection specified herein and such other inspections as necessary to determine that all the requirements of the contract have been met.

4.5 Quality conformance inspection.

4.5.1 Inspection lot. The formation, size and presentation of inspection lots of feeders and parts shall be in accordance with MIL-STD-105 and MIL-W-13855. Feeders shall be assembled from lots of component parts that have met all inspection requirements specified herein. Endurance test lot size shall be as specified in 4.5.3.3.

4.5.2 Examination.

4.5.2.1 Component parts and concurrent repair parts. Examination of component parts and concurrent repair parts shall be performed in accordance with the criteria specified in the contract (6.2). The contractor's examination of these parts shall be accomplished prior to their assembly into the end item or submission for acceptance as repair parts.

Source: https://assist.dla.mil -- Downloaded: 20260-22T04:30Z
Check the source to verify that this is the current version before use.

4.5.2.2 Feeders. Visually and manually examine each feeder to determine conformance with the applicable requirements. Each step in the examination shall include a visual examination for proper cleaning and presence of the specified protective coating and to determine the general quality, completeness of manufacture, assembly, clarity and legibility of markings and workmanship. The examination provisions shall be applied at the earliest practical point in manufacture at which it is feasible to inspect for acceptance without risk of change in the characteristic by subsequent operations. Reinspections of these characteristics on the completed product is not required provided assurance exists that the characteristic has not been changed, degraded or damaged by subsequent manufacturing, assembly or handling and that adequate inspection records are maintained. Feeders failing to meet the requirements shall be rejected.

4.5.2.2.1 Parts and assemblies. Parts and assemblies shall be visually and manually examined to determine compliance with the materials, construction and design requirements of 3.2 and the applicable requirements of 3.2.1 through 3.2.14. Parts and assemblies failing to meet the requirements shall be rejected.

4.5.2.2.2 Solenoid operation. Feeders shall be examined for solenoid operation to determine compliance with 3.2.14.1.

4.5.2.2.3 Electrical circuit. Examine feeders for continuity to determine compliance with 3.2.14.2.

4.5.2.2.4 Solenoid electrical characteristics. Feeders shall be examined for solenoid electrical characteristics to determine compliance with 3.2.14.3.

4.5.2.2.5 Timing. Feeders shall be examined to determine compliance with 3.2.15.

4.5.2.2.6 Torque. Feeders shall be examined for torque to determine compliance with 3.2.16. Torque shall be measured by rotating feeder shaft with a torque wrench. Observe average peak dynamic torque reading, not initial starting torque.

4.5.2.2.7 Visually examine all marking required by the final assembly drawing to assure they are clear and eligible.

4.5.2.2.8 Visually examine the identification plate for compliance with the applicable drawing, for secure assembly (see 3.8), serialization and to assure that all pertinent data has been applied.

Source: https://assist.dla.mil -- Downloaded: 202640-22T04:30Z
Check the source to verify that this is the currentversion before use.

4.5.3 Testing.

4.5.3.1 Failure data. Unless otherwise specified herein, all tests shall be conducted on a complete feeder. Failure of feeders to meet the test requirements specified herein shall be cause for rejection of the feeder or the inspection lot of feeders. Acceptance of feeders shall be deferred and the contractor shall accomplish as applicable the following actions:

a. Conduct a failure analysis study performing a dimensional, physical and visual examination of the components which are suspected to be the cause of failure or malfunction.
b. Evaluate and correct the applicable production processes and procedures to prevent recurrence of the same defect(s) in future production.
c. Examine feeders, partially assembled feeders and components (including components and subassemblies at in-process or final assembly) to insure that material containing the same defect is purged from the inventory and not presented to the Government for acceptance.
d. Submit the results of the failure analysis and the corrective actions taken to the Government for review and approval prior to submitting a reconditioned lot or reconditioned feeders for retest.

4.5.3.2 Function testing. Each feeder shall be tested for functioning (see 3.3.1) by using the test method specified in 4.6.1. Failure of the feeder to meet the requirements shall be cause for rejection.

4.5.3.3 Endurance testing.

4.5.3.3.1 Lot size. The initial endurance test lot size shall consist of the initial month's production; subsequent endurance test lot size shall consist of 100 feeders.

4.5.3.3.2 Procedure. One feeder shall be selected from each endurance test lot and tested for endurance (see 3.3.2) using the test method specified in 4.6.2. Failure of the feeder to meet the requirements shall be cause for rejection of the represented lot.

4.5.3.4 Interchangeability testing.

4.5.3.4.1 In plant.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:30Z
Check the source to verify that this is the current version before use.

4.5.3.4.1.1 Feeders. A sample of three feeders selected from each month's production shall be tested for interchangeability (see 3.4) using the test method specified in 4.6.3.1.1. Feeders taken for interchangeability testing shall have been found satisfactory in all other examinations and tests. The three feeders shall be inspected for and shall comply with the requirements for timing and torque after interchange of parts (see 4.5.2.2.5 and 4.5.2.2.6). In addition, the feeders shall be tested for functioning requirements after interchange of parts using the test methods specified in 4.6.1. Failure of feeders to meet the requirements of the interchangeability test shall be cause for rejection of the represented lot.

4.5.3.4.1.2 Concurrent repair parts. At least two parts from each inspection lot of concurrent repair parts shall be subjected to the interchangeability test specified in 4.6.3.1.2. Failure of any part to meet the requirements shall be cause for rejection of the represented lot and the contractor shall perform the corrective action as specified in 4.5.3.1. Parts subject to reconditioning and further test shall become a reconditioned lot and a sample of double the number of parts used in the original test shall be tested from each reconditioned lot using the test method specified in 4.6.3.1.2.

4.5.3.4.2 Interplant. When feeders are manufactured concurrently by more than one contractor, each contractor shall forward monthly three feeders for the interplant interchangeability test specified in 4.6.3.2 (see 6.2). The contractor shall be informed of any failure of the feeders to meet prescribed requirements. Upon completion of testing agency inspection, samples may be commercially packaged and will be returned to the contractor for repackaging in accordance with procurement documents at the contractor's expense.

4.5.3.5 Certification. Unless otherwise specified, the contractor shall furnish the Government representative with certified statements that each inspection lot conforms to the applicable drawings, specifications of the materials and processes specified on Drawing F11838573.

4.5.3.6 Component parts and concurrent repair parts testing. Raw material testing, part testing and certification shall be performed in accordance with the criteria specified in the contract (see 6.2). This will include chemical analysis and physical tests of materials and tests of protective finish, heat treatment, bonding and function of parts as applicable. The contractor shall accomplish these tests prior to assembly of parts into the end item.

4.5.4 Packaging examination and testing. Unless otherwise specified (see 6.2), the packaging examination and testing shall be in accordance with MIL-P-14232.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:30Z
Check the source to verify that this is the current version before use.

4.5.5 Inspection equipment.

4.5.5.1 Unless otherwise specified in the procurement documents (see 6.2), responsibilities for acquisition, maintenance and disposition of measuring and testing equipment prescribed on lists contained on the Index of Inspection Equipment Lists, Drawing IEL11838573 (M89) or IEL12007300 (M89E1), and for all other inspection equipment required to perform inspection required by applicable specifications, shall be in accordance with MIL-I-45607.

4.5.5.2 Accuracy of standard measuring equipment. When commercial and modified commercial inspection and test equipment is used, it must be capable of repetitive measurements to an accuracy of 10 percent of the total tolerance of the characteristic being inspected.

4.6 Test methods.

4.6.1 Functioning test. Feeders shall be tested for functioning requirement (see 3.3.1) using slave M197 or M197E1 gun, or contractor designed Government approved test equipment which simulates the function of the gun. Two belts of 100 rounds each of linked ammunition shall be used for testing each feeder. The feeders shall be accelerated up to a feeding steady state rate of 1350 to 1650 rounds per minute with a maximum acceleration time of 0.3 seconds from start of gun rotation to a 1,350 rounds per minute rate of fire, before the feeder is declutched at approximately the middle of the belt. The feeder shall provide a means of clearing the gun after termination of a firing burst within a maximum stopping time of 0.3 seconds from 1,350 rounds per minute to a complete stop. The feeder solenoid shall be deenergized to declutch the feeder at the instant power to the drive is removed. The feeder solenoid shall not be energized for more than 30 seconds at any one time. After feeding each belt of ammunition the recorded data shall be checked to assure proper operation of the declutching mechanism. Instrumentation shall be of the contractor's design and shall be such that gun speed curve, gun and feeder timing, primer impulse, and feeder clutching and declutching actuation is taken and recorded concurrently for use in computing required data for each feeder.

4.6.2 Endurance test.

4.6.2.1 Feeders shall be tested for endurance requirement (see 3.3.2) using slave M197 or M197E1 gun, or contractor designed Government approved test equipment which simulates the function of the gun.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:30Z
Check the source to verify that this is the current version before use.

4.6.2.2 Linked ammunition in belts of 100 rounds each shall be used. The feeders shall be accelerated to a feeding steady state rate of 1,350 to 1,650 rounds per minute with a maximum acceleration time of 0.3 seconds from the start of gun rotation to a 1,350 rounds per minute rate of fire before the feeder is declutched at approximately the middle of the belt. The feeder shall provide a means of clearing the gun after termination of a firing burst within a maximum stopping time of 0.3 seconds from 1,350 rounds per minute to a complete stop. The feeder solenoid shall be deenergized to declutch the feeder at the instant power to the drive is removed. The feeder solenoid shall not be energized for more than 30 seconds at any one time. Only scheduled preventative maintenance shall be permitted during testing. Scheduled maintenance shall consist of lubrication of the feeder at each 2500 round interval using lubricant conforming to MIL-L-46150. Instrumentation shall be in accordance with 4.6.1. Data shall be taken and recorded from one belt in each 1500 round series for use in computing required data.

4.6.2.3 Endurance tested feeders shall be disposed of as specified in the contract (see 6.2).

4.6.3 Interchangeability test.

4.6.3.1 In plant.

4.6.3.1.1 Feeders. Each of the three feeders shall be disassembled to the extent required to remove the parts specified below. The disassembled parts from feeder number 1 shall be placed in a tray and identified as tray number 1. The disassembled parts from feeder numbers 2 and 3, shall be placed in trays and identified as tray number 2 and 3, respectively. Any commercial part rendered unserviceable by disassembly shall be replaced without penalty to the interchangeability test. The reassembly of three feeders, identified as A, B, and C, shall be accomplished by utilizing the applicable part from tray numbers 1, 2, and 3. Inability to reassemble parts shall be cause for rejection of the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:30Z
Check the source to verify that this is the current version before use.

Part	Part No.	Feeder A Tray No.	Feeder B Tray No.	Feeder C Tray No.
Gear, spur	11838505	2	3	1
Gear, cluster	11838506	3	1	2
Gear, spur, drive	11838509	2	3	1
Housing assembly, aft (M89)	11838510	1	2	3
Housing assembly, aft (M89E1)	12007301	1	2	3
Clip, chuting	11838511	3	1	2
Clip, chuting	11838512	2	3	1
Guide, nose, inner	11838513	3	1	2
Guide, nose, outer	11838514	1	2	3
Sprocket assembly, feeder	11838517	2	3	1
Sprocket assembly, stripper	11838518	3	1	2
Sprocket assembly, accelerator	11838519	2	3	1
Stripper, link	11838520	3	1	2
Gear, spur	11838528	3	1	2
Solenoid	63C10952	2	3	1
Vane, rotating	11838542	1	2	3
Retainer, bearing	11838545	2	3	1
Wedge, clutch	11838548	2	3	1
Cap retaining	11838555	1	2	3
Lock assembly, clutch	11838556	2	3	1
Arm, drive, wedge	11838565	3	1	2
Guide, assembly, T-bar	11838569	3	1	2
Pin, timing	11838571	3	1	2
Housing assembly, forward (M89)	11838572	2	3	1
Housing assembly, forward (M89E1)	12007302	2	3	1

4.6.3.1.2 Concurrent repair parts. Concurrent repair parts shall be tested for interchangeability requirement (see 3.4) by disassembling two feeders, previously tested in 4.6.3.1.1, as necessary and then reassembling them using the concurrent repair parts. No hand refinement of parts will be allowed, and the feeders shall operate and function properly. This test may be performed independently of the feeder interchangeability test specified in 4.5.3.4.1.1 and at more frequent intervals using accepted feeders taken from current production.

4.6.3.2 Interplant. Feeders to be subjected to the interplant interchangeability test shall be inspected for timing, torque and functioning requirements specified in 4.5.2.2.5, 4.5.2.2.6 and 4.6.1 respectively. Feeders shall be interchanged in a manner similar to the detailed plan specified in 4.6.3.1.1 except that when disassembling, every other feeder shall be one produced by a different manufacturer. After assembly, the feeders shall be inspected for timing, torque and functioning requirements as specified in 4.5.2.2.5, 4.5.2.2.6 and 4.6.1 respectively. Before feeders are returned to the contractors, the original parts shall be reassembled to their respective feeders.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:30Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Pilot pack. A pilot pack shall consist of a complete feeder packaged in accordance with Packaging Data Sheet P11838573 (M89) or P12007300 (M89E1) to the level of protection specified in the contract (see 6.2), packed level C and forwarded in accordance with 3.1.

5.2 Preservation, packaging, packing and marking. Feeders shall be preserved, packaged, packed and marked in accordance with Packaging Data Sheet P11838573 (M89) or P12007300 (M89E1) for the level of protection specified in the contract (see 6.2).

5.3 Repair parts. Repair parts shall be preserved, packaged, packed and marked in accordance with the Packaging Data Sheet or other requirements and for the level of protection specified in the contract (see 6.2).

6. NOTES

6.1 Intended use. The feeder assembly M89 or M89E1 is intended to be used to supply ammunition to, and clear rounds from, the M197 or M197E1, 20 Millimeter Automatic Gun.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Lists of drawings and specifications pertinent to the feeder, showing applicable revision dates.
c. Inspection criteria for components (see 4.5.2.1 and 4.5.3.6).
d. Index of inspection equipment lists pertinent to the feeder, showing applicable revision dates.
e. Shipping instructions for first article and pilot pack (see 3.1 and 5.1).
f. Packaging examination and testing, if different (see 4.5.4).
g. List of acceptance inspection equipment to be furnished the contractor (see 4.5.5.1) and responsibilities for other Government property to be furnished the contractor.
h. Shipping instructions for feeders and parts when an interplant interchangeability test is required (see 4.5.3.4.2).
i. Disposition of endurance tested feeders (see 4.6.3.3).
j. Selection of applicable levels of preservation, packaging and packing (see 5.1 and 5.2).
k. Packaging of repair parts (see 5.3).
l. Block of serial numbers (see 3.8).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:30Z
Check the source to verify that this is the current version before use.

6.3 Contract data requirements. When warranted, requirements for reports of the results of the examination and testing (e.g. functioning, endurance and interchangeability, etc.) shall be specified on a DD Form 1423 included in the contract.

6.4 Unless otherwise specified (see 6.2) the contract should specify the application of MIL-I-45607 and MIL-C-45662 on the Management Control Summary List, DD Form 1660.

6.5 When warranted, the contract should specify the application of MIL-Q-9858 or MIL-I-45208 as appropriate, on the Management Control Systems Summary List DD Form 1660.

6.6 Supersession data. This specification includes the requirements of U.S. Army Weapons Command Purchase Description USAWECOM PD-45, dated 13 July 1972.

Custodian:
Army - WC
Navy - OS

Preparing activity:
Army - WC

Project number:
1005-A474

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:30Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Rock Island Arsenal
ATTN: SARRI-LE-S
Rock Island, Illinois 61201

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-F-45966; Feeder, Automatic Gun: M89 and M89E1

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRAC

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202640-22T04:30Z
Check the source to verify that this is the current version before use.