MILITARY SPECIFICATION

GUN, AIR DEFENSE ARTILLERY, 20MM: SELF-PROPELLED, M163A1

This amendment forms a part of Military Specification MIL-G-45980(WC) dated 2 March 1976.

PAGE 1

Para 1.1, line 3: Delete "radar range" and substitute "range only radar".

PAGE 3

Para 3.2.2: Delete line 1 and substitute "Range only radar AN/VPS-2. The AN/VPS-2 range only radar shall be in".

Para 3.3.1.2b, first sentence, line 3: At end of sentence add "and acquisition time delay (ATD) shall be accomplished."

Para 3.3.1.2b: Add at end of paragraph "Desire actual target for ATD, but this can be accomplished by simulation."

PAGE 4

Para 3.3.2: Delete entire paragraph and substitute

"3.3.2 Design functions. The weapon system controls and indicators shall sequentially function by manual and automatic means. The system shall be capable of five independent modes of operation after the system power is applied as specified in 3.3. Functional requirements shall be in accordance with 3.3.2.1 through 3.3.2.4 and MIL-F-60664. Testing shall be as specified in 4.5.2.2."

PAGE 5

Para 3.3.2.3, lines 1 and 2: Delete title and "The radar operational indicator" and substitute "Ready when lit light. The READY WHEN LIT light".

FSC 2350

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

PAGE 6

Para 3.3.3: Delete entire paragraph and substitute

"3.3.3 System reaction time. With radar system in radar mode after the two minute warmup period, the weapon system shall slew 180 degrees and acquire track and fire on a target in not more than 10.5 seconds with the following two conditions present. Testing shall be as specified in 4.5.2.2:

a. Target with a minimum of one square meter cross sectional area, traveling at a relative velocity of 450 knots.
b. Target range less than 2500 meters (1600 meters outbound)."

PAGE 12

Para 3.6.1: Add to end of paragraph: "Use of vehicle engine shall not degrade radar system performance."

PAGE 15

Para 4.6.2, line 2: Delete "sight generator" and substitute "sight current generator".

Para 4.6.2, line 3: Delete "GOOD TEST" and substitute "GOOD WHEN LIT".

Para 4.6.3: Delete second sentence and substitute "The radar range accuracy and lead computing accuracy features of the sight shall be determined. The radar shall supply range data to the weapon system. The weapon system and gun mount shall rotate and track the target and ATD shall occur."

Para 4.6.3: Add at end of paragraph "Radar system parameters shall meet the specified requirements."

Para 4.6.4, line 5: Delete "high speed".

PAGE 16

Para 4.6.7: Delete "through each mode of operation" and "as specified on Figure 1".

Para 4.6.7.4: Delete entire paragraph and substitute

"4.6.7.4 Ready when lit light test. The READY WHEN LIT light shall be tested to determine compliance with 3.3.2.3."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

PAGE 22

Para 4.6.33nn: Delete "AN/VPS-2B sight" and substitute "AN/TVS-2B night vision sight". Delete "AN/VPS lens cover" and substitute "AN/TVS-2B lens cover".

Para 4.6.33oo: Delete "AN/VPS-2B" and substitute "AN/TVS-2B".

Para 4.6.33pp, line 1: Delete "AN/VPS-2B night sight" and substitute "AN/TVS-2B night vision sight".

Para 4.6.33pp, line 3: Delete "AN/VPS-2B" and substitute "AN/TVS-2B night vision sight".

Para 4.6.33pp, line 4: Delete "AN/VPS-2B" and substitute "AN/TVS-2B night vision".

PAGE 24

Para 4.6.34.2, TABLE I (continued), Equipment, Slip ring, Part Number: Delete "84377092" and substitute "8437092".

PAGE 28

FIGURE 1. SEQUENCE OF EVENTS DIAGRAM: Delete entire Figure.

Custodian:
Army - WC

Preparing activity:
Army - WC

Project No.
2350-A271

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.