INCH-POUND
MIL-H-45984B (AR)
AMENDMENT 2
20June93
SUPERSEDING
AMENDMENT 1
27 March 1985

MILITARY SPECIFICATION

HOWITZER, MEDIUM, TOWED, 155MM: M198

This amendment forms a part of Military Specification MIL-H-45984B (AR), dated 22 October 1984, and is approved for use by the U.S. Army Armament Munitions and Chemical Command. and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 7

3.3.3.5, Rod pull curves. Change: "Range 1: Peak rod pull shall occur within the first 20 milliseconds for long recoil, and 60 milliseconds for short recoil." to: "Range 1: Peak rod pull shall occcur within the first 20 milliseconds for long recoil."

Change: "Range 2: Within 280 milliseconds (max.) for long recoil. or 180 milliseconds (max.) for short recoil, the continuous rod PU1l shall not exceed the peak rod pull of Range l." To: "Range 2: For long recoil, the continuous rod pull curve shall not exceed the peak rod pull of Range 1. For short recoil (900 roils and above) the maximum rod pull shall not exceed the peak rod pull in Range 1 by more than 6000 lbs."

3.3.4 Road test. Delete in its entirety and substitute:

"3.3.4 Road test, The howitzer shall be Capable of withstanding the following 300 mile road test without damage. permament deformation or loosening of parts. Testing shall be as specified in 4.5.3.5.

- 150 miles at speeds between 30 and 55 mph over hard surface or improved roads.

- 120 miles at speeds between 10 and 15 mph over Belgian block or equivalent.

. - 30 miles at speeds between 10 and 15 mph over cross country roads.

AMSC N/A

FSC 1025

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:34Z
Check the source to verify that this is the current version before use.

PAGE 8

Figure 1: For short recoil sketch only, delete: "Note 1".

PAGE 11

4.5.1 Sampling

Delete the sentence "A howitzer lot shall consist of two months production or thirty-five howitzers, whichever quantity is smaller" and substitute: "A howitzer lot shall consist of six months production or 100 howitzers, whichever quantity is smaller."

PAGE 23

3.6.3 TABLE I. Proof firing, Round Number.

Change From:	Change To:
1	1
2	2
3	3-7
4	8-12
5	13-17
6	18-22
7	23-27
8	28-32

The margins of this amendment are marked with an astrisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1025-A177)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:34Z
Check the source to verify that this is the current version before use.