MILITARY SPECIFICATION

RIFLE, 7.62MM: M14, NATIONAL MATCH

This Amendment forms a part of Military Specification MIL-R-45979, dated 24 September 1976, and is approved for use within the US Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 8

3.2.16.6, Delete in its entirety and substitute:

"3.2.16.6 Swivels. The butt swivel shall be fastened securely to the stock by the long butt plate screw. The sling swivel assembly shall be fastened securely to the stock by rivets. There shall be no relative movement of these parts.".

3.2.19, Delete in its entiretY and substitute:

"3.2.19 Headspace. After proof firing, the headspace shall be 1.6330 inches mininum to 1.6360 inches maximum. Testing shall be as specified in 4.5.10.4."

3.3.2, Delete in its entirely and substitute.

"3.3.2 Trigger pull The trigger pull shall be free of creep and shall e within the range of 4 1/2 to 4 3/4 pounds. Creep shall be interpreted to mean any perceptible rough movement between the time the trigger slack is taken up and the hammer is released. Testing shall be as specified in 4.5.10.5.".

PAGE 9

3.3.5.1 and 3.3.5.2, Delete in their entireity and substitute

"3.3.5.1 The average extreme spread for three consectutive ten shot groups shall not exceed six (6) inches at a ranges of 300 meters using caliber 7.62 mm M852 match ammunition.".

DISTRIBUTION STATEMENT A. Approved for public release distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.

PAGE 21

4.6.3 Headspace test: Delete the first sentence and substitute the following:

"Rifles shall be gaged for headspace (see 4.5.10.4) after proof firing, prior to acceptance, using government approved standard test measuring equipment."

PAGE 22

4.6.7 Function and targeting and accuracy firing test: Delete the first sentence and substitute the following:

"Testing of rifles for functioning and targeting and accuracy at a range of 300 meters (see 4.5.10.6) shall be accomplished with the rifles held in a targeting jack simulating shoulder firing and conforming to drawing F6511841."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1OO5-A655)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:33Z
Check the source to verify that this is the current version before use.