MIL-C-82580(OS)
6 October 1969

Superseding
NOTS XS 432 Rev D
1 April 1969

MILITARY SPECIFICATION

CONTAINER, MOTOR, 11'' 65 ROCKET, MK 178 MOD 0

This specification has been approved by the Naval Ordnance Systems Command, Department of the Navy

1. SCOPE

1 1 Scope This specification establishes the requirements for the Container, Motor, 11'' 65 Rocket, Mk 178 Mod 0, LD 497698, which is used for shipping and storing one ASROC Motor Assembly The container is of one type and one class, and is referred to herein as the container (See 6.1.2 for description.)

2 APPLICABLE DOCUMENTS

2.1 The following standards and drawings, or such portions thereof as may be designated herein, of the issue in effect on the date of invitation for bids, form a part of this specification

STANDARDS

MILITARY

MIL-STD-129	Marking for Shipment and Storage

DRAWINGS

NAVAL ORDNANCE SYSTEMS COMMAND

LD 497698	Container, Motor, 11'' 65 Rocket, Mk 178 Mod 0, (and all drawings listed thereon)

(Copies of standards, and drawings, requested by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC-8140

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:16Z
Check the source to verify that this is the current version before use.

3 REQUIREMENTS

3.1 General requirements Unless otherwise specified in the contract or purchase order, all materials and treatment of materials and parts used in the manufacture of the container shall be in accordance with the requirements specified herein and with the applicable documents listed in LD 497698

3.2 Preproduction sample Unless otherwise specified in the contract or purchase order, a preproduction sample of the container shall be manufactured using the methods and procedures proposed for the production lot This sample shall be tested as specified in Section 4 herein and is for the purpose of determining that the production item meets the requirements of this specification and the design See 4.3 2

3 3 Performance requirements and product characteristics The container shall meet the following performance requirements and product characteristics

3.3 1 Airtightness The container shall show no visible evidence of air leakage when subjected to an internal pressure of 1 0 plus 0 5 minus 0 0 pounds per square inch gage (psig)

3.4 Environmental requirements.

3 4 1 Vibration The loaded container shall withstand vibrations of 1 5 to 5 5g (a unit of gravitational acceleration) over the frequency range of 23 to 43 cycles per second (cps) and thereafter shall show no damage to the stored contents and shall meet all the performance requirements of this specification

3 4 2 Shock The loaded container shall withstand shock loading as induced by freefall drops of 18 to 24 inches onto a hard surface on ends, sides, and corners Thereafter the container shall show no damage to the stored contents and shall meet the performance requirements of this specification

3 5 Workmanship The workmanship and finish shall be of sufficiently high grade to assure satisfactory operation consistent with the requirements of this specification All parts used in the container shall be thoroughly clean and free of excess materials, chips, and loose or spattered foreign materials The standards of workmanship exhibited in any approved sample, subject to any qualification stated in the Government Notice of Approval. shall be determinitive of the requirements of the contract relative to workmanship insofar as not specifically covered by applicable specifications

4 QUALITY ASSURANCE PROVISIONS AND TEST REQUIREMENTS

4 1 Responsibility for inspection Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:16Z
Check the source to verify that this is the current version before use.

contract or purchase order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements

4 2 Classification of tests The inspection and testing of containers shall be classified as follows

4 2 1 Preproduction and periodic production tests Preproduction and periodic production tests are those which are accomplished on samples selected as specified in 4.3 2 and 4.3.3 which are representative of the production of the container after the award of the contract to determine that the lot and production meet the requirements of this specification These tests are detailed in 4 6. Acceptance shall be based on no defects in a sample Failure of a sample to comply with these requirements shall result in the rejection of the lot or the cessation of production as determined by the procuring activity

4 2.2 Quality conformance tests These tests are to be accomplished on each container being submitted for acceptance under contract These tests are defined in 4 5.

4.3 Sampling

4 3 1 Lot size As applied to inspection of units of product, the term "lot" shall mean "inspection lot", that is, a collection of units of product subjected to inspection by a supplier

4 3 2 Preproduction sample Unless otherwise specified for each contract or purchase order, a representative sample of one container shall be manufactured using the methods and procedures proposed for the production lot This sample shall be subjected to the preproduction tests for purposes of determining compliance with the requirements of the contract, specification, and drawings Further production of the container by the contractor prior to approval of the contracting activity or the completion of tests on the preproduction sample shall be at the contractor's risk The preproduction sample, if accepted, will be applied as part of the quantity specified by the contract or purchase order

4 3 3 Periodic production samples Unless otherwise specified in the contract or purchase order, from each succeeding lot or grand lot of three hundred (300) or less, a random sample of one container shall be selected for testing, to determine compliance of the sample with the requirements of the contract, specification, and drawing The container shall be considered satisfactory if the container meets all specifications and pertinent drawing requirements, and withstands all the tests specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:16Z
Check the source to verify that this is the current version before use.

4 4 Test equipment The following items of test equipment are required to perform the tests set forth in this specification

4.4.1 Quality conformance test equipment

4 4 1 1 Air compressor or suitable pressurized tank The air compressor or suitable air pressurized tank shall be capable of pressurizing the container to 1 5 pounds per square inch gage (psig) The air compressor or air pressurized tank shall have a pressure gage capable of indicating 3 0 psig and shall have a suitable length of air hose terminating in a standard inflating chuck

4 4 1 2 Soap solution and brush The soap solution and brush shall be adequate to perform the test specified in 4 5.3.1 satisfactorily

4.4.2 Preproduction and periodic production test equipment

4.4.2.1 Vibration test machine Vibration tests shall be conducted by any vibration machine that is capable of meeting the conditions specified in 4.6 1 Means shall be provided for controlling the direction of vibration of the machine and for adjusting and measuring its frequency and amplitudes of vibration

4 4 2.2 Hoist A hoist capable of safely lifting a load of 1000 pounds shall be provided

4 5 Quality conformance tests.

4 5.1 The contractor shall conduct quality conformance tests as specified in 4.2.2 to assure that the container complies with the requirements of 3.1, 3 3, and 3.5.

4 5.2 Test conditions. Unless otherwise specified, the container shall be subjected to quality conformance tests under the following conditions·

4.5.2 1 Temperature Room ambient 65 degrees Fahrenheit (F) to 95 degrees F (18.33 degrees Centigrade (C) to 35 degrees C).

4.5.2 2 Humidity Room ambient to 95 percent relative

4.5.3 Test procedure.

4 5.3.1 Airtightness The container shall be tested for air leakage by performing the soap bubble test described below

4.5.3.1.1 Remove cap from tank valve

4 5 3.1.2 Using a standard inflating chuck, pressurize the container to 1.0 plus 0 5 minus 0 0 psig Remove the inflating chuck and replace the cap on the tank valve

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:16Z
Check the source to verify that this is the current version before use.

4 5.3.1.3 Apply a heavy, soapy solution to all **seam** welds, to the air relief and tank valves, around the circumference of the **humidity** indicator, and to the gasket sealed area of the container

4 5 3 2 Acceptance criteria. There shall be no bubbles or other evidence of air leakage

4 6 Preproduction and periodic production tests.

4 6.1 Vibration The container, with a dummy motor assembly or simulated contents of equal weight distribution enclosed, shall be rigidly mounted on the vibration machine and tested in accordance with the vibration schedule of table 1

Table 1 - Vibration test schedule

Double amplitude displacement (inches)	Speed (cps)	Time (min)	Load (g)
.016	43	75	1.5
0225	43	38	2 0
0225	37	10	1.5
.031	31	10	1 5
.043	43	1	4
043	38	6	3
043	27	10	1 5
.060	23	10	1.5
060	23-43	Continuous sweep (up and down)	1.5 to 5.5

4 6.2 Shock The container, with a dummy motor assembly or simulated contents of equal weight distribution enclosed, shall be shock tested as follows

4.6.2 1 End drop test The container shall be supported at one end on a block approximately five inches high The other end of the container shall be raised to a height of 18 inches and allowed to drop freely to a hard surface Each end of the container shall be end drop tested once.

4.6.2.2 Corner drop test. The container shall be supported at one end on two blocks, one 5 inches high under one corner, and one 10 inches high under the other corner The opposite end of the container shall be raised to a height of 24 inches and allowed to drop freely to a hard surface The corner drop test shall be conducted once to each corner of the container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:16Z
Check the source to verify that this is the current version before use.

4.6.2.3 Roll test. The container shall be placed erect on its base on a hard level floor. The container shall be tipped slowly until it rolls freely of its own weight, striking the floor on its side The roll test shall consist of a complete revolution.

4.6.2 4 End impact test The container shall be raised off the floor and allowed to swing as a pendulum against a nominal 8 by 8 inch or larger timber resting horizontally on the floor and rigidly blocked. The container shall be raised by two cables, one at each end, and pivoted at least 16 feet above the floor, to a height of one to three inches above the floor, and shall slightly touch the timber. The container shall be pulled back from the timber until the center of gravity is raised 14 inches plus or minus 0 5 inch then released and allowed to strike the timber. The end impact test shall be conducted once to each side and each end of the container.

4.6.3 Acceptance criteria. The container shall be examined immediately after the vibration and shock tests to determine the ability of the container to protect the contents. There shall be no evidence of a substantial amount of shifting of the contents within the container that would create conditions likely to cause damage during shipment. There shall be no evidence of binding as the contents are removed from the container

4.6.4 The container. after being subjected to the tests of 4.6. shall be resealed and subjected to the quality conformance tests specified in 4 5.3

4.7 Failure of the container to meet any of the requirements and tests of this specification shall be considered cause for rejection

5 PREPARATION FOR DELIVERY

5.1 Packing.

5.1.1 Level C. Unless otherwise specified, packing for domestic shipment shall be in accordance with approved commercial packing methods, adequate to protect the container from damage and to assure delivery at destination. The method used shall be commensurate with shipping at the lowest practical commercial rates.

5.2 Labeling and marking. Unless otherwise specified, labeling and marking of all shipments shall be in accordance with MIL-STD-129 Any special marking required by the contract or order shall be provided.

6. NOTES

6.1 Intended use and description.

6.1.1 Intended use. This container is intended for use in both foreign and domestic shipment, and storage of one ASROC Motor Assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:16Z
Check the source to verify that this is the current version before use.

6 1 2 Description. The container is a steel cylinder, 76.6 inches long by 18.82 inches in diameter divided longitudinally so that it is top-opening. The upper shell weldment secures to the lower shell weldment by means of swing bolts and flange nut assemblies. The lower shell weldment is provided with four shock mounts. Strap assemblies, fastened to the shock mounts, are used to secure the ASROC Motor Assembly in the container Pressure-relief valves, a tank valve, and a humidity indicator are installed in the end of the upper shell weldment Fork lift pockets and sling hook rings are provided to facilitate handling The container is a reusable container.

6 2 Ordering data Procurement documents should specify the specific title, number, and date of this specification and exceptions to this specification, applicable drawings, and other documents.

6.3 Level C. Minimum military packing is intended for items which will be used immediately upon receipt at the first domestic receiving activity.

6 4 Definitions. Definitions applicable to the environmental requirements of this specification are set forth below

6.4.1 Vibration Vibration is a sinusoidal motion defined by amplitude and frequency. The amplitude may refer to displacement or acceleration The displacement is given in inches peak to peak or the corresponding maximum acceleration in gravity units (g's). The frequency is given in cycles per second (cps)

6 4.2 Shock Shock is an abrupt change in the motion of a body resulting from the sudden application of a large external force of short duration.

Project No. 8140-N070

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:16Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*

SPECIFICATION
MIL-C-82580(OS) CONTAINER, MOTOR 11?65 ROCKET MI 178 MOD C

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3 IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4 REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 62 1426

C-8870

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:16Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Naval Ordnance Systems Command
Washington, D.C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

NAVAL ORDNANCE SYSTEMS COMMAND (ORD 9343)
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:16Z
Check the source to verify that this is the current version before use.