INCH-POUND


MIL-PRF-83421/2C
24 January 2006
SUPERSEDING
MIL-PRF-83421/2B
9 July 2001

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, METALLIZED PLASTIC FILM DIELECTRIC, (DC, AC, OR DC AND AC), HERMETICALLY SEALED IN METAL CASES, ESTABLISHED RELIABILITY STYLES CRH11, CRH12, AND CRH13 (INSULATED)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-83421.



NOTES:
1. Number 18 AWG wire .040 inch ± .002 (1.02 ± 0.05 mm).
2. Dimensions are in inches.
3. Metric equivalents are in parentheses and are given for general information only.
4. See table I for additional dimensions.
5. Insulating sleeve shall extend beyond the capacitor body. Insulating sleeve thickness shall not exceed .005 inch (0.13 mm).
6. Plastic insulating sleeve shall be transparent; marking shall be applied to the capacitor case.

FIGURE 1. Capacitor configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:05Z
Check the source to verify that this is the current version before use.

* TABLE I. Electrical characteristics, dimensions, and dash numbers.

Capacitance value (nom) (in μf)	Dimensions 1/ (in inches with mm in parentheses)			Dash numbers 2/						ESR 20 kHz 100 kHz (ohms maximum)	AC rating maximum 400 Hz (volts rms)	Ripple current 20 kHz to 100 kHz (amperes rms) maximum case temperature °C 3/		
				Capacitance tolerance value (in %)										
	L +.030 (0.76) -.090 (2.29)	D +.020 (0.51) -.010 (0.25)	G, max	±0.25	±0.5	±1.0	±2.0	±5.0	±10.0			25	85	105
CRH11 - 100 volts (dc rating)														
0.47	.875 (22.23)	.400 (10.16)	1.075 (27.31)	1001-	1002-	1003-	1004-	1005-	1006-	0.025	60	5.3	2.6	0.8
0.56	.875 (22.23)	.500 (12.70)	1.075 (27.31)	1007-	1008-	1009-	1010-	1011-	1012-	0.024	60	6.0	3.0	1.0
0.68	.875 (22.23)	.500 (12.70)	1.075 (27.31)	1013-	1014-	1015-	1016-	1017-	1018-	0.023	60	6.2	3.1	1.0
0.82	.875 (22.23)	.500 (12.70)	1.075 (27.31)	1019-	1020-	1021-	1022-	1023-	1024-	0.022	60	6.3	3.2	1.0
1.0	.906 (23.01)	.562 (14.27)	1.106 (28.09)	1025-	1026-	1027-	1028-	1029-	1030-	0.017	60	7.7	3.9	1.2
2.0	1.094 (27.80)	.670 (17.02)	1.294 (32.87)	1031-	1032-	1033-	1034-	1035-	1036-	0.014	60	10.3	5.2	1.6
3.0	1.094 (27.80)	.750 (19.05)	1.294 (32.87)	1037-	1038-	1039-	1040-	1041-	1042-	0.013	60	11.4	5.7	1.8
5.0	1.406 (35.70)	.750 (19.05)	1.606 (40.79)	1043-	1044-	1045-	1046-	1047-	1048-	0.012	60	13.6	6.8	2.1
10.0	1.687 (42.85)	1.000 (25.40)	1.887 (47.93)	1049-	1050-	1051-	1052-	1053-	1054-	0.010	60	15.0	9.1	2.9
20.0	2.437 (61.90)	1.000 (25.40)	2.637 (66.98)	1055-	1056-	1057-	1058-	1059-	1060-	0.009	60	15.0	11.5	3.6
25.0	2.437 (61.90)	1.000 (25.40)	2.637 (66.98)	1061-	1062-	1063-	1064-	1065-	1066-	0.008	60	15.0	11.7	3.7
CRH12 - 200 volts (dc rating)														
0.18	.875 (22.23)	.400 (10.16)	1.075 (27.31)	2001-	2002-	2003-	2004-	2005-	2006-	0.031	120	4.8	2.4	0.8
0.22	.875 (22.23)	.500 (4.32)	1.075 (27.31)	2007-	2008-	2009-	2010-	2011-	2012-	0.030	120	5.4	2.7	0.9
0.27	.875 (22.23)	.500 (4.32)	1.075 (27.31)	2013-	2014-	2015-	2016-	2017-	2018-	0.029	120	5.5	2.8	0.9
0.33	.875 (22.23)	.500 (4.32)	1.075 (27.31)	2019-	2020-	2021-	2022-	2023-	2024-	0.028	120	5.6	2.8	0.9
0.39	.906 (23.01)	.562 (14.27)	1.106 (28.09)	2025-	2026-	2027-	2028-	2029-	2030-	0.026	120	6.2	3.1	1.0
0.47	1.094 (27.80)	.562 (14.27)	1.294 (32.87)	2031-	2032-	2033-	2034-	2035-	2036-	0.025	120	7.0	3.5	1.1
0.56	1.094 (27.80)	.562 (14.27)	1.294 (32.87)	2037-	2038-	2039-	2040-	2041-	2042-	0.024	120	7.2	3.6	1.1
0.68	1.094 (27.80)	.670 (17.02)	1.294 (32.87)	2043-	2044-	2045-	2046-	2047-	2048-	0.023	120	8.0	4.0	1.3
0.82	1.094 (27.80)	.670 (17.02)	1.294 (32.87)	2049-	2050-	2051-	2052-	2053-	2054-	0.022	120	8.2	4.1	1.3
1.0	1.094 (27.80)	.670 (17.02)	1.294 (32.87)	2055-	2056-	2057-	2058-	2059-	2060-	0.021	120	8.4	4.2	1.3
2.0	1.406 (35.70)	.750 (19.05)	1.606 (40.79)	2061-	2062-	2063-	2064-	2065-	2066-	0.017	120	11.1	5.5	1.8
3.0	1.437 (36.50)	1.000 (25.40)	1.637 (41.58)	2067-	2068-	2069-	2070-	2071-	2072-	0.015	120	13.9	7.0	2.2
5.0	1.687 (42.85)	1.000 (25.40)	1.887 (47.93)	2073-	2074-	2075-	2076-	2077-	2078-	0.013	120	15.0	8.2	2.6
CRH13 - 400 volts (dc rating) 4/														
0.033	.875 (22.23)	.400 (10.16)	1.075 (27.31)	3223-	3224-	3225-	3226-	3227-	3228-	0.08	240	2.85	1.42	0.45
0.039	.875 (22.23)	.400 (10.16)	1.075 (27.31)	3229-	3230-	3231-	3232-	3233-	3234-	0.07	240	3.04	1.52	0.48
0.047	.875 (22.23)	.400 (10.16)	1.075 (27.31)	3235-	3236-	3237-	3238-	3239-	3240-	0.06	240	3.29	1.64	0.52
0.056	.875 (22.23)	.400 (10.16)	1.075 (27.31)	3001-	3002-	3003-	3004-	3005-	3006-	0.058	240	3.5	1.7	0.6
0.068	.875 (22.23)	.500 (12.70)	1.075 (27.31)	3007-	3008-	3009-	3010-	3011-	3012-	0.046	240	4.4	2.2	0.7
0.082	.875 (22.23)	.500 (12.70)	1.075 (27.31)	3013-	3014-	3015-	3016-	3017-	3018-	0.039	240	4.7	2.4	0.7
0.10	.875 (22.23)	.500 (12.70)	1.075 (27.31)	3019-	3020-	3021-	3022-	3023-	3024-	0.035	240	5.0	2.5	0.8
0.12	.906 (23.01)	.562 (14.27)	1.106 (28.09)	3025-	3026-	3027-	3028-	3029-	3030-	0.033	240	5.5	2.8	0.9
015	.906 (23.01)	.670 (17.02)	1.106 (28.09)	3031-	3032-	3033-	3034-	3035-	3036-	0.032	240	6.2	3.1	1.0
0.18	.906 (23.01)	.670 (17.02)	1.106 (28.09)	3037-	3038-	3039-	3040-	3041-	3042-	0.031	240	6.3	3.1	1.0

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:05Z
Check the source to verify that this is the current version before use.

* TABLE I. Electrical characteristics, dimensions, and dash numbers - Continued.

Capacitance value (nom) (in μf)	Dimensions 1/ (in inches with mm in parentheses)			Dash numbers 2/						ESR 20 kHz 100 kHz (ohms maximum)	AC rating maximum 400 Hz (volts rms)	Ripple current 20 kHz to 100 kHz (amperes rms) maximum case temperature °C 3/		
	L +.030 (0.76) -.090 (2.29)	D +.020 (0.51) -.010 (0.25)	G, max	Capacitance tolerance value (in %)										
				±0.25	±0.5	±1.0	±2.0	±5.0	±10.0			25	85	105
CRH13 - 400 volts (dc rating) 4/														
0.22	1.094 (27.80)	.670 (17.02)	1.294 (32.87)	3043-	3044-	3045-	3046-	3047-	3048-	0.030	240	7.0	3.5	1.1
0.27	1.094 (27.80)	.670 (17.02)	1.294 (32.87)	3049-	3050-	3051-	3052-	3053-	3054-	0.029	240	7.2	3.6	1.1
0.33	1.094 (27.80)	.670 (17.02)	1.294 (32.87)	3055-	3056-	3057-	3058-	3059-	3060-	0.028	240	7.3	3.7	1.2
0.39	1.094 (27.80)	.750 (19.05)	1.294 (32.87)	3061-	3062-	3063-	3064-	3065-	3066-	0.026	240	7.9	3.9	1.2
0.47	1.094 (27.80)	.750 (19.05)	1.294 (32.87)	3067-	3068-	3069-	3070-	3071-	3072-	0.025	240	8.1	4.0	1.3
0.56	1.406 (35.70)	.750 (19.05)	1.606 (40.79)	3073-	3074-	3075-	3076-	3077-	3078-	0.025	240	9.2	4.6	1.4
0.68	1.406 (35.70)	.750 (19.05)	1.606 (40.79)	3079-	3080-	3081-	3082-	3083-	3084-	0.024	240	9.4	4.7	1.5
0.82	1.656 (42.06)	.750 (19.05)	1.856 (47.14)	3085-	3086-	3087-	3088-	3089-	3090-	0.023	240	10.4	5.2	1.6
1.0	1.656 (42.06)	.750 (19.05)	1.856 (47.14)	3091-	3092-	3093-	3094-	3095-	3096-	0.022	240	10.7	5.3	1.7
2.0	1.938 (49.23)	1.000 (25.40)	2.138 (54.31)	3097-	3098	3099-	3100-	3101-	3102-	0.017	240	15.0	7.5	2.4

1/ L and D dimensions are bare case dimensions (See figure 1).
2/ The complete dash number will include the applicable letter completing the FR level symbol (M, P, R, or S).
3/ This is the ambient case temperature prior to the application of current.
4/ 400V PINs with values less than 0.033 μF (dash numbers -3103 through -3222) are no longer available.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:05Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and table I.

Dielectric: Polypropylene, metallized.

Case material: Nonmagnetic.

Leads: Type designation in accordance with MIL-STD-1276.

* L W .040 C 32 N

Capacitance value: See table I.

Capacitance tolerance: See table I.

DC rated voltage: 100 V dc, 200 V dc, and 400 V dc.

Operating temperature range: -55°C to +105°C.

AC current ratings: See table I.

Failure rate (FR) levels: M (1.0%), P (0.1%), R (0.01%), and S (0.001%).

Thermal shock: 10 cycles, method 107 of MIL-STD-202, -65°C, +105°C.

Seal: Method 112 of MIL-STD-202, test condition C, procedure IIIa with the following exceptions and details: a bomb pressure of 45 ±5 lbf/in^2 (gage), exposure time of 1 hour +1, -0 hour, dwell time of 1 hour maximum, and a reject limit of R_1 = 1 X 10^{-6} atm cm^3/s. Upon completion of test condition C, perform either test condition A at +100°C or test condition B with mineral oil at +100°C.

* Dielectric withstanding voltage (DWV): Method 301 of MIL-STD-202, terminal to terminal.

* AC: 100 Hz ± 10 Hz square wave, peak-to-peak voltage, three times dc rated voltage for 60 to 90 seconds, not to exceed 800 V p/p (see table II).




FIGURE 2. Waveform characteristics.

DC: 200 percent of dc rated voltage for 60 seconds minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:05Z
Check the source to verify that this is the current version before use.

* TABLE II. Insulation resistance versus capacitance value.

Temperature	Capacitance	Minimum insulation resistance (terminal to terminal)
+25°C	0μF to .1μF	3,000,000 megohms
	Greater than .1μF	300,000 megohm-microfarads
+85°C	0μF to .1μF	150,000 megohms
	Greater than .1μF	15,000 megohm-microfarads
+105°C	0μF to .1μF	20,000 megohms
	Greater than .1μF	2,000 megohm-microfarads

Insulation resistance (IR): Method 302 of MIL-STD-202. Charge to rated voltage, +105°C for 5 minutes maximum; however, for capacitance values greater than 1.0 μF, an additional 1 minute per μF is permitted.

* Terminal to terminal: See table II.

Dissipation factor (DF): 0.07 percent maximum.

Barometric pressure (reduced): Method 105 of MIL-STD-202, condition D (100,000 feet). 125 percent of dc rated voltage applied. See MIL-PRF-83421 for voltage limitations.

Vibration, random (optional): In accordance with MIL-PRF-83421 when ordered with "-" replaced with "H" in the PIN.

AC burn-in: 40 kHz for 24 hours ± 8 hours at rms current as specified in table I at 85°C.

Dielectric absorption: 0.1 percent maximum.

Immersion: Method 104 of MIL-STD-202, test condition C.

DWV:

Insulating sleeves: Greater than 4,000 volts, dc.

Terminal to terminal: 200 percent of dc rated voltage.

Terminals to case: 200 percent of dc rated voltage.

IR:

Insulating sleeves: 10,000 megohms, minimum.

Terminal to terminal: Not less than 50 percent of initial requirement.

Terminal to case: 5,000 megohms, minimum.

Δ C: Maximum of ±0.25 percent.

DF: 0.15 percent.

Moisture resistance: Method 106 of MIL-STD-202.

DWV, IR, ΔC, and DF: Same as for immersion.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:05Z
Check the source to verify that this is the current version before use.

Low temperature life: In accordance with MIL-PRF-83421, except measurements shall be made at the following temperatures:

t_1 = +25°C: Record initial capacitance, dissipation factor, and insulation resistance.

t_2 = - 65°C: 48 hours rated dc voltage applied.

t_3 = Maximum operating temperature: Two hours rated dc voltage applied (allow for derating).

t_4 = +25°C: Record capacitance, dissipation factor, and insulation resistance. Limits of change shall be as specified in table III.

TABLE III. Post measurement limits.

t_1 to t_4	Styles CRH11 through CRH13
Capacitance	± 0.5%
Dissipation factor	0.15% maximum
Insulation resistance	Within initial requirements

Resistance to soldering heat: Method 210 of MIL-STD-202, condition B.

ΔC: Maximum of ± 0.25 percent.

Temperature coefficient: In accordance with MIL-PRF-83421. Capacitance shall be measured at the temperatures specified in table IV.

TABLE IV. Temperature coefficient.

Temperature 1/	Styles CRH11 through CRH13
t_3 to t_2	0 to -4%
t_3 to t_4	0 to +3%
t_3 to t_1 or t_5	± .25%

1/ t_1 = +25°C ±3°C
t_2 = +105°C ±3°C
t_3 = +25°C ±3°C
t_4 = -55°C +0°C, -3°C
t_5 = +25°C ±3°C

DC life (at +105°C): Method 108 of MIL-STD-202.

Accelerated condition: 140 percent of dc rated voltage.

Rated condition: 100 percent of dc rated voltage.

IR:

Terminal to terminal: Not less than 33.3 percent of initial requirement.

Terminals to case: 5,000 megohms, minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:05Z
Check the source to verify that this is the current version before use.

ΔC: Maximum of ± 2.0 percent.

DF (at +25°C) after life: Maximum of 0.25 percent.

AC conditioning: In accordance with MIL-PRF-83421 with the following exceptions:

The ac performance shall be at the rated ac ripple current at +85°C, 40 kHz for 250 hours, +40, -0 hours (see table V).

TABLE V. AC test samples.


DC rated voltage (volts)	Sample size		Capacitance range for selection of sample (μF)
	Qualification	group B	
100	.47 μF - 4 20.0 μF - 4	15	.47 to 20.0
200	.18 μF - 4 5.0 μF - 4	15	.18 to 5.0
400	.056 μF - 4 2.0 μF - 4	15	.056 to 2.0

Qualification: Four each of the highest and lowest capacitance values in each voltage group (see table V).

Group B: 15 units shall be selected which are representative of capacitor ratings produced during the current productions period on a semi-annual basis and shall be representative of ratings manufactured during the period (see table V).

Marking: In accordance with MIL-PRF-83421.

Part or Identifying Number (PIN): Consists of the basic number of this specification sheet with a dash number coded as shown in the following:



Packaging: Capacitors may be furnished in tape and reel packaging when so specified in the ordering data.

Changes from previous issue: The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:05Z
Check the source to verify that this is the current version before use.

* Referenced documents: In addition to MIL-PRF-83421, this document also references MIL-STD-202 and MIL-STD-1276.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC
NASA - NA

Preparing activity:
DLA - CC

(Project 5910-2005-016)

Review activities:
Army - AR
Navy - AS, MC, OS, SH
Air Force - 19, 99

* NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at http://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:05Z
Check the source to verify that this is the current version before use.