INCH-POUND
MIL-PRF-83421/6B
AMENDMENT 2
15 November 2002
SUPERSEDING
AMENDMENT 1
24 January 2002

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, METALLIZED PLASTIC FILM DIELECTRIC,
DC AND AC, HERMETICALLY SEALED IN METAL CASES,
ESTABLISHED RELIABILITY,
STYLES CRH31, CRH32, CRH33, CRH34, AND CRH35

This amendment forms a part of MIL-PRF-83421/6B, dated 18 June 2001, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 11

* Seal test, delete and substitute:

"Seal: Method 112 of MIL-STD-202, test condition C, procedure IIIa with the following exceptions and details: a bomb pressure of 45 ±5 lbf/in$^2$ (gage), exposure time of 1 hour +1, -0 hour, dwell time of 1 hour maximum, and reject limit of $R_1$ = 1 X $10^{-6}$ atm cm$^3$/s. Upon completion of test condition C, perform either test condition A, test condition B with mineral oil, or test condition D."

PAGE 13

AC conditioning, delete and substitute:

"AC conditioning: In accordance with MIL-PRF-83421 at 40kHz and rated voltage or rated current. Test samples shall be in accordance with table V."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5910-2212)

Review activities:
Army - AR
Navy - AS, MC, OS, SH
Air Force - 19


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:06Z
Check the source to verify that this is the current version before use.