MIL-I-2781D
INTERIM AMENDMENT - 1(SHIPS)
10 December 1964

MILITARY SPECIFICATION

INSULATION, PIPE, THERMAL

(This interim amendment forms a part of Military Specification MIL-I-2781D, 13 June 1963. It was developed by the Department of the Navy, Bureau of Ships for immediate use pending the inclusion of its contents in a coordinated document.)

Page 5, table III, columns 3 through 8: Change densities from "13.0", "15.0", "13.0", "13.0", "20.0" and "20.0" to "14.0", "15.0", "14.0", "14.0", "22.0" and "20.0", respectively.

Page 5, paragraph 4.3.1.1.1, line 3: Change "I" to "II" and "4.0 percent" to "2.5 percent".

Page 5, paragraph 4.3.1.1.2, line 3: Change "L-6" to "II".

Page 6, table IV: Delete and substitute:

"Table IV - Sampling for tests.

Lot size in half section or segments	Sample size = Number of test specimens for each test (4.4.2, 4.4.4, 4.4.5, 4.4.6)	Number of test failures allowed (each test)
Up to 63	None	—
64 to 160	2	0
161 to 400	3	0
401 to 1,000	5	0
1,001 to 2,500	8	0
2,501 to 6,300	13	1
6,301 to 16,000	20	2
16,001 to 40,000	32	3

Preparing activity:
Navy - SH
(Project 5640-N030Sh)

FSC 5640

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:42Z
Check the source to verify that this is the current version before use.