NOT MEASUREMENT SENSITIVE

MIL-DTL-11589/295C
15 September 1995
SUPERSEDING
MIL-R-11589/295B
30 March 1993

DETAIL SPECIFICATION SHEET

RIBBON, ARMY RESERVE COMPONENT, OVERSEAS TRAINING

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11589 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

COLOR PATTERN SIZE: Regular FINISH: Moire

TOTAL WIDTH	WIDTH OF STRIPES INCHES & METRIC	FUNCTION OF STRIPES	COLOR & CABLE NUMBER STRIPES	FILLING YARN
	1/32 (0.8 mm)	Edge & Binder	Ultramarine Blue HS 67118	
	5/64 (2.0 mm)	Ground	Ultramarine Blue HS 67118	
	9/64 (3.6 mm)	Ground	White HA 67101	
	11/32 (8.7 mm)	Ground	Ultramarine Blue HS 67118	
	3/64 (1.2 mm)	Ground	White HA 67101	
1-3/8	3/32 (2.4 mm)	Ground	Old Glory Red HBF 67156	White HA 67101
(35.0 mm)	3/64 (1.2 mm)	Ground	White HA 67101	
	11/32 (8.7 mm)	Ground	Ultramarine Blue HS 67118	
	9/64 (3.6 mm)	Ground	White HA 67101	
	5/64 (2.0 mm)	Ground	Ultramarine Blue HS 67118	
	1/32 (0.8 mm)	Edge & Binder	Ultramarine Blue HS 67118	

NOTE: Ribbon will be cut in 1-3/8 inch (35.0 mm) strips and mounted horizontally on the ribbon bar. The ribbon edges shall be neatly trimmed and treated with a colorless transparent adhesive or resin to prevent raveling. The Old Glory Red HBF 67156 stripe will be centered and aligned straight in the horizontal position.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0816)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T19:54Z
Check the source to verify that this is the current version before use.