MILITARY SPECIFICATION SHEET

HULL FITTING, STUFFING TUBE, TYPE MX2646/U (LONG BODY), FOR FLEXIBLE, SOLID-DIELECTRIC, RADIO-FREQUENCY CABLE

This specification is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the stuffing tube described herein shall consist of this specification and the latest issue of MIL-H-21367(SH).




FIGURE 1. Assembly M21367/14-001 (MX2646/U) (long body).

FSC 5975

DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:24Z
Check the source to verify that this is the current version before use.




FIGURE 2. Body.

SH12844

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:24Z
Check the source to verify that this is the current version before use.

TABLE I. Standard parts.

Item no. 1/	Description	Fig	Qty	Material/spec	Formerly covered on Drawing
01	Body	2	1	NI-CU Alloy, QQ-N-281 CL A, Cold Drawn (Stress Relieved)	REC2687551-3
02	O-Ring		1	MS28775-111	
03	O-Ring		1	MS28775-211	
04	Socket Head Cap Screw 0.190-32, UNF-2A x 3/4 L		1	NI-CU Alloy, QQ-N-281 CL A	
05	Ring		1	MIL-H-21367/1, Fig. 7	
06	Clamp		1	MIL-H-21367/3, Fig. 4	
07	Cable Seal Nut		1	MIL-H-21367/3, Fig. 5	
08	O-Ring		1	REA10083-17, MIL-P-25732	
09	Washer		2	MIL-H-21367/3, Fig. 6	
10	Retainer		1	MIL-H-21367/3, Fig. 7	
11	Nut		1	MIL-H-21367/3, Fig. 11	
12	Gasket		1	MIL-H-21367/3, Fig. 10	
13	Clamp		1	MIL-H-21367/3, Fig. 9	
14	Dielectric Clamp		1	MIL-H-21367/3, Fig. 8	

1/ Item numbers are the same as numbers shown in circles on figures.

NOTES:

1. Military part number M21367/14-001.
2. All dimensions in inches.
3. Unless otherwise specified herein, tolerances shall be plus or minus 1/64-inch for fractions and plus or minus 0.005 for decimals. Angular tolerance shall be plus or minus 1/2 degree.
4. Type RG-130A/U cable conforms to MIL-C-17/56 and type RG-294A/U conforms to MIL-C-23020/2.
5. Type MX2646/U, long body, should be used for replacement purposes only. For new installations, use type MX8210/U conforming to MIL-H-21367/3.

Preparing activity:
Navy - SH
(Project 5975-N578-14)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:24Z
Check the source to verify that this is the current version before use.