MILITARY SPECIFICATION

PLOTTING BOARDS, SHIP'S STATUS AND TACTICAL DISPLAY (NAVAL SHIPBOARD USE)

This amendment forms a part of Military Specification MIL-P-21381B(SHIPS), 28 January 1963.

Page 1, paragraph 2.1: Under "SPECIFICATIONS MILITARY" add "MIL-Q-9858 - Quality Control Systems Requirements".

Page 3, paragraph 3.4.2: Delete and substitute:

"3.4.2 Plotting surface. - The plotting surface shall be of a transparent acrylic plastic material in accordance with MIL-P-5425. For boards desired to be fabricated in two halves, the plotting surface (not the supporting frame) shall be composed of two halves arranged for assembly with the joint vertical on board ship. The support frame for split boards shall be fabricated in two pieces as indicated on Drawing 815-1,853,032. The bottom member of the support frame for split boards shall be cut approximately one-fourth of the distance from the left edge and the top member shall be cut approximately one-fourth of the distance from the right edge as viewed from the front. These cuts shall be made equidistant from adjacent lamp holders and provided with sleeves for rigidity when assembled. Each half of the plotting surface shall be composed of a 3/8-inch thick front sheet and a 1/8-inch thick back sheet. The front and back sheets shall be secured to each other by means of countersunk machine screws located at each corner of the board where the sheets are covered by the upper and lower pencil tray angle pieces. At the center of the plotting surface the back (cover) sheet shall be secured to the front sheet (marking board) by means of small screws in holes countersunk into the back sheet and tapped in the back side of the front sheet (marking board) as indicated in Drawing 815-1,853,032. These screws shall not protrude through the front surface. To provide essential rigidity at the center of the plotting surface and to furnish an additional means of keeping the adjoining inner edges in alignment, the two halves of the plotting surface of split construction boards shall be clamped together at the center point. This clamp shall consist of a bolt, through both front and back sheets, not larger than 1/4-inch in diameter, with a washer on the front and back of the plotting surface. The washers shall not exceed 1 inch in diameter, and the securing nut thereon shall be on the back."

Page 3, paragraph 3.4.2.1: At the end of the paragraph add "On plotting boards with hand rotatable dials at the center, bearing lines shall begin at the edge of the hole cut for the dial."

FSC 6605

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:28Z
Check the source to verify that this is the current version before use.

Page 3, table I: Opposite "48" to but not including 60", under "Diagram design" delete S2407-1, 230, 368" and substitute "S2407-1, 230, 368 or S2407-756, 641".

Page 4, paragraph 3. 4. 3: In the first sentence delete "top to bottom" and substitute "top and bottom". In the third sentence delete "All plotting boards provided under this specification" and substitute "When specified (see 6. 1), plotting boards". In the tenth sentence delete "variable transformer". In the eleventh sentence delete "Wherever feasible". Delete the last sentence entirely.

Page 4, paragraph 3. 4. 6, last sentence: Delete.

Page 5: Insert paragraph 4. 1. 1 as follows:

"4. 1. 1 Quality control system. - The contractor shall provide and maintain a quality control system acceptable to the Government for equipment covered by this specification. The system for quality control shall be in accordance with MIL-Q-9858. "

Page 6, paragraph 4. 6. 2. 2: In the first sentence delete "5G" and substitute "23TR6". In the last sentence delete "1/2" and substitute "2" and delete "1" and substitute "4".

Page 7, paragraph 6. 1: Add (ℓ) as follows:

"(ℓ) Whether red lamps are required (see 3. 4. 3). "

Preparing activity:
Navy - Ships
(Project 6605-N066Sh)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:28Z
Check the source to verify that this is the current version before use.