INCH-POUND

MIL-R-55182/9E
AMENDMENT 3
22 March 1995
SUPERSEDING
AMENDMENT 2
14 December 1993

MILITARY SPECIFICATION

RESISTORS, FIXED, FILM, ESTABLISHED RELIABILITY
STYLE RNC90 1/

This amendment forms a part of MIL-R-55342/9E, dated 26 January 1990, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

TABLE I, delete and substitute:

" TABLE I. Style and terminal type.

Symbol	Terminal
RNC	Solderable/weldable (type C32 or C52 of MIL-STD-1276)
RNN 1/	Weldable (type N-2 of MIL-STD-1276)

1/ Type N terminals are not available for resistance values less than 500 ohms (see 6.3)."

PAGE 2

* 1.2.1.2, delete and substitute:

"1.2.1.2 Characteristic. Style RNC90 is available in characteristics Y and Z.

Characteristic Y - Nonhermetically sealed - Resistance temperature characteristic (referenced to +25°C) ± ±5 ppm/°C up to and including +125°C; and ±10 ppm/°C from +125°C to +175°C. 300 volts maximum working voltage.

Characteristic Z - Nonhermetically sealed - Resistance temperature characteristic (referenced to +25°C) ± ±5 ppm/°C up to and including +125°C; and ±10 ppm/°C from +125°C to +175°C. 100 volts maximum working voltage."

PAGE 3

* 3.5, delete and substitute:

"3.5 Voltage rating. The maximum continuous working voltage shall not exceed 300 volts for characteristic Y and 100 volts for characteristic Z."

PAGE 4

3.16, second line, delete "±.05" and substitute "±0.5".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:36Z
Check the source to verify that this is the current version before use.

* 6.4, delete and substitute:

"6.4 Power rating at +70°C. The power rating at +70°C for 2,000 hours of life test has been established at 0.6 watt, not to exceed the maximum working voltage. It should be noted that the failure rate level is established at a single condition of +125°C, 0.3 watt, and 10,000-hour life test duration."

6.5 and 6.6, delete and substitute the following:

"6.5 Low tolerance resistors. In low tolerance resistors (.005 and .01), resistance shifts due to high humidity are normal to precision, fixed, resistors. Before being considered out of tolerance, resistors should be conditioned in a dry oven at +125°C for 1 hour, +15/-0 minutes followed by 2 hours, +30/-0 minutes stabilization at ambient before measurement. Resistors which continue to be out of tolerance after the above conditioning process shall be considered rejects.

"6.6 Supersession data. Prior to MIL-R-55182/9A, dated 20 March 1975, the four digit code for resistance specified in MIL-R-55182 applied.

* 6.7, delete and substitute the following:

"6.7 Extent of qualification. Qualification of the higher power rating shall qualify the lower power rating.

6.8 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, AT, AV, ME
Navy - AS, CG, MC, OS
Air Force - 17, 99
DLA - ES

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5905-1412)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:36Z
Check the source to verify that this is the current version before use.