
INCH-POUND
MIL-PRF-55514/10E
w/AMENDMENT 1
17 September 2018
SUPERSEDING
MIL-PRF-55514/10E
6 September 2013

PERFORMANCE SPECIFICATION SHEET

CAPACITOR, FIXED, PLASTIC DIELECTRIC, DC, IN NONMETAL CASES, ESTABLISHED RELIABILITY, STYLE CFR15

This specification sheet is approved for use by all Departments and and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-55514.



NOTES:
1. Dimensions are in inches.
2. Millimeters are in parentheses.
3. Metric equivalents are given for general information only.

FIGURE 1. Style CFR15 capacitors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics.

Characteristic K, style CFR15 capacitors							
Part or identifying number (PIN) 1/	Capacitance (µF)	Capacitance tolerance available	DC Voltage at +105°C (volts)	Voltage at +85°C at 20 kHz (volts)	dv/dt volt/µs (volts)	D	L ± .062
CFR15AKC123--	.012	J, K, M	200	60	300	.179 (4.55) ± .047 (1.19)	.750 (19.05)
CFR15AKC153--	.015	J, K, M	200	60	300	.197 (5.00) ± .047 (1.19)	.750 (19.05)
CFR15AKC183--	.018	J, K, M	200	60	300	.212 (5.39) ± .047 (1.19)	.750 (19.05)
CFR15AKC223--	.022	J, K, M	200	60	300	.232 (5.89) ± .047 (1.19)	.750 (19.05)
CFR15AKC273--	.027	J, K, M	200	60	300	.251 (6.38) ± .062 (1.57)	.750 (19.05)
CFR15AKC333--	.033	J, K, M	200	60	300	.263 (6.68) ± .062 (1.57)	.750 (19.05)
CFR15AKC393--	.039	J, K, M	200	60	300	.242 (6.15) ± .062 (1.57)	.938 (23.83)
CFR15AKC473--	.047	J, K, M	200	60	300	.261 (6.63) ± .062 (1.57)	.938 (23.83)
CFR15AKC563--	.056	J, K, M	200	60	300	.270 (6.86) ± .062 (1.57)	.938 (23.83)
CFR15AKC683--	.068	J, K, M	200	60	300	.297 (7.54) ± .062 (1.57)	.938 (23.83)
CFR15AKC823--	.082	J, K, M	200	40	300	.259 (6.58) ± .062 (1.57)	1.250 (31.75)
CFR15AKC104--	.10	J, K, M	200	40	300	.284 (7.21) ± .062 (1.57)	1.250 (31.75)
CFR15AKC124--	.12	J, K, M	200	40	300	.310 (7.87) ± .062 (1.57)	1.250 (31.75)
CFR15AKC154--	.15	J, K, M	200	40	300	.345 (8.76) ± .062 (1.57)	1.250 (31.75)
CFR15AKC184--	.18	J, K, M	200	40	300	.377 (9.58) ± .062 (1.57)	1.250 (31.75)
CFR15AKC224--	.22	J, K, M	200	40	300	.416 (10.57) ± .062 (1.57)	1.250 (31.75)
CFR15AKC274--	.27	J, K, M	200	40	300	.389 (9.88) ± .062 (1.57)	1.688 (42.88)
CFR15AKC334--	.33	J, K, M	200	40	300	.427 (10.85) ± .062 (1.57)	1.688 (42.88)
CFR15AKC394--	.39	J, K, M	200	40	300	.462 (11.74) ± .062 (1.57)	1.688 (42.88)
CFR15AKC474--	.47	J, K, M	200	40	300	.501 (12.73) ± .093 (2.36)	1.688 (42.88)
CFR15AKC564--	.56	J, K, M	200	40	300	.635 (16.13) ± .093 (2.36)	1.688 (42.88)
CFR15AKC684--	.68	J, K, M	200	40	300	.706 (17.93) ± .093 (2.36)	1.688 (42.88)
CFR15AKC324--	.82	J, K, M	200	40	300	.675 (17.15) ± .093 (2.36)	2.063 (52.40)
CFR15AKC105--	1.00	J, K, M	200	40	300	.748 (19.00) ± .093 (2.36)	2.063 (52.40)
CFR15AKE682--	.0068	J, K, M	400	95	400	.217 (5.51) ± .047 (1.19)	.750 (19.05)
CFR15AKE822--	.0082	J, K, M	400	95	400	.230 (5.84) ± .047 (1.19)	.750 (19.05)
CFR15AKE103--	.01	J, K, M	400	95	400	.232 (5.89) ± .047 (1.19)	.750 (19.05)
CFR15AKE123--	.012	J, K, M	400	95	400	.250 (6.35) ± .047 (1.19)	.750 (19.05)
CFR15AKE153--	.015	J, K, M	400	95	400	.260 (6.60) ± .062 (1.57)	.750 (19.05)
CFR15AKE183--	.018	J, K, M	400	95	400	.243 (6.17) ± .047 (1.19)	.938 (23.83)
CFR15AKE223--	.022	J, K, M	400	95	400	.262 (6.66) ± .062 (1.57)	.938 (23.83)
CFR15AKE273--	.027	J, K, M	400	95	400	.275 (6.98) ± .062 (1.57)	.938 (23.83)
CFR15AKE333--	.033	J, K, M	400	95	400	.301 (7.65) ± .062 (1.57)	.938 (23.83)
CFR15AKE393--	.039	J, K, M	400	50	400	.261 (6.63) ± .062 (1.57)	1.250 (31.75)
CFR15AKE473--	.047	J, K, M	400	50	400	.284 (7.21) ± .062 (1.57)	1.250 (31.75)
CFR15AKE563--	.056	J, K, M	400	50	400	.307 (7.80) ± .062 (1.57)	1.250 (31.75)
CFR15AKE683--	.068	J, K, M	400	50	400	.336 (8.53) ± .062 (1.57)	1.250 (31.75)
CFR15AKE823--	.082	J, K, M	400	50	400	.367 (9.32) ± .062 (1.57)	1.250 (31.75)
CFR15AKE104--	.1	J, K, M	400	50	400	.404 (10.26) ± .062 (1.57)	1.250 (31.75)
CFR15AKE124--	.12	J, K, M	400	50	400	.441 (11.20) ± .062 (1.57)	1.250 (31.75)
CFR15AKE154--	.15	J, K, M	400	50	400	.491 (12.47) ± .062 (1.57)	1.250 (31.75)
CFR15AKE184--	.18	J, K, M	400	50	400	.456 (11.58) ± .062 (1.57)	1.688 (42.88)
CFR15AKE224--	.22	J, K, M	400	50	400	.500 (12.73) ± .062 (1.57)	1.688 (42.88)
CFR15AKE274--	.27	J, K, M	400	50	400	.533 (13.54) ± .093 (2.36)	1.688 (42.88)

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

Characteristic K, style CFR15 capacitors							
(PIN) 1/	Capacitance (µF)	Capacitance tolerance available	DC Voltage at +105°C (volts)	Voltage at +85°C at 20 kHz (volts)	dv/dt volt/µs (volts)	D	L ± .062
CFR15AKE334--	.33	J, K, M	400	50	400	.591 (15.01) ± .093 (2.36)	1.688 (42.88)
CFR15AKE394--	.39	J, K, M	400	50	400	.643 (16.33) ± .093 (2.36)	1.688 (42.88)
CFR15AKE474--	.47	J, K, M	400	50	400	.708 (17.98) ± .093 (2.36)	1.688 (42.88)
CFR15AKE564--	.56	J, K, M	400	50	400	.749 (19.02) ± .093 (2.36)	2.438 (61.93)
CFR15AKE684--	.68	J, K, M	400	50	400	.818 (20.78) ± .093 (2.36)	2.438 (61.93)
CFR15AKE824--	.82	J, K, M	400	50	400	.901 (22.89) ± .093 (2.36)	2.438 (61.93)
CFR15AKE105--	1.00	J, K, M	400	50	400	.998 (25.35) ± .093 (2.36)	2.438 (61.93)
CFR15AKF102--	.001	J, K, M	600	110	500	.243 (6.17) ± .047 (1.19)	.750 (19.05)
CFR15AKF122--	.0012	J, K, M	600	110	500	.253 (6.53) ± .062 (1.57)	.750 (19.05)
CFR15AKF152--	.0015	J, K, M	600	110	500	.261 (6.63) ± .062 (1.57)	.750 (19.05)
CFR15AKF182--	.0018	J, K, M	600	110	500	.299 (7.60) ± .062 (1.57)	.750 (19.05)
CFR15AKF222--	.0022	J, K, M	600	110	500	.257 (6.53) ± .062 (1.57)	.750 (19.05)
CFR15AKF272--	.0027	J, K, M	600	110	500	.265 (6.73) ± .062 (1.57)	.750 (19.05)
CFR15AKF332--	.0033	J, K, M	600	110	500	.240 (6.10) ± .047 (1.19)	.750 (19.05)
CFR15AKF392--	.0039	J, K, M	600	110	500	.253 (6.43) ± .062 (1.57)	.750 (19.05)
CFR15AKF472--	.0047	J, K, M	600	110	500	.258 (6.55) ± .062 (1.57)	.750 (19.05)
CFR15AKF562--	.0056	J, K, M	600	110	500	.265 (6.73) ± .062 (1.57)	.750 (19.05)
CFR15AKF682--	.0068	J, K, M	600	110	500	.268 (6.81) ± .062 (1.57)	.750 (19.05)
CFR15AKF822--	.0082	J, K, M	600	110	500	.257 (6.53) ± .062 (1.57)	.938 (23.83)
CFR15AKF103--	.01	J, K, M	600	110	500	.267 (6.78) ± .062 (1.57)	.938 (23.83)
CFR15AKF123--	.012	J, K, M	600	110	500	.290 (7.37) ± .062 (1.57)	.938 (23.83)
CFR15AKF153--	.015	J, K, M	600	110	500	.320 (8.13) ± .062 (1.57)	.938 (23.83)
CFR15AKF183--	.018	J, K, M	600	110	500	.347 (8.81) ± .062 (1.57)	.938 (23.83)
CFR15AKF223--	.022	J, K, M	600	110	500	.381 (9.68) ± .062 (1.57)	.938 (23.83)
CFR15AKF273--	.027	J, K, M	600	110	500	.328 (8.33) ± .062 (1.57)	1.250 (31.75)
CFR15AKF333--	.033	J, K, M	600	110	500	.358 (9.09) ± .062 (1.57)	1.250 (31.75)
CFR15AKF393--	.039	J, K, M	600	65	500	.387 (9.83) ± .062 (1.57)	1.250 (31.75)
CFR15AKF473--	.047	J, K, M	600	65	500	.421 (10.69) ± .062 (1.57)	1.250 (31.75)
CFR15AKF563--	.056	J, K, M	600	65	500	.457 (11.61) ± .062 (1.57)	1.250 (31.75)
CFR15AKF683--	.068	J, K, M	600	65	500	.501 (12.73) ± .093 (2.36)	1.250 (31.75)
CFR15AKF823--	.082	J, K, M	600	65	500	.516 (13.11) ± .093 (2.36)	1.250 (31.75)
CFR15AKF104--	.1	J, K, M	600	65	500	.571 (14.50) ± .093 (2.36)	1.250 (31.75)
CFR15AKF124--	.12	J, K, M	600	65	500	.501 (12.73) ± .093 (2.36)	1.688 (42.88)
CFR15AKF154--	.15	J, K, M	600	65	500	.559 (14.20) ± .093 (2.36)	1.688 (42.88)
CFR15AKF184--	.18	J, K, M	600	65	500	.613 (15.57) ± .093 (2.36)	1.688 (42.88)
CFR15AKF224--	.22	J, K, M	600	65	500	.677 (17.20) ± .093 (2.36)	1.688 (42.88)
CFR15AKF274--	.27	J, K, M	600	60	500	.706 (17.93) ± .093 (2.36)	2.063 (52.40)
CFR15AKF334--	.33	J, K, M	600	60	500	.783 (19.89) ± .093 (2.36)	2.063 (52.40)
CFR15AKF394--	.39	J, K, M	600	60	500	.854 (21.69) ± .093 (2.36)	2.063 (52.40)
CFR15AKF474--	.47	J, K, M	600	60	500	.939 (23.85) ± .093 (2.36)	2.063 (52.40)
CFR15AKF564--	.56	J, K, M	600	60	500	.908 (23.06) ± .093 (2.36)	2.438 (61.93)
CFR15AKF684--	.68	J, K, M	600	60	500	1.003 (25.48) ± .093 (2.36)	2.438 (61.93)
CFR15AKF824--	.82	J, K, M	600	60	500	1.005 (28.07) ± .093 (2.36)	2.438 (61.93)
CFR15AKF105--	1.00	J, K, M	600	60	500	1.223 (31.06) ± .093 (2.36)	2.438 (61.93)

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics- Continued.

Characteristic K, style CFR15 capacitors							
(PIN) 1/	Capacitance (µF)	Capacitance tolerance available	DC Voltage at +105°C (volts)	Voltage at +85°C at 20 kHz (volts)	dv/dt volt/µs (volts)	D	L ± .062
CFR15AKL562--	.0056	J, K, M	800	405	600	.201 (5.10) ± .047 (1.19)	1.250 (31.75)
CFR15AKL682--	.0068	J, K, M	800	405	600	.217 (5.51) ± .047 (1.19)	1.250 (31.75)
CFR15AKL822--	.0082	J, K, M	800	405	600	.236 (5.99) ± .047 (1.19)	1.250 (31.75)
CFR15AKL103--	.01	J, K, M	800	405	600	.251 (6.38) ± .062 (1.57)	1.250 (31.75)
CFR15AKL123--	.012	J, K, M	800	405	600	.264 (6.71) ± .062 (1.57)	1.250 (31.75)
CFR15AKL153--	.015	J, K, M	800	405	600	.294 (7.47) ± .062 (1.57)	1.250 (31.75)
CFR15AKL183--	.018	J, K, M	800	405	600	.321 (8.15) ± .062 (1.57)	1.250 (31.75)
CFR15AKL223--	.022	J, K, M	800	405	600	.354 (8.99) ± .062 (1.57)	1.250 (31.75)
CFR15AKL273--	.027	J, K, M	800	405	600	.392 (9.96) ± .062 (1.57)	1.250 (31.75)
CFR15AKL333--	.033	J, K, M	800	405	600	.433 (11.00) ± .062 (1.57)	1.250 (31.75)
CFR15AKL393--	.039	J, K, M	800	140	600	.380 (9.65) ± .062 (1.57)	1.688 (42.88)
CFR15AKL473--	.047	J, K, M	800	140	600	.414 (10.51) ± .062 (1.57)	1.688 (42.88)
CFR15AKL563--	.056	J, K, M	800	140	600	.451 (11.46) ± .062 (1.57)	1.688 (42.88)
CFR15AKL683--	.068	J, K, M	800	140	600	.501 (12.73) ± .093 (2.36)	1.688 (42.88)
CFR15AKL823--	.082	J, K, M	800	140	600	.523 (13.28) ± .093 (2.36)	1.688 (42.88)
CFR15AKL104--	.1	J, K, M	800	140	600	.579 (14.71) ± .093 (2.36)	1.688 (42.88)
CFR15AKL124--	.12	J, K, M	800	85	600	.582 (14.78) ± .093 (2.36)	2.063 (52.40)
CFR15AKL154--	.15	J, K, M	800	85	600	.652 (16.56) ± .093 (2.36)	2.063 (52.40)
CFR15AKL184--	.18	J, K, M	800	85	600	.716 (18.19) ± .093 (2.36)	2.063 (52.40)
CFR15AKL224--	.22	J, K, M	800	85	600	.793 (20.14) ± .093 (2.36)	2.063 (52.40)
CFR15AKL274--	.27	J, K, M	800	85	600	.779 (19.79) ± .093 (2.36)	2.438 (61.93)
CFR15AKL334--	.33	J, K, M	800	85	600	.863 (21.42) ± .093 (2.36)	2.438 (61.93)
CFR15AKL394--	.39	J, K, M	800	85	600	.940 (23.88) ± .093 (2.36)	2.438 (61.93)
CFR15AKL474--	.47	J, K, M	800	85	600	1.034 (26.26) ± .093 (2.36)	2.438 (61.93)
CFR15AKL564--	.56	J, K, M	800	85	600	1.131 (28.73) ± .093 (2.36)	2.438 (61.93)

1/ The complete PIN will include additional symbols to indicate capacitance tolerance and product level (C, M, P, R, and S).

REQUIREMENTS:

Dimensions and configuration: See figure 1 and table I.

Case: Non-hermetic.

Dielectric: Normally polypropylene, foil.

Capacitance (cap.) value: See table I.

Cap. Tolerance: See table I.

Rated voltage: See table I.

dv/dt: See table I.

Operating temperature range: -55°C to +105°C for dc operation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.

Product level: Non-established reliability - C; Established reliability - M, P, R or S.

Preconditioning: Not applicable.

Burn-in: In accordance with MIL-PRF-55514, except for the following conditions:

DC burn-in voltage shall be 140 percent of the dc rated voltage applied for 48 hours, minimum at +105°C, +4°C, -0°C.

AC burn-in: Not applicable.

Dielectric withstanding voltage (DWV): In accordance with MIL-PRF-55514, except the charge time shall be 2 minutes, maximum at 200 percent of the rated dc voltage.

Insulation resistance: In accordance with MIL-PRF-55514, except the test voltage shall be 100 V dc.

Dissipation factor (DF): Not more than 0.1 percent when measured in accordance with MIL-PRF-55514.

Low temperature conditioning and capacitance change with temperature: In accordance with MIL-PRF-55514.

Resistance to soldering heat: In accordance with MIL-STD-202-210, condition B.

ΔCap: ± 0.25 percent, maximum.

Life (at +105°C): In accordance with MIL-PRF-55514.

Accelerated condition: 140 percent of the +105°C rated voltage.

Rated condition: 100 percent of the +105°C rated voltage.

IR (at +25°C terminal to terminal): Not less than 50.0 percent of the initial requirement.

ΔCap (at +25°C): 2.0 percent, maximum.

DF (at +25°C) after life: .12 percent, maximum.

AC conditioning: In accordance with MIL-PRF-55514. The following details shall apply:

Qualification: Rated ac voltage at +85°C and 20 kHz on test samples in accordance with table II herein at 12-month intervals.

TABLE II. AC conditioning test samples.

DC rated voltage (volts)	Sample size	Cap range for selection of sample 1/ (μF)
200	24	.012 to 1.0
400	24	.0068 to 1.0
600	24	.001 to 1.0
800	24	.0056 to 0.56

1/ Each test sample shall contain at least one capacitor of the highest and lowest capacitance value of each voltage group manufactured during the 12-month period.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.

Amendment notations: The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-PRF-55514, this document references MIL-STD-202-210.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Navy - AS, MC, OS
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-2018-035)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.