MIL-S-51371CEA)
6 May 1987
SUPERSEDING
MIL-S-513713B
30 December 1985

MILITARY SPECIFICATIONS

SERVICE KIT, PORTABLE RIOT CONTROL AGENT DISPERSER, M254

This specification is approved for use within U.S. Army Chemical Research, Development and Engineering Center Deaprtment of the Army, and is available for use by all Departmetns and Agencies of the Department of Defense

SCOPE

1.1 Scope. This specification covers on type of service kit.

2. APPLICABLE DOCUMENTS

2.1 Government Documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issure of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

PPP-B-26 - Bag, Plastic, (General Purpose)
PPP-3-636 - Boxes, Shipping, Fiberboard.
PPP-C-1120 - Cushioning Material, Uncompressed Bound Fiber, for Packaging.
PPP-291 - Paperboard Wrapping and Cushioning.
PPP-T-76 - Packaging, Paper (For Carton Sealing).

: beneficial comments (recommendations, additions, deletions) and. any perti- :
: nent data which may be of use in improving this document should be addressed:
: to: Commander, U.S. Army Chemical Research, Development and Engineering:
: Center, ATTN: SMCOR-SPT-S, Aberdeen Proving Ground , MD 21010-5423 by using:
: the self-addressed Standardization Document Improvement Proposal (DD Form :
: 1426). appearing at the end of this document or by letter. :

AMSC N/A FSC 1040

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116 - Preservation, Methods of
MIL-B-117 - Bags, Sleeves and Tubing-Interior Packaging.
MIL-C-5501/7 - Caps and Plugs, Protective, Dust and Moisture Seal (Cap-Plug, General Purpose).

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1158 - Ammunition Lot Numbering.

2.1.2 Drawings. The following drawings form 2 part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. CHEMICAL REASEARCH, DEVELOPMENT AND ENGINEERING CENTER

116-3-104 - Service Kit, Portable Riot Control Agent Diserser; M254.
150-1-1 - Coupling Half, Quick Disconnect, Nipple, Type I - Plain, Size 4, 1/4 Nos. Tube 0.D.

(Copies of specifications, standards and drawings required by contractors in connection with specific acquisition functions shoud be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing 116-3-104 or on the subsidiary drawings shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the service kit shall conform to the specifications and drawings listed on Drawing 116-3-104 and subsidiary drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

3.2 Leakage.

3.2.1 In-line pressure check gauge assembly. The assembly (Drawing 116-3-63) sahll not lreak when tested in accordance with 4.4.6.1(a).

3.2.2 Pressure check gauge assembly. The assembly (Drawing 116-3-62) shall not leak except that a maximum pressure drop of 100 pounds per square inch gage (psig) in one minute is allowed through the air vent when tested in accordance with 4.4.6.1(b).

3.3 Preproduction. Prior to the start of regular production, a preproduction sample of service kit components shall be produced for examination and, tests in accordance with this specification.

3.4 Workmanship. The service kit components shall be free from foreign matter, damage, hose irregularities, dents or abrasions that, would, prevent, their intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with. all req.dire-ments of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction inspection.

4.3.1 Sample. A preproduction sample of five each of all components and subassemblies shall be manufactured using the same methods, materials, equipment, and processes as will be used during regular production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

4.3.2 Inspection procedure.

4.3.2.1 For examination and tests. The sample components and subassemblies shall be examined and tested in accordance with the classification of defects.

4.3.2.2 Acceptance/rejection criteria. If any assembly, components, or test specimen fails to comply with any of the applicable requirements, the preproduction sample shall be rejected. The Government reserves the right to terminate inspection upon any failure of any assembly, component, or test specimen to comply with any of the requirements.

4.4 Quality conformance inspections.

4.4.1. Lotting. Each lot dshall be identified and controlled in accordance with MIL-STD-1168.

4.4.2 Sampling for examination and nondestructive tests. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.3 Inspection procedures for examination and nondestructive test. The service kit components and the level A packaging shall be examined and tested in accordance with the classification of defects and with MIL-STD-105.

4.4.4 Critical defects. Each pressure check gauge assembly in the lot shall be inspected for the critical characteritics listed in the classification of defects.

4.4.5 Classification of detects.

(a) In-line pressure check gauge assembly (Drawing 116-3-63).

Categories	Defects	Acceptance Standards
Critical:	None-defined	
Major:	AQL 1.0 percent defective	
101	Leakage	4.4.6.1(a)

(b) Pressure check gauge assembly (Drawing 116-3-62).

Catagories	Defects	Acceptance standards
Critical:		
1	Leakage	4.4.6.1(b)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

(c) Filling adapter (Drawing 116-3-94).

Catagories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Thread incorrect
102	Undercut incorrect
103	Location (depth) undercut incorrect
Minor:	AQL 4.0 percent defective
201	knurl missing
202	hose barb missing

(d) Adapter assembly (Drawing 116-3-47).

Catagories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Washer missing
102	Internal thread incorrect
103	External thread incorrect
Minor	AQL 4.0 percent defective
201	Knurl missing

(e) Packaging (see section 5).

Categories	Defects
Critical:	None defined
Major:	AQL 4.0 percent defective
101	Components improperly cleaned and dried
102	Components missing or incorrectly arranged and packaged
103	Containers incorrect, broken or crushed
104	Containers closure incorrect
105	Cushioning incorrect
106	Straps loose or missing
107	Markings missing, incorrect, or illegible

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

4.4.4 Tests. Test shall be conducted as follows:

4.4.5.1 Leakage.

(a) In-line pressure check gauge assembly. The assembly shall be s~.ejected to a minimum of 200 psig air pressure for a minimum period of one minute and observed for leakage. Check for leakage with a suitable leak detecting solution (see 6.3).

(b) Pressure check gauge assembly. The assembly shall be subjected to a minimum 2100 psig air pressure. Stabilize the pressure and "top-off" to 2100 psig minimum. Check for leakage with a suitable leak detecting solution. If leakage is observed through the air vent, observe the gauge for one minute minimum and record the pressure drop (see 6.3).

5. PACKAGING

5.1 Cleaning. The components shall be cleaned, as neccessry, to be free of foreign matter that would interfere with the satisfactory performance of, or cause damage to the item. Cleaning shall be in accordance with cleaning process C-1, and drying shall be in accordance withany of the drying procedures outline in MIL-P-116.

5.2 Preservation and unit packing. Level shall be as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Gauge assembly, in-line pressure check, 300 psig. The gauge, cleaned in accordance with 5.1, shall have openings closed with plastic closures conforming to MIL-C-550l/7 and then wrapped in a piece of bound fiber cushioning material whose dimensions in inches shall be 1 by 5 by 12 and conforming to type IV, class A of PPP-C-1120. The wrapped gauge shall then be enclosed in a fiberboard box having inside dimensions in inches of 4-1/2 by 4-1/2 by 3 length, width and depth, respectively and conforming to W6c, style RSC of PPP-B-636. The box shall be closed in accordance with method III or IV of the appendix to PPP-B-636. The closed box shall then be sealed in a barrier bag, size 8-3/4 by 10 conforming to type II, class E, style 1 of MIL-B-117. The box shall be free of any projections or sharp edges or points that could rupture or damage the barrier bag. Included air volume shall be kept to a practicable minimum when the bag is sealed.

5.2.1.2 Gauge assembly, pressure check, 3000 psig. The gauge, cleaned in accordance with 5.1, shall have openings closed with plastic closures conforming to MIL-C-5501/7 and then wrapped in a piece of bound fiber cushioning material whose dimensions in inches shall be 1 by 7 by 12 and be placed in a fiberboard box 7-1/4 by 4-1/2 by 3 inches inside length, width and depth respectively, conforming to W6c, style RSC of PPP-B-636. The box shall be closed in accordance with method III or IV of the appendix to PPP-B-636. The closed box shall then be sealed within a barrier bag, size 8-3/4 by 12, conforming to type

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T20:58Z
Check the source to verify that this is the currentversion before use.

II, class E, style 1 of MIL-B-117. The box shall be free of any projections or sharp edges or corners that could rupture or damage the barrier bag. Included air volume shall be kept to a practicable minimum when the bag is sealed.

5.2.1.3 Dummy pack and gasket. The dummy pack shall be a fiberboard box conforming to style RSC, type CF, class weather-resistant, variety SW, grade W5c or W6c of PPP-3-636, having inside dimensions of 14 by 1-1/2 by 4-1/2 inches length, width and depth respectively. The-box shall be closed in accordance with the appendix of PPP-B-636 for weather-resistant boxes. The gasket (Drawing 116-3-112) , cleaned and dried in accordance with 5.1, shall be placed within a form fitting polyethylene bag which shall either be closed by heat sealing or folded and taped. The bag shall then be placed within the compartment for the pressure gauge assembly of the wood shipping container (Drawing 116-3-111).

5.2.1.4 Agent transfer tube assembly. The tube, cleaned in accordance with 5.1, shall have the open end of P/N D150-1-11-5-l-B closed by means of closure conforming to MIL-C-5501/7.

5.2.1.5 Technical publications. Applicable technical publications shall be sealed within a polyethylene bag, size 12 by 14 inches, conforming to type II, style 1 of PPP-B-26. Included air volume shall be kept to a practicable minimum when bag is sealed.

5.2.1.6 Adapter (P/N 2021-4-4S). The adapter shall be unit packed in accordance with method IC-1 of MIL-P-116, using cushioning confirming to PPP-P-291. The cushioning shall be not larger than necessary to provide full protection to the item, and shall be taped in place using PPP-T-76 tape. The cushioned item shall then be placed in a polyethylene bag conforming to style 1, type 1, class C of MIL-B-117 and heat sealed. The bag shall be of sufficient size to hold the cushioned item with a minimum of’ overage.

5.2.1.7 Nipple (Drawing 150-1-1). Unit packing shall be as specified in 5.2.1.6.

5.2.1.8 Adapter assembly. The adapter assembly shall be installed on the agent transfer tube assembly and its open end closed by means of closure conforming to MIL-C-5501/7.

5.2.l.9 Filter assembly. The filter assembly (Drawing 116-3-113) shall be placed within a form fitting polyethylene bag which shall either be closed by heat sealing or folded and taped. The bag shall then be placed within the compartment for the pressure check gauge of the wood shipping container, Drawing 115-3-111.

5.2.2 Level B. Unit packing shall be in accordance with 5.2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

5.3 Packing. Level shall be as specified (see 6.2).

5.3.1 Level A. The components of the service kit, prepared in accordance with 5.2.1, shall be packed together, one complete kit per box, in accordance with Drawing 116-3-111.

5.3.2 Level B. The service kit shall be packed in accordance with 5.3.1 except the wood bo shall be grade 3 without wood preservative treatment.

5.4 Marking. In conjunction with information furnished in the contract or order, marking shall be as specified herein.

5.4.1 Interior package marking. Unit packs and unpackaged items (5.2) shall be provided with marking information pertaining to the Federal stock number, item description, quantity and unit of issue, contract or purchase order number, level of preservation and unit packing and date packed, as applicable, in accordance with the requirements for interior package marking in MIL-STD-129. Marking of technical publications packages not required. Unpackaged items may be marked by tagging in accordance with MIL-STD-129.

5.4.2 Packing marking. The shipping and storage container shall be marked in accordance with Drawing 116-3-119.

6. NOTES

6.1 Intended use. This item is intended for use in servicing the M33 and M33A1 riot control agent dispersers

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Level of unit packing and packing required.

6.3 Caution. Due to the hazards inherent in testing with high pressures, contractors are advised that every precaution possible should be exercised for the safety and protection of personnel engaged in such testing.

6.4 International interest. Certain provisions of this specification are the subject of international standardization agreement ABCA-Army Quadripartite Standardization Agreement - 317. When amendment, revision, or cancellation of this specification is proposed which will modify the international agreement concerned, the preparng activity will take appropriate action through international standardization channels including departmental standardization offices to change the agreement or make other appropriate accommodations.

6.5 Subject term (key word) listing.

Disperser
Riot control agent
Service kit

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 1040-A186

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 Alexandria, VA

POSTAGE WILL BE PAID BY

Commander
U.S. Army Chemical Research, Development
and Engineering Center
ATTN: SMCCR-SPT-S
Aberdeen Proving Ground, MD 21010-5423

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-51371C(EA)	SERVICE KIT, PORTABLE RIOT CONTROL AGENT DISPERSER, M254

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

NOTICE OF INACTIVATION
FOR NEW DESIGN

INCH– POUND

MIL-S-51371C(EA)
NOTICE 1
28 September 1995

MILITARY SPECIFICATION

SERVICE KIT, PORTABLE RIOT CONTROL AGENT DISPERSER, M254

This notice should be filed in front of MIL-S-51371C(EA)
dated 6 May 1987.

MIL–S–51371C(EA) is inactive for new design and is no longer used except for replacement purposes.

Preparing activity:

Army – EA

Project No. 104O–A219

AMSC N/A

FSC 1040

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.