MILITARY SPECIFICATION

FUZE, MT, SQ, M577A1
LOADING, ASSEMBLING, PACKING AND METAL PARTS
FUZE, MT, SQ, M582A1 METAL PARTS

This Amendment forms a part of Military Specification MIL-F-64042A (AR), dated 6 June 1986, and is approved for use within the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.3: After the second sentence, add the following sentence:

"There shall not be any sealant internally beyond the body and ogive thread."

PAGE 4

3.11.3.1: Change to read as follows:

"3.11.3.1 Target impact non-function distance. The fuze, when set PD (see 6.5), shall not cause the projectile to function upon impact of the PD element when fired in the 105MM, M103 or M102 Tube, Charge 7 at a six (6) inch thick plywood target located 150 - 5 feet from the muzzle of the weapon."

PAGE 11

4.3.1: Add the following items to the listed items:

"Timer Assembly	12624555	80
Plate No. 1 Assembly, Timer	12624556	80"

Add Page 29a attached.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:11Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Timer Assembly (Dwg. 12624555)				
	Examination for Defects	30	-	3.2	4.4.2.98
	Timer Functioning Test	80	-	3.9.2	4.5.9
	Timer Non-Functioning Test	80	-	3.9.2	4.5.10
	SetBack Pin Arming Test	80	-	3.12	4.5.11
	Timer Beat Rate & Amplitude	80	-	3.13	4.5.13
	9 lb. Axial Load	40*	-	3.2	4.5.1.w
	Plate No. 1 Assembly Timer (Dwg. 12624556)				
	Examination for Defects	30	-	3.2	4.5.2.99
	50 lb. Torque Load on Ring Gear Assy	80	-	3.2	4.5.2.d
	5 lb. Axial unseating load on bushing	80	-	3.2	4.5.1.u
	5 lb. Axial unseating load on spin Detent Pivot Pin	80	-	3.2	4.5.1.t
	40 lb. Axial unseating load on Dowels Pins	80	-	3.2	4.5.1
	22 lb. Pull Off Load on Hairspring Support Bracket	40*	-	3.2	4.5.1.a.1

NOTES: *Destructive Test

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:11Z
Check the source to verify that this is the current version before use.

PAGE 53

4.4.2.23: Add "12624556" to the Next Higher Assembly block.

PAGE 54

4.4.2.24: Add "12624556" to the Next Higher Assembly block.

PAGE 57

4.4.2.27: Add "12624555" to the Next Higher Assembly block.

PAGE 58

4.4.2.28: Add "12624555" to the Next Higher Assembly block.

PAGE 61

4.4.2.31: Add "12624555" to the Next Higher Assembly block.

PAGE 64

4.4.2.34: Add "12624555" to the Next Higher Assembly block.

PAGE 67

4.4.2.37: Add "12624555" to the Next Higher Assembly block.

PAGE 69

4.4.2.39: Add "12624555" to the Next Higher Assembly block.

PAGE 71

4.4.2.41: Add "12624555" to the Next Higher Assembly block.

PAGE 72

4.4.2.42: Add "12624555" to the Next Higher Assembly block.

PAGE 73

4.4.2.43: Add "12624555" to the Next Higher Assembly block.

PAGE 74

4.4.2.44: Add "12624555" to the Next Higher Assembly block.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:11Z
Check the source to verify that this is the current version before use.

PAGE 80

4.4.2.50: Add "12624555" to the Next Higher Assembly block.

PAGE 82

4.4.2.56: Add "12624555" to the Next Higher Assembly block.

PAGE 89

4.4.2.59: Add "12624556" to the Next Higher Assembly block.

PAGE 102

4.4.2.72: Major Category 105, change "adhesive" to "sealant".

PAGE 104

4.4.2.73: Delete Info Category 300, and add the following Major Category:

"108 Evidence of sealant beyond the body and ogive threads, i, h, 3.2 and 3.3 "

PAGE 105

Add note i as follows:

"i To be performed on fuzes that are disassembled after Jolt and Jumble, transportation vibration, twelve meter drop and waterproofness tests."

Add pages 130a and 130b attached.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.98	Timer Assembly	1 OF 1	12624555
			NEXT HIGHER ASSEMBLY 9236718

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Limits of angle between tumbler and scroll exit port		0.40%	3.2	Gage
102	Balance wheel not detented in proper position and setback detent not restraining spin detent		0.40%	3.2	Visual
103	Mainspring not would as indicated		0.40%	3.2	Manual
104	Mainspring barrel stakes missing or insufficient		0.40%	3.2	Visual
105	Timer funtion test	a	100%	3.9.2	4.5.9
106	Timer non-function test	a	100%	3.9.2	4.5.10
107	Setback pin arming test	a	100%	3.12	4.5.11
108	Timer beat rate and ampliture	a	100%	3.13	4.5.13
109	Expansion plug above flush		0.40%	3.2	Visual
110	Protective cap missing		0.65%	3.2	Visual
111	9 lb. axial load	b	c	3.2	4.4.3.4
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES: a. Non destructive
b. Destructive test, see ara 4.4.3.4 for applicable sampling plan.
c. Reject timer assembly inspection lot if one (1) or more defective units are found.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.99	Plate No. 1 Assembly, Timer				12624556
					NEXT HIGHER ASSEMBLY
					12624555
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of balance wheel, staff and hairspring assembly		0.40%	3.2	Gage
102	50 in. lb. torque load on ring gear assembly	a	0.40%	3.2	4.5.2.d
103	5 lb. axial unseating load on spin	a	0.40	3.2	4.5.1.t
104	5 lb. axial unseating load on bushing	a	0.40%	3.2	4.5.1.u
105	40 lb. axial unseating load on dowel pins	a	0.40%	3.2	4.5.1.v
106	Balance wheel outside tolerance zone	a	0.40%	3.2	Gage
107	22 lb. pull off load on hairspring support bracket	b	0.40%	3.2	
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:
a. Non destructive test
b. Destructive test

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:11Z
Check the source to verify that this is the current version before use.

PAGE 132

4.3.3.4: In the third sentence after drawing 9236711 add "/12624555".

PAGE 137

4.5.1.t: Delete "(Dwg. 9236712)" and add "(Dwg. 9236712/12624556)".

PAGE 138

4.5.1.u: Delete "(Dwg 9236712)" and add "(Dwg. 9236712/12624556)".

4.5.1.v: Delete "(Dwg 9236712)" and add "(Dwg. 9236712/12624556)".

4.5.1.w: Delete "(Dwg 9236712)" and add "(Dwg. 9236712/12624556)".

PAGE 140

Add Para. 4.5.1.al as follows:

"Test	Load & Application
Hairspring Support Bracket, Plate No. 1 Assembly, Timer (Dwg 12624556)	22 lb. min pull of as per dwg"

PAGE 151

Remove this page and insert new page 151 attached.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

TABLE V. Ballistic performance.

TEST	WEAPON	TUBE	PROJECTILE	CHARGE ZONE	SETTING	TEMPERATURE	SAMPLE a SIZE	SAMPLE b SIZE
Non-Function[e]	105MM	M103 or M102	M1	7	PD	70°F ±10°F	15[c]	10[c]
Function[e]	155MM	M1	M107	1	PD	70°F ±10°F	15	10
Mechanical Time[d]	155MM	M185	M107	8	50.0 Sec.	70°F ±10°F	10[c]	10[c]
	155MM	M185	M107	8	75.0 Sec.	70°F ±10°F	10	10
	105MM	M103 or M102	M1	7	50.0 Sec.	70°F ±10°F	10	20
	8 Inch	M2	M106	1	15.0 Sec.	70°F ±10°F	10	
Extreme Temperature[d]	105MM	M103 or M102	M1	7	50.0 Sec.	+145°F -5°F	10	-
	8 Inch	M2	M106	1	25.0 Sec.	-35°F +5°F	10	10

NOTES:

a. For First Article and three consecutive acceptable lots (See 4.4.3.6.1).

b. For subsequent lots after "a" above (See 4.4.3.6.2).

c. Transportation Vibration samples.

d. The Quadrant Elevation (QE) and Height of Burst (HOB) shall be as specified in 6.10. All rounds fired shall use Spotting Charge, Model APG-2 (9297939).

e. The Spotting Charge above shall not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:11Z
Check the source to verify that this is the current version before use.

4.5.21.6: Delete in its entirety.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A473)

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:11Z
Check the source to verify that this is the current version before use.