MILITARY SPECIFICATION

GELLING UNITS, FUEL
MARK 1, MOD 0 AND MOD 1

This specification is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers the minimum requirements for electrically powered, mechanical gelling units used for the production of gelled fuel for fire bombs. All gelling units covered by this document have complete dual voltage (220/440) capabilities.

1.2 Classification. Units shall be wired to the following types as specified in the contract or purchase order (see 6.2):

Type I - 220 volts, 60 hertz (Hz), 3 phase

Type II - 440 volts, 60 Hz, 3 phase

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2,1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of-the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Engineering Specifications and Standards Department (Code 93), Naval Air Engineering Center, Lakehurst, NJ 08733 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1040

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

QQ-S-781	Strapping, Steel, and Seals
PPP-B-601	Boxes, Hood, Cleated-Plywood
PPP-B-636	Boxes, Shipping, Fiberboard
PPP-T-97	Tape, Pressure-Sensitive Adhesive, Filament Reinforced

MILITARY

MIL-P-116	Preservation, Methods of
MIL-G-5572	Gasoline, Aviation, Grades 80/87, 100/130, 115/145
MIL-H-83282	Hydraulic Fluid, Fire Resistant, Synthetic Hydrocarbon Base, Aircraft, NATO Code Number H-537
MIL-T-5624	Turbine Fuel, Aviation, Grades JP-4 and JP-5

STANDARDS

MILITARY

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-143	Standards and Specifications, Order of Precedence for the Selection of
MIL-STD-810	Environmental Test Methods and Engineering Guidelines
MIL-STD-889	Dissimilar Metals

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

NAVAL AIR SYSTEMS COMMAND (Code Ident 30003)

AS-1532-1	Gel Component (Non-Alkaline), Fire Bomb (Solution A)
AS-1533-1	Gel Component (Alkaline), Fire Bomb (Solution B)
NAVAIR 19-1-112	Gelling Unit, Fuel, Mark 1, Mod 0 Operational Maintenance and Overhaul Instructions with IPB
DL2581669	Gelling Unit, Fuel, Mark 1 Mod 0
DL1558AS100	Gelling Unit, Fuel, Mark 1 Mod 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM 01655-83 Turbine Fuels, Specification for

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

UNIFORM CLASSIFICATION COMMITTEE, Agent

Uniform Freight Classification Rules

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.4 and 6.3).

3.2 Selection of specifications and standards. Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

3.3 Materials. Materials shall conform to applicable specifications and drawings, and shall be as specified herein. Materials which are not covered by specifications, or which are not specifically described herein, shall be of the best quality, of the lightest practical weight, and suitable for the purpose intended.

3.3.1 Metal parts. All metal parts shall be of corrosion resistant material or treated in a manner to render them adequately resistant to corrosion.

3.3.1.1 Dissimilar metals. Unless suitably protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MIL-STD-889.

3.4 Design and construction. The design and construction of the Mod 0 unit shall be in accordance with the applicable drawings listed on DL2581669 and the Mod 1 unit shall be in accordance with the applicable drawings listed on DL1558AS100, and the requirements listed herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

3.5 Performance.

3.5.1 Wiring and rotation. The motor shall rotate in a counterclockwise direction as viewed from the fan end when the unit is examined in accordance with 4.6.2 through 4.6.2.2, with assignment of voltage as specified by the procuring activity (see 6.2).

3.5.2 Gel mobility. The average flow of the gelled fuel produced by the unit shall not exceed 4 inches in 60 ± 1 seconds when tested in accordance with 4.6.3 through 4.6.3.3.

3.5.3 Blending. The unit shall blend the gelling agents in the ratios of 4.8 to 5.04 volumes of Solution A (see 6.4) and 2.42 to 2.54 volumes of Solution B (see 6.4) per 100 volumes of fuel in accordance with 4.6.4 through 4.6.4.2.1.

3.5.4 Capacity. The unit shall deliver gelled fuel at a minimum rate of 35 gallons per minute (gpm) from the gel-discharge hose when operated in accordance with instructions given in 4.6.4 through 4.6.4.2.2 with a suction head of 6 ± 1 feet for solutions and fuel.

3.5.5 Leakage. There shall be no gage indicated pressure drop and no external leakage from any joint, shaft seal, or mating surface of the unit when subjected to 150 ± 5 pounds per square Inch gage (psig) pressure in accordance with the testing procedures specified in 4.6.5 through 4.6.5.1.

3.5.6 Pressure switch requirements. The pressure switch shall automatically shut down the unit within 20 seconds after the supply of Solution A is depleted. Functioning shall be tested in accordance with 4.6.6.

3.5.7 Temperature switch. The temperature switch shall automatically shut down the unit when the aviation gasoline (115/145 octane) in the fuel section is 175 ± 5°F. Functioning shall be tested in accordance with 4.6.7.

3.6 Environmental. The unit shall meet all the requirements as specified herein during operating and after non-operating exposure to the following environmental conditions when tested as specified in 4.6.8 through 4.6.10.

a. Operating

(1) Low temperature: +20° F

(2) High temperature: +120°F

b. Non-operating

(1) Low temperature: -65°F

(2) High temperature: +165°F

(3) Vibration: 5 to 30 Hz at 1.5 gravity units (g); 31 to 50 Hz at 0.033 inch double amplitude (da)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

3.7 Workmanship. The unit, including all parts and accessories, shall be constructed and finished in a manner to ensure compliance with all the requirements of this specification. Particular attention shall be given to neatness and thoroughness of soldering, wiring, marking of parts, plating, painting, and freedom from burrs and sharp edges (see 4.6.1).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (4.4)

b. Quality conformance inspection (4.5)

4.3 Test conditions. Unless otherwise specified, the units shall be tested under the following standard conditions:

a.	Temperature:	77 ± 18°F
b.	Humidity:	90 percent maximum
c.	Barometric pressure:	Local standard

4.3.1. Stabilization. Temperature stabilization will have been attained when the temperature of the part of the test item considered to have the longest thermal lag does not change more than 3.6°F per hour.

4.4 First article inspection. First article inspection shall consist of all the examinations and tests listed in Table I in the sequence shown.

4.4.1 First article sample. Unless otherwise specified, as soon as practicable after the award of the contract or order, the manufacturer shall submlt one unit. The unit shall be representative of the construction, workmanship, components, and materials to be used during production.

4.4.1.1 Upon completion of the first article inspection, all applicable inspection reports will be forwarded to the government quality control representative (see 6.2).

4.4.1.2 Following acceptance by the government activity, the first article sample may be delivered as one of the units of supply under the contract. Approval of the first article sample shall not relieve the contractor of his obligation to meet the requirements of the specification for the remaining units being furnished under the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

4.4.1.3 Failure and retest. Failure to meet any of the requirements specified herein or pass any of the first article examinations or tests specified in Table I shall be cause for rejection. Full particulars concerning the failure and measures to be taken to correct the defects shall be forwarded to the government inspector, contracting officer, and responsible design activity with 30 days of the failure (see 6.2). Upon resubmission of the unit for inspection after a failure, the inspection shall start at the beginning of the test during which the failure occurred.

TABLE I. First article inspection

SEQUENCE	EXAMINATION OR TEST	REQUIREMENT PARAGRAPHS	METHOD PARAGRAPH
1	Workmanship/Examination of product	3.7	4.6.1
2	Wiring and rotation	3.5.1	4.6.2
3	Leakage	3.5.5	4.6.5
4	Gel mobility (standard conditions)	3.5.2	4.6.3
5	Low temperature (mobility with solutions and fuel at +20 ± 5°F)	3.5.2 3.6a(1) 3.6b(l)	4.6.8
6	High temperature (mobility with solutions and fuel at +120 ± 5°F	3.5.2 3.6a(2) 3.6b(2)	4.6.9
7	Vibration	3.6b(3)	4.6.10
8	Gel mobility (standard conditions)	3.5,2	4.6.3
9	Blending and capacity (standard conditions)	3.5.3 3.5.4	4.6.4
10	Pressure switch	3.5.6	4.6.6
11	Temperature switch	3.5.7	4.6.7
12	Examination of product		4.6.1

4.5 Quality conformance inspection. Quality conformance inspections shall be as specified in Table II in the sequence shown. Failure to pass any of the examinations or tests specified in Table II shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

TABLE II. Quality conformance inspection

SEQUENCE	EXAMINATION OR TEST	REQUIREMENT PARAGRAPHS	METHOD PARAGRAPH
1	Workmanship/Examination of product	3.7	4.6.1
2	Wiring and rotation	3.5.1	4.6.2
3	Leakage	3.5.5	4.6.5
4	Temperature switch	3.5.7	4.6.7
5	Pressure switch	3.5.6	4.6.6
6	Gel mobility (standard conditions)	3.5.2	4.6.3
7	Examination of product	3.7	4.6,1
8	Packaging	Section 5	4.7

CAUTION

The materials used in some of these tests are volatile or caustic. Extreme caution should be observed during the following tests (see NAVAIR 19-1-112).

4.6 Methods of examination and test.

4.6.1 Examination of product. The units shall be examined for conformance with this specification and applicable drawings with respect to workmanship, material, dimensions, and markings.

4.6.2 Wiring and rotation. For both the Mod 0 and the Mod 1, examination of the wiring and rotation shall be made to determine that the internal wiring corresponds to the requirements of the specified documents and for use at the voltage designated in the procurement document as follows:

4.6.2.1 Mod 0. Examination shall determine that the internal wiring to the latching coil, heater coils, and motor shall correspond to the requirements of the documents specified in DL2581669 for use at the voltage designated (see 6.2).

4.6.2.2 Mod 1. Examination shall determine that the internal wiring to the latching coil, overload relays, and motor shall correspond to the requirements of the documents specified in DL1558AS100 for use at the voltage designated (see 6.2).

4.6.3 Gel mobility.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

4.6.3.1 Test materials. When preparing gels for test purposes, the following materials shall be employed:

a. Fuel: Aviation gasoline as specified in MIL-G-5572; aviation turbine fuel JP-4 and JP-5 as specified in MIL-T-5624; or aviation turbine fuel as specified in ASTM D1655.

b. Solution A that has met the requirements of AS-1532-1.

c. Solution B that has met the requirements of AS-1533-1.

4.6.3.2 Test apparatus. The apparatus required for the gel mobility test shall consist of the following:

A steel “test plate” inclined at an angle of 45 ± 2° to the horizontal plane. The plate shall be covered with a piece of clean, dry, 20-weight bond paper, a minimum 8 by 13 inches in size.

b. A 50-milliliter (ml) beaker.

c. A stopwatch.

4.6.3.3 Test procedure. Gel mobility shall be tested by the following procedures:

Stabilize the unit (4.3.1), aviation gasoline (115/145 octane), Solution A, and Solution B at the test temperature (Table I or Table II).

b. After production of gel for 45 seconds In accordance with NAVAIR? 19-1-112 a sample (approximately one quart) of the gelled fuel shall be taken during full flow from the end of the discharge hose during the last 5 seconds of gel production.

c. In not less than 3 and not more than 12 minutes after sampling, select a single, integral piece of gelled fuel (from b) 30 to 40 ml in size and transfer it intact to the 50 ml beaker.

d. At a height of approximately 25 inches above the upper half of the bond paper on the test plate, invert the 50 ml beaker.

e. Immediately after impact of sample on the paper, draw a horizontal line at the lower edge of the gel and start the stopwatch.

f. After 60 ± 1 seconds, draw a horizontal line at the same lower edge of the gel.

g. Measure the distance in inches between the two lines on the bond paper. Record the distance of movement.

Repeat c through g on another piece of gel from the same quart sample obtained in b. Average the results of the two mobility tests.

4.6.4 Blending and capacity. Blending and capacity tests shall be performed under standard conditions (see 4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

4.6.4.1 Facilities and apparatus. Testing facilities and apparatus shall be in accordance with the following:

The surfaces of the three gel components shall be at least 6 feet below the intake ports of the unit.

b. Flow meters shall be installed in the Solution A, Solution B, and fuel supply lines. The flowmeters shall measure volumes with an accuracy of ±2 percent and shall not restrict the rate of flow of the fluid.

4.6.4.2 Procedure. Set up the unit for operation in accordance with NAVAIR 19-1-112. Start the unit and assure production of gel. Close the discharge valve and record readings on each of the three flowmeters. Open the discharge valve to full open and produce gel for 60 ±2 seconds, close discharge valve and record flowmeter readings. Open discharge valve to full open and produce gel for 120 ±2 seconds, close discharge valve and record flowmeter readings. Again open discharge valve to full open and produce gel for 120 ±2 seconds, close discharge valve, shut unit off and record flowmeter readings. Compute the blending and capacity ratios for each of the gel producing sequences as follows:

A = volume of Solution A (gallons)

B = volume of Solution B (gallons)

F = volume of fuel (gallons)

T = "Open" time for discharge valve (minutes)

4.6.4.2.1 Blending formulas,

R_A = Ratio of volume of Solution A to 100 volumes of fuel

$$R_A = \frac{100A}{F}$$

R_{B-} = Ratio of volume of Solution B to 100 volumes of fuel

$$R_B = \frac{100B}{F}$$

4.6.4.2.2 Capacity formula.

C = Capacity of unit (gpm)

$$C = \frac{A + B + F}{T}$$

4.6.5 Leakage. Inspection for leakage shall be conducted under standard conditions (4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

4,6.5.1 Procedure. To verify conformance to the leakage requirements proceed as follows:

a. Turn the Solution A and B regulator valves to the 20°F settings on the dials and open the discharge valve to full open.

b. Supply hydraulic fluid as specified in MIL-H-83282 at a pressure of 150 ±5 psig to the solution A and B quick disconnect fittings and to the fuel fitting.

c. Close the discharge valve when an uninterrupted flow exists from the valve.

d. Shut off hydraulic fluid source, read the fluid pressure gage (capable of being read in 1-pound increments and located between fluid supply shut off valve and unit), and record reading. After a 10 minute period, read pressure gage and record reading.

4.6.6 Pressure switch testing. With the unit producing gelled fuel under the standard conditions (4.3) and in accordance with procedures described in NAVAIR 19-1-112, the probe shall be removed from the supply of Solution A simultaneously with the starting of a stopwatch. Stop the watch and record the pressure when the switch stops the operation of the unit.

4.6.7 Temperature switch testing. Prior to installation of the temperature switch to the unit, calibrate switch by simulating actual working installation to function at 175 ±2°F, install into unit and proceed with test. With the unit producing gelled fuel under the standard conditions (4.3) and in accordance with procedures described in NAVAIR 19-1-112, the delivery nozzle shall be closed and remain closed to provide continuous recirculation of fuel, Solution A, and Solution B within the unit. Determination of the recirculating fuel temperature shall be made on the exterior of the plumbing at a point immediately downstream from the (automatic) temperature sensing device to ensure correct knowledge of the fuel temperature within. The temperature of the recirculating fuel shall be recorded upon automatic shutdown of the unit.

4.6.8 Low temperature. The following low temperature test procedures shall be performed in the order given.

a. Place the unit in a test chamber at standard conditions (4.3).

b. Lower test chamber temperature to - 65 ±3°F and stabilize unit (4.3.1).

The temperature shall then be raised to +20 ± 3°F and the unit stabilized (4.3.1). The unit shall then be operated with aviation gasoline or turbine fuel and Solutions A and B supplied at +20 ±3°F.

d. A sample shall be tested according to test procedures specified in 4.6.3.3.

e. Stabilize unit and solution at 20°F.

f. Operate “A” probe with kerosene.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

g. Operate "B" probe with kerosene.

h. Operate "A" probe with Solution A.

i. Operate "B" probe with Solution B.

j Time flow of each solution.

k. Measure flow rate of each solution.

l. If solution will not flow, use probe without screen.

m. Then raise temperature to 25°F and repeat step "h" and "i" with screen in probe.

n. Continue to raise temperature in 5° increments until solutions flow.

o. Mix gel at best low temperature.

P. If gel mixes, repeat cold test per test plan at new temperature,

q. If no-gel condition arises, continue test at next highest 5° increment until gel condition Is accomplished.

4.6.9 High temperature. Place the unit in a test chamber at standard conditions (4.3). Raise test chamber temperature to +160 ±3°F and stabilize unit (4.3.1). The temperature shall then be reduced to +120 ±3°F and the unit stabilized. The unit shall then be operated with aviation gasoline or turbine fuel and Solutions A and B supplied at +120 ±3°F. A sample shall be tested as specified in 4.6.3.

4.6.10 Vibration. The unit shall be mounted and vibrated (non-operating) in accordance with the requirements specified in MIL-STD-810, Method 514.2, Category F, with the following exceptions:

a. Unit shall be directly mounted on the vibration table without use of shock mounts.

b. Unit shall have all hoses (input and output) removed at the quick disconnect fittings.

The cycle shall be limited to 5 to 50 Hz. The test level shall be in accordance with MIL-STD-810, Curve VW of Figure 514.2-6 and Time Schedule of Table 514.2-VI, Procedure VIII, Wheeled Vehicles.

4.7 Inspection of packaging. The packaging shall be examined to comply with Section 5.

5. PACKAGING

5.1 Preservation. Preservation shall be Level A (see 6.2).

5.1.1 Level A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

5.1.1.1 Cleaning. Unless otherwise specified, the unit shall be cleaned in accordance with MIL-P-116, Method C-1.

5.1.1.2 Drying. Unless otherwise specified, the unit shall be dried in accordance with MIL-P-116 by either or both Methods D-4 and D-1.

5.1.1.3 Preservation. Unless otherwise specified, all units shall be thoroughly preserved by flushing (see NAVAIR 19-1-112) with hydraulic fluid in accordance with MIL-H-83282. Any preservation applied by the contractor shall not damage the mechanism, structure, or functioning of the unit.

5.1.1.4 Unit packs. Unless otherwise specified, the gelling unit and hose components shall be packed in accordance with the methods of MIL-P-116 designated herein ensuring compliance with the applicable requirements of that specification.

5.1.1.4.1 Gelling unit. The gelling unit shall be packaged in accordance with MIL-P-116, Method III.

5.1.1.4.2 Hose components. The hose components shall be packaged in accordance with MIL-P-116 and as follows:

a. Suction Hose Probe Assembly (2581674) - seal ends with tape in accordance with PPP-T-60, Type III.

b. Discharge Hose Assembly (2581665) - seal ends with tape in accordance with PPP-T-60, Type III.

c. After packaging in accordance with a and b above, place hose into a carton conforming to PPP-B-636 and seal with tape conforming to PPP-T-97 on centers and edges making a seal.

5.2 Packing. Packing shall be Level A or Level C as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Exterior containers. The gelling unit packaged as specified in 5.1.1.4.1 shall be packed into a plywood box, shielded in accordance with PPP-B-601, and bolted in place. The box shall be provided with two skids positioned on 38 inch centers.

5.1.1.2 Hose components packing. The hoses as packaged under 5.1.1.4.2 shall be positioned and secured to the base (aft} utilizing strapping conforming to QQ-S-781.

5.2.2 Level C. The gelling unit and components packaged in accordance with 5.1.1.4.1 and 5.1.1.4.2 shall be packed to afford protection against damage during shipment from the supply source to the first receiving activity for immediate use. Containers shall comply with Uniform Freight Classification Rules or other common carrier regulations applicable to the modes of transportation.

5.3 Marking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

5.3.1 Special markings. The following markings shall be required: Date manufactured, voltage type designation, and lot numbers.

5.3.2 Normal marking. In addition to the markings required by contract or purchase order, unit packages and shipping containers shall be marked in accordance with the requirements of MIL-STD-129, including serial numbers,

6. NOTES

6.1 Intended use. Fuel gelled in these units constitutes the filler for flame weapons such as fire bombs. The unit described in this document is intended primarily for use aboard aircraft carriers and at forward air bases.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this document

b. First article sample, if different from 3.1

c. Testing activity designated for first article sample

d. Failure and retest, design activity (NAEC/SEED (92722), (see 4.4.1.3)

e, Serial numbers (see 5.3)

f. Designation for external electrical supply (see 1.2)

g* Levels of preservation, packaging and packing (see 5.1)

h. Special packing and packaging requirements (see 5.2)

i. Inspection reports required

6.3 First article. when a first article inspection is required, the item will be tested and should be a first article sample as specified in 4.4.1. The first article should consist of one unit. Arrangements for examinations and test approval of the documents first article shall be specified in the contract or purchase order.

6.4 Solution A and Solution B. Solution A is a proprietary product. Solution A and Solution B are procurable through the Western Company of North America, Research Division, 2201 North Waterview Parkway, Richardson, TX 75080.

6.5 Changes from previous issues. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Preparing activity
Navy- AS
(Project No. 1040-N157)

*U.S. GOVERNMENT PTINTING OFFICE: 1984-505-038/A4643

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T06:02Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions - Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-G-81737A(AS)	Gelling Units, Fuel, Mark 1, Mod 0 and Mod 1

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.