INCH-POUND

MIL-S-81746/1
5 April 1991

MILITARY SPECIFICATION SHEET

SERVTORQ, TYPE 15ST4A

This specification is approved for use by all Departments and Agencies of the Department of Defense. The requirements for acquiring the Servtorqs described herein shall consist of this specification sheet and the issue of the following specification listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-S-81746.

TABLE I. Requirements.

Requirement	Value	Unit	Tolerance
Reference voltage 1/	115	volts	±1%
Frequency	400	hz	±1%
Power:			
Primary	2.0	watts	maximum
Stall	12.0	watts	maximum
Current:			
Primary	80	milliamps	maximum
Stall	500	milliamps	maximum
Electrical error	12	minutes	maximum
Stall torque	2.0	ounce-inches	minimum
No-load slewing speed	1200	rpm	minimum
Servtorq sensitivity	---	minutes	maximum
Dynamic error	30	minutes	maximum
Synchronizing time:			
30° ±2°	0.5	seconds	maximum
177° ±2°	1.0	seconds	maximum
183° ±2°	1.0	seconds	maximum
330° ±2°	0.5	seconds	maximum
Slewing speed under load	---	rpm	minimum
Temperature rise:			
Quiescent	---	degrees (C)	maximum
Stall	---	degrees (C)	maximum
Torque gradient	9.0	oz-in per degree	minimum
Shaft load inertia	0-250	$gm\text{-}cm^2$	min.-max.
Velocity constant	720	$seconds^{-1}$	minimum
Variation of voltage (±10%) & frequency (±5%)	2.4	watts	maximum
Radial play	0.0010	inches	maximum
End play	0.0020	inches	±0.0010
Weight	8.0	ounces	maximum

FSC 5990

AMSC - N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:03Z
Check the source to verify that this is the current version before use.

NOTES:

1/External power of 25VDC @ 0.5 amps maximum is required.

2/Type 15ST4A servtorqs shall be capable of operating in ambient temperatures ranging from -55°C to +85°C.

TABLE II. Part identifying number variant characteristics.

Part Identifying Number 1/	A ±.010	B ±.010	G Maximum	Shaft Style	Terminal End	U +.0000 -.0002
M81746/1-01A	.555	.500	3.600	Splined	Terminal Board	.1872

1/Part identifying number M81746/1-01A shall be the NATO standard.

1/The suffix letter following the numerical dash number corresponds to the latest modification letter in the type designation.

Custodian:
Navy-AS

Preparing Activity:
Navy-AS

Review Activities:

(Project No. 5990-0396-01)

User Activities:
Navy-SH,EC

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:03Z
Check the source to verify that this is the current version before use.