INCH-POUND
MS21400B
W/AMENDMENT 1
26 August 2026
SUPERSEDING
MS21400B
24 August 2007


PERFORMANCE SPECIFICATION SHEET

COILS, RADIO FREQUENCY, MOLDED, FIXED, MICRO-MINIATURE, MAGNETICALLY SHIELDED, (IRON CORE-IRON SLEEVE), LT10K469 TO LT10K482 INCL

Inactive for new design
after 21 February 2003

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the products described
herein shall consist of this specification and MIL-PRF-15305.



Ltr	Dimensions in inches with metric equivalents (mm) in parentheses	
	Minimum	Tolerance
A	.136 (3.45)	Max
B	.335 (8.51)	± .010 (0.25)
C	1.438 (36.53)	± .188 (4.78)
D	.020 (0.51)	± .002 (0.05)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. These coils are intended to be supported by their leads.
4. Tinned copper lead wire, AWG number 24.

FIGURE 1. Dimensions and configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:38Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design, construction, and physical dimensions: See Figure 1.

Style: LT10

Grade: 1
Class: A

Weight: .50 grams, maximum.

Operating temperature range: -55° to +105°C.

Ambient temperature: + 90°C maximum.

Temperature rise: 15°C.

Terminal pull: 5 pounds minimum.

Altitude: 70,000 feet.

Shock, specified pulse: MIL-STD-202-213, test condition I, is applicable. Dielectric withstanding voltage:

At sea level: MIL-STD-202-301, test voltage 700 V rms for a minimum of 60 seconds.

At reduced barometric pressure: MIL-STD-202-105, test condition C, test voltage100 V rms for a minimum of 60 seconds.

Percent coupling: 3 percent, maximum.

Electrical characteristics: See tables I and II.

Inductance: See table I.

Q values: See table I.

Self-resonant frequency (SRF): See table I.

DC resistance (DCR): See table I. DC resistance shall be the last measurement taken in the electrical characteristics test sequence.

Part or Identifying Number (PIN): MS21400 - (dash number from table I).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:38Z
Check the source to verify that this is the current version before use.

TABLE 1. Electrical characteristics (initial).

Dash number 1/	Inductance (μH) ±10%	Q (min)	Test frequency (MHz)	SRF min (MHz)	DC resistance at 25°C max (ohms)	Max rated DC current (mA)
-01	1.0	38	25	135	.170	678
-02	1.2	38	7.9	124	.177	664
-03	1.5	38	7.9	114	.212	607
-04	1.8	38	7.9	105	.242	568
-05	2.2	38	7.9	95	.263	545
-06	2.7	38	7.9	85	.300	510
-07	3.3	38	7.9	78	.345	476
-08	3.9	42	7.9	74	.411	436
-09	4.7	42	7.9	68	.562	373
-10	5.6	42	7.9	62	.742	324
-11	6.8	45	7.9	55	1.00	280
-12	8.2	47	7.9	51	1.20	255
-13	10	51	7.9	45	1.84	206
-14	12	51	2.5	41	2.60	173

1/ The dash number added to the MS military standard number constitutes the MS part number, for example, MS21400-01

TABLE II. Electrical characteristics (final). 1/

Inspection group	Allowable variation from Initial measurement		Allowable percent from specified minimum value in electrical characteristics (initial) table	
	Inductance (percent)	DC resistance	Self-resonant frequency	Q
Qualification inspection				
Group II	±5	---	---	-10
Group III	±5	±(3% +.001 ohm)	-8	-10
Group IV	±5	±(2% +.001 ohm)	-5	-10

1/ After the overload test is performed, a period of 24 hours shall elapse prior to taking electrical characteristics (final) measurements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:38Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical line to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. MIL-PRF-15305, MIL-STD-202-213, MIL-STD-202-301, MIL-STD-202-105

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Air Force – 19

Preparing activity:
DLA – CC

(Project 5950-2026-025)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:38Z
Check the source to verify that this is the current version before use.