


FED. SUP CLASS
4730










FIGURE 1, MALE END

FIGURE 2, FEMALE END

TABLE I-DIMENSIONS OF SOLDERED JOINT ENDS

STANDARD REFR TUBE SIZE	STANDARD WATER TUBE SIZE	MALE END OUTSIDE DIAMETER A		LENGTH K	FEMALE END INSIDE DIAMETER F		DEPTH G	METAL THICKNESS T	INSIDE DIA OF FITTING O
		MIN	MAX	MIN	MIN	MAX	MIN	MIN	MIN
1/4		.249	.251	.375	.253	.255	.312	.022	.18
3/8	1/4	.374	.376	.375	.378	.380	.312	.026	.30
1/2	3/8	.499	.501	.438	.503	.505	.375	.031	.39
5/8	1/2	.624	.626	.563	.628	6.30	.500	.036	.52
3/4	5/8	.749	.751	.688	.753	755	.625	.038	.63
7/8	3/4	.874	.876	.813	.878	.880	.750	041	.74
1 1/8	1	1.1235	1.1265	.969	1.1285	1.1305	.906	.046	.98
1 3/8	1 1/4	1 3735	1.3765	1.031	1.3785	1.3805	.969	.050	1.23
1 5/8	1 1/2	1.623	1.627	1.156	1.629	1.6315	1.094	.055	1.47
2 1/8	2	2.123	2.127	1.406	2.129	2.1315	1.344	.064	1.94
2 5/8	2 1/2	2.623	2.627	1.531	2.629	2.6315	1.469	.074	2.42
3 1/8	3	3.123	3.127	1.719	3.129	3.1315	1.656	.083	2.89
3 5/8	3 1/2	3.623	3.627	1.969	3.629	3.632	1.906	.093	3.37
4 1/8	4	4.123	4.127	2.219	4.129	4.132	2.156	.101	3.84

NOTE: (B) SEE SHEET 2 FOR PRESSURE RATINGS AND NOTES

THIS IS A DESIGN STANDARD AND SHALL NOT BE USED AS A PART NUMBER

(A) ENTIRE STANDARD REVISED

APPROVED 22 SEPT 1958 REVISED (A) 28 SEPT 1967 (B) 19 SEPT 72

Review: User
Army ME Sh MC
Navy 85
USAF GS
CSA

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. ARMY - GL (Other Cust) USAF - 82	TITLE: CONNECTION END, SOLDER-JOINT, REFRIGERATION	MILITARY STANDARD MS 35925
PROCUREMENT SPECIFICATION: NONE	SUPERSEDES	SHEET 1 OF 2

DD FORM 1 SEP 67 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:31Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS 4730

(A) THE MAXIMUM RECOMMENDED PRESSURE TEMPERATURE RATINGS FOR SOLDER-JOINTS MADE WITH COPPER TUBE AND BRONZE FITTINGS, USING REPRESENTATIVE COMMERCIAL SOLDERS ARE LISTED IN THE TABLE BELOW.

TABLE II-PRESSURE RATINGS

SOLDER USED IN JOINTS	WORKING TEMPERATURES DEG F	MAXIMUM WORKING PRESSURE, PSI		
		1/8 TO 1 IN. INCL	1 1/4 TO 2 IN. INCL	2 1/2 TO 4 IN. INCL
50-50 TIN-LEAD	100	200	175	150
	150	150	125	100
	200	100	90	75
	250	85	75	50
95-5 TIN-ANTIMONY	100	500	400	300
	150	400	350	275
	200	300	250	200
	250	200	175	150
SOLDERS MELTING AT OR ABOVE 1100 F	350	270	190	155

NOTES

1. ALL DIMENSIONS IN INCHES.
2. THE STANDARD REFRIGERATION TUBE SIZES IN TABLE I ARE NOMINAL OUTSIDE DIAMETERS CONFORMING TO ASTMB 280-66 - SEAMLESS COPPER TUBE FOR AIR CONDITIONING AND REFRIGERATION FIELD SERVICE.
3. THE STANDARD WATER TUBE SIZES SHOWN IN TABLE I ARE NOMINAL INSIDE DIAMETER CONFORMING TO ASA H23.1 - AMERICAN STANDARD SPECIFICATION FOR COPPER WATER TUBE.
4. FIGURES 1 AND 2 ARE ILLUSTRATIVE ONLY. DIMENSIONS SPECIFIED SHALL GOVERN IN ALL CASES.
5. FITTINGS SHALL BE MADE FROM MATERIALS CONFORMING TO ANSI B16.22 FOR WROUGHT COPPER AND BRONZE SOLDER JOINT PRESSURE FITTINGS. AND AS AN OPTION TO TABLE I, APPENDIX B OF ANSI B16.22 "OPTIONAL GAGING METHOD" MAY BE USED.
6. REFERENCED DOCUMENTS SHALL BE THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BIDS OR REQUEST FOR PROPOSAL.
7. FOR DESIGN FEATURE PURPOSE, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

APPROVED 22 SEPT 1958 REVISED (A) 28 SEPT 1967 (B) 19 SEPT 72

P.A. ARMY-GL Other Cust USAF-82	TITLE CONNECTION END, SOLDER-JOINT, REFRIGERATION	MILITARY STANDARD MS 35925
Procurement Specification NONE	SUPERSEDES:	SHEET 2 OF

DD FORM 1 SEP 67 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:31Z
Check the source to verify that this is the current version before use.

Validation

MS 35925B
NOTICE 1
12 February 1988

MILITARY STANDARD

CONNECTION END, SOLDER-JOINT, REFRIGERATION

Military Standard MS 35925B, dated 19 September 1972, has been reviewed and determined to be current.

Custodians:

Army - GL
Air Force - 99

Interested activities:

Army ML
Navy - SH, MC
Air Force - 99
DLA - CS

Preparing Activity:

Army - GL

FSC 4730

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:31Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:31Z
Check the source to verify that this is the current version before use.