FED. SUP CLASS
6850

REVIEWER: GL MD MI MR PS

USER: MO SM

PART NUMBER	PACKAGING
MS36436-1	5 gal pail
MS36436-2	55 gal drum

SAFETY PRECAUTIONS: DANGER! HARMFUL OR FATAL IF SWALLOWED CAUSES SEVERE EYE AND SKIN BURNS

If swallowed, do not induce vomiting. Do not get in eyes, on skin, on clothing. In case of contact, immediately flush skin or eyes with plenty of water for at least 15 minutes; for eyes get medical attention. Avoid prolonged or repeated breathing of vapor. Use with adequate ventilation. The use of gloves and protective equipment is recommended.

INTENDED USE: For use in removing oils, greases, asphalt, tars, and preservative type materials from metallic and painted surfaces. Application method may be by swab, brush, spray or soak.

MATERIAL: Liquid. Ready to use.

NOTES:

1. Referenced documents shall be of the issue in effect on date of invitations for bid.
2. Safety Precaution given is based on compounds of the Comparison Formula.

APPROVED 12 March 1965 REVISED

This standard is approved by the Munitions Command, Department of the Army and is mandatory for use by the activity. All other military activities are required to employ this standard where suitable.

P.A. MU	TITLE	MILITARY STANDARD
Other Cust	CLEANING COMPOUND, SOLVENT self-emulsifying	MS36436(MU)
Procurement Specification MIL-C-11090	SUPERSEDES:	SHEET 1 OF 2

DD FORM 1 SEP 57 672 (Limited coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:40Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
6850

REVIEWER: GL MD MI MR PS

USER: MO SM

REQUIREMENTS: Qualification required. Compound shall be equal or superior in performance to the comparison formula. Phenolic or cresylic type acids or their salts, chlorinated hydrocarbons or other chlorine compounds, and compounds containing benzene or toluene shall not be used. Minimum flash point, 100 degrees Fahrenheit.

COMPARISON FORMULA
(For information. Does not necessarily indicate composition, either compound or quantity, of the qualified product)

Ingredient Material	Parts by Volume
Solvent (70 per cent high flash coal tar naphtha, 30 percent kerosene)	100
Detergent concentrate (Cyclohexanol, ethylene glycol monobutyl ether, diacetone-diethylene triamine condensate, ethanolamine oleate in high flash naphtha, diglycol oleate, aromatic amine sulfonate, and sorbitan oleate)*	12.25

*compounded in proportion and procedure as specified in the procurement document.

DIRECTIONS FOR USE: Do not dilute. Allow the cleaning compound to remain on work for 3 to 5 minutes before rinsing. Two recommended precedures for spray application are as follows:

Method 1. Apply compound by spray gun at pressure of 4 pounds/square inch. Hold spray nozzle of the gun about 6 inches away from the work. Use a heavy stream of liquid rather than a dispersion. Examine the soil 3 to 5 minutes after application. If the soil is not softened, spray a second application of the compound. Allow 3 to 5 minutes, then rinse by means of a steam jenny at pressure of 40 to 50 pounds/square inch, or if not available, then with hot water preferably at pressure of 25 to 50 pounds/square inch. If water must be avoided, rinse with Stoddard Solvent.

Method 2. Apply compound by spray gun at pressure of 20 pounds/square inch. Hold spray nozzle of the gun about 6 inches away from the work. Do not rinse. In this method the compound may be repeatedly recycled and reused.

APPROVED 12 March 1965 REVISED

This standard has been approved by the Munitions Command Department of the Army and is mandatory for use by the activity. All other military activities are required to employ this standard where suitable.

P.A. MU Other Cust	TITLE CLEANING COMPOUND, SOLVENT self-emulsifying	MILITARY STANDARD MS36436(MU)
Procurement Specification MIL-C-11090	SUPERSEDES:	SHEET 2 OF 2

DD FORM 1 SEP 67 672 (Limited coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:40Z
Check the source to verify that this is the current version before use.