
FED. SUP CLASS
6140

REVIEWERS: ARMY-EL ; NAVY-DOCKS ; AF-ROAMA
USERS: ARMY-GL ; NAVY-MC, SHIPS, WEPS



© ENTIRE STANDARD REVISED

APPROVED 18 JULY 1956 REVISED © 11 JUNE 1964

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use should be made from this document.

P.A. MO(ATAC) Other Cust NAVY - Docks AF-ROAMA	TITLE BATTERY, STORAGE, LEAD-ACID PORTABLE, BB 236/U	MILITARY STANDARD MS 91318
PROCUREMENT SPECIFICATION MIL-B-11188	SUPERSEDES	SHEET 1 OF 2

DD FORM SEP 67 672-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:41Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
6140

REVIEWERS: ARMY-EL; NAVY-DOCKS; AF-ROAMA
USERS: ARMY-GL; NAVY-MC, SHIPS, WEPS

PHYSICAL AND ELECTRICAL REQUIREMENTS	
MS PART NUMBER	MS 91318-236
CLASS	ER
WEIGHT (FILLED)	0.6 POUNDS, MAXIMUM
NOMINAL VOLTAGE	2 VOLTS
FINAL VOLTAGE AT 20-HOUR RATE	1.75 VOLTS
RATED CAPACITY AT 20-HOUR RATE	2.3 AMPERE-HOURS
DISCHARGE AT 20-HOUR RATE	0.115 AMPERES
CHARGING RATE	0.25 AMPERES

QUALIFICATION AND QUALITY CONFORMANCE INSPECTIONS	
TEST	MINIMUM VALUE
FILLED DISCHARGE AT 80° F	1.75 AMPERE-HOURS
FULL CHARGE CAPACITY AT 80° F	2.3 AMPERE-HOURS
LOW TEMP PERFORMANCE AT MINUS 40° F	0.69 AMPERE-HOURS
LIFE CYCLE CAPACITY TEST II	200 CYCLES
RETENTION OF CHARGE	1.61 AMPERE-HOURS

NOTES:

1. UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. TOLERANCES ARE ± 1/16 ON FRACTIONS, ± 0.010 ON DECIMALS, AND ± 1 1/2° ON ANGLES.
2. PHENOLIC INSULATING WASHER, OPTIONAL.
3. THE MS PART NUMBER CONSISTS OF THE MS MILITARY STANDARD NUMBER FOLLOWED BY A DASH NUMBER. THE DASH NUMBER "236" IS DERIVED FROM ASSIGNED NOMENCLATURE.
4. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.
5. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.
6. THIS STANDARD IS NOT INTENDED TO LIMIT CONSTRUCTION TO FEATURES OTHER THAN AS SHOWN HEREON BY DIMENSIONS, NOTATIONS, OR REFERENCED DOCUMENTS.

APPROVED 18 JULY 1956 REVISED © 11 JUNE 1964

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. MO (ATAC) Other Cust NAVY - Docks AF - ROAMA	TITLE BATTERY, STORAGE, LEAD-ACID PORTABLE, BB 236/U	MILITARY STANDARD MS 91318
PROCUREMENT SPECIFICATION MIL-B-11188	SUPERSEDES	SHEET 2

DD FORM 672-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:41Z
Check the source to verify that this is the current version before use.