DATA ITEM DESCRIPTION

Form Approved
OMB No. 0704-0188

2. TITLE	1. IDENTIFICATION NUMBER
IN-PROCESS SUBASSEMBLY INSPECTION/TEST SUMMARY REPORT	DI-QCIC-80375

3 DESCRIPTION / PURPOSE

3.1 The In-Process Subassembly Inspection/Test Summary Report is a summary of inspection and test data and all in-process and subassembly failures. Each summary report is limited to an equipment type such as space, ground, etc.

(Continued on Page 2)

4. APPROVAL DATE (YYMMDD)	5. OFFICE OF PRIMARY RESPONSIBILITY (OPR)	6a. DTIC APPLICABLE	6b. GIDEP APPLICABLE
870619	G/Y213		

7. APPLICATION / INTERRELATIONSHIP

7.1 This data item description (DID) contains the format and content preparation instructions for the data product generated by the specific and discrete task requirement for this data included in the contract.

7.2 This report is required when equipment parts are subject to in-process and subassembly testing.

7.3 This DID supersedes paragraph 10.1.2 of DI-R-5468.

8. APPROVAL LIMITATION	9a. APPLICABLE FORMS	9b. AMSC NUMBER
		G4139

10. PREPARATION INSTRUCTIONS

10.1 Content and format. The report shall contain the following:

10.1.1 Title page that includes:

10.1.1.1 Report title.

10.1.1.2 Equipment nomenclature.

10.1.1.3 Report date.

10.1.1.4 Security classification of the report.

10.1.1.5 Contract number.

10.1.1.6 Name(s) and official title(s) of the preparer(s) of the report.

10.1.1.7 Signature of authorized company representative.

10.1.2 Brief introduction that includes the scope and purpose of the report.

10.1.3 A summary of all in-process and subassembly inspection/test data shall be listed by defect and also by subassembly and/or part. The summary shall include the following information (data shall be based on "first time seen"):

(Continued on page 2)

11 DISTRIBUTION STATEMENT

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:36Z
Check the source to verify that this is the current version before use.

Block 3, Description/Purpose (Continued)

3.2 The report is used to evaluate the quality of parts during various phases of manufacture and assembly.

Block 10, Preparation Instructions (Continued)

10.1.3.1 Test failed.

10.1.3.2 Subassembly part number.

10.1.3.3 Subassembly serial number.

10.1.3.4 Subassembly reference designator.

10.1.3.5 Part name.

10.1.3.6 Part number.

10.1.3.7 Part referenced designator.

10.1.3.8 Part manufacturer.

10.1.3.9 Part date code.

10.1.3.10 Manufacturer's part number.

10.1.3.11 Reference Failure Analysis Report (FAR) number and Noncomforming Material Report (NCMR) number.

10.1.3.12 FAR dash number (i.e., 3-2 indicates third failure of a part number and the second failure of the part number in that mode).

10.1.3.13 Quantity of each subassembly tested that month.

10.1.3.14 Quantity of each subassembly failed that month.

10.1.3.15 Percentage of Printed Wiring Assembly (PWA) requiring touch-up and top five defects.

10.1.3.16 Percentage (yield) from PWA pre-conformal coat test, in-circuit test and functional test including top five defects found during each respective test.

10.1.3.17 Percentage (yield) from PWA post-conformal coat functional test/inspection including top five defects found.

10.1.3.18 Percentage (yield) from remaining sub-assembly (cables, harnesses, etc.) inspection/test including top five defects found.

10.1.4 Histograms which reflect the recorded variables in 10.1.3 above.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:36Z
Check the source to verify that this is the current version before use.