DATA ITEM DESCRIPTION

Title: In-Process Subassembly Inspection/Test Summary Report

Number: DI-QCIC-80375A
AMSC Number: 7653
DTIC Applicable: No
Office of Primary Responsibility: NS/I5223
Applicable Forms: N/A

Approval Date: 21 NOV 2006
Limitation: N/A
GIDEP Applicable: No

Use/relationship:

The In-Process Subassembly Inspection/Test Summary Report is a summary of inspection and test data and all in-process and subassembly failures. Each summary report is limited to an equipment type such as space, ground, etc.

The report is used to evaluate the quality of parts during various phases of manufacture and assembly.

This Data Item Description (DID) contains the format and content preparation instructions for the data product generated by the specific and discrete task requirement for this data included in the contract.

This report is required when equipment parts are subject to in-process and subassembly testing.

This DID supercedes DI-QCIC-80375.

Requirements:

1. Reference documents. None.

2. Format:

The In-Process Subassembly Inspection/Test Summary Report shall be provided in contractor format.

3. Content:

The report shall contain the following information:

3.1. Title Page that includes:

3.1.1. Report title.

3.1.2. Equipment nomenclature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:36Z
Check the source to verify that this is the current version before use.

3.1.3. Report date.

3.1.4. Security classification of the report.

3.1.5. Contract number.

3.1.6. Name(s) and official title(s) of the preparer(s) of the report.

3.1.7. Signature of authorized company representative.

3.2. Brief introduction the includes the scope and purpose of the report.

3.3. A summary of all in-process and subassembly inspection/test data shall be listed by defect and also by subassembly and/or part. The summary include the following information (data shall be based on “first time seen”):

3.3.1. Test failed.

3.3.2. Subassembly part number.

3.3.3. Subassembly serial number.

3.3.4. Subassembly reference designator.

3.3.5. Part name.

3.3.6. Part number.

3.3.7. Part referenced designator.

3.3.8. Part manufacturer.

3.3.9. Part date code.

3.3.10. Manufacture’s part number.

3.3.11. Reference Failure Analysis Report (FAR) number and Noncomforming Material Report (NCMR) number.

3.3.12. FAR dash number (i.e., 3-2 indicates third failure of a part number and the second failure of the part number in the mode).

3.3.13. Quantity of each subassembly tested that month.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:36Z
Check the source to verify that this is the current version before use.

3.3.14. Quantity of each subassembly failed that month.

3.3.15. Percentage of Printed Wiring Assembly (PWA) requiring touch-up and top five defects.

3.3.16. Percentage (yield) from PWA pre-conformal coat test, in-circuit test and functional test including top five defects found during each respective test.

3.3.17. Percentage (yield) from PWA post-conformal coat functional test/ inspection including top five defects found.

3.3.18. Percentage (yield) from remaining sub-assembly (cables, harnesses, etc) inspection/test including top five defects found.

3.4. Histograms which reflect the recorded variables in 3.3 above.

4. END OF DI-QCIC-80375A

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:36Z
Check the source to verify that this is the current version before use.