INCH-POUND

MIL-C-48480C(AR)
30 May 1995
(see 6.4)

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY - LOGIC AND REFERENCE

This specification is approved for use by the U.S. Army Armament, Research, Development and Engineering Center (ARDEC) and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements and quality assurance provisions for the Circuit Card Assembly Logic and Reference, 11732517 (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-F-13926 - Fire Control Materiel, General Specification Governing the Manufacture and Inspection of

MIL-I-45607 - Inspection Equipment; Acquisition, Maintenance, and Disposition of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use to improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: AMSTA-AR-EDE-S, Picatinny Arsenal, New Jersey 07806-5000 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-100	- Engineering Drawing Practices
MIL-STD-454	- Standard General Requirements for Electronic Equipment
MIL-STD-810	- Environmental Test Methods
MIL-STD-2000	- Standard Requirements for Soldered Electrical and Electronic Assemblies
MIL-STD-2073-1	- Procedures for Development and Application of Packaging Requirements

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from: DODSSP - Customer Service, Standardization Documents Order Desk, 700 Robbins Avenue, Bldg 4D, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issue shall be those in effect on date of the solicitation.

U.S. Army Armament Research Development and Engineering Center (ARDEC)

DRAWINGS

11732517	- Circuit Card Assembly - Logic and Reference

(Copies of Government drawings and packaging data sheets required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets or MS standards), the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained (See control provisions for additional precedence criteria).

3. REQUIREMENTS

3.1 Fabrication. The logic and reference circuit card assembly, herein referred to as the assembly, shall be manufactured in accordance with Drawing 11732517 and drawings pertaining thereto and, when assembled, shall meet the requirements of this specification (see 4.5.1).

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:28Z
Check the source to verify that this is the currentversion before use.

3.1.1 Function. The assembly shall provide the following functions:

a. Logic, control and timing signals

b. Plus and minus 10 volt dc reference voltages

c. Modular reference signals (MR1, MR2)

d. AC reference signals (AC Ref. 1, AC Ref. 2)

3.1.2 General specifications. (see 4.6.3)

3.1.2.1 Manufacture and inspection. The following provisions of MIL-F-13926 apply:

a. Dimensions and tolerances
b. Effect of protective coating on dimensions (Inorganic type coating)
c. Part identification and marking
d. Workmanship (Including applicable portions of MIL-STD-2000 and MIL-STD-454, Requirement 9)

3.1.2.2 Standards of manufacture.

3.1.2.2.1 Assembly and soldering. The requirements of MIL-STD-2000 shall apply, as a minimum.

3.1.2.2.2 Interchangeability. The assembly shall be manufactured in accordance with interchangeability requirements as specified in MIL-STD-100.

3.1.3 Ambient conditions. Standard ambient conditions shall be as follows:

a.	Temperature	73° ± 18°F
b.	Relative humidity	50 percent ± 30 percent
c.	Atmospheric pressure	28.5 + 2.0 -3.0 in. Hg.

3.2 First article. When specified in the contract or purchase order (see 6.2), the contractor shall furnish sample units for first article inspection and approval (see 4.4).

3.3 Performance. Unless otherwise specified, the assembly shall meet the performance requirements specified herein under standard ambient conditions of 3.1.3.

3.3.1 AC reference output. With the power sources (items 2.1 and 2.2 of Table I), the loads (items 1.1 and 1.2 of Table I), and the signal sources (item 3.1 of Table I) applied to the assembly; then AC REFERENCE 2 shall be a 400 + 1 hertz sine wave

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

and shall be + 0.003V rms from the signal source (item 3.1) voltage applied to the assembly. AC reference 1 shall be a 400 ± 1 hertz sine wave and shall be +0.003V rms from the AC REFERENCE 2 and shall be 180 degrees out of phase with AC REFERENCE 2 (see 4.6.1.1).

3.3.2 Modular reference output. With the power sources (items 2.1 and 2.2 of Table I), the loads (items 1.3 and 1.4 of Table I), and the signal sources (item 3.1 of Table I) applied to the assembly, the modular REFERENCE 1 signal (MR1) and the modular REFERENCE 2 signal (MR2) shall be each a 400 ± 1 hertz square wave as shown in Figure 1. MR1 shall be in phase with the voltage at pins A26, A27, B27 (ACREF 1) and MR2 shall be 180 degrees out of phase with the voltage at pins A26, A27, B27 (see 4.6.1.2).

3.3.3 Plus and minus 10V dc reference voltage outputs. With the power sources (items 2.1 and 2.2 of Table I), the loads (items 1.5 and 1.6 of Table I), and the signal sources (item 3.1 of Table I) applied to the assembly; the 10V dc reference voltage shall be 10.000 ± 0.010V dc with respect to ground pins A3 and B3. The -10V dc reference voltage shall be -10.000 + 0.010V dc with respect to ground pins A3 and B3 (see 4.6.1.3).

TABLE I. Loads, power and signal sources.

Item	Conditions	Characteristics	Connections 1/
1.0	Loads		
1.1	Resistors	1.0 Kilohm - 5% 1w	A26, A27, B27-A3
1.2	Resistors	1.0 Kilohm + 5% 1w	A28, B28, A29-A3
1.3	Resistors	100 Kilohm + 5% 1w	B9-A3
1.4	Resistors	100 Kilohm + 5% 1w	B25, B26-A3
1.5	Resistors	1.0 Kilohm ± 5% 1w	A7, B7-A3
1.6	Resistors	1.0 Kilohm ± 5% 1w	A24, B24-A3
1.7	Resistors	5.1 Kilohm + 5% 1/4w	A4-A14
1.8	Resistors	5.1 Kilohm + 5% 1/4w	A4-A19
1.9	Resistors	5.1 Kilohm + 5% 1/4w	A4-A25
1.10	Resistors	5.1 Kilohm ± 5% 1/4w	A4-A23
1.11	Resistors	5.1 Kilohm ± 5% 1/4w	A4-B23
1.12	Resistors	5.1 Kilohm ± 5% 1/4w	A4-B17
1.13	Resistors	5.1 Kilohm + 5% 1/4w	A4-B18
1.14	Resistors	5.1 Kilohm + 5% 1/4w	A4-B17
1.15	Resistors	5.1 Kilohm ± 5% 1/4w	A4-B11

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

TABLE I. Loads, power and signal sources. (continued)

Item	Conditions	Characteristics	Connections 1/
2.0	Power sources		
2.1	15V dc	Tolerance: ± 0.030V dc Ripple: 20mV p-p max Current: 500 ma min	A1, B1 Return A3
2.2	-15V dc	Tolerance: + 0.030V dc Ripple: 20mV p-p max Current: 500 ma min	A30, B30 Return A3
2.3	5.25V dc	Tolerance: ± 0.150V dc Ripple: 20mV p-p max Current: 500ma min	A4 Return A13, B13
3.0	Signal sources		
3.1	5V rms, 400 Hz	Tolerances: + 0.005V rms; ± 1 Hz	B29 Return A3

1/ A3 is A3, B3.
A4 is A4, B4.
For test purposes, pins A3, B3, A13, B13 may be connected together.




FIGURE 1. Modular reference 1 and 2 signal waveform.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

3.3.4 Logic timing signals and clock outputs. With the power sources (item 2 of Table I) and the signal source (item 3.1 of Table I) applied to the assembly pins A9 and B19 grounded to pins A3, B3, and with pins A2 and B2 switched simultaneously as specified in Table II, the clock output timing signals shall be as shown in Figure 2.

TABLE II. Logic timing signal.

Condition	Pin A2	Test Initiate (Pin B2)
1	Open	Ground
2	Ground	Open

3.3.5 Reset signal. With the power sources (item 2 of Table I) applied to the assembly and with pin A9 grounded to pins A3, B3 the following requirements shall apply (see 4.6.1.5):

a. With pin A2 grounded to pins A3, B3, the output at pin A8 shall be 5.00 +0.50/-2.60V dc for 25 + 3 seconds.

b. With the connection from pin A9 to pins A3, B3, the output at pin A8 shall immediately change to 0.00 to +0.50V dc.

3.3.6 Logic control signals. With the power source (item 2.3 of Table I) applied to the assembly and with the input conditions of Table III established in any item number order, the corresponding phase logic signals shall be as specified in Table III (see 4.6.1.6).

3.3.7 Fail logic outputs. With the power source (item 2.3 of Table I), and the loads (items 1.7 through 1.15 of Table I) applied to the assembly, and with the input logic conditions of Table IV established in any item number order, the Fail Logic outputs ABCV and not K at pins A10 and B14 respectively shall be as specified in Table IV (see 4.6.1.7).

Source: https://assist.dla.mil Downloaded: 202610-22T19:28Z
Check the source to verify that this is the current version before use.




FIGURE 2. FTS timing diagram.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

TABLE III. Logic control signals.

Item	Pin Grounded To A3 B3	Outputs at Pins 1/										
		Not Ph 1 Logic B15	Phase 1 Logic A15	Not Ph 2 Logic A21	Phase 2 Logic B21	Not Ph 3 Logic A12	Phase 3 Logic B12	Not Ph 4 Logic A20	Phase 4 Logic B20	Not Ph 5 Logic A5	Phase 5 Logic B17	Not Ph 4 or PH 5 Logic A11
1	B16	0	1	1	0	1	0	1	0	1	0	1
2	A16	1	0	0	1	1	0	1	0	1	0	1
3	A18	1	0	1	0	0	1	1	0	1	0	1
4	B19	1	0	1	0	1	0	0	1	1	0	0
5	A22	1	0	1	0	1	0	1	0	0	1	0

1/ 1 = +5.00 +0.50/-2.60V dc

0 = 0.0 + 0.5V dc

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

TABLE IV. Fail logic outputs.

Item	Inputs 1/												Outputs 2/	
	B11	A22	B16	B19	A18	A14	A19	A25	A23	B23	A17	B18	A10	B14
1	1	NA	NA	NA	0	NA	NA	NA	NA	NA	NA	1	0	NA
2	0	1	1	1	NA	NA	NA	NA	NA	NA	NA	1	1	NA
3	0	1	1	0	NA	NA	NA	NA	NA	NA	NA	1	0	NA
4	0	0	1	1	NA	NA	NA	NA	NA	NA	NA	1	0	NA
5	0	1	0	1	NA	NA	NA	NA	NA	NA	NA	1	0	NA
6	0	1	1	1	1	1	0	0	0	0	0	0	0	NA
7	0	1	1	1	1	1	0	0	0	0	0	1	1	NA
8	0	1	1	1	1	1	0	0	0	0	1	0	1	NA
9	0	1	1	1	1	1	0	0	0	1	0	0	1	NA
10	0	1	1	1	1	1	0	0	1	0	0	0	1	NA
11	0	1	1	1	1	1	0	1	0	0	0	0	1	0
12	0	1	1	1	0	0	0	0	0	0	0	0	1	1
13	0	1	1	1	0	0	1	0	0	0	0	0	0	NA
14	0	1	1	1	0	1	0	0	0	0	0	0	1	NA
15	0	1	1	1	0	1	1	0	0	0	0	0	1	NA
16	0	1	1	1	1	0	0	0	0	0	0	0	1	NA
17	0	1	1	1	1	0	1	0	0	0	0	0	1	NA
18	0	1	1	1	1	1	0	0	0	0	0	0	0	NA
19	0	1	1	1	1	1	1	0	0	0	0	0	1	NA

1/ 1 = 5.25 ± 0.15V dc
0 = 0.00 + 0.50V dc
NA = Indicates a not applicable condition.

2/ 0 = 0.00 ± 0.50V dc
1 = +5.000 +0.50/-2.60V dc
NA = Indicates a not applicable condition.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

3.4 Environmental.

3.4.1 Temperature. The assembly shall be capable of operating as specified herein over the operating temperature range of +40°F to 100°F and shall not be damaged when subjected to the storage conditions ranging from -65°F to 160°F (see 4.6.2.1 and 4.6.2.2).

3.4.2 Vibration. The assembly shall be capable of operating as specified herein after withstanding exposure under the conditions of 3.1.3 to a sinusoidal vibration displacement of .03 inch double amplitude, 10 - 55 Hz in accordance with Figure 3. Duration of exposure shall be not less than 80 minutes in each of three mutually perpendicular axes (see 4.6.2.3).




FIGURE 3. Vibration Curve.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:28Z
Check the source to verify that this is the current version before use.

3.4.3 Shock. The assembly shall be capable of operating as specified herein after withstanding exposure under the conditions of 3.1.3 to half sine wave shock pulses of 40 ± 4 gravity unit (g's) for a duration of 18 ± 3 milliseconds (msec) in accordance with Figure 4. The assembly shall withstand three shock pulses applied in both directions along three mutually perpendicular axes (18 shocks). In addition, the assembly shall be capable of withstanding three half sine wave shock pulses of 100.0 ± 10.0 g's for a duration of 1.5 ± 0.2 msec applied in each direction along three mutually perpendicular axes (see 4.6.2.4).




FIGURE 4. Shock Pulse.

3.4.4 Temperature cycling. The assembly shall be capable of operating as specified herein after withstanding exposure to temperature cycling and soaking between the temperatures of -25°F and 140°F in accordance with Figure 5 (see 4.6.2.5).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.




FIGURE 5. Temperature Cycling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Inspection equipment. Unless otherwise specified in the contract, the contractor shall supply, maintain and calibrate inspection equipment in accordance with the provisions of MIL-I-45607 and standard commercial practice. Contractor inspection equipment designs shall be submitted for Government approval as specified in the contract (see 6.5).

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5 and 6.8).

4.3 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the quality assurance provisions of MIL-F-13926 and the conditions of 3.1.3.

4.4 First article inspection. The requirements for first article approval and the designation of responsibility for first article inspection to either the Government or the contractor shall be specified in the contract (see 6.3).

4.4.1 Sample. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.4.2. The first article sample shall consist of two assemblies.

4.4.2 Inspection. Two assemblies shall be subjected to all the inspections specified in Tables V, VI and VII. Tests 301 and 302 of Table VII shall be performed first.

TABLE V. Performance tests.

Item	Characteristics	Requirement	Test Procedure
101	AC reference output	3.3.1	4.6.1.1
102	Modular reference output	3.3.2	4.6.1.2
103	Plus and minus 10 Vdc reference voltage outputs	3.3.3	4.6.1.3
104	Logic timing signals and clock outputs	3.3.4	4.6.1.4
105	Reset signal	3.3.5	4.6.1.5
106	Logic control signals	3.3.6	4.6.1.6
107	Fail logic outputs	3.3.7	4.6.1.7

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

TABLE VI. Environmental tests.

Item	Characteristics	Requirement	Test Procedure
201	High temperature	3.4.1	4.6.2.1
202	Low temperature	3.4.1	4.6.2.2
203	Vibration	3.4.2	4.6.2.3
204	Shock	3.4.3	4.6.2.4
205	Temperature Cycling	3.4.4	4.6.2.5

TABLE VII. General tests.

Item	Characteristics	Requirement	Test Procedure
301	Fabrication	3.1	Applicable drawings - Visual
302	General specifications	3.1.2	4.6.3 - Visual
303	Packaging inspection	5.1	4.6.4 - Visual

4.4.3 Failure. Failure of any assembly to meet any requirement shall be cause for refusal to grant first article approval. The Government reserves the right to terminate first article inspection upon any failure of any assembly to comply with any stated requirement.

4.4.4 Responsibility. The contractor, whether or not responsible, shall inspect the sample for conformance to all contractual requirements and shall submit a record of this inspection and certificates of conformance for materials. The Government reserves the right to witness inspections performed by the contractor.

4.5 Quality conformance inspection.

4.5.1 Procurement conditions. The following inspection plans shall apply where the assembly is procured for use as a:

	Use	Plan
a.	Logistics spare assembly apart from the next higher assembly	A, B and C
b.	Component assembly of the next higher assembly	B and C

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

4.5.2 Inspection plan A.

4.5.2.1 Environmental sample and tests. One assembly, as a control sample, shall be selected at random by the Government representative from each 50 assemblies produced or from each month's production, whichever occurs first. All the tests in Table VII shall be applied separately to the assembly.

4.5.2.2 Acceptance. When the sample assembly of the quantity produced fails to meet any specified requirement, the lot shall be rejected. Rejected lots shall be resubmitted for reinspection only after all assemblies are re-examined or retested and all defective assemblies are removed or defects corrected.

4.5.3 Inspection plan B.

4.5.3.1 Sample and tests. The sample shall be selected by the Government representative. All the tests in Table VII and only the test of item 205 in Table VI shall apply. The following sampling test plan (except that the visual examination for completeness, improper assembly and evidence of poor workmanship per items 301 and 302 shall be performed 100%) shall be utilized:

100%, c=0 for lot sizes of 10 or less
n=10, c=0 for lot sizes of 11 to 150
n=32, c=0 for lot sizes greater than 150

where, n=sample size and c=0 requires zero defects during inspection for acceptance

4.5.3.2 Acceptance. When any one assembly in the sample fails to meet any specified requirement, the lot shall be rejected. Rejected lots shall be resubmitted as above.

4.5.4 Inspection plan C.

4.5.4.1 Sample and tests. Each assembly in every lot shall be subjected to all the tests in Table V and shall be examined visually for completeness, improper assembly and evidence of poor workmanship per items 301 and 302 of Table VII. The conditions of 3.1.3 apply.

4.5.4.2 Acceptance. Where any one assembly fails to meet any specified requirement, the defective assembly shall be removed from the lot and resubmitted only after all defects have been corrected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

4.6 Methods of inspection.

4.6.1 Performance tests.

4.6.1.1 AC reference output. Apply the power sources, interconnections and other input conditions of 3.3.1. Verify the output conditions as specified in 3.3.1.

4.6.1.2 Modular reference output. Apply the power sources, interconnections and other input conditions of 3.3.2. Verify the output conditions as specified in 3.3.2.

4.6.1.3 Plus and minus 10 vdc reference voltage outputs. Apply the power sources, interconnections and other input conditions of 3.3.3. Verify the output conditions as specified in 3.3.3.

4.6.1.4 Logic timing signal and clock outputs. Apply the power sources, interconnections and other input conditions of 3.3.4. Verify the output conditions as specified in 3.3.4.

4.6.1.5 Reset signals. Apply the power sources, interconnections and other input conditions of 3.3.5. Verify the logic output conditions as specified in 3.3.5.

4.6.1.6 Logic control signals. Apply the power sources, interconnections and other input conditions of 3.3.6. Verify the logic output conditions as specified in 3.3.6.

4.6.1.7 Fail logic output. Apply the power sources, interconnections and other input conditions of 3.3.7. Verify the logic output conditions as specified in 3.3.7.

4.6.2 Environmental tests.

4.6.2.1 High temperature. Subject the assembly to the high temperature test specified in MIL-STD-810, Method 501 except storage temperature shall be 160°F for 48 hours. At the conclusion of the storage temperature test, stabilize the assembly at 100°F and subject it to the performance tests of Table IX. After testing, return the assembly to room temperature and subject it to the performance tests of Table V.

4.6.2.2 Low temperature. Subject the assembly to the low temperature test specified in MIL-STD-810, Method 502. Maintain the temperature at -65°F for a period of 12 hours minimum. At the conclusion of the storage temperature test, stabilize the assembly at 40°F and subject it to the performance tests of Table V. After testing, return the assembly to room temperature and subject the assembly to the performance tests of Table V.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

4.6.2.3 Vibration. Vibration A as specified in 4.6.2.3.1 shall be conducted only for first article inspection. Vibration B as specified in 4.6.2.3.2 shall be conducted only for quality conformance inspection.

4.6.2.3.1 Vibration A. Mount the assembly in a suitable vibration fixture and subject the assembly to the vibration test specified in MIL-STD-810, Method 514, General Procedures, and 3.4.2. The vibration amplitude shall have a tolerance of +10%. The tolerance of the vibration frequency shall be ±2%, or ±1/2 Hz for frequencies below 25 Hz. Vibration sweeps shall be conducted with the duration of exposure not less than 80 minutes in each of three mutually perpendicular axes. At the conclusion of this test, subject the assembly to the performance tests in Table V.

4.6.2.3.2 Vibration B. This test shall be conducted as in 4.6.2.2.1 except that the period of vibration shall be not less than 15 minutes in each axis.

4.6.2.4 Shock. Mount the assembly in a suitable shock fixture and subject it to the functional shock test for ground equipment specified in MIL-STD-810, Method 516, for a total of three half sine wave shock pulses in both directions along three mutually perpendicular axes (18 shocks). Peak amplitude shall be 40 ± 4 g's with a time duration of 18 ± 3 msec in accordance with Figure 4. At the conclusion of this test, subject the assembly to the performance tests of Table V. Repeat this test with peak amplitude of 100.0 ± 10.0 g's with a time duration of 1.5 ± 0.2 msec in accordance with Figure 4.

4.6.2.5 Temperature cycling. With power and loads of table I applied, subject the assembly to the temperature profile specified in Figure 5. At the conclusion of this test, subject the assembly to the performance tests of Table V.

4.6.3 General specifications. Verification shall be provided by examination, visually or through the use of standard measuring equipment, in accordance with 3.1.2.

4.6.4 Packaging inspection. The sampling and inspection of the preservation, packaging, packing and container marking shall be in accordance with MIL-STD-2073-1.

5. PACKAGING

5.1 Packaging, packing and marking. Packaging, packing and marking shall be in accordance with MIL-STD-2073-1. The level of protection shall be as specified in the procurement document (see 4.6.4 and 6.2d).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The logic and reference circuit card (A4) assembly is intended to be used in the Field Test Set, 11733200, which is used in the field for test of all of the M21 Computer subsystem components.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1).

c. Inspection provisions for first article (see 6.3).

d. Applicable levels of preservation, packaging, packing, and container marking (see 5.1 and 6.7).

6.3 First article. The contracting officer should provide specific guidance to offerors for submission of a first article sample to be tested as specified in 4.4.2. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Supersession. Previous revisions of MIL-C-48480(AR) were for the US Army Armament, Research, Development and Engineering Center's internal use only, and were not forwarded to the Naval Publications and Form Center for publication.

6.5 Submission of contractor inspection equipment designs for approval. Submit copies of designs as required to: Commander, U.S. Army ARDEC, Attn: AMSTA-AR-QAC-F, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.6 Drawings. Drawings listed in Section 2 of this

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

specification under the heading U.S. Army Armament, Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as U.S. Army Armament, Research and Development Command (ARRADCOM), Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.7 Levels of packaging. The following definitions describe the three levels of packaging in accordance with MIL-STD-2073-1.

a. Level A - Adequate protection for indeterminate storage and worldwide distribution.

b. Level B - Adequate protection for known shipment conditions and storage conditions normally not exceeding one year.

c. Level C - Adequate protection for shipment to a known site for immediate use.

6.8 Alternative quality conformance provisions. Alternative quality conformance procedures, methods, or equivalent, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equivalent, the contractor shall describe them in a written proposal submitted to the Government for evaluation. When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality assurance provision(s) herein. In cases of dispute as to whether the contractor's proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or detailed inspection system, as applicable. Unless otherwise specified in the contract, proposed alternative quality conformance provisions will be submitted by the contractor for evaluation by the technical activity.

6.9 Subject term (key word) listing.

Computer, M21
Fire Control
Tank, M60A3

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1240-0006)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL–C–48480C (AR)	950530

3. DOCUMENT TITLE: CIRCUIT CARD ASSEMBLY – LOGIC AND REFERENCE

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial: (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S. ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial: 201–724–6629	(2) AUTOVON DSN–880–6629
c. ADDRESS (Include Zip Code) ATTN: AMSTA–AR–EDE–S PICATINNY ARSENAL, NJ 07806–5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041–3466 Telephone (703) 756–2340 AUTOVON 289–2340	

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:28Z
Check the source to verify that this is the current version before use.