MIL-F-50495A (PA)
5 November 1975
SUPERSEDING
MIL-F-50495
28 April 1970

MILITARY SPECIFICATION

FIRING DEVICE, PRESSURE RELEASE TYPE, M5 AND M5 INERT ASSEMBLY PARTS FOR AND LOADING, ASSEMBLING AND PACKING

*This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts for, loading assembling and packing for one type of firing device designated as Firing Device, Pressure Release Type, M5 and M5 Inert Assembly.

*2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Packaging, Methods of
MIL-P-12951 - Primer, Percussion, M39A1, Loading, Assembling and Packing
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

*STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables For Inspection by Attributes (ABC-STD-105)

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

*(For meaning of asterisks (*) see 6.5).

*DRAWINGS

U.S. ARMY PICATINNY ARSENAL

2128139 - Package Shipping and Storage (For 24 Firing Device, Pressure Release Type, M5)
2816287 - Pack Shipping and Storage (For 96 Firing Device, Pressure Release Type M)
8799108 - Packing and Marking for, Firing Device, Pressure Release, Type, M5 and M5 Inert
9249244 - Firing Device, Pressure Release Type, M5 and M5 Inert Assembly

(Copies of specifications, standards and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

*3. REQUIREMENTS

3.1 Materials. - Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Assemblies. - The assemblies shall comply with all requirements specified on Drawing (dwg.) 9249244 and with all requirements specified in applicable specifications.

3.3 Spring embrittlement. - Springs manufactured for use in this assembly shall be free from embrittlement as evidenced by not fracturing when extended to the point of minimum permanent distortion.

3.4 Non-functioning. - The firing device shall not function when a load of 5 pounds (lbs), maximum (max.) is applied to the release plate.

3.5 Underwater functioning. - The firing device shall function underwater. (This requirement is not applicable to the M5 inert item.)

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:26Z
Check the source to verify that this is the current version before use.

*3.6 Workmanship. - All parts shall be fabricated and loaded in a thorough, workmanlike manner, and all manufacturing processing and assembly operations shall be correctly performed. The parts shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

3.7 First Article Inspection. - The specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

*4.1 Responsibility for inspection and standard quality assurance provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply, and are hereby made a part of this detail specification.

*4.2 Classification of inspection. - The following types of inspection shall be conducted on this item.

a. First article inspection
b. Quality conformance inspection

*4.3 First article inspection

4.3.1 Submission. - The Contractor shall submit a first article sample as designated by the Contracting Officer. The first article sample shall consist of 125 complete assemblies and thirty-two (32) complete sets of parts and sub-assemblies (i.e., 32 each of every component and sub-assembly). The first article shall be evaluated in accordance with the provisions of 4.3.2 and 4.3.3.

4.3.2 Inspections to be performed. - See MIL-A-48078 and paragraphs 4.4.2 and 4.4.3 specified herein. The inspections listed in 4.4.2.1 through 4.4.2.16 may be inspected for Critical and Major Defects only.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:26Z
Check the source to verify that this is the current version before use.

4.3.3 Rejection. - See MIL-A-48078.

*4.4 QUALITY CONFORMANCE INSPECTION

*4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of firing devices shall contain:

a. Parts from not more than one interfix lot number from one manufacturer.
b. Primers from not more than one interfix lot number from one manufacturer.

*4.4.2 Examination. - See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:26Z
Check the source to verify that this is the currentversion before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50495A (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
#4.4.2.1	Safety Pin				9249234
					NEXT HIGHER ASSEMBLY 9249244
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	Crack in safety pin (not applicable to inert item).		100%	3.2	Visual
Major B:					
131.	Large diameter		0.40%	3.2	Gage
132.	Small diameter		0.40%	3.2	Gage
133.	Protective finish missing or incomplete		0.40%	3.2	Visual
Minor:					
201.	Diameter of cotter pin hole		0.65%	3.2	Gage
202.	Diameter of safety cord hole		0.65%	3.2	Gage
203.	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

5

SARPA-QA FORM 2567 FEB 74

Source: https://asist.dla.mil -- Downloaded: 2026-02-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-F-50495A (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.2	Pivot Pin				9249236
					NEXT HIGHER ASSEMBLY
					9249244
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None Defined				
Major B:					
131.	Small outside diameter		0.40%	3.2	Gage
132.	Length of small outside diameter, minimum, (min.)		0.40%	3.2	Gage
133.	Protective finish missing or incomplete		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: http://assist.dla.mil - Downloaded: 2026-02-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
#4.4.2.3	Firing Pin Spring		9249237
			NEXT HIGHER ASSEMBLY
			9249244

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Radius of end which enters case hole, max.		0.40%	3.2	Gage
132.	Width of firing pin opening		0.40%	3.2	Gage
133.	Length from center of pivot pin hole to firing pin end		0.40%	3.2	Gage
134.	Protective finish missing or incomplete		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

—1

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-F-50495A (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.4	Base Coupling		8837263
			NEXT HIGHER ASSEMBLY 8837262

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Pitch diameter of large thread, min		0.40%	3.2	Gage
132.	Major Diameter of large thread, min.		0.40%	3.2	Gage
133.	Pitch diameter of small thread, min.		0.40%	3.2	Gage
134.	Major diameter of small thread, min.		0.40%	3.2	Gage
135.	Diameter of primer cavity, max.		0.40%	3.2	Gage
136.	Diameter of flash hole, min.		0.40%	3.2	Gage
137.	Length from primer end to beginning of knurl		0.40%	3.2	Gage
138.	Flash hole obstructed		0.40%	3.2	Visual
139.	Protective finish missing or incomplete		0.40%	3.2	Visual
Minor:					
201.	Total length		0.65%	3.2	Gage
202.	Outside diameter at flash hole end		0.65%	3.2	Gage
203.	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

Source: http://assist.dla.mil -- Downloaded: 2020-10-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50495A (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.5	Coupling Base Assembly				8837262
					NEXT HIGHER ASSEMBLY
					9249244
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	Primer Incorrect (applicable to inert item only)		100%	3.2	Visual
Major A:					
101.	Primer incorrectly seated or punctured		0.40%	3.2	Visual
102.	Presence of gasket prior to installation of shipping cup		0.40%	3.2	Visual
Major B:					
131.	Sealing compound missing		0.40%	3.2	Visual
132.	Shipping cup missing or damaged		0.40%	3.2	Visual
Minor:					
201	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-12T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-F-50495A (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.6	Case				9249241
					NEXT HIGHER ASSEMBLY 9249244
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	Location of interceptor hole		100%	3.2	Gage
Major B:					
131.	Pitch diameter of thread		0.40%	3.2	Gage
132.	Minor diameter of thread		0.40%	3.2	Gage
133.	Diameter of safety pin hole		0.40%	3.2	Gage
134.	Location of release plate pivot hole		0.40%	3.2	Gage
135.	Location of firing pin pivot hole		0.40%	3.2	Gage
136.	Location of coupling base hole		0.40%	3.2	Gage
Minor:					
201.	Location of spring hole		0.65%	3.2	Gage
202.	Wall thickness		0.65%	3.2	Gage
203.	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50495A (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
*4.4.2.7	Firing Pin	1 OF 1	9249242
			NEXT HIGHER ASSEMBLY 9249244

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Location of pivot hole		0.40%	3.2	Gage
132.	Diameter of pivot hole(s)		0.40%	3.2	Gage
133.	Profile of point		0.40%	3.2	Gage
134.	Distance from point to pivot pin hole		0.40%	3.2	Gage
135.	Inside width, max.		0.40%	3.2	Gage
136.	True position of point with datum		0.40%	3.2	Gage
137.	Protective finish missing or incomplete		0.40%	3.2	Visual
Minor:					
201.	Thickness		0.65%	3.2	Gage
202.	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-F-50495A (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
#4.4.2.8	Safety Pin Spring				9249238
					NEXT HIGHER ASSEMBLY 9249243
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Location of hole from end		0.40%	3.2	Gage
132.	Radius missing		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-F-50495A (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
#4.4.2.9	Release Plate		9249235
			NEXT HIGHER ASSEMBLY 9249243

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None Defined				
Major B:					
131.	Length		0.40%	3.2	Gage
132.	Location of safety pin slot		0.40%	3.2	Gage
133.	Width of safety pin slot		0.40%	3.2	Gage
134.	Depth of safety pin slot		0.40%	3.2	Gage
135.	Width		0.40%	3.2	Gage
Minor:					
201.	Thickness		0.65%	3.2	Gage
202.	Location of cutout in safety pin slot		0.65%	3.2	Gage
203.	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

13

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-F-50495A (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9249243
*4.4.2.10	Release Plate Assembly				NEXT HIGHER ASSEMBLY 9249244
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	Plate cracked (Not applicable to inert item)		100%	3.2	Visual
Major B:					
131.	Safety pin spring not staked		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50495A (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
*4.4.2.11	Pin, Interceptor	1 OF 1	9281782
			NEXT HIGHER ASSEMBLY
			9249244

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Protective finish missing or incomplete		0.40%	3.2	Visual
Minor:					
201.	Length, min.		0.65%	3.2	Gage
202.	Outside diameter, max		0.65%	3.2	Gage
203.	Distance between holes, min.		0.65%	3.2	Gage
204.	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.12	Assembly				9249244
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	Color code incorrect (not applicable to inert item)		100%	3.2	Visual
2.	Cotter pin not spread		100%	3.2	Visual
3.	High explosive item marked "INERT"		100%	3.2	Visual
Major B:					
131.	Release plate pivot pin not peened		0.40%	3.2	Visual
132.	Firing pin pivot pin not peened		0.40%	3.2	Visual
133.	Component assembled incorrectly		0.40%	3.2	Visual
Minor:					
201.	Grease coating missing or incomplete on safety pin		0.65%	3.2	Visual
202.	Safety pin cord missing or improperly tied		0.65%	3.2	Visual
203.	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50495A (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
*4.4.2.13	Box, Fiberboard	1 OF 1	9287713
			NEXT HIGHER ASSEMBLY 8799108

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Number of firing devices incorrect		0.40%	3.2	Visual
132.	Box damaged		0.40%	3.2	Visual
133.	Box improperly taped		0.40%	3.2	Visual
Minor:					
201.	Marking misleading or unidentifiable		0.65%	3.2	Visual
202.	Packing material missing		0.65%	3.2	Visual
203.	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

Source: https://assist.dla.mil Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50495A (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
#4.4.2.14	Separator				9287712
					NEXT HIGHER ASSEMBLY
					8799108
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131	Length		0.40%	3.2	Scale
132	Width		0.40%	3.2	Scale
133	Thickness		0.40%	3.2	Scale
Minor:					
201	Separator torn		0.65%	3.2	Visual
202	Cavities and holes left with ragged edges		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-F-50495A (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
#4.4.2.15	Sealed Barrier Bag				9287714
					NEXT HIGHER ASSEMBLY
					8799108
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Waterproofness or barrier bag destroyed by rupture, puncture, or separation of heat seal		0.40%	3.2	Visual
132.	Evidence of crushed carton (See Note 1)		0.40%	3.2	Visual
Minor:					
201.	Heat seal of barrier bag located so that one or more subsequent seals cannot be applied		0.65%	3.2	Visual
202.	Marking of bag misleading or unidentifiable		0.65%	3.2	Visual
203.	Evidence of poor workmanship		1.00%	3.6	Visual
Note 1:	Package should be opened if there is evidence of crushing				

NOTES:

19

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T20:26Z
Check the source to verify that this is the current version before use.

20

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50495A (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
#4.4.2.16	Box, Wood		9287715
			NEXT HIGHER ASSEMBLY
			8799108

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131	Number of fiberboard boxes incorrect		0.40%	3.2	Visual
132	Board broken or split		0.40%	3.2	Visual
133	Strapping missing broken or loose		0.40%	3.2	Visual
Minor:					
201	Marking misleading or unidentifiable		0.65%	3.2	Visual
202	Strapping improperly assembled		0.65%	3.2	Visual
203	Contents move when box is tilted		0.65%	3.2	Manual
204	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: http://assist.dla.mil - Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
#4.3.2.17	Package, Shipping and Storage, Prior to Closing				2128139
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Any packing component missing or misassembled		0.40%	3.2	Visual
Minor:					
201.	Number of dessicant units incorrect		0.65%	3.2	Visual
202.	Dessicant bags not properly secured		0.65%	3.2	Visual
203.	Indicator card missing		0.65%	3.2	Visual
204.	Number of inner packages incorrect		0.65%	3.2	Visual
205.	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:
21

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50495A (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 2128139
*4.3.2.18	Package, Shipping and Storage				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	CFR markings missing or unidentifiable		100%	3.2	Visual
Major B:					
131.	Tray interferes with seal of lid		0.40%	3.2	Visual
Minor:					
201.	Descriptive marking missing, misleading or unidentifiable		0.65%	3.2	Visual
202.	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-02-10-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.3.2.19	Pack, Shipping and Storage, Prior to Closing				2816287
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Package missing or improperly positioned		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

23

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50495A (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 2816287
*4.3.2.20	Pack, Shipping and Storage				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	CFR marking missing or unidentifiable		100%	3.2	Visual
Major B:					
131.	Wire binding not properly secured		0.40%	3.2	Visual
132.	Car seal missing		0.40%	3.2	Visual
Minor:					
201.	Descriptive marking missing, misleading or unidentifiable		0.65%	3.2	Visual
202.	Evidence of poor workmanship		1.00%	3.6	Visual

NOTES:

Source: https://assist.dla.mil Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

4.4.3 TESTING

4.4.3.1 Spring embrittlement.- (see 3.3), Major Defect B, A sample of 30 springs shall be selected from each heat treatment lot. If one or more springs fail to comply with the specified requirement, the heat treatment lot represented by the sample springs shall be rejected. The test shall be performed as specified in 4.5.1, using test equipment in accordance with 4.4.4.

4.4.3.2 Torque test of firing pin spring (See dwg. 9249237). Major Defect B, - A sample of 30 springs shall be selected from each lot of springs to determine the torque at the specified angular displacement. If one or more springs fail to comply with the applicable torque requirement, the lot shall be rejected. The test shall be as specified in 4.5.2, using test equipment in accordance with 4.4.4.

4.4.3.3 Non-functioning (see 3.4)

4.4.3.3.1 Critical Defect (Not applicable to inert item). - This test shall be conducted 100 percent. Any firing device that fails to comply with the specified requirements shall be classed defective and removed from the lot. The test shall be performed as specified in 4.5.3, using test equipment in accordance with 4.4.4.

4.4.3.3.2 Major Defect A, (Applicable to inert item). - A single sampling plan shall be used for this test in accordance with MIL-STD-105, using Code Letter J and an AQL of 0.65 percent. The test shall be performed as specified in 4.5.3, using test equipment in accordance with 4.4.4.

4.4.3.4 Underwater functioning test (see 3.5), Major Defect A,. - A single sampling plan shall be used for this test in accordance with MIL-STD-105, using Code Letter J and AQL of 0.65 percent. The test shall be performed as specified in 4.5.4 using test equipment in accordance with 4.4.4.

4.4.3.5 Check test for possible deterioration of primers Major Defect. - If the total elapsed time between the original acceptance of any primer lot and the assembly of that lot into the firing devices exceeds two years, or if the primers have been subjected to adverse conditions, however brief, at any

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:26Z
Check the source to verify that this is the current version before use.

to and must satisfactorily pass the check test specified in MIL-P-12951 immediately before the primer lot is assembled into the firing device assembly. This test shall be performed by the contractor on primers selected by the Government inspector at the facility assembling the primer lot into the firing device assembly and shall be conducted at Government expense without cost to the contractor (see 6.4), who loaded the primers or the contractor assembling the primers into the firing device assembly. Furthermore, this test shall not constitute a basis for rejection against either contractor except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

4.4.3.6 Heat Seal test of sealed bag (see dwg. 8799108). - Major A defect. - Sampling, acceptance criteria and test procedures for this test shall be as specified in MIL-P-116.

*4.4.4 Inspection Equipment. - The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and section 6.2 herein.

*4.5 Test Methods and Procedures

4.5.1 Spring Embrittlement. - The spring shall be pulled to the minimum point of permanent distortion by an approved method. (Springs so tested shall be scrapped).

4.5.2 Torque test of firing pin spring. - The torque shall be determined at the specified angular displacement. Observation shall be made for compliance with the applicable drawing requirement. (Destructive)

*4.5.3 Non-Functioning. - The firing device shall be mounted to a suitable test fixture. The specified restraining load shall be applied to the release plate. The safety pin shall be removed leaving the interceptor pin in place. Observation shall be made for actuation of the firing pin. The firing device shall be classed defective if the firing pin is released. (Non-destructive)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

*4.5.4 Underwater Firing Test. - The firing device shall be submerged in water to a depth of approximately six (6) inches. Then the firing device shall be shaken to expel all air bubbles and mounted to a test fixture. A restraining load shall be placed on the firing device and the safety pin and interceptor pin removed. The firing device shall be made to function by removing the load. The firing device shall be classed defective if the primer fails to function. (Destructive)

4.5.5 Heat seal of sealed bag. - The adequacy of the seal on the bag shall be determined in accordance with MIL-P-116.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging

5.1.1 Level A. - The firing devices shall be preserved and packaged in accordance with dwg. 8799108.

5.1.2 Level A. - For Marine Corps use, Preservation and Packaging shall be in accordance with dwgs. 2128138, 2113834 and 2128139.

5.2 Packing

5.2.1 Level A. - The packaged device shall be packed in accordance with dwg. 8799108.

5.2.2 Level A . - For Marine Corps use, packing shall be in accordance with dwg. 2816287.

5.2.2 Level C. - The packaged devices shall be packed in accordance with dwg. 8799108.

5.3 Marking

5.3.1 Marking shall be in accordance with dwg. 8799108.

5.3.2 For Marine Corps use, Marking shall be in accordance with dwgs. 2128138, 2128139 and 2816287.

6. NOTES

6.1 Ordering Data. - Procurement documents shall specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

a. Title, number and date of this specification.
b. Provisions for submission of first article samples.
c. Provisions of MIL-A-48078.

6.2 Submission of Inspection Equipment Designs for Approval.- (see MIL-A-48078) - Submit equipment designs as required, to Commander, Picatinny Arsenal, ATTN: SARPA-QA-T, Dover, New Jersey 07801.

6.3 Distribution of Ammunition Data Cards. - Distribution of data cards shall include the following: Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M, Dover, New Jersey 07801.

6.4 Check Test for Possible Deterioration. - The following test is designed to prevent primers that have deteriorated from being assembled into major ammunition items. The test shall be performed on primers from each lot which have been stored under normal conditions for more than two years or under adverse conditions for any period of time. If the specification for the ammunition item into which the primers are assembled does not require that the check test be performed, the Contracting Officer should insert in the contract a provision for the performance of the check test. The Contracting Officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check test for possible deterioration. Primer assemblies shall be selected from each lot for this test.

6.5 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
ARMY-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-116

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:26Z
Check the source to verify that this is the current version before use.