MIL-I-81316A(AS)
17 April 1967
Superseding
MIL-I-81316(WP)
30 August 1965

MILITARY SPECIFICATION

INITIATOR, CARTRIDGE ACTUATED, MARK 11 MOD 0

This specification has been approved by the Naval Air Systems Command, Department of the Navy

1. SCOPE

1.1 This document governs the manufacture, assembly and preparation for delivery of the MARK 11 MOD 0 cartridge actuated initiator and the methods of inspection and tests upon which product acceptance will be based.

2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards, drawings, and publications, of the issue in effect on date of invitation for bids, form a part of this document to the extent specified herein.

SPECIFICATIONS

Military

MIL-C-23024	Cartridge, Delay, MARK 36 MOD 0
MIL-D-23615	Design and Evaluation of Cartridge Actuated Devices
MIL-P-116	Preservation, Methods of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for inspection by Attributes

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.

MIL-STD-129 — Marking for Shipment and Storage

DRAWINGS

Bureau of Naval Weapons

DL 2518122 — Initiator, Cartridge Actuated, MARK 11 MOD 0

PUBLICATIONS

BUSANDA Instruction 4030.17 — Preservation, Packaging Packing and Marking; Navy Policy for

Bureau of Naval Weapons

OP 5 — Ammunition Ashore (This publication is not furnished to bidders and contractors by the procuring activity. Contractors should contact the Government Inspector for use of the publication.)

WR-43A — Preparation of Quality Assurance Provisions

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.2 Other publications. The following document forms a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 71-78 — Transportation, Interstate Commerce Commission, Explosives and Other Dangerous Articles

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402. Orders for the above publication should cite the latest edition and supplements thereto.)

3. REQUIREMENTS

3.1 General.

3.1.1 The MARK 11 MOD 0 cartridge actuated initiator covered by this specification shall be manufactured in accordance with DL 2518122 and all documents listed thereon.

3.2 Material. All materials used in the manufacture of the initiators shall conform strictly with the specifications referenced on the respective Bureau of Naval Weapons drawings unless specific approval in writing covering a departure therefrom has been obtained from the Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.2.1 Preproduction sample. Unless otherwise specified by the procuring activity, a preproduction sample of 22 MARK 11 MOD 0 initiators shall be furnished to the Government prior to start of full production. See 4.3.2.

3.3 Primary components. For the purposes of this specification, the Cartridge, Delay, MARK 36 MOD 0 is defined as a primary component. See 4.3.3.

3.4 Firing pin. Free movement, proper alignment, and proper protrusion of the firing pin shall be verified during assembly of each firing mechanism produced under a contract. See Drawing 2518124 of DL 2518122.

3.5 Firing mechanism. Firing mechanisms from each lot, selected in accordance with 4.7.1.1 and 4.7.1.2, shall meet the requirements listed below when subjected to the tests prescribed in 4.7.1.1 and 4.7.1.2.

3.5.1 Non-actuation. Firing mechanisms shall not actuate when subjected to a minimum pressure of 400 psi applied for 1 minute at the inlet port. See 4.7.1.1.

3.5.2 Actuation. Firing mechanisms not previously subjected to the non-actuation pressure of 3.5.1 shall actuate when a pressure of 500 psi $^{+50}_{-0}$ psi is applied to the inlet port at any temperature between -65°F and +160°F. See 4.7.1.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.

3.6 Complete initiator assemblies.

3.6.1 Firing mechanisms. Only firing mechanisms from lots which have passed the requirements of 3.5 shall be used in the complete initiator assemblies.

3.6.2 Cartridges. Only MARK 36 MOD 0 delay cartridges manufactured within a year past and accepted for service in accordance with the provisions of MIL-C-23024 shall be used in complete initiator assemblies.

3.6.3 Visual inspection. Completely assembled initiators shall be free of the visible defects noted in 4.7.2.1.

3.6.4 X-ray. Each initiator produced under a contract shall be subjected to the X-ray examination of 4.7.2.2.

3.7 Ballistic requirements. Completely assembled initiators from each lot, selected in accordance with 4.7.2.3.1, shall meet the requirements listed below when subjected to the test prescribed in 4.7.2.3.1.

3.7.1 Delay time. The delay time shall be measured from initial motion of the firing pin to start of pressure rise. The lower and upper limits of delay time shall be L = 0.40 second and U = 0.75 second, respectively.

3.7.2 Level and duration of pressure.

3.7.2.1 Maximum pressure. The lower limit of maximum pressure shall be L = 1000 psi.

3.7.2.2 Duration of pressure. The lower limit of duration of pressure at or above the minimum pressure of 1000 psi shall be L = 0.01 second.

3.7.3 Misfires. There shall be no misfires. See 4.7.2.3.2.4.

3.7.4 Mechanical failures. The initiator shall function without mechanical failure. See 4.7.2.3.2.5.

3.8 Workmanship. Initiators shall be constructed and finished in a manner to assure compliance with all the provisions of this specification and the applicable drawings. Special attention should be directed to dimensions, finishes, and coatings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling. Unless otherwise specified, and when applicable, the sampling plans and procedures used in the determination of the acceptability of products submitted by a supplier shall be in accordance with the provisions of MIL-STD-105. Unless otherwise specified in the contract, order, or requisition, all samples for test purposes shall be provided at the expense of the contractor.

4.3 Lots.

4.3.1 Inspection lots. Inspection lot definition, formation, and size shall be in accordance with MIL-STD-105.

4.3.2 Preproduction sample. Before entering into quantity production, an acceptable preproduction sample of 22 MARK 11 MOD 0 initiators shall be prepared and submitted to the test activity. Nineteen of these initiators shall be expended in the tests listed below and three shall be retained for investigative purposes. A preproduction sample acceptable for functional and environmental testing shall be defined as a sample which has met the requirements of paragraphs 3.4 through 3.6.4 of this specification. The contractor shall deliver the initiators to the activity designated by the contracting agency for test. Preproduction sample inspection shall consist of the following tests as prescribed in MIL-D-23615: 15 "g" shock (4); vibration (4); salt spray (4); 6 foot drop (3). These initiators, together with 4 untreated initiators, will be conditioned at +70°F ± 5°F and fired, using the test device of 4.7.2.3.1. Acceptance shall be based on integrity of the parts and legibility of markings after environmental treatment and ballistic performance in accordance with the limits prescribed in 3.7. Any quantity production prior to notification by the contracting agency of preproduction sample acceptability shall be at the contractor's risk. The preproduction initiators will not be applied as a part of the quantity specified for delivery by the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.

4.3.3 Production lot. The suggested production lot size is 91 minimum and 500 maximum initiators. Initiators required for all test purposes are selected from the production lot and will not be applied as a part of the quantity specified for delivery by the contract. Only primary components from a single lot shall be used in a production lot of initiators. One primary component production lot may be used in more than one initiator production lot.

4.4 Gages. The contractor shall provide himself with whatever gages are necessary and adequate to insure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings.

4.5 Classification of characteristics. The characteristics verified by the tests and examinations herein are classified as Critical, Major or Minor in accordance with WR-43A. Tests and examinations that verify critical characteristics are identified by the symbol (C) and major characteristics by the symbol (M). The number following the classification symbol indicates the serial number of test or examination. Tests and examinations which are not annotated with a classification code are classified minor.

4.6 Production and acceptance inspection. Production and acceptance inspection shall consist of verification of the characteristics classified on the drawings of DL 2518122 and the following tests and examinations:

Item	Nature of Test	Requirement	Test	Classification (WR-43A)
Primary Component	Single Lot Verification	3.3	4.3.3	(M10[1])
Firing Pin	Movement, Alignment and Protrusion Verification	3.4	---	(C1)
Firing Mechanism	Non-actuation	3.5.1	4.7.1.1	(C2)
Firing Mechanism	Actuation	3.5.2	4.7.1.2	(C3)
Firing Mechanism	Lot Acceptance Verification	3.6.1	---	(C4)
Cartridge	Age and Acceptance Verification	3.6.2	---	(C5)
Initiator	Visual Inspection	3.6.3	4.7.2.1	(C6)
Initiator	X-ray	3.6.4	4.7.2.2	(C7)
Initiator	Ballistics	3.7	4.7.2.3	(C8)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.

4.6.1 Packing, packaging and marking. (M102) The inspector shall ascertain that the packing and packaging of the initiators and the container markings conform to Section 5 of this document.

4.7 Tests.

4.7.1 Firing mechanism.

4.7.1.1 Non-actuation. The number of firing mechanisms selected from each lot shall be in accordance with Table I, Inspection Level I of MIL-STD-105 with the additional requirement that the sample size shall be not less than eight units. One-half of the samples shall be conditioned for not less than 12 hours at -65°F ± 5°F and the remaining half shall be conditioned for not less than 12 hours at +160°F ± 5°F. Within 3 minutes after removal from the conditioning chamber, a minimum pressure of 400 psi shall be applied for a period of 1 minute to the inlet port of each firing mechanism. Actuation of any firing mechanism at a minimum pressure of 400 psi, applied for 1 minute shall result in rejection of the lot.

4.7.1.2 Actuation. The number and conditioning of firing mechanisms selected from each lot shall be as in 4.7.1.1 above. Within 3 minutes after removal from the conditioning chamber, a pressure of 500 psi $^{+50}_{-0}$ psi shall be applied to the inlet port of each firing mechanism by means of a solenoid valve, or other quick-acting valve. Failure of any firing mechanism to actuate shall result in rejection of the lot. Proper actuation is defined as the shearing of the shear pin, followed by propulsion of the firing pin terminating in the firing pin body striking the bottom of the firing pin bore, or back-up washer.

4.7.1.3 Rework. If the cause of failure in 4.7.1.1 or 4.7.1.2 above can be corrected by rework of the lot, the lot in question may be reworked to correct the deficiency and a new sample submitted for test. Firing mechanisms which pass the tests of 4.7.1.1 and 4.7.1.2 may be reworked by replacement of the shear pins.

4.7.2 Completely assembled initiators.

4.7.2.1 Visual inspection. Examine each initiator produced under a contract and reject for cracks, splits, incomplete or damaged threads on inlet and outlet ends, cartridge missing, firing mechanism not properly seated on cartridge, missing lock pin, or other defect which might prevent proper mating with connecting parts or proper functioning of the device.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.

4.7.2.2 X-ray. Examine each initiator produced under contract and reject for: bent or missing shear pin in firing mechanism, cocked or missing back-up disc, back-up disc not in contact with cartridge, cartridge missing, or any other defect which might affect the reliability of the initiator or result in failure to perform its required function. X-ray plates may be destroyed after ballistic acceptance of the initiators.

4.7.2.3 Ballistic tests.

4.7.2.3.1 The number of initiators selected from each lot for the ballistic tests shall be in accordance with the requirements of Table I of MIL-STD-105, Inspection Level I with the additional requirement that the sample size shall be not less than eight initiators. The initiators shall be delivered to the activity specified by the procuring agency for test. Preproduction samples shall be as provided in 4.3.2. The initiators shall be conditioned for 24 hours at +70°F ± 5°F. A closed chamber having an internal volume of 0.3 cubic inch and adapted for the measurement of pressure shall be attached to the outlet port of the initiator, and the initiator actuated by the application of 500 psi $^{+50}_{-0}$ psi. In addition to the sample of initiators for the above test, three additional initiators shall be furnished from the production lot for investigative purposes.

4.7.2.3.2 Criteria of acceptability.

4.7.2.3.2.1 Delay time. No initiator firing shall result in delay times outside the limits of 3.7.1.

4.7.2.3.2.2 Maximum pressure. No initiator firing shall result in maximum pressures below the limit of 3.7.2.1.

4.7.2.3.2.3 Duration of pressure. No initiator firing shall result in a duration of pressure below the limit of 3.7.2.2.

4.7.2.3.2.4 Misfire. No initiator shall fail to fire.

4.7.2.3.2.5 Mechanical failure. No initiator firing shall result in a mechanical failure. A mechanical failure is defined as any deformation or breakage of a part, or separation of parts which is other than a design function.

4.7.3 Retest. There shall be no retests.

4.7.4 Test failure. If test failure is attributable to an assignable cause, excluding the test initiators, original test results should be discarded and the complete test reconducted with a new sample of initiators.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. For definitions of packaging levels, see 6.4.

5.1.1 Level A. Level A packaging shall be used for packaging of all production lots for service use. Two initiators shall be packaged in an inner container in accordance with Bureau of Naval Weapons Drawing 2518132 of DL 2518122.

5.1.2 Level B. Not applicable.

5.1.3 Level C. When directed by the procuring activity, those initiators which are intended for expenditure in preproduction sample testing and for production lot acceptance tests shall be packaged in accordance with Method III of MIL-P-116, and with the Code of Federal Regulations 49 CFR 71-78.

5.2 Packing. For definitions of packing levels, see 6.4.

5.2.1 Level A. Level A packing shall be used for packing of all production lots for service use. Six inner containers as described in 5.1.1 shall be packed in accordance with Bureau of Naval Weapons Drawing 2518179 of DL 2518122.

5.2.2 Level B. Not applicable.

5.2.3 Level C. When directed by the procuring activity, those initiators which are intended for expenditure in preproduction sample testing and for production lot acceptance tests, and are packaged in accordance with 5.1.3 shall be packed to afford protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. Shipping containers shall be in accordance with the Code of Federal Regulations 49 CFR 71-78.

5.3 Markings.

5.3.1 Special markings. Marking of exterior containers shall be in accordance with the Code of Federal Regulations 49 CFR 71-78.

5.3.2 Normal markings. In addition to the markings required by contract or order, and as specified on Bureau of Naval Weapons Drawings 2518132 and 2518179 of DL 2518122, unit packages and shipping containers shall be marked in accordance with the requirements of MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The MARK 11 MOD 0 cartridge actuated initiator was designed primarily for use in the sequencing portion of the escape system in the T2 aircraft.

6.2 Ordering information. Procurement documents should specify the following:

a. title, number and date of this specification;

b. whether preproduction inspection is required and if so, specify the test activity;

c. production lot size and test activity (see 4.3.3);

d. items of data required for each preproduction and production lot (see 6.3).

6.3 Data. For the information of Contractors and Contracting Officers, any of the data specified in (a) subparagraphs below, (b) applicable documents listed in Section 2 of this specification or (c) referenced lower-tier documents, need not be prepared for the Government and shall not be furnished to the Government unless specified in the contract or order. The data to be furnished shall be listed on DD Form 1423 (Contractor Data Requirements List), which shall be attached to and made a part of the contract or order. NAVWEPS Form 4200/15 (Drawings, Lists, and Specifications Required) shall be attached where applicable.

6.3.1 Test report. Results of ballistic tests shall be forwarded to the Naval Air Systems Command and the procuring activity.

6.3.2 Data cards. The contract or order should state the format, quantity and destination of data cards.

6.4 Definitions. The definitions of Levels A and C packaging and packing given below were extracted from BUSANDA Instruction 4030.17.

6.4.1 Level A packaging. The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during handling, shipment, indeterminate storage and world-wide redistribution.

6.4.1.1 Level C packaging. The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during shipment from supply source to the first receiving activity, for immediate use. This level may

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.

conform to supplier's commercial practice when such meets the requirements of this level.

6.4.2 Level A packing. The degree of packing which will afford adequate protection during shipment, handling, indeterminate storage and world-wide redistribution.

6.4.2.1 Level C packing. The degree of packing which will afford protection against damage during direct domestic shipment from the supply source to the first receiving activity for immediate use. This level in general will conform to applicable carrier rules and regulations, and may be the supplier's commercial practice when such meets the requirements of this level.

6.5 Explosives safety precautions.

6.5.1 Applicability. The loading, assembly and handling of the explosives, subassemblies and the finished items covered by this specification, involve hazardous operations and therefore require suitable explosives safety precautions. At plants of the Naval Air Systems Command, Department of the Navy, and other Government plants where the Government is responsible for safety, the precautions listed below are mandatory. These same minimum provisions listed below are recommended for observance by a contractor or manufacturer that explosively loads the item covered in this specification in order to fulfill his own safety responsibility. Other warnings and precautions, pertaining to the operational effectiveness or safety of the specified item during its use (for example, during its handling, launching or firing) are included in the detailed technical requirements of the specification. Use of this specification shall not be construed to replace other safety regulations of governmental agencies or to relieve the contractor or manufacturer of responsibility for the safety of his operations.

6.5.2 Personnel and equipment. Proper care must be exercised at all times to protect personnel from accidents, fires or explosions, and to limit damage to equipment and loading areas. In connection with the above, the precautionary measures in the following paragraphs should be observed. (See also paragraph 6.5.4, Static and electrical and other applicable parts of these safety precautions.)

6.5.2.1 Explosives operations shall be kept under strict supervision. Periodic inspections shall be employed to assure compliance with established safety regulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.

6.5.2.2 Safe equipment and methods should be utilized for handling and transporting explosives and loaded parts.

6.5.2.3 Where required, remote control barricaded handling equipment shall be used for explosives operations such as mixing, pouring, weighing, charging, sifting, drying, pressing, casting, crimping, etc.

6.5.2.4 Employ properly proportioned and properly located protective barricades, screens or shields at all required points.

6.5.2.5 Maintain equipment such as presses, dies, crimpers, blenders, mixers, sifters, conveyors, and the like, in safe operating condition.

6.5.2.6 Enforce, where necessary, the wearing of suitable safety footwear, gloves, goggles, respirators, and impregnated garments to protect personnel against burns, poisoning and associated industrial hazards.

6.5.2.7 During static tests, propulsion units such as rocket motors shall be restrained against full thrust to prevent flight if ignited, for example, during test of igniter circuit. Also, means to vent flames and exhaust gases harmlessly shall be provided.

6.5.3 Operating procedures. All loading operations shall be conducted in full accordance with a formalized operating procedure which shall include the following:

6.5.3.1 Keep only minimum limited quantities of explosives and completed or partially loaded parts present at each stage of operation.

6.5.3.2 Allow no fires or exposed electrical or other sparking equipment, and little or no flammable material to be present in loading, handling and storage spaces. Enforce proper "Match" and "No Smoking" rules where necessary.

6.5.3.3 Appropriate safety instructions for specific operations shall be posted and personnel instructed as to the hazards present and precautions involved.

6.5.3.4 The number of working personnel and transients permitted in each work space shall be established and posted in such areas. The numbers shall be the minimum number required to accomplish necessary operations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.

6.5.3.5 All loading operations should be conducted in a neat and orderly manner.

6.5.3.6 Enforce good housekeeping and maintain effective policing, inspection and supervisory methods throughout the loading area and surroundings.

6.5.3.7 Employ effective cleaning methods periodically to minimize the accumulation of explosives or explosive dust and other contamination upon, and assure its removal from, floors, walls, ceiling, ledges, tables, benches, piping, and equipment or the items loaded. Clean up any spilled material immediately.

6.5.3.8 The exposure of explosive materials and related parts should be so controlled as to minimize the absorption of moisture from the atmosphere or other sources during loading and handling operations.

6.5.3.9 Personnel handling detonators, primers, delay elements, lead-ins, boosters, and related parts which affect functioning should, insofar as practicable, avoid using bare fingers or improper equipment, in order to prevent damage, corrosion, or deterioration from perspiration or other contaminating deposits.

6.5.3.10 Keep explosives and explosive parts in approved covered receptacles with covers in place when material is not being taken out of or put into the receptacles. Where necessary, receptacles should be conductive to ground electrostatic charges. (See paragraph 6.5.4.)

6.5.4 Static and electrical.

6.5.4.1 Protect operations from electrostatic charges by effectively grounding all machinery, equipment, and fixtures; and, where necessary, employ suitable grounded conductive coverings for floors, work benches and tables, and workers' conductive shoes. Workers' clothing of a type to minimize the accumulation of static charges shall be employed. Fabrics such as silk and nylon, which promote static generation shall be avoided. Additional grounding devices such as grounded bracelets for workers should be employed where operations are conducted with items which are unusually sensitive to initiation by static electricity. Such items include initiating explosives, tracer mixtures, and low energy type electric primers, detonators and squibs. The latter types of items shall have the free ends of lead wires bared and twisted together, and be packed in relatively small groups wrapped in bare non-insulated aluminum foil or other uncoated metal foil. During assembly and processing operations such sensitive electric items should be short circuited by clips or other devices until installed with safety shunt in the final

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.

device. Additional precautions for these items should include mechanical shielding to contain or deflect fragments and blast, also electrical shielding from induced electric currents originated by sources such as lightning, static, electromagnetic radiations, etc. Where necessary for safety, humidity of work rooms should be appropriately increased, as required to lessen electrostatic effects but without inducing excessive moisture absorption by any of the components of the item being processed.

6.5.4.2 Protect all explosive operations from effects of electric current originating in equipment such as soldering irons or guns, heaters, switches, wiring, motors, lights, test instruments, etc., by suitable insulation, grounding, separation or shielding. Such electric sources may initiate explosives by heat, sparks, arcs, or due to completing an electric circuit through an electric primer, detonator or squib. For example, circuits may be inadvertently completed from a defective electric soldering iron through a grounded contact. All electric type primers, detonators, or squibs provided with wire leads shall have the free ends of the wires bared and twisted together to short circuit each unit, except when in process of assembly into a finished item. Removable short circuiting clips, or other devices should be employed during manufacturing operations involving items such as electric primers, detonators or squibs.

6.5.4.3 Where necessary, protect personnel and operations from electromagnetic energy. In certain work with very sensitive explosives or items, a shielded environment free from significant electromagnetic energy should be provided.

6.5.5 Operating facility and storage regulations.

6.5.5.1 All explosives and completely or partially loaded items should be stored in suitable storage magazines located in accordance, at a minimum, with the American Table of Distances (ATD); and, while in process, in safety lockers and chests if in loading rooms, or in adequate ready or service magazines located in accordance with Intraplant Distances set forth in the ATD when outside of loading rooms. For Navy managed or contractor managed Navy owned explosives loading plants, the Armed Services Explosives Safety Board standards approved by the Department of Defense, the Secretary of the Navy and the Naval Air Systems Command, covering quantity-distance regulations for explosives, apply.

*U.S. GOVERNMENT PRINTING OFFICE: 1967-251-520/6754

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION
MIL-I-81316A(AS) INITIATOR, CARTRIDGE ACTUATED, MARK 11 MOD 0

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD, FORM 1 APR 63 1426

C-8979

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:11Z
Check the source to verify that this is the current version before use.