INCH-POUND

MIL-P-52348C (ME)
26 July 1989
SUPERSEDING
MIL-P-52348B (ME)
21 November 1980

MILITARY SPECIFICATION

PACKING KIT, HOSELINE

This specification is approved for use within the USA Belvoir Research, Development and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a packing kit consisting of a hoist, hose puller, and hose clamps designed for use in packing sections of a hoseline system in flaking boxes.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

PPP-B-601	–	Boxes, Wood, Cleated-Plywood
PPP-T-60	–	Tape: Packaging, Waterproof

MILITARY

MIL-P-116	–	Preservation, Methods of
MIL-T-704	–	Treatment and Painting of Materiel

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to USA Belvoir Research, Development and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3835

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	–	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	–	Marking for Shipment and Storage
MIL-STD-130	–	Identification marking of US Military Property
MIL-STD-889	–	Dissimilar Metals
MIL-STD-1472	–	Human Engineering Design Criteria for Military Systems, Equipment and Facilities
MIL-STD-1190	–	Minimum Guidelines for Level C Preservation, Packing and Marking

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Taylor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Government drawing. The following Government drawing forms a part of this document to the extent specified herein. (Unless otherwise specified, the issues are those cited in the solicitation.

DRAWING

ME

TA13200E6230	–	Hoseline Packing Kit

(Copies of drawings required by contractors in connection with specific acquisition functions should be obtained from the USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-FSH, Fort Belvoir, VA 22060-5606.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document however, supercedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The hoseline packing kit (hereinafter called "kit") shall be in accordance with TA13200E6230 and as specified herein.

3.1.1 Drawing. The drawing forming a part of this specification is an end-product drawing. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, on request, for inspection by the contracting officer or his designated representative.

3.2 First article. Unless otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

3.3 Materials. Materials shall be as specified herein and on the drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 3.3.2).

3.3.1 Material deterioration prevention and control. The packing kit shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments to which the packing kit may be exposed.

3.3.1 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.3.1.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with component and subcomponent, and shall make information available on request to the contracting officer or designated representative.

3.3.2. Recovered materials. For the purpose of this requirement, recovered materials are those materials that have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the packing kit may be newly fabricated from recovered materials to the maximum extent practicable, provided the packing kit produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the packing kit.

3.4 Chest. A steel chest shall be provided for the components of the kit. The chest shall be not more than 22 inches (558.8 mm) in height, and shall be constructed of steel not less than 0.073 inch (1.85 mm) thick. The chest shall have a hinged cover and latches to secure the cover in the closed position. The cover shall be self-supporting in the open position. Handles shall be in accordance with MIL-STD-1472, 5.9.11.5. The chest cover and front shall be labeled "HOSELINE PACKING KIT" in 1-inch (25.4 mm) high letters. Bins, cradles, or blocking shall be provided for the components of the kit to prevent damage during shipment and handling. Break all exposed sharp edges and corners and deburr.

3.4.1 Loading plan. A loading plan indicating the location of all items in the chest shall be furnished. The loading plan shall be permanently attached without adhesives to the inside of the cover. The loading plan shall provide pictorial and verbal instruction for loading the chest. Lettering shall comply with MIL-STD-1472, 5.5.5.

3.5 Treatment and painting. The chest and all components of the kit, except the hoist cable, shall be cleaned, treated, and painted in accordance with MIL-T-704, type F or G. Unless otherwise specified (see 6.2), the color shall be camouflage green 383.

3.6 Identification marking. The kit shall be identified in accordance with MIL-STD-130. Marking shall be applied to the outer cover of the chest.

3.7 Workmanship. All components of the kit shall be free of harmful extraneous material such as sand, dirt, sprues, scale and flux. External surfaces shall be free from burrs, sharp edges, and corners.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. The contractor is responsible for ensuring that components and materials used are manufactured and examined in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4)
c. Inspection of packaging (see 4.6)

4.3 First article inspection.

4.3.1 Examination. The first article shall be examined as specified in 4.5.1 in the order shown. The presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Examination. Each kit shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.5 Inspection procedure.

4.5.1 Examination. The kit shall be examined as specified herein for the following defects:

Major

101. Hoseline packing kit not in accordance with drawings (see 3.1).
102. Drawings not furnished (see 3.1.l).
103. Materials not as specified (see 3.3).
104. Materials not resistant to corrosion and deterioration or treated to be resistant to corrosion and deterioration for the applicable storage and operating environments (see 3.3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

105. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other (see 3.3.1.1).
106. Contractor does not have documentation available for identification of material, material finishes, or treatment (see 3.3.1.2).
107. Used rebuilt or remanufactured components, pieces, or parts are incorporated in the kit (see 3.3.2).
108. Chest not as specified (see 3.4).
109. Loading plan missing or not as specified (see 3.4.1).
110. Workmanship not as specified (see 3.7).

Minor

201. Treatment and painting not as specified (see 3.5).
202. Color not as specified (see 3.5).
203. Identification marking missing, incomplete or illegible (see 3.6).

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of packaging.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

111. Unpainted metal surfaces of components requiring a contact preservative not coated as specified.
112. Chest lid not sealed with tape as specified.
113. Marking missing, illegible, incorrect or incomplete for level A, B, or C.
114. Packing not as specified for level A, B, or C.

5. PACKAGING

5.1 Preservation (see 6.5). Unpainted metal surfaces of components of the kit requiring the application of a contact preservative in accordance with MIL-P-116, shall be coated with type P-1 or, as applicable, P-19 preservative. The preservatives shall be in accordance with the applicable specifications listed in MIL-P-116 and shall be applied in accordance with MIL-P-116. The preserved components comprising a complete kit shall then be placed and secured on the chest (see 3.4) in accordance with the loading plan (see 3.4.1). The chest cover shall then be closed and latched in the closed position with the provided fastening/latching devices (see 3.4). After the cover has been latched, the seam between the chest cover and the chest body shall be completely sealed with tape conforming to PPP-T-60, type IV.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Each complete kit, preserved and secured within the chest as specified in 5.1, shall be individually packed in a close-fitting box in accordance with PPP-B-601, overseas type,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

style optional. Box closure and strapping shall be as specified in the box specification, except that strapping shall be flat and the finish B.

5.2.2 Level B. Each complete kit, preserved and secured within the chest as specified in 5.1, shall be packed as specified in 5.2.1 for level A, except that boxes shall be domestic type and the strapping may be finish A.

5.2.3 Level C. Each complete kit, preserved and secured within the chest as specified in 5.1, shall be individually packed in accordance with MIL-STD-1190.

5.3 Marking. In addition to any special or identification markings required by the contract or purchase/delivery order (see 6.2), each container, excluding the chest, shall be marked in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The kit is intended for use with a 4-inch, lightweight, collapsible hoseline system.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).
c. When a first article is not required (see 3.2).
d. Color required (see 3.5).
e. Level of packing required (see 5.2).
f. Any special marking (see 5.3).

6.3 First article. When a first article inspection is required, the item(s) should be a preproduction model. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of the first article test results and disposition of the first articles. Invitation for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Subject term (key word) listing.

Hoseline, collapsible packing kit

6.5 Levels of protection. For marking purposes, the levels of protection and packing shall be A/A, A/B, or A/C.

6.6 AOL certification. This specification is certified to be in compliance with current Army Materiel Command (AMC) policy for the elimination of AQL's/LTPD's (Acceptable Quality Levels/Lot Tolerance Percent Defectives) from military specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

(Certified by/date _____)

6.7 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army – ME

Review activity:
DLA – CS

Preparing activity:
Army – ME

Project 3835-A090

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-P-52348C	890726

3. DOCUMENT TITLE
PACKING KIT, HOSELINE

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)
Reinstatement

5. REASON FOR RECOMMENDATION
Reinstatement in order to convert to a performance specification.

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
Mitchell, Elizabeth C.	US ARMY TACOM-TARDEC	
c. ADDRESS (Include Zip Code) US Army Tank-automotive and Armaments Command AMSTA-TR-D/210 Warren, MI 48397-5000	d. TELEPHONE (Include Area Code) (1) Commercial (810) 574-4154 (2) AUTOVON (If applicable) 786-4154	7. DATE SUBMITTED (YYMMDD) 990201

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
Mitchell, Elizabeth C.	(1) Commercial (810) 574-4154	(2) AUTOVON 786-4154
c. ADDRESS (Include Zip Code) US Army Tank-automotive and Armaments Command AMSTA-TR-D/210 Warren, MI 48397-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.