MIL-P-48528(PA)
13 November 1975
SUPERSEDING
See Section 6

MILITARY SPECIFICATION

PISTON MOTOR ASSEMBLY

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of electrically activated motor, entitled Piston Motor Assembly which is used in the Lance warhead section.

1.2 This item contains explosive material and, therefore, tests must be performed with proper safeguards for personnel and equipment.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-202	- Test Methods for Electronic and Electrical Component parts.
MIL-STD-271	- Nondestructive Testing Methods for Metals.
MIL-STD-810	- Environmental Test Methods.
MIL-STD-1169	- Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

DRAWINGS

U.S. ARMY

8878857	- Piston Motor.
9257184	- Glass to Metal Seal.

NUOR

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The piston motor shall comply with all requirements specified on the drawing (dwg) 8878857, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.5 Bridge wire circuit resistance. The wire resistance shall be 1.00 ± 0.10 ohms when tested as specified in 4.4.1.

3.6 Insulation resistance. The insulation resistance of lead wires tied together and case shall not be less than 20 megohms when tested as specified in 4.4.2.

3.7 Leakage.

3.7.1 Prefire leakage. The piston motor shall demonstrate an indicated leak rate no greater than 1×10^{-6} atmosphere cubic centimeters of helium per second when subjected to the test per 4.4.3.1.

3.7.2 Post-fire leakage. The piston motor shall reveal no holes or fissures in the housing when subjected to the test per 4.4.3.2.

3.8 Activation energy. Testing to determine compliance with 3.8.1 and 3.8.2 shall be as specified in 4.4.4.

3.8.1 Non-function. The piston motor shall not function when a direct current of 1.0 +0.00 -0.05 amperes is applied for a duration of 200 millisecond minimum. Non-function shall be evident when a visual examination shows no evidence of piston movement.

3.8.2 Function. The piston motor shall function at a maximum of 3.0 amperes when subjected to a current rising at a rate of two (2) amperes in 300 milliseconds. Functioning shall be evident when the piston movement of 0.150 inch minimum and a force of 500 pounds minimum is displayed against a test gage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

3.9 Environmental testing. The piston motor shall comply with MIL-STD-810, visual inspection and failure criteria, section 3. The piston motor shall also comply with 4.3.3.1 before and after each environmental test. Testing shall be as specified in 4.4.5. Tests shall be conducted in the order specified.

3.9.1 Thermal shock (165 ± 5°F to -65 ± 5°F). The piston motor shall withstand 3 temperature shock cycles without external damage (see 6.5). A cycle shall be considered completed when the piston motor has been subjected to a temperature of 165 ± 5°F for 4 hours minimum and then subjected to a temperature of -65 ± 5°F for 4 hours minimum. The transfer of the piston motor from one test chamber to the other test chamber shall be accomplished within 20 seconds. Testing shall be as specified in 4.4.5.1.

3.9.2 Mechanical shock. The piston motor shall show no evidence of external damage (see 6.5) when subjected to mechanical shock. Shocks of 50 ± 5 g's peak amplitude, half-sine duration of 11 ± 1 milliseconds, shall be applied once in each direction along each of the three principal axes for a total of 6 shocks. Testing shall be as specified in 4.4.5.2.

3.9.3 Transportation vibration. The piston motor shall withstand vibrations along each of its three mutually perpendicular axes without evidence of external damage (see 6.5). While being maintained at the temperatures indicated in Cycles I and II, the piston motor shall be subjected to the vibration spectrum in Table I. Testing to Cycles I and II, in that order, shall be as specified in 4.4.5.3. After testing to each temperature cycle, the piston motor shall be examined for evidence of external damage.

Table I

Frequency (Hz)	Input Gravity Units (g) Double Amplitude (da) (inches)	Logarithmic Sweep Rate Temperature Cycles 165 ± 5°F* (Cycle I)	-65 ± 5°F* Cycle II)
5-15-5 15-75-5 75-500-75	0.4 g 0.036 da 10.0 g	1 frequency sweep from 5-500-5 Hz (15 min for each sweep) for a total of 15 min per axis.	1 frequency sweep from 5-500-5 Hz (15 min for each sweep) for a total of 15 min per axis.

*See 6.4 for temperature stabilization.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

3.9.4 Temperature-humidity. The piston motor shall withstand two complete 15 day "JAN temperature of humidity cycle", consisting of recycling piston motor nine times between the extremes of +165°F (95 percent rh) and -65°F without evidence of external damage (see 6.5). Testing as specified in 4.4.5.4.

3.9.5 High temperature. The piston motor shall withstand temperatures of 165 ± 5°F for 24 hours minimum without evidence of external damage (see 6.5). Testing shall be as specified in 4.4.5.5.

3.9.6 Low temperature. The piston motor shall withstand temperatures of -65 ± 5°F for 24 hours minimum without evidence of external damage (see 6.5). Testing shall be as specified in 4.4.5.6.

3.9.7 Radiographic examination. The piston motor shall be radiographically processed for evidence of defects such as cocked piston, flaws in glass to metal seal, voids in powder charge, component missing, improper, damaged or loose, improper assembly of component and defects in metal. Testing shall be in accordance with 4.4.5.7.

3.10 Workmanship.

3.10.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.10.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.10.3 Burrs. Parts shall be free from burrs.

3.10.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.10.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

3.10.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 16 complete assemblies (see dwg 8878857) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table II. Tests shall be conducted in order specified in Table II.

Table II

First article inspection and tests

Inspection or Test	Sequence of Testing, Unit Nos.
1. Classification of characteristics (see 4.3.2.1)	
2. Thermal shock (see 3.9.1)	3;6-9;13,15,16
3. Transportation vibration -65°F (see 3.9.3)	1;2;3;6;11;13;14;16
4. Transportation vibration 165°F (see 3.9.3)	4;5;7-10;12;15
5. Mechanical shock (see 3.9.2)	3;6-8;10-12;14
6. Low temperature (see 3.9.6)	3-6;10;12;13;16
7. High temperature (see 3.9.5)	3-6;9;11;14;15
8. Temperature-humidity (see 3.9.4)	2;3;5;8-10;13;14
9. Bridge wire circuit resistance (see 3.5)	1 thru 16
10. Insulation resistance (see 3.6)	1 thru 16
11. Non-function (see 3.8.1)	1 thru 16
12. Prefire leakage (see 4.4.3.1)	1 thru 16
13. *Function (see 3.8.2 and 3.9.6)	1;5;6;8;12-15
14. *Function (see 3.8.2 and 3.9.5)	2;3;4;7;9;10;11;16
15. Post-fire leakage (see 3.7.2)	1 thru 16

*The piston motor shall be functioned at extreme temperature after being temperature soaked for 2 hours minimum in lieu of 24 hours minimum. Inspection for external damage (see 6.5) shall be performed at room temperature after functioning.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Inspection lot formation. All items in each inspection lot shall be from one production line, one shift, one batch of products, one manufacturer of raw material or components, one production method or manufacturing operation. The entire lot shall be submitted as a unit for inspection.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table III and Table IV), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

Table IV
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Glass to metal seal (see dwg 9257184).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Leakage test per MIL-STD-202, Method 112A, Condition C, Procedure I, incorrect	Gage
	102. Serial number assignment missing or illegible (see 3.4)	Visual
Minor:	None defined.	

4.3.2.1.2 Piston motor assembly (see dwg 8878857).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Diameter, outside, maximum	Gage
	102. Length of housing, maximum	Gage
	103. Length of insulated lead, minimum	Gage
	104. Color of lead wire, incorrect	Visual
	105. Lead wire damaged	Visual
	106. Adhesive around lead insulation, incorrect	Visual
	107. Serial numbers missing or illegible	Visual
	108. Evidence of poor workmanship (see 3.10)	Visual
	109. Objective evidence relative to material missing or improper (see 3.1)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

Minor: None defined.

4.3.3.1.3 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Preservation, packaging and packing not in accordance with MIL-STD-1169	Visual
102.	Marking not in accordance with MIL-STD-1169	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.10)	Visual

4.3.3 Testing. All tests shall be performed. Tests need not be performed in the order specified below:

Test	Test Classification
a. Bridge wire circuit resistance	Major
b. Insulation resistance	Major
c. Prefire leakage	Major
d. Radiographic examination	Major
e. Function	Major

Since test e is considered destructive, samples so tested may not be returned to lot.

4.3.3.1 Bridge wire circuit resistance, insulation resistance, prefire leakage, and radiographic examination. Each piston motor shall be tested in accordance with 4.4.1, 4.4.2, 4.4.3.1 and 4.4.5.7. If any item fails to comply with 3.5, 3.6, 3.7.1 and 3.9.7, the item shall be rejected and removed from the lot.

4.3.3.2 Function. A sample shall be selected at random in accordance with Table V. The sample shall be tested in accordance with 4.4.4. If any item fails to comply with 3.8.2, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

Table V

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions and calibration instructions designed or specified by the contractor. The contractor shall obtain approval of such designs, operating instructions and calibration instructions prior to use on the contract from Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T as defined in 6.1.2.

4.3.4.2 Minor characteristics and tests. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Bridge wire circuit resistance. The wire resistance shall be measured with an approved measuring device. A direct current of 10 milliampere (ma) maximum shall be applied when tested to determine compliance with 3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

4.4.2 Insulation resistance. The insulation resistance shall be measured with an approved tester at a potential of 500 ± 50 vdc and current shall not exceed five (5) milliamperes (ma). The potential shall be applied for 40 ± 20 seconds while tested to determine compliance with 3.6.

4.4.3 Leakage.

4.4.3.1 Prefire leakage. The piston motor shall be evacuated to 29 inches of Hg for twenty (20) minutes, and then shall be tested in accordance with MIL-STD-202, Method 112, Test Condition C, Procedure IIIa. The gross leak test shall be performed per Test Condition B using water. Test for compliance with 3.7.1.

4.4.3.2 Post-fire leakage. The piston motor shall be visually observed, (four power magnification is permissible) to determine compliance with 3.7.2.

4.4.4 Activation energy. The piston motor energy and piston movement where applicable shall be measured with an approved measuring device when testing to determine compliance with 3.8.1 and 3.8.2.

4.4.5 Environmental testing (see 3.9).

4.4.5.1 Temperature shock. The piston motor shall be placed into a test chamber that has been stabilized (see 6.4) at the respective temperature specified in 3.9.1. After the test has been completed the piston motor shall be visually examined for evidence of external damage (see 6.5).

4.4.5.2 Mechanical shock. The piston motor shall be placed in a suitable fixture and rigidly mounted on a shock machine. After the shock requirement has been applied in each of three principal axis, the piston motor shall be examined, visually, to determine compliance with 3.9.2.

4.4.5.3 Transportation vibration. The piston motor shall be placed into a temperature chamber and mounted on a fixture capable of being positioned along the three mutually perpendicular axes. The mounted piston motor then shall be mounted on an approved shaker table and subjected to the vibration spectrum at the respective temperatures described in 3.9.3. After the test has been completed, the piston motor shall be visually examined for evidence of external damage (see 6.5).

4.4.5.4 Temperature humidity. The piston motor shall be tested to the requirements in 3.9.4. After the test is completed, the piston motor shall be visually examined for evidence of external damage (see 6.5).

4.4.5.5 High temperature. The piston motor shall be placed into a test chamber and the temperature raised to 160 ± 5°F for 24 hours minimum. The piston motor shall then be returned to room temperature and examined visually to determine compliance with 3.9.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

4.4.5.6 Low temperature. The piston motor shall be placed into a test chamber and the temperature lowered to -65 ± 5°F for 24 hours minimum. The piston motor shall then be returned to room temperature and examined visually to determine compliance with 3.9.6.

4.4.5.7 Radiographic examination. The piston motor shall be x-rayed in accordance with MIL-STD-271 and in two (2) positions 90° apart and perpendicular to the longitudinal axis. The radiographic inspection shall be accomplished by using the film technique. The film shall be visually examined for compliance with 3.9.7. Radiographic records must be arranged to maintain individual piston motor identity.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The piston motor shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Level C. The piston motor shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.2 Packing.

5.2.1 Levels A and C. The piston motor shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 3.9.7 and 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

6.4 Temperature stabilization. The temperature is considered stabilized when the greatest peaks (both highest and lowest) continually observed over 5 minutes min. do not exceed the nominal temperature plus tolerance specified.

6.5 External damage. Characteristics such as obliterated markings, damaged finish exposing base metal, damaged wire insulation, rust and cracks that are detectable by visual examination, shall be considered cause for rejection.

6.6 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-2044 dated 31 March 1972, with Amendment 3, dated 6 July 1973.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. NUOR-A059

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

100 c/c

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No 22-R255

INSTRUCTIONS The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government Fold on lines on reverse side, staple in corner, and send to preparing activity Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3 IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4 REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN SARPA-QA-N-Q
Dover, New Jersey 07801

FOLD

8710

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.