MILITARY SPECIFICATION

TRUCK, FIRE FIGHTING A/S32P-4; AIR TRANSPORTABLE, MULTIPURPOSE

This amendment forms a part of Military Specification MIL-T-83235(USAF) dated 17 November 1969, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.1, line 2: Add "(see 6.5)".

2.1, under SPECIFICATIONS, Federal, delete:

"O-F-555 Foam Liquid, Fire Extinguisher, Mechanical".

under SPECIFICATIONS, Federal, add:

"O-E-915 Extinguisher Fire, Dry-Chemical (Hand Portable)".

under SPECIFICATIONS, Military, delete:

"MIL-E-7589 Extinguisher, Fire Vaporizing, Type D-2, Bromochloromethane Portable (Extinguisher, Fire, Bromochloromethane, Portable, Type D-2)
MIL-F-23905 Fire Extinguishing Agent, Light Water, Liquid Concentrate (6 Percent)
MIL-S-38265 Saw, Circular Blade, Metal-Cutting MXU-346/E, Gasoline-Engine-Driven, Portable".

under SPECIFICATIONS, Military, add:

"MIL-P-23377 Primer Coating; Epoxy-Polyamide, Chemical Solvent Resistant
MIL-E-24385 Fire Extinguishing Agent, Aqueous, Film Forming Foam (AFFF), Liquid Concentrate, Six Percent, For Fresh and Sea Water
MIL-C-83286 Coating, Urethane, Aliphatic Isocyenate, for Aerospace Application".

FSC 4210

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:40Z
Check the source to verify that this is the current version before use.

under STANDARDS, Military, delete:

"MS28741	Hose Assembly, Detachable End Fitting, Medium Pressure
MS33586	Metals, Definition of Dissimilar

under STANDARDS, Military, add:

"MIL-STD-889 Dissimilar Metals".

PAGE 4

2.2, under "United States of American Standards", delete and substitute:

"American National Standards Institute

S1.4	Specification for Sound Level Meters
S1.6	Preferred Frequencies and Band Numbers for Acoustical Measurements
Z24.10	Octave-Band Filter Set for the Analyses of Noise and Other Sounds
Z26.1	Safety Code for Safety Glazing Materials for Glazing Motor Vehicles Operating on Land Highways

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10018.)"

PAGE 5

3.4.2, line 5: Delete "MS33586" and substitute "MIL-STD-889".

PAGE 6

3.5.2b. Add: "Components, for the purpose of this specification, are defined as those parts or functional blocks as required to be set out under the design prediction procedure of MIL-STD-756."

PAGE 8

3.5.3, delete first and second sentence and substitute: "The truck shall be designed and constructed for maintainability in accordance with the design guidelines of MIL-STD-470, paragraph titled, Established Maintainability and shall provide for the following:"

Source: https://assist.dla.mil -- Downloaded: 202640-23T07:40Z
Check the source to verify that this is the current version before use.

PAGE 12

3.5.4.4, line 1: Delete words "front grills, louvers, headlamps,".

PAGE 20

3.6.3, line 5: Delete "O-F-555 and MIL-F-23905." and substitute "MIL-F-24385".

PAGE 24

3.7.7.1: Delete.

PAGE 25

3.7.8.2: Delete and substitute:

"3.7.8.2 Transfer case output shafts. The transfer case drive for the output shafts shall contain features which will compensate for differences in speed between the front and rear axles. The transfer case shall be provided with a torque proportioning differential equipped with operator-controlled differential lockouts."

PAGE 26

3.7.9.1.2: Delete and substitute:

"3.7.9.1.2 Front axle. The front axle shall be equipped with steering drive ends which afford near constant velocity."

PAGE 27

3.7.11.2, line 2: Delete the words "cross-country".

PAGE 28

3.7.12.2, line 2: Delete "of the hand lever operated type" and substitute "provided".

3.7.13, line 3: Delete "three" and substitute "five".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:40Z
Check the source to verify that this is the current version before use.

3.10.5: Delete and substitute:

"3.10.5 Doors. All outside cab and compartment door handles shall consist of a large loop at least 4-1/2 inches long, with adequate depth for operation by personnel wearing artic-type mittens as specified in SAE J925, and the latches shall be protected to prevent entrance of ice and rain into the mechanism. The outside door handles shall be not more than 66 inches above ground level and shall not protrude appreciably beyond the body skin. The inside door handles shall be not less than 27 inches above cab floor level. Weather stripping shall be provided to prevent drafts around the doors. The door latches and hardware shall be of quality design. If piano hinges are used, they shall be of stainless steel. Features shall be furnished which are capable of protecting the doors against winds and fast stops while in the open position."

3.10.6: Delete and substitute:

"3.10.6 Windshield. The windshield shall be of laminated, safety plate glass conforming to MIL-C-3787, Class I. The width of the windshield shall be the maximum consistant with the cab width. If necessary to meet specified winterization requirements, readily removeable transparent panels of a size to fully match the windshield may be provided to direct hot air flow between the panels for defrosting and anti-icing. If glass inner panels are provided, they shall be safety glass."

3.10.7: Delete and substitute:

"3.10.7 Windows. Windows of tempered safety plate glass conforming to ANSI Z26.1 shall be provided in the cab and doors. All windows shall be of such size as to provide maximum practical visibility. Unless otherwise approved by the procuring activity, all windows, except the windshield, shall be double-sliding open type and shall be of double-panel dehumidified design or shall be provided with frost shields for winterization."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:40Z
Check the source to verify that this is the current version before use.

PAGE 34

3.10.11: Delete and substitute:

"3.10.11 Rearview mirrors. An adjustable rearview mirror not less than 90 square inches in area, with spotter mirror mounted integral with the lower portion, shall be mounted on each side of the truck. The mirrors shall be so positioned that the driver can clearly observe personnel, the roadway, and vehicles on either side of the truck."

3.10.14: Delete and substitute:

"3.10.14 Forward view mirrors. A spotter mirror shall be provided on each side of the driver's windshield. The mirrors shall be so installed that the driver can see personnel, equipment, or fires directly in front of the vehicle that otherwise would be observed from sight below the bottom of the windshield."

PAGE 35

3.10.15: Delete.

3.10.16, line 5: Delete "ram" and substitute "ramp".

PAGE 36

3.11.2c: Delete "ammeter" and substitute "voltmeter/battery condition indicator".

PAGE 37

3.11.4d: Delete.

PAGE 38

3.12.2: Delete and substitute:

"3.12.2 Agent system piping. The agent system piping and all components shall withstand a hydrostatic pressure of 350 psi on the suction side of the pumps and 500 psi on the discharge side of the pumps without leaking. All piping sections between valves and other agent system components shall be readily removable without disturbing the components. Seamless tubing and groove-type couplings shall be used to the maximum practical extent. Large pipe sections and pipe sections which could be subjected to excessive movement during operation shall be firmly mounted or braced.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:40Z
Check the source to verify that this is the current version before use.

Sharp bands and changes in cross section shall be avoided. The piping shall be designed and mounted to facilitate drainage. All pipe openings from heated compartments to the outside of the truck shall be protected with grommets or other devices to limit air passage around the pipes. Hose of sufficient size and strength for the application may be used in lieu of metal pipe and tubing where practical."

3.12.2.1: Delete.

3.12.3, line 18: Delete "5 psi" and substitute "1 psi".

PAGE 42

3.12.7.2: Delete and substitute:

"3.12.7.2 Pumper discharge connections. Two 2-1/2-inch NH male discharge connections shall be located on the left (driver's) side of the truck and two on the right side in the same relative position. Each connection shall incorporate a valve of the quarter turn quick closing ball type with the twist to lock in any position. The valves on the right shall be operable from either the right or left side of the truck. The connections shall be no more than 48 inches above the ground. Each connection shall be provided with a chained-on pin or rocker lug cap. All caps shall be brass or chromium plated brass. Piping to the connections shall be sized corresponding to the size of the connections without use of reducers."

PAGE 45

3.12.9.4.2: Delete and substitute:

"3.12.9.4.2 Foam discharge. The turret nozzles shall discharge foam with at least eight expansion and having a 25-percent drainage time above 4-1/2 minutes when measured as specified in NFPA Standard 412 using foam concentrate in accordance with MIL-F-24385. The turret nozzles shall be capable of this performance at any pattern dispersal when the turret is elevated for maximum range. The spread of the dispersed patterns of the turret nozzles and the minimum distance from the tip of the nozzles to the far side of the patterns when the turrets are elevated for maximum range and where the application rate is at least 0.20 gpm per square foot shall be as specified below:

Turret	Straight Stream Distance (Feet)	Dispersed Pattern Distance (Feet)	Dispersed Pattern Width (Feet)
Bumper	125	60	25
Roof (both rates)	160	80	30."

Source: https://assist.dla.mil -- Downloaded: 202610-23T07:40Z
Check the source to verify that this is the current version before use.

3.12.10: Delete and substitute:

"3.12.10 Foam handline. A combination water foam agent handline shall be provided. The handline shall be capable of selectively discharging either foam at a rate of at least 100 gpm (water rate) or water at a rate of 50 gpm. The handline shall incorporate a type II nozzle conforming to MIL-N-26206 and 150 feet of 1-1/4 inch ID hose. The hose conforming to MIL-H-4497 shall be in 50-foot sections joined by reusable couplings conforming to MIL-C-7580. The nozzle shall be capable of producing foam of at least eight expansion and having a 25-percent drainage time above 4-1/2 minutes when measured as specified in NFPA Standard 412 using foam concentrate in accordance with MIL-F-24385. The nozzle attached to the handline shall be stored in a compartment at the right front corner of the truck and shall be capable of being withdrawn by an operator standing at the side of the truck. Also included shall be a bayonet nozzle so fabricated that it can be used in conjunction with the assembly of the handline nozzle. The bayonet nozzle shall be mounted in a quick-release bracket either in the handline nozzle compartment or in a separate protected location adjacent to the handline nozzle compartment. The bayonet nozzle shall connect into the bayonet joint of the handline nozzle assembly. Quick attach-detach provisions shall be incorporated for installing the bayonet nozzle."

PAGE 46

3.12.10.1: Delete and substitute:

"3.12.10.1 Hose reel. The handline hose shall be mounted on a 150-foot capacity reel which shall be located in a compartment which provides for handline hose withdrawal to the front of the truck. Hose compartment shall permit complete hose removal and rewind with hose charged or uncharged. Horizontal and vertical rollers shall be provided to reduce chafing and friction of the hose or catching of the couplings when the hose is being withdrawn to the front or either side. Provisions shall be incorporated to permit flushing of the handline hose and reel compartment. The design of the hose reel assembly shall be such as to prevent dragging, snarling, and overrunning of the reel during unreeling of the hose and agent discharge operation. Manual means for rewinding the hose which will include features to eliminate rewind motor drag shall be provided. Electrical or pneumatic means for rewinding the hose at an average rate of 85 fpm shall be provided. The rewind control switch shall be positioned to allow one person to actuate the switch and feed the hose on the reel. The switch shall be protected from hose interference. Controls for operation of the handline valve shall be

Source: https://assist.dla.mil -- Downloaded: 20260-23T07:40Z
Check the source to verify that this is the current version before use.

placed in or adjacent to the handline nozzle compartment. It shall not be necessary to clean the hose or nozzle after use at the scene of an emergency in order to accomplish rewind operations and storage. An air purge system, with check valves to prevent water from entering the truck air system, shall be provided to purge the hose to prevent freezing under low temperature conditions. The air purge system control shall be located in the handline nozzle compartment."

PAGE 48

3.12.14 j: Delete.

3.12.14 k: Delete.

3.12.14 l: Delete.

3.13 d: Delete "MIL-E-7589" and substitute "O-E-915, Type I, Size 30".

PAGE 49

3.13 i: Delete and substitute:

"i. One circular blade metal cutting saw stored in storage compartment."

3.13 j, line 1: Delete "Class W" and substitute "Class 2".

3.13 l, line 1: Delete "Class E" and substitute "Class 3".

PAGE 55

3.16, line 1: Delete "When specified (see 6.2).".

PAGE 57

3.20, line 1: Delete "28,200 pounds" and substitute "32,000 pounds".

3.21: Delete and substitute:

"3.21 Finishes and protective coatings. The truck and all components and equipment shall be cleaned, treated, and painted in accordance with MIL-STD-808. Paint shall be aliphatic polyurethane in accordance with MIL-C-83286 and shall be applied over epoxy primer in accordance with MIL-P-23377. Paint colors shall conform to FED-STD-595. Cab and body exterior surfaces shall be lime-yellow, color 13670. Cab and other compartment interior surfaces shall be green, color 24300."

Source: https://assist.dla.mil -- Downloaded: 202610-23T07:40Z
Check the source to verify that this is the current version before use.

PAGE 59

4.1: Delete and substitute:

"4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

4.2.2: Delete "Acceptance tests" and substitute "Quality conformance tests".

PAGE 62

4.5: Delete "Acceptance tests" and substitute "Quality conformance tests".

PAGE 63

4.6.1.3, line 2: Delete "5 psig" and substitute "1 psig".

PAGE 65

4.6.1.14: Delete.

4.6.1.15, line 1, title: Delete "MIL-F-23905" and substitute "MIL-F-24385".

line 6: Delete "MIL-F-23905" and substitute "MIL-F-24385".

line 12: Delete "5 expansion" and substitute "8 expansion".

PAGE 66

4.6.1.19: Delete and substitute:

"4.6.1.19 Agent tank exhaustion. The capability to discharge 90 percent of the water tank capacity at a rate of 1200 gpm when the truck is on level ground shall be demonstrated. This capability shall also be demonstrated when the truck is headed up, down, right, or left on a 20-percent slope."

Source: https://assist.dla.mil -- Downloaded: 202610-23T07:40Z
Check the source to verify that this is the currentversion before use.

PAGE 69

.1.20.4.2, line 7: Delete "USA Standard" and substitute "ANSI".

PAGE 74

6.2.18.1: Add "During four traversals, the differential lockouts shall engaged."

PAGE 75

2 d: Delete.

PAGE 76

.3.2, line 2: Delete "L Corpos" and substitute "Corps".

PAGE 77

.5: Add:

"6.5 This specification also covers the basic requirements for the A/S32P-4A Truck, Fire Fighting. The A/S32P-4A incorporates a transfer case provided with a torque proportioning differential equipped with operator controlled differential lockouts; a manually operated roof turret with an installed non-aspirating, constant flow, variable stream nozzle; a remote hydraulically controlled bumper turret with an installed non-aspirating, constant flow, variable stream nozzle; a non-aspirating, constant flow, variable stream handline nozzle, and a final finish exterior color or yellow gloss number 13538 in accordance with FED-STD-595. The A/S32P-4 and A/S32P-4A are identical in all other respects. For additional information concerning the A/S32P-4A contact: Commander, Naval Facilities Engineering Command, Attn: Code 103B, 200 Stovall Street, Alexandria, VA 22332."

ustodian:
Air Force - 11

eview activity:
Air Force - 99

Preparing activity:
Air Force - 11

Project No. 4210-F130

Source: https://assist.dla.mil -- Downloaded: 202610-23T07:40Z
Check the source to verify that this is the current version before use.