INCH-POUND
MIL-C-62135A(AT)
AMENDMENT 2
4 April 1989
SUPERSEDING
AMENDMENT 1
29 November 1982

MILITARY SPECIFICATION

CRANE: MATERIAL HANDLING (BASIC AND REBUILD)

This amendment forms a part of Military Specification MIL-C-62135A(AT), dated 21 May 1976, and is approved for use by U.S. Army Tank-automotive and Armaments Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

*1.1, delete and substitute:

"1.1 Scope. This specification covers the basic and rebuilt models of a revolving type material handling crane, having a lifting capacity of not less than 2500 pounds at its maximum reach."

Beneficial comments paragraph, line 4, after the word "Command" insert "ATTN: AMSTA-TR-E/BLUE, Warren, MI 48397-5000".

PAGE 2

2.1, under "DRAWING", line 1, delete "Receptable" and substitute "Receptacle".

*Add new paragraph 2.2 as follows:

"2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets, MS standards or drawings), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained."


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:20Z
Check the source to verify that this is the current version before use.

PAGE 3

*Add new paragraph 3.2.1 as follows:

"3.2.1 Recycled, virgin and reclaimed materials. There are no requirements for the exclusive use of virgin materials. The use of recycled or reclaimed (recovered) materials is acceptable provided that all other requirements of this specification are met (see 6.5.1)."

PAGE 4

*3.3.1, line 7, after "operations.", add sentence as follows:

"The two part line provided shall be corrosion resistant cable conforming to type I, class 2, 6x19 of RR-W-410, and have a rated breaking strength of not less than 5,000 pounds."

PAGE 6

*3.9, delete in its entirety and substitute:

"3.9 Installation instructions and operator's manual. The contractor's commercial operator's manual with a breakdown of his commercial part numbers and installation instruction shall be packaged in a waterproof envelope, and placed in the location specified by the contracting officer (see 6.2 and 6.9)."

PAGE 7

*Add new paragraph 4.1.3 as follows:

"4.1.3 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

PAGE 10

*4.4.1.4, line 1, delete "(see 6.8)".



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:20Z
Check the source to verify that this is the current version before use.

*4.4.1.5, line 1, delete "(see 6.8)".

*TABLE I, defect number 202, delete "Instructions: Improper, Not Legible" and substitute "Installation instructions and operator's manual: Improper location, improperly packaged".

PAGE 14

*4.9, delete in its entirety:

*5., delete in its entirety and add:

"5. PACKAGING

5.1 Preservation, packaging, packing, and marking. Preservation, packaging, packing, and marking for the desired level shall be in accordance with the applicable packaging requirements specified by the contracting authority (see 6.2)."

*6.2, delete item (c) and add new items (c) and (d) as follows:

"(c) Location of installation instructions and operator's manual.
(d) Selection of applicable level and packaging requirements (see 5.1)."

PAGE 15

*6.4, delete and substitute:

"6.4 Crane missions. A crane mission is the loading and unloading of an 8 ton palletized cargo from an M877 cargo truck every second mission of the truck. A truck mission and life operational profile are:

a. One M877 truck mission shall consist of 100 miles of operation under the following conditions of load, speed, distance, terrain and environment with special tractor and cargo carrying functions described.

| Terrain | Distance | Operating speed range MPH |
|---|---|---|
| Hard surface | 20 miles | 0 - 30 |
| Secondary | 40 miles | 0 - 30 |
| Level cross country | 16 miles | 0 - 30 |
| Level cross country (mud) 1/ | 4 miles | 0 - 10 |
| Hilly cross country 1/ | 20 miles | 0 - 15 |
| Swimming 1/ | Traverse water barrier | 5 minute operation |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:20Z
Check the source to verify that this is the current version before use.

| Terrain | Distance | Operating speed range MPH |
|---|---|---|
| 60% grades | 1/10 of 1% of hilly cross country operation w/o towed load | |
| 30% side slopes | 1/10 of 1% of hilly cross country operation w/o towed load | |

1/ 4-Wheel drive: 100% mud and swim, cross country as required, all other operation is in 2-Wheel drive.

CLIMATIC EXTREMES

| | |
|---|---|
| Temperature: | -25°F to 125°F ambient. |
| Altitude: | 500 to 5000 feet. |

TRACTOR FUNCTIONS

| | |
|---|---|
| Idle: | 30 minutes. |
| Starts: | One cold, one hot at two minutes, one hot at 15 minutes after shutdown (cold means coolant and oil at ambient, hot at maximum obtained). |
| Reverse: | 10 operations at 130 feet each. |
| Front winch: | Once each 10 missions: One overload attempt (110% of rated capacity) followed by recovery of a load at 90% capacity. |

CARGO CARRYING FUNCTION

| | |
|---|---|
| Operation: | 50% of time at 8 ton payload, 25% of time at 4 ton payload, and 25% at no load, 10% with towed load. |
| MHE Crane: | Load and unload 8 ton palletized cargo every second mission. |

b. An M877 truck typical life operational profile is:
   1. Renewal life - 25 000 miles or 1250 hours.
   2. Average speed - 20.0 miles per hour.
   3. Total missions - 250.
   4. Mission - 100 miles in 5 hours.”



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:20Z
Check the source to verify that this is the current version before use.

*Add new paragraph 6.5 as follows:

"6.5 Definitions.

6.5.1 Recovered materials. "Recovered materials" means materials that have been collected or recovered from solid waste (see 6.5.2).

6.5.2 Solid waste. "Solid waste" means (a) any garbage, refuse, or sludge from a waste treatment plant, water supply treatment plant, or air pollution control facility; and (b) other discarded material, including solid, liquid, semisolid, or contained gaseous material resulting from industrial, commercial, mining, and agricultural operations, and from community activities. It does not include solid or dissolved material in domestic sewage, or solid or dissolved material in irrigation return flows or industrial discharges which are point sources subject to permits under section 402 of the Clean Water Act, (33 U.S.C. 1342 et seq.), or source, special nuclear, or byproduct material as defined by the Atomic Energy Act of 1954 (42 U.S.C. 2011 et seq.) (Source: Federal Acquisition Regulations, section 23.402)."

PAGE 16

*6.8, line 1, delete "(2) paragraph 6.8 "Definitions of Recurring Major and Minor Defects." and substitute "6.8 Deficiency sheet."

*Add new paragraph 6.9 as follows:

"6.9 Installation instructions and operator's manual. The contracting officer shall specify in the contract the location on the crane for storing the instructions and manual, and the quantity and office symbols of other organizations to be furnished this material (see 3.9)."

Add new paragraph 6.10 as follows:

"6.10 Subject term (key word) listing.

Crane assembly
Data plates
Radio Interference Suppression
Safety features
Treatment and painting"

The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:20Z
Check the source to verify that this is the current version before use.

inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AT

Preparing Activity:
Army - AT

(Project 3950-A007)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:20Z
Check the source to verify that this is the current version before use.