ADMINISTRATIVE
NOTICE

INCH-POUND
MIL-PRF-55365H
NOTICE 2
9 January 2012
SUPERSEDING
NOTICE 1
18 February 2011

PERFORMANCE SPECIFICATION

CAPACITOR, FIXED, ELECTROLYTIC (TANTALUM), CHIP, ESTABLISHED RELIABILITY,
NONESTABLISHED RELIABILITY, AND HIGH RELIABILITY,
GENERAL SPECIFICATION FOR

MIL-PRF-55365H that was released on 4 February 2011, should have the following note added to the top of the front page.

The requirements to comply with the change in the surge current (optional) paragraph 4.7.18 must be completed by 1 December 2012. Before then, use of the surge current test method as outlined in paragraph 4.7.18 of MIL-PRF-55365G is authorized.

This delayed implementation is necessary for manufacturers to make changes to their equipment and test procedures.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
Army - CR

Agent:
DLA - CC

Review activities:
Army - AR, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99
NASA - NA

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.daps.dla.mil .

AMSC N/A FSC 5910
DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.