INCH-POUND


MIL-DTL-41819/57D
13 January 2020
SUPERSEDING
MIL-DTL-41819/57C
7 June 2018

DETAIL SPECIFICATION SHEET


RIBBON ATTACHMENT, LETTER "R" AND LETTER R WITH WREATH

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-R-41819.



"R" DEVICE



"R" DEVICE WITH WREATH

DASH NO.

-1: Bronze, Regular Size
-2: Bronze, With Wreath, Regular Size
-3: Silver, Regular Size
-4: Silver, With Wreath Regular Size
-5: Gold, Regular Size
-6: Gold, With Wreath, Regular Size
-7: Bronze, Miniature Size
-8: Bronze, With Wreath, Miniature Size
-9: Silver, Miniature Size
-10: Silver, With Wreath, Miniature Size
-11: Gold, Miniature Size
-12: Gold, With Wreath, Miniature Size

MATERIAL: Red Brass 85/15 (UNS Alloy No.C-230)

FINISH:

-1,-2, -7 and -8: Brass, Oxidized, Buffed Relieved and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 4.

-3, -4, -9 and -10: Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

-5, -6, -11 and -12: 24K Gold Plated. Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:03Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
HEIGHT:
-1, -3 and -5: 1/4 inch (REF)
-2, -4 and -6: 5/16 inch (REF)
-7, -9 and -11: 1/8 inch (REF)
-8, -10 and -12: 5/32 inch (REF)
WIDTH:
-1, -3 and -5: 1/4 inch (REF)
-2, -4 and -6: 5/16 inch (REF)
-7, -9 and -11: 1/8 inch (REF)
-8, -10 and -12: 5/32 inch (REF)
THICKNESS (At thickest point):
-1, -3 and -5: 0.043 inch $\pm$ .005 inch
-2, -4 and -6: 0.043 inch $\pm$ .005 inch
-7, -9 and -11: 0.031 inch $\pm$ .005 inch
-8, -10 and -12: 0.031 inch $\pm$ .005 inch

ATTACHING DEVICE: The attaching device shall be a staple prong, as specified in MIL-R- 41819. The staple prong for the “R” shall be place vertically and centered on along of the “R”. The “R” with the wreath the staple prong will be centered at the bottom of the wreath.

PIERCING: The R and R with wreath (shaded) shall be pierced on both regular size and miniature size R’s.

NOTE:
The term (REF) refers to the measurements taken from the Government furnished hub or die.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - IH
Navy - MC
Air Force - 11

Preparing activity:
Army - IH

Review activities:
Navy - CG1
DLA - CT

(Project No. 8455-2020-106)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:03Z
Check the source to verify that this is the current version before use.