INCH-POUND

MIL-DTL-41819/59
27 July 2016

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, EXPEDITIONARY SERVICE DEVICE, USPHS

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-R-41819.

MATERIAL: Red Brass 85/15 (UNS Alloy No.C-230) or Gilding Metal 95/5 (UNS Alloy No. C-210)

FINISH: 24K Gold Plated, Mirror like Polished and shall match The Institute of Heraldry Metal Finish Chip Number 6.

DIMENSIONS:
HEIGHT: 5/16 inch (REF)
WIDTH: 5/16 inch (REF)
THICKNESS: 0.050 inch $\pm$ .010 inch

ATTACHING DEVICE: The attaching device must be a staple type prong, as specified in MIL-R-41819. The prong will be located on the horizontal center line of the ribbon attachment.

NOTE:
The term (REF) refers to the measurements taken from the Government furnished hub or die.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:04Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2016-687)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:04Z
Check the source to verify that this is the current version before use.