NOT MEASUREMENT SENSITIVE

MIL-DTL-41819/62A
20 December 2021
SUPERSEDING
MIL-DTL-41819/62
14 February 2017

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, SECRETARY'S DISTINGUISHED HONOR AWARD, DEPARTMENT OF STATE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-R-41819.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C230)

FINISH (Obverse and Reverse): 24K Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.

DIMENSIONS:
DIAMETER: 5/16 inch (REF)
THICKNESS: 0.062 ± 0.010 inch

ATTACHING DEVICE: The prong shall be a staple type prong center on the reverse.

EPOXY: Epoxy resin shall be applied to the Ribbon Attachment as indicated above, and shall match TIOH Hard Enamel Color Chip Numbers listed below. Hard cloisonné enamel may be

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:05Z
Check the source to verify that this is the current version before use.

used in lieu of epoxy. If hard cloisonné enamel is used, the required base material shall be Gilding Metal 95/5 (UNS Alloy C-210).

TIOH HARD ENAMEL COLOR CHIP NUMBER	LOCATION
Blue #20	Outer ring (Shaded)

NOTE:
The term (REF) refers to the measurements taken from the Government furnished hub or die.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2022-045)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:05Z
Check the source to verify that this is the current version before use.