NOT MEASUREMENT SENSITIVE


MIL-DTL-41819/65
13 January 2025

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, TAEGUK

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-R-41819 and the request from Department of Justice.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Stoned Epoxy, Nickel Plated, Polished Highlights, and shall match The Institute of Heraldry Metal Finish Chip Number 16.

DIMENSIONS:
DIAMETER: 9/32-inch (REF)
THICKNESS (at rim): 0.055 ± 0.005

ATTACHING DEVICE: Attaching device shall be a staple-type prong centered on the reverse of the ribbon attachment.

EPOXY: Epoxy resin shall be stoned and applied to the Ribbon Attachment as shown and shall match TIOH Hard Enamel Color Chip Numbers listed below.

Enamel Chip Number	Location
Red #1	Top
Blue #18	Bottom

NOTE:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:05Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2025-043)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:05Z
Check the source to verify that this is the current version before use.