INCH POUND
MIL-DTL-41835E
May 8, 2020
SUPERSEDING
MIL-K-41835D
25 MAR 1988

DETAILED SPECIFICATION
KIT BAG, FLYER'S

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type and size flyer's kit bag made of nylon duck with slide fastener closure.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 or 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 or 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the solicitation or contract.

AMERICAN STANDARD OF TESTING AND MATERIALS

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8460

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:07Z
Check the source to verify that this is the current version before use.

ASTM-D1974/D1974M	Fiberboard Boxes, Methods of Closing, Sealing, and Reinforcing, Standard Practice for
ASTM-D5118/D5118M	Boxes, Fiberboard Shipping, Fabrication of

Non government standards can be found at https://www.astm.org/.

NATIONAL AEROSPACE STANDARDS

NASM27980 - Fasteners, Snap, Style 2 (Regular Wire Spring Clamp Type)

Non government standards can be found at https://www.aia-aerospace.org/.

COMMERCIAL ITEM DESCRIPTIONS

A-A-1451	-	Twine, Fibrous
A-A-203	-	Paper, Kraft, Untreated
A-A-55634	-	Fasteners, Slide, Interlocking
A-A-59963	-	Thread, Polyester

Commercial item descriptions can be found at: https://quicksearch.dla.mil.

DoD SPECIFICATIONS

MIL-DTL-10884	-	Fasteners, Snap
MIL-DTL-32439	-	CLOTH, DUCK, TEXTURED NYLON

DoD specifications can be found at: https://quicksearch.dla.mil.

MILITARY STANDARDS

MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads

Military standards can be found at: https://quicksearch.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:07Z
Check the source to verify that this is the current version before use.

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues should be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

11-1-302	-	Kit Bag, Flyer's (Assembly, Details and Sections)
11-1-303	-	Kit Bag, Flyer's (Details and Sections)

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.3.2. Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AMERICAN SOCIETY FOR QUALITY (ASQ)

ASQ/ANSI Z1.4 - Sampling Procedures and Tables for Inspection by Attributes

(Copies of specifications, standards, and handbooks required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification should take precedence. Nothing in this specification, however, should supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.4).

3.2 Materials. Unless otherwise specified herein, all materials shall be as specified on Drawings 11-1-302 and 11-1-303 (see 6.5).

3.2.1. Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.2).

3.2.1 Thread. The thread shall be nylon as specified on the drawings, or shall be polyester conforming to types I, II, or III, class 1, subclass A, size FF of A-A-59963. The color for the polyester thread shall be Camouflage Green color chip 3933.

3.2.2 Fastener, slide, interlocking. The slide fastener shall conform to type I, style 18, size MHS nylon or polyester continuous monofilament element fastener (spiral or serpentine) in accordance with A-A-55634 and the requirements in 3.2.2.1, 3.2.2.2, 3.2.2.3, and 3.2.2.4. As an alternate to pre-

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:07Z
Check the source to verify that this is the current version before use.

assembled slide fastener, the use of continuous chain method in accordance with 3.4.11.1.1.1 of A-A-55634 is allowed.

3.2.2.1 Color. The color of the element, element sewing thread, slider, stops, tab pull, and thongs shall match the Camouflage Green 3933 color chip. As alternate, the stops may be black.

3.2.2.2 Fastener length. The fastener length shall be such as to provide a smooth and secure closure and shall meet the requirements specified in Drawing 11-1-303.

3.2.2.3 Fastener slider and stirrup pulls. The fastener shall have multiple (throat to throat) sliders with long pulls. The pulls shall have a hole large enough to accommodate the thong. The color for the fastener slider and stirrup pulls shall be Camouflage Green color chip 3933.

3.2.2.3.1 Slider identification. For purpose of aiding in end item repair situations, the slider shall be identified with a symbol or marking as to identify the fastener manufacturer.

3.2.2.4 Slide fastener tape. The slide fastener tape shall be 3/4 inch wide, dyed camouflage green 483 to match the standard sample and shall be water repellent treated. The shade imparted by the treatment will be considered acceptable. The dyed tape shall show fastness to weathering equal to or better than the standard sample (see 6.3). When no standard sample is available, the dyed tape shall show good fastness to weathering.

3.2.3 Fasteners, snap. The snap fasteners shall conform to style 2, MS 27980, Part No. MS 27980-1B button, MS 27980-6B socket, MS 27980-7B stud, and MS 27980-8B eyelet, and shall have finish 2 in accordance with MIL-DTL-10884.

3.3 Construction. The construction shall conform to the documents and drawings listed in section 2 and as specified herein. Dimensions shown on the drawings for body pieces A and B, carrying strap, and the flap, represent dimensions after sub-assembly, and are not to be construed as dimensions of cut parts.

3.3.1 Type 301 stitching. Thread breaks and skips in stitching shall be overstitched not less than 1 inch. Run-offs shall be restitched to conform to the stitch pattern specified on the drawings. Exclusive of automatic machinery, ends of stitching shall be backstitched a minimum of $^{1}/_{2}$ inch, except where turned under in a hem or held down by other stitching. Thread tension shall be maintained so that there will be no loose stitching and the lock will be embedded in the materials sewed. All thread ends shall be trimmed.

3.3.1.1 Stitching, automatic machinery. Stitching patterns produced by automatic machines may be utilized in lieu of those specified, providing seam strength efficiency and function are equal to, or better than, the specified pattern, and upon approval by the contracting activity.

3.3.1.2 Thread ends. All thread ends shall be trimmed even with the material to a maximum length of $^{1}/_{4}$ inch.

3.3.2 Setting of snap fasteners. When snap fasteners are installed manually holes shall be pre-punched to receive the snap fasteners. The manual hole shall be smaller than the outside diameter of the fastener tube so that the tube must be forced through the hole. Pre-punched holes shall not be accomplished by using the stud or eyelet tubes. When using automatic equipment, holes need not be

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:07Z
Check the source to verify that this is the current version before use.

pre-punched. Fastener components shall be securely clinched without cutting the material. The roll of the clinched eyelet of the assembled fastener components shall not possess more than two scores (splits).

3.4 Marking. Identification marking shall be as specified on drawing 11-1-302.

3.5 Workmanship. The kit bag shall conform to the quality of product established by this document and the occurrence of defects shall not exceed the specified acceptable quality levels.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2)
b. Quality conformance inspection (see 4.3)

4.2 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3. The presence of any defect shall be cause for rejection of the first article.

4.3 Conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with ASQ/ANSI Z1.4.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.3.2 In-process inspection. Inspection shall be made at any point or during any phase of the manufacturing process to determine whether cut lengths, out parts, marking for location of components, and location of assembled component parts are in accordance with specified requirements. In addition, inspection shall be made to determine that pre-punched or predrilled holes for receiving snap fasteners are smaller than the outside diameter of the hardware tube or barrel. When nonconformance is noted, correction shall be made to the items affected and to the operation.

4.3.3 End item visual examination. The end item shall be examined for the defects listed in table I. The lot size shall be expressed in units of kit hags. The sample unit shall be one kit bag.

4.3.4 End item dimensional examination. The end item shall be examined for conformance to the dimensions specified on the drawings. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of bags. The sample unit shall be one bag.

TABLE I
End item visual examination

Examine	**Defect**	**Classification**	
		Major	**Minor**
Fabric:			

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:07Z
Check the source to verify that this is the current version before use.

Duck	Any hole (except exposed drill holes), cut, tear, smash, open place, or broken or missing yarn	100	
	Two or more exposed drill holes		200
	Shade bar, or fine or coarse filling bar		201
Webbing and tape	Not firmly and tightly woven; edge frayed or scalloped	101	
	Exposed end of lug tape not dipped in wax as required		202
Hardware	Broken or malformed; protective finish omitted; corroded area; burr or sharp edge which may cause injury in handling	102	
Seams and stitching:			
Open seam	More than $^1/_2$ inch (except box stitching)	103	
	$^1/_2$ inch or less (except box stitching)		203
	Any open seam on box stitching 1/		204
Raw edge	More than $^1/_2$ inch when securely caught in stitching 2/		205
Seam and stitch types	Wrong seam or stitch type	104	
Stitch tension	Loose, resulting in a loosely exposed top or bobbin thread; tight resulting in excessive tightness of fabric on seam		206
Stitches per inch	Two or more stitches less than minimum specified	105	
	One stitch less than minimum specified		207
	One or more stitches in excess of maximum specified 3/		208
Stitching margin; gage on double needle stitching	Not as specified, affecting serviceability or appearance		209
Stitching end	Backstitched less than $^1/_2$ inch (except where end is turned under in a hem or held down by other stitching)		210
Thread break, skip, or run-off	Overstitched less than 1 inch 4/		211
Box stitching	Two or more rows of stitching omitted	106	
	One row of stitching omitted		212
Components and assembly	Any required component or operation omitted or not as specified	107	
	Needle chew	108	
	Mend, darn, or patch	109	
	One or more rows of stitching omitted (except box stitching)	110	
Binding	Improperly or loosely applied showing raw edge of fabric	111	
	End of binding not finished as specified or overlapped less than $^3/_8$ inch		213

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:07Z
Check the source to verify that this is the current version before use.

Handles	Edges of grip section overlapped; edges not folded or not stitched as indicated on drawing		214
Carrying strap	End of carrying strap not finished as specified		215
Reinforcement "A"	Misplaced or not properly attached, failing to serve intended purpose	112	
Marking identification	Omitted, illegible, incorrect, misplaced, or size characters not as specified		216
	Marking not specified color		217
Snap fasteners	Any fastener not functioning properly (i.e., fails to snap closed, provide a secure closure, or open freely)	113	
	Improper or insecure clinching	114	
	Clinched excessively tight, cutting adjacent material	115	
	Clinched loosely, permitting components to rotate freely in the hole of the material	116	
	Incorrect style	117	
	Roll of clinched eyelet fastener assembly contains more than two scores (splits)		218
Slide fastener	Not specified type or size	118	
	Does not provide a smooth and secure closure full length of bag opening	119	
	Slider jams or fails to interlock chain scoops	120	
	Any portion of fastener broken, bent, missing, or not aligned making fastener unusable	121	
	Fastener tape not $^{3}/_{4}$ inch wide	122	
	Sliders not assembled throat to throat	123	
	Single slider provided instead of two; not furnished with two stirrup pulls, or stirrup pulls not made out of wire	124	
	Thong omitted	125	
	Thong not secured to stirrup pulls as specified		219
	Chain not plastic or not of the configuration specified	126	
Cleanness	Grease, oil, or ink stains clearly noticeable; thread ends not trimmed as specified		220

1/ Seam shall be classified as open when one or more stitches joining a seam are broken or when two or more continuous skipped or run-off stitches occur. On double stitched seams, a seam shall be classified as open when either one or both sides of the seam are open.

2/ A raw edge not securely caught in stitching shall be classified as an open seam.

3/ Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy places or heavy seams, or in turning corners shall be classified as follows:

(a) Within the major defect classification - Minor defect

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:07Z
Check the source to verify that this is the current version before use.

(b) Within the minor defect classification - No defect

4/A thread break, skip, or run-off not overstitched shall be classified as an open seam.

5. PACKAGING

5.1. Packaging examination. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2.). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

6.1 Intended use. The flyer's kit bag is designed primarily to be used for airdropping, recovering, carrying and storing personnel type parachutes and miscellaneous equipment.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.3, and 6.4).
c. Stock number.
d. Selection of the applicable levels of preservation and packing (see 5.1).

6.3 Standard sample. For access to samples of the cotton duck, webbing, tape, and nylon thread, address the contracting activity issuing the invitation for bids via: https://www.dla.mil/TroopSupport/ClothingandTextiles/SpecRequest.aspx.

6.4 First article. When a first article is required, it will be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.6 Subject term (key word) listing.

Airdrop equipment

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:07Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:
Army – GL
Navy – AS

Air Force - 99
DLA – CT

Review activities:
Air Force – 11
Navy – MC

Preparing activity:
DLA – CT
Project number
8460-2019-001

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:07Z
Check the source to verify that this is the current version before use.