MIL-C-23333B(AS)
4 February 1969
Superseding
MIL-C-23333A(AS)
27 October 1964

MILITARY SPECIFICATION

CARTRIDGE, IMPULSE, MARK 38 MOD 0

This specification has been approved by the Naval Air Systems Command, Department of the Navy.

1. SCOPE

1.1 This document governs the manufacture, assembly and preparation for delivery of the MARK 38 MOD 0 impulse cartridge and the methods of inspection and tests upon which product acceptance will be based.

2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards, drawings, and publications, of the issue in effect on date of invitation for bids, form a part of this document to the extent specified herein.

SPECIFICATIONS

Military

MIL-P-46610	Primers, Percussion, Styphnate and Chlorate Types, for Small Arms Ammunition
MIL-P-116	Preservation, Methods of
MIL-D-21625	Design and Evaluation of Cartridges for Cartridge Actuated Devices

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-414	Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-129	Marking for Shipment and Storage

DRAWINGS AND ASSOCIATED LISTS

Naval Air Systems Command (Code Ident No. 30003)

DL 2838270	Test Set for Cartridge, Impulse, MARK 38 MOD 0
LD 419709	Cartridge, Impulse, MARK 38 MOD 0 (Formerly Code Ident No. 10001)
LD 537897	Container, Inner, for Cartridge, Impulse, MARK 38 Type (Formerly Code Ident No. 10001)
LD 537898	Container, Outer, for Cartridge, Impulse, MARK 38 Type (Formerly Code Ident No. 10001)
2164486	Cartridge, Impulse, MARK 38 MOD 0, Assembly (Formerly Code Ident No. 10001)

Ordnance Corps of the Army (Code Ident No. 19200)

B-7645332	Primer (120M)

PUBLICATIONS

BUSANDA Instruction 4030.17	Preservation, Packaging, Packing and Marking; Navy Policy for

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.

Bureau of Naval Weapons

OP 5	Ammunition Ashore (This publication is not furnished to bidders and contractors by the procuring activity. Contractors should contact the Government Inspector for use of the publication)
WR-43	Preparation of Quality Assurance Provisions

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 71-78	Transportation, Interstate Commerce Commission, Explosives and Other Dangerous Articles

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402. Orders for the above publication should request the latest edition and supplements thereto.)

3. REQUIREMENTS

3.1 General.

3.1.1 The MARK 38 MOD 0 impulse cartridge covered by this specification shall be manufactured in accordance with LD 419709 and all documents listed thereon.

3.2 Material. All materials used in the manufacture of the cartridges shall conform strictly with the specifications referred to on the respective Naval Air Systems Command drawings unless specific

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.

approval in writing covering a departure therefrom has been obtained from the Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.2.1 Preproduction sample. When specified by the procuring activity, a preproduction sample of 94 MARK 38 MOD 0 impulse cartridges shall be manufactured using the same methods and procedures proposed for the production lot. The sample shall be tested as specified in 4.3.2 and is for the purpose of determining that the contractor, prior to starting production, is capable of producing items which comply with the technical requirements of the contract.

3.3 Primary components. For the purposes of this specification, the primer and the main propellant charge are defined as primary components. See 4.3.3.

3.4 Primer. The 120M primers shall have been manufactured within the preceding 12 months; loaded with Olin Industries primer mixture No. 257W; and shall be in accordance with Drawing B-7645332 and MIL-P-46610, Class 1. See 4.7.1.

3.4.1 X-ray. Primers shall be free of the following defects when examined by X-ray in accordance with 4.7.2: missing or abnormally thin charge; charge broken, cracked or porous; cracked or off-center anvil, or other misplaced or deformed inert parts; anvil abnormally close to primer cup dome; and all other observable defects in assembly.

3.5 Propellant and booster charges.

3.5.1 Quantity. All propellant and booster charges shall be as specified on Drawing 2164486. Charges shall be determined by weight rather than by volume measurement.

3.5.2 Smokeless powder. Do not subject the smokeless powder to unnecessary handling or exposure to the atmosphere. The handling and loading of smokeless powder exposed to the atmosphere shall be performed only under conditions that do not permit the relative humidity to exceed 75 percent.

3.5.2.1 Smokeless powder condition. The smokeless powder utilized shall exhibit no evidence of decomposition. See 4.7.3.

3.6 Change of propellant lot. Whenever a change occurs in the propellant lot, validity of the charge determination shall be verified by performing the test prescribed in 4.10.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.

3.7 Cartridge inspection.

3.7.1 Visual inspection. Cartridges shall be free of the following visible defects: dents, deep scratches, split or cracked lip in the crimped area, chipping or flaking of the anodized finish, burrs or sharp edges (particularly on the under side of the shoulder); and all other defects which could conceivably prevent entry into the firing chamber, or affect stability or resistance to moisture. See 4.7.4.

3.7.2 Leakage. Cartridge leakage rate shall not exceed 10^{-5} cc of air or gas per second when tested in accordance with 4.7.5.

3.7.3 X-ray. All cartridges shall pass the X-ray examination of 4.7.6.

3.8 Ballistic requirements. Cartridges from each production lot, selected in accordance with 4.7.7, shall meet the requirements listed below when subjected to the test prescribed in 4.7.7.

3.8.1 Velocity. The lower (L) and upper (U) specification limits for velocity shall be 69 and 125 feet per second, respectively.

3.8.2 Maximum chamber pressure. The upper specification limit (U) for maximum chamber pressure, when measured over a time interval of one millisecond, shall be 26,000 pounds per square inch.

3.8.3 Misfire. There shall be no misfires, see 4.7.7.2.3.

3.8.4 Hangfire. There shall be no hangfires, see 4.7.7.2.4.

3.9 Workmanship. Cartridges shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention should be directed to dimensions, finishes and coatings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.

inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling. Unless otherwise specified, and when applicable, the sampling plans and procedures used in the determination of the acceptability of products submitted by a supplier shall be in accordance with the provisions of MIL-STD-414 or MIL-STD-105, whichever applies.

4.3 Lots.

4.3.1 Inspection lots. Inspection lot definition, formation, and size shall be in accordance with MIL-STD-414 or MIL-STD-105, whichever applies.

4.3.2 Preproduction sample. Before entering into quantity production, an acceptable preproduction sample of 94 MARK 38 MOD 0 impulse cartridges shall be prepared. Of these cartridges, 84 shall be expended in the tests listed below and 10 shall be retained for investigative purposes. A preproduction sample acceptable for functional and environmental testing shall be defined as a sample which has met the requirements of 3.4 through 3.7.3 of this specification. The contractor shall deliver the cartridges to the activity designated by the contracting agency for test. Preproduction sample acceptance shall consist of the following tests as prescribed in Table 3 of MIL-D-21625: 40-foot drop (6), 15 "g" shock (12), temperature and humidity cycling (18), vibration (12), -65°F (12), +70°F (12), +160°F (12). The number in parentheses denotes the number of cartridges allocated for test. The cartridges shall be fired in the test fixture of 4.7.7.1. No cartridge shall produce results outside the limits set forth in 3.8.1 through 3.8.4. Any quantity production prior to notification by the contracting agency of preproduction sample acceptability shall be at the contractor's risk. The preproduction cartridges will not be applied as a part of the quantity specified for delivery by the contract.

4.3.3 Production lot. Unless otherwise specified in the contract, the minimum and maximum production lot size shall be 181 and 500 cartridges, respectively. Cartridges required for all test purposes are selected from the production lot and will not be applied as a part of the quantity specified for delivery by the contract. Only primary components from a single lot shall be used in a production lot of cartridges; however, one primary component production lot may be used in more than one cartridge production lot. Cartridges selected for the ballistic test shall be delivered to the activity designated by the contracting agency.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.

4.4 Gages. The contractor shall provide gages as necessary to insure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings.

4.5 Classification of characteristics. The characteristics verified by the tests and examinations herein are classified as Critical, Major or Minor in accordance with WR-43. Tests and examinations that verify critical characteristics are identified by the symbol (C) and major characteristics by the symbol (M). The number following the classification symbol indicates the serial number of test or examination. Tests and examinations which are not annotated with a classification code are classified minor.

4.6 Quality conformance inspection. Quality conformance inspection shall consist of verification of the characteristics classified on the drawings of LD 419709 and verification of the following requirements and tests:

Item	Nature of Requirement Verification	Applicable Paragraphs	Classification
Primary Component	Single lot	3.3, 4.3.3	(M101)
Primer	Age, loading and acceptance	3.4, 4.7.1	(C1)
Primer	X-ray	3.4.1, 4.7.2	(C2)
Propellant and Booster Charges	Type and weight	3.5.1	(C3)
Smokeless Powder	Condition	3.5.2.1, 4.7.3	(C4)
Cartridge	Ballistics (change in propellant lot)	3.6, 4.10	(C5)
Cartridge	Visual inspection	3.7.1, 4.7.4	(M102)
Cartridge	Leakage	3.7.2, 4.7.5	(C6)
Cartridge	X-ray	3.7.3, 4.7.6	(C7)
Cartridge	Ballistic requirements	3.8, 4.7.7	(C8)
Cartridge	Packaging, packing and container markings	4.6.1	(M103)

4.6.1 Packaging, packing and marking. The packaging and packing of cartridges and the container markings shall be in accordance with Section 5. Quality conformance inspection shall be conducted in accordance with the inspection criteria on the applicable drawings referenced in Section 5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.

4.7 Tests.

4.7.1 Primer verification. Verify that the primers to be used were manufactured within the preceding 12 months; were loaded in accordance with 3.4; and were accepted in accordance with Drawing B-7645332 and the applicable portions of MIL-P-46610, Class 1.

4.7.2 Primer X-ray. Examine all primers by X-ray and reject those having any of the defects of 3.4.1. Pressure-sensitive tape may be used as an aid in positioning the primers in suitable grooved racks. For the most revealing exposure, the primers are laid on their side with the anvil cutouts vertical.

4.7.3 Smokeless powder, condition. Smokeless powder shall be inspected in accordance with the applicable portions of paragraphs 1308-1318 and 1322 of OP 5. Evidence of decomposition shall be cause for rejection.

4.7.4 Visual inspection. Examine all cartridges and reject those having any of the defects of 3.7.1.

4.7.5 Leakage. Each cartridge in the preproduction sample or ballistic sample shall be leak tested in a dry gas or dry air leak tester. Cartridges which exhibit a leak rate in excess of 10^{-5} cc/sec gas or air at a pressure differential of one atmosphere shall be considered defective. If one or more cartridges of the preproduction sample leak, the preproduction sample shall be rejected. If one or more cartridges of the ballistic sample leak, then a 100 percent leak test of the lot being tested shall be required, at no additional expense to the government. Cartridges which exhibit a leak rate in excess of that specified above shall be rejected.

4.7.6 X-ray examination. Examine all cartridges by X-ray and any observable imperfections in assembly shall be cause for cartridge rejection.

4.7.7 Ballistic tests.

4.7.7.1 The number of cartridges selected from each production lot for the ballistic tests shall be in accordance with the requirements of Table A-2 of MIL-STD-414, Inspection Level IV. The cartridges shall be conditioned for a minimum of 12 hours at $+70^{\circ} \pm 5^{\circ}$F and fired in Test Set, DL 2838270, using an ejection load of 9 pounds. In addition to the sample of cartridges required for the above test, 10 additional cartridges shall be furnished from each production lot for investigative purposes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.

4.7.7.2 Criteria of acceptability.

4.7.7.2.1 Velocity. The velocity of the propelled load shall be measured over the interval from 0 to 5.25 inches of horizontal travel. The instrumentation to be used shall record the velocity to within an accuracy of 1.0 percent. The lower (L) and upper (U) limits of velocity shall be as specified in 3.8.1. With respect to velocity, the lot shall be acceptable if the estimated lot percent defective (p) is equal to or less than the maximum allowable percent defective (M), at an AQL of 0.04, when computed in accordance with MIL-STD-414, Part II, Table B-3.

4.7.7.2.2 Maximum chamber pressure. The upper limit (U) of maximum pressure shall be as specified in 3.8.2. With respect to maximum pressure, the lot shall be acceptable if the quantity $(U-\bar{X})/S$ is equal to or greater than the appropriate value of k, at an AQL of 0.04, when computed in accordance with MIL-STD-414, Part I, Table B-1. The instrumentation to be used shall record the maximum pressure to within an accuracy of 2.0 percent.

4.7.7.2.3 Misfire. The failure of any cartridge to fire shall result in rejection of the lot represented, unless such failure is plainly attributable to faulty test equipment or procedure.

4.7.7.2.4 Hangfire. One or more hangfires shall result in rejection of the lot represented. A hangfire is defined as a firing in which the elapsed time between actuation of the firing mechanism and first indication of pressure rise exceeds 0.050 second.

4.8 Retest. There shall be no retests.

4.9 Test failure. If test failure is attributable to an assignable cause, excluding the test cartridges, original test results should be discarded and the complete test reconducted.

4.10 Change in propellant lot. Whenever a change in propellant lot occurs, validity of the charge determination shall be verified by firing 36 cartridges which have been temperature conditioned for a minimum of 12 hours (12 at -65° ± 5°F, 12 at +70° ± 5°F and 12 at +160° ± 5°F). Results of these firings shall be within the limits specified in 3.8.1 through 3.8.4.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. For definitions of packaging levels, see 6.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. Level A packaging shall be used for packaging of all production lots for service use. Four cartridges shall be packaged in an inner container in accordance with LD 537897.

5.1.2 Level B. Not applicable.

5.1.3 Level C. When directed by the procuring activity, those cartridges which are intended for expenditure in preproduction sample testing and for production lot acceptance tests shall be packaged in accordance with Method III of MIL-P-116 and with the Code of Federal Regulations 49 CFR 71-78.

5.2 Packing. For definitions of packing levels, see 6.4.

5.2.1 Level A. Level A packing shall be used for packing of all production lots for service use. Six inner containers as described in 5.1.1 shall be packed in accordance with LD 537898.

5.2.2 Level B. Not applicable.

5.2.3 Level C. When directed by the procuring activity, cartridges intended for expenditure in preproduction sample testing and for production lot acceptance tests, and are packaged in accordance with 5.1.3, shall be packed to afford protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. Shipping containers shall be in accordance with the Code of Federal Regulations 49 CFR 71-78.

5.3 Markings.

5.3.1 Special markings. Marking of exterior containers shall be in accordance with the Code of Federal Regulations 49 CFR 71-78.

5.3.2 Normal markings. Unless otherwise specified in the contract or order, the marking information on unit packages and shipping containers shall be as specified on the drawings of LD 537897 and LD 537898. The specified marking information shall be applied to the containers in accordance with the applicable provisions of MIL-STD-129.

6. NOTES

6.1 Intended use. The MARK 38 MOD 0 impulse cartridge was originally designed to provide the power to actuate the piston of the drogue chute thruster in the A5 series aircraft escape system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.

6.2 Ordering information. Procurement documents should specify the following:

a. title, number, and date of this specification;

b. whether preproduction inspection is required, and if so, specify the test activity;

c. production lot size and test activity (see 4.3.3);

d. items of data required for each preproduction and production lot (see 6.3).

6.3 Data. For the information of contractors and contracting officers, any of the data specified in (a) subparagraphs below, (b) applicable documents listed in Section 2 of this specification or (c) referenced lower-tier documents need not be prepared for the Government and shall not be furnished to the Government unless specified in the contract or order. The data to be furnished shall be listed on DD Form 1423 (Contractor Data Requirements List) which shall be attached to and made a part of the contract or order. NAVWEPS Form 4200/15 (Drawings, Lists, and Specifications Required) shall be attached where applicable.

6.3.1 Test report. Results of ballistic tests shall be forwarded to the Naval Air Systems Command and the procuring activity.

6.3.2 Data cards. The contract or order should state the format, quantity and destination of data cards.

6.4 Definitions. The definitions of Levels A and C packaging and packing given below were extracted from BUSANDA Instruction 4030.17.

6.4.1 Level A packaging. The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during handling, shipment, indeterminate storage and world-wide redistribution.

6.4.1.1 Level C packaging. The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during shipment from supply source to the first receiving activity for immediate use. This level may conform to supplier's commercial practice when such meets the requirements of this level.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.

6.4.2 Level A packing. The degree of packing which will afford adequate protection during shipment, handling, indeterminate storage and world-wide redistribution.

6.4.2.1 Level C packing. The degree of packing which will afford protection against damage during direct domestic shipment from the supply source to the first receiving activity for immediate use. This level in general will conform to applicable carrier rules and regulations and may be the supplier's commercial practice when such meets the requirement of this level.

6.5 Explosives safety precautions.

6.5.1 Applicability. The loading, assembly and handling of the explosives, subassemblies and the finished items covered by this specification involve hazardous operations and therefore require suitable explosive safety precautions. At plants of the Naval Air Systems Command, Department of the Navy, and other Government plants where the Government is responsible for safety, the precautions listed below are mandatory. These same minimum provisions are recommended for observance by a contractor or manufacturer that explosively loads the item covered in this specification in order to fulfill his own safety responsibility. Other warnings and precautions, pertaining to the operational effectiveness or safety of the specified item during its use (for example, during its handling, launching or firing), are included in the detailed technical requirements of the specification. Use of this specification shall not be construed to replace other safety regulations of governmental agencies or to relieve the contractor or manufacturer of responsibility for the safety of his operations.

6.5.2 Personnel and equipment. Proper care must be exercised at all times to protect personnel from accidents, fires or explosions and to limit damage to equipment and loading areas. In connection with the above, the precautionary measures in the following paragraphs should be observed. (See also paragraph 6.5.4, Static and electrical and other applicable parts of these safety precautions.)

6.5.2.1 Explosives operations shall be kept under strict supervision. Periodic inspections shall be employed to assure compliance with established safety regulations.

6.5.2.2 Safe equipment and methods should be utilized for handling and transporting explosives and loaded parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.

6.5.2.3 Where required, remote control-barricaded-handling equipment shall be used for explosives operations such as mixing, pouring, weighing, charging, sifting, drying, pressing, casting, crimping, etc.

6.5.2.4 Employ properly proportioned and properly located protective barricades, screens or shields at all required points.

6.5.2.5 Maintain equipment such as presses, dies, crimpers, blenders, mixers, sifters, conveyors, and the like in safe operating condition.

6.5.2.6 Enforce, where necessary, the wearing of suitable safety footwear, gloves, goggles, respirators, and impregnated garments to protect personnel against burns, poisoning and associated industrial hazards.

6.5.2.7 During static tests, propulsion units such as rocket motors shall be restrained against full thrust to prevent flight if ignited, for example, during test of igniter circuit. Also, means shall be provided to harmlessly vent flames and exhaust gases.

6.5.3 Operating procedures. All loading operations shall be conducted in full accordance with a formalized operating procedure which shall include the following:

6.5.3.1 Keep only minimum, limited quantities of explosives and completed or partially loaded parts present at each stage of operation.

6.5.3.2 Allow no fires, exposed electrical or other sparking equipment, and little or no flammable material to be present in loading, handling and storage spaces. Enforce proper "Match" and "No Smoking" rules where necessary.

6.5.3.3 Appropriate safety instructions for specific operations shall be posted and personnel instructed as to the hazards present and precautions involved.

6.5.3.4 The number of working personnel and transients permitted in each work space shall be established and posted in such areas. The numbers shall be the minimum number required to accomplish necessary operations.

6.5.3.5 All loading operations should be conducted in a neat and orderly manner.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.

6.5.3.6 Enforce good housekeeping and maintain effective policing, inspection and supervisory methods throughout the loading area and surroundings.

6.5.3.7 Employ effective cleaning methods periodically to minimize the accumulation of explosives or explosive dust and other contamination upon, and assure its removal from, floors, walls, ceiling, ledges, tables, benches, piping, and equipment or the items loaded. Clean up any spilled material immediately.

6.5.3.8 The exposure of explosive materials and related parts should be so controlled as to minimize the absorption of moisture from the atmosphere or other sources during loading and handling operations.

6.5.3.9 Personnel handling detonators, primers, delay elements, lead-ins, boosters, and related parts which affect functioning should, insofar as practicable, avoid using bare fingers or improper equipment in order to prevent damage, corrosion, or deterioration from perspiration or other contaminating deposits.

6.5.3.10 Keep explosives and explosive parts in approved covered receptacles with covers in place when material is not being taken out or put into the receptacles. Where necessary, receptacles should be conductive to ground electrostatic charges. (See paragraph 6.5.4.)

6.5.4 Static and electrical.

6.5.4.1 Protect operations from electrostatic charges by effectively grounding all machinery, equipment, and fixtures; and, where necessary, employ suitable grounded conductive coverings for floors, work benches and tables, and workers' conductive shoes. Workers' clothing of a type to minimize the accumulation of static charges shall be employed. Fabrics, such as silk and nylon, which generate static electricity shall be avoided. Additional grounding devices, such as grounded bracelets for workers, should be employed where operations are conducted with items which are unusually sensitive to initiation by static electricity. Such items include initiating explosives, tracer mixtures, and low energy type of electric primers, detonators and squibs. The latter types of items shall have the free ends of lead wires bared and twisted together and be packed in relatively small groups wrapped in bare non-insulated aluminum foil or other uncoated metal foil. During assembly and processing operations, such sensitive electric items should be short circuited by clips or other devices until installed with safety shunt in the final device.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.

Additional precautions for these items should include mechanical shielding to contain or deflect fragments and blast; also electrical shielding from induced electric currents originated by sources such as lightning, static, electromagnetic radiations, etc. Where necessary for safety, humidity of work rooms should be appropriately increased, as required to lessen electrostatic effects, but without inducing excessive moisture absorption by any of the components of the item being processed.

6.5.4.2 Protect all explosive operations from the effects of electric current originating in equipment (such as soldering irons or guns, heaters, switches, wiring, motors, lights, test instruments, etc.) by suitable insulation, grounding, separation or shielding. Such electric sources may initiate explosives by heat, sparks, arcs, or by completing an electric circuit through an electric primer, detonator or squib. For example, circuits may be inadvertently completed from a defective electric soldering iron through a grounded contact. All electric types of primers, detonators or squibs provided with wire leads shall have the free ends of the wires bared and twisted together to short circuit each unit, except when in process of assembly into a finished item. Removable short circuiting clips or other devices should be employed during manufacturing operations involving items such as electric primers, detonators or squibs.

6.5.4.3 Where necessary, protect personnel and operations from electromagnetic energy. In certain work with very sensitive explosives or items, a shielded environment free from significant electromagnetic energy should be provided.

6.5.5 Operating facility and storage regulations.

6.5.5.1 All explosives including partially loaded items should be stored in suitable storage magazines located in accordance with the minimum distances prescribed in the American Table of Distances (ATD). While the explosive or loaded items are in process, stored in loading rooms, or in ready or service magazines, they should be located in accordance with Intraplant Distances set forth in the ATD. For Navy managed or contractor managed-Navy owned-explosives loading plants, the Armed Services Explosives Safety Board standards approved by the Department of Defense, the Secretary of the Navy and the Naval Air Systems Command covering quantity-distance regulations for explosives apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION
MIL-C-23333B(AS) CARTRIDGE, IMPULSE, MARK 38 MOD 0

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426

C-8879

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Naval Air Systems Command
Washington, D.C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

NAVAL AIR SYSTEMS COMMAND (AIR-52021)
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:26Z
Check the source to verify that this is the current version before use.