MILITARY SPECIFICATION
Transmitter Group, Telemetric Data OA-1208 ( )/DPN

This Amendment forms a part of MIL-T-23369B (AS) dated 2 January 1968 and has been approved by the Naval Air Systems Command, Department of the Navy.

Add to Appendix 1:

60.0 TRANSMITTER POWER REQUIREMENTS

60.1 Connect transmitter plug 13P1 into jack 13J1.

60.2 On the wattmeter insert the 5 watt load.

60.3 Insure arrow on wattmeter is pointing in the proper direction.

60.4 Connect the wattmeter input to the transmitter output jack.

60.5 Connect the 0 to 100 millimeter in series with the OA-1208( )/DPN pin (13J5-H) and the positive terminal on the 240-280 VDC supply.

60.6 Verify the 0-100 millimeter indicates not more than 50 MA.

(12) NMT 50 MA

60.7 The wattmeter should indicate not less than 0.5 watts.

(13) NLT 0.5 watts

60.8 Transmitter frequency should be within plus/minus 0.01% of specified value.

(14) NMT plus/minus 0.01% RF Freq.

Project No. 5821-N064

FSC-5821

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:33Z
Check the source to verify that this is the current version before use.