
MILITARY SPECIFICATION SHEET

WAVEGUIDES, SINGLE RIDGE


(BANDWIDTH RATIO 2.4:1)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the waveguides described herein shall consist of this document and the latest issue of Specification MIL-W-23351.



Configuration 1.



Configuration 2.

FIGURE 1. Waveguide.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Naval Electronic Systems Command, Department of the Navy, ATTN: ELEX 5043, Washington, D.C. 20360 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:29Z
Check the source to verify that this is the current version before use.

FSC 5985

TABLE I. Part number dimensions and material.

Part number M23351/03-	Dimensions 1/				
	A	B	C	D	E
001 2/ 002 003 004	28.129 ±.020 (714.48) (.51)	12.658 ±.020 (321.51) (.51)	28.379 Max (720.83)	12.908 Max (327.86)	5.278 ±.010 (134.06) (.25)
005 006 007 008	18.421 ±.015 (467.89) (.38)	8.289 ±.015 (210.54) (.38)	18.671 Max (474.24)	8.539 Max (216.89)	3.457 ±.007 (87.81) (.18)
009 010 011 012	11.695 ±.010 (297.05) (.25)	5.263 ±.010 (133.68) (.25)	11.945 ±.015 (303.40) (.38)	5.513 ±.015 (140.03) (.38)	2.195 ±.005 (55.75) (.13)
013 014 015 016	7.682 ±.010 (195.12) (.25)	3.457 ±.010 (87.81) (.25)	7.932 ±.015 (201.47) (.38)	3.707 ±.015 (94.16) (.38)	1.442 ±.004 (36.63) (.10)
017 018 019 020	5.847 ±.005 (148.51) (.13)	2.631 ±.005 (66.83) (.13)	6.007 ±.010 (152.40) (.25)	2.791 ±.010 (70.89) (.25)	1.097 ±.003 (27.86) (.08)
021 022 023 024	3.276 ±.004 (83.21) (.10)	1.474 ±.004 (37.44) (.10)	3.436 ±.009 (87.27) (.23)	1.634 ±.009 (41.50) (.23)	.6150 ±.0025 (15.621) (.064)
025 026 027 028 2/	2.456 ±.004 (62.38) (.10)	1.105 ±.004 (28.07) (.10)	2.616 ±.009 (66.45) (.23)	1.265 ±.009 (32.13) (.23)	.461 ±.002 (11.71) (.05)
029 3/ 030 031 032	1.404 ±.003 (35.66) (.08)	.632 ±.003 (16.05) (.08)	1.532 ±.008 (38.91) (.20)	.760 ±.008 (19.30) (.20)	.2640 ±.0015 (6.706) (.038)
033 034 035 036	1.034 ±.003 (26.26) (.08)	.465 ±.003 (11.81) (.08)	1.134 ±.008 (28.80) (.20)	.565 ±.008 (14.35) (.20)	.194 ±.001 (4.93) (.03)
037 038 039 040	.6550 ±.0025 (16.637) (.064)	.2950 ±.0025 (7.493) (.064)	.7550 ±.0075 (19.177) (.191)	.395 ±.0075 (10.03) (.191)	.123 ±.001 (3.12) (.03)
041 042 043 044	.4466 ±.0020 (11.344) (.051)	.2010 ±.0020 (5.105) (.051)	.527 ±.007 (13.39) (.18)	.281 ±.007 (7.14) (.18)	.0838 ±.0005 (2.129) (.013)
045 046 047 048 3/	.2729 ±.0010 (6.932) (.025)	.1228 ±.0010 (3.119) (.025)	.353 ±.006 (8.97) (.15)	.203 ±.006 (5.16) (.15)	.0512 ±.0005 (1.300) (.013)

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:29Z
Check the source to verify that this is the current version before use.

TABLE I. Part number dimensions and material - Continued.

Part number M23351/03-	Dimensions (continued) 1/ F Max	G ±10%	H	J	K	Material
001 2/ 002 003 004	.051 (1.30)	1.056 (26.82)	4.360 ±.010 (110.74) (.25)	.020 (.51)	.010 (.25)	Aluminum alloy Copper alloy Copper Silver alloy
005 006 007 008	.051 (1.30)	.691 (17.55)	2.855 ±.007 (72.52) (.18)	.015 (.38)	.007 (.18)	Aluminum alloy Copper alloy Copper Silver alloy
009 010 011 012	.047 (1.19)	.439 (11.15)	1.813 ±.003 (46.05) (.08)	.010 (.25)	.005 (.13)	Aluminum alloy Copper alloy Copper Silver alloy
013 014 015 016	.047 (1.19)	.288 (7.32)	1.191 ±.004 (30.25) (.10)	.010 (.25)	.004 (.10)	Aluminum alloy Copper alloy Copper Silver alloy
017 018 019 020	.047 (1.19)	.219 (5.56)	.906 ±.003 (23.01) (.08)	.005 (.13)	.003 (.08)	Aluminum alloy Copper alloy Copper Silver alloy
021 022 023 024	.047 (1.19)	.123 (3.12)	.5080 ±.0025 (12.903) (.064)	.004 (.10)	.0025 (.064)	Aluminum alloy Copper alloy Copper Silver alloy
025 026 027 028 2/	.047 (1.19)	.092 (2.34)	.3810 ±.0020 (9.677) (.051)	.004 (.10)	.0020 (.051)	Aluminum alloy Copper alloy Copper Silver alloy
029 3/ 030 031 032	.031 (.79)	.053 (1.35)	.2180 ±.0015 (5.537) (.038)	.003 (.08)	.0015 (.038)	Aluminum alloy Copper alloy Copper Silver alloy
033 034 035 036	.031 (.79)	.039 (.99)	.160 ±.001 (4.06) (.03)	.003 (.08)	.001 (.03)	Aluminum alloy Copper alloy Copper Silver alloy
037 038 039 040	.015 (.38)	.025 (.64)	.1015 ±.0010 (2.578) (.025)	.0025 (.064)	.001 (.03)	Aluminum alloy Copper alloy Copper Silver alloy
041 042 043 044	.015 (.38)	.017 (.43)	.0692 ±.0005 (1.758) (.013)	.002 (.05)	.0005 (.013)	Aluminum alloy Copper alloy Copper Silver alloy
045 046 047 048 3/	.015 (.38)	.010 (.25)	.0423 ±.0005 (1.074) (.013)	.001 (.03)	.0005 (.013)	Aluminum alloy Copper alloy Copper Silver alloy

1/ Dimensions are in inches. Metric equivalents (in parentheses) are given for general information only and are based upon 1.00 inch = 25.4 mm.
2/ The waveguide shall be in accordance with configuration 1.
3/ The waveguide shall be in accordance with configuration 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:29Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design, construction, and physical dimensions: See figure 1 and table I.
Material: See table I.
Part number: M23351/3- (dash number from table I).

NOTES:

Engineering information and frequency range: See table II.
Cross reference: See table III.

TABLE II. Engineering information.

Part number M23351/3-	Suggested frequency range TE_{10} mode	Cutoff frequency		Theoretical attenuation at $f = \sqrt{3}\, f_{c_{10}}$ 1/ 2/	Theoretical power handling capacity at $f = \sqrt{3}\, f_{c_{10}}$ 3/
		TE_{10} mode	TE_{20} mode		
	GHz	GHz	GHz	dB/ft	kW
001-XXX 002-XXX 003-XXX 004-XXX	.175 - .420	.148	.431	.00036 .00036 .00024 .00026	32,870
005-XXX 006-XXX 007-XXX 008-XXX	.267 - .640	.226	.658	.00068 .00067 .00045 .00048	14,100
009-XXX 010-XXX 011-XXX 012-XXX	.420 - 1.00	.356	1.036	.00130 .00129 .00087 .00093	5,682
013-XXX 014-XXX 015-XXX 016-XXX	.640 - 1.53	.542	1.577	.00247 .00243 .00164 .00176	2,451
017-XXX 018-XXX 019-XXX 020-XXX	.840 - 2.00	.712	2.072	.00373 .00368 .00248 .00266	1,421
021-XXX 022-XXX 023-XXX 024-XXX	1.50 - 3.60	1.271	3.699	.00888 .00877 .00591 .00633	445.8
025-XXX 026-XXX 027-XXX 028-XXX	2.00 - 4.80	1.695	4.933	.0136 .0135 .00908 .00972	250.6
029-XXX 030-XXX 031-XXX 032-XXX	3.50 - 8.20	2.966	8.632	.0319 .0315 .0212 .0227	81.87
033-XXX 034-XXX 035-XXX 036-XXX	4.75 - 11.00	4.025	11.714	.0501 .0494 .0333 .0357	44.43
037-XXX 038-XXX 039-XXX 040-XXX	7.50 - 18.00	6.356	18.498	.0994 .0981 .0661 .0708	17.82

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:29Z
Check the source to verify that this is the current version before use.

TABLE II. Engineering information - Continued.

Part number M23351/3-	Suggested frequency range TE_{10} mode	Cutoff frequency		Theoretical attenuation at $f = \sqrt{3}\, f_{c_{10}}$ 1/ 2/	Theoretical power handling capacity at $f = \sqrt{3}\, f_{c_{10}}$ 3/
		TE_{10} mode	TE_{20} mode		
	GHz	GHz	GHz	dB/ft	kW
041-XXX	11.00 -26.50	9.322	27.130	.176	8.285
042-XXX				.174	
043-XXX				.117	
044-XXX				.125	
045-XXX	18.00 -40.00	15.254	44.393	.370	3.095
046-XXX				.365	
047-XXX				.246	
048-XXX				.263	

1/ $f_{c_{10}}$ = cutoff frequency for TE_{10} mode.

2/ Actual attenuation of waveguides may be considerably greater depending upon operating frequency and temperature. For further information or to calculate for frequencies other than those tabulated, see S. Hopfer, "The Design of Ridged Waveguides", IRE Transactions on Microwave Theory and Techniques, MTT-3 pp 20-29, October 1955, and MIL-HDBK-216, "Transmission Lines and Fittings", chapter 6. Typical resistivities of materials (at 20° C): aluminum alloy (6061) = 4.0 microhms-cm; copper alloy (brass) = 3.9 microhm-cm; copper = 1.77 microhm-cm; silver alloy (coin silver) = 2.03 microhm-cm.

3/ Actual power handling capability of waveguides may be considerably less depending upon waveguide temperature, altitude, operating frequency, etc. For further information or to calculate values for frequencies other than those tabulated, see S. Hopfer, "The Design of Ridged Waveguides", IRE Transactions on Microwave Theory and Techniques, MTT-3 pp 20-29, October 1955, and MIL-HDBK-216, "Transmission Lines and Fittings", chapter 6. The tabulated values were calculated based upon the E field produced breakdown in a nonpressurized air dielectric waveguide under continuous wave (CW) conditions. The breakdown strength of air was considered to be 15000 volts per centimeter, corner radii considered.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:29Z
Check the source to verify that this is the current version before use.

TABLE III. Cross reference (type designation to part number).

Type designation	Part number M23351/3-	Type designation	Part number M23351/3-
WRS175U24A	001	WRS200D24A	025
WRS175U24B	002	WRS200D24B	026
WRS175U24C	003	WRS200D24C	027
WRS175U24D	004	WRS200D24S	028
WRS267U24A	005	WRS350D24A	029
WRS267U24B	006	WRS350D24B	030
WRS267U24C	007	WRS350D24C	031
WRS267U24S	008	WRS350D24S	032
WRS420U24A	009	WRS475D24A	033
WRS420U24B	010	WRS475D24B	034
WRS420U24C	011	WRS475D24C	035
WRS420U24S	012	WRS475D24S	036
WRS640U24A	013	WRS750D24A	037
WRS640U24B	014	WRS750D24B	038
WRS640U24C	015	WRS750D24C	039
WRS640U24S	016	WRS750D24S	040
WRS840U24A	017	WRS110C24A	041
WRS840U24B	018	WRS110C24B	042
WRS840U24C	019	WRS110C24C	043
WRS840U24S	020	WRS110C24S	044
WRS150D24A	021	WRS180C24A	045
WRS150D24B	022	WRS180C24B	046
WRS150D24C	023	WRS180C24C	047
WRS150D24S	024	WRS180C24S	048

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Army -
Navy - OS, SH
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AR
Navy - MC, AS
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5985-0855-3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:29Z
Check the source to verify that this is the current version before use.